

# Surrogate Head Forms for the Evaluation of Head Injury Risk

Anna MacAlister  
Virginia Tech – Wake Forest University  
Center for Injury Biomechanics

## ABSTRACT

This paper summarizes the use of surrogate head forms in biomechanical research pertaining to head injury and, more specifically, mild traumatic brain injury. Because cadavers are limited and controlled studies of brain injury using live human subjects would be unethical, surrogate head forms are used to study the response of the human head to impact. Different head forms have been developed and optimized for different purposes. The Hybrid III 50<sup>th</sup> percentile male crash test dummy was developed for use in vehicle crash testing and instrumented in such a way as to provide HIC values in frontal crash tests. The NOCSAE head form is used by the National Operating Committee on Standards for Athletic Equipment to be used in the certification of commercially produced athletic helmets. The Facial and Ocular Countermeasure Safety (FOCUS) head form was developed jointly by the Virginia Tech – Wake Forest Center for Injury Biomechanics, Robert A. Denton, Inc., and the United States Army Aeromedical Research Laboratory as a tool to aid in the development and evaluation of safety devices designed to prevent face and eye injuries. The vast majority of biomechanical research of head injury conducted using surrogate anthropomorphic test devices (ATDs) utilized one of these three head forms.

Key Words: Mild traumatic brain injury, head, head form, brain injury

## PRESENTATION SUMMARY

It is estimated that up to 3.8 million sports related concussions occur in the United States each year [1]. An additional 10,000 to 28,000 cases of mTBI are reported each year in the United States military [2]. During wartime, the incidence of mTBI increases significantly in the military [3]. In the current Iraq and Afghanistan wars it is estimated that as many as 22.8% of military personnel sustained a concussion while deployed [2]. Concussion is now thought to contribute to long term neurocognitive deficits, rather than just simple transient symptoms, increasing the need for research into the biomechanics of concussion and head injury. Because controlled studies of concussion using live human volunteers would be unethical, and cadavers available for research are limited, researchers use surrogate head form anthropomorphic test devices (ATDs) to evaluate the biomechanics of concussion. Three of the head forms most commonly used to evaluate brain and face injury mechanisms are the Hybrid III 50<sup>th</sup> percentile male headform, the NOCSAE medium head form, and the FOCUS head form.

## Hybrid III

The Hybrid III head form is the most extensively used head form in biomechanical research (**Figure 1**). The Hybrid III has been used in the fields of auto safety, military safety and

sports biomechanics but was first developed and validated for use in vehicle crash tests. The dummy was developed by Hubbard and McLeod in 1974 [4]. The Hybrid III ATD was built to the dimensions of the 50<sup>th</sup> percentile male. Despite the biofidelity of the head form in total mass and crown circumference, the Hybrid III head form lacks anatomical accuracy. The stylized facial features of the head form replace accurate bone structure. Missing from the head form are anatomically accurate zygoma, maxilla and mandible. The absence of these features can lead to difficulty in testing any device or equipment designed to engage the human face. Currently, a complete 'family' of Hybrid III ATDs is manufactured, including a 5<sup>th</sup> percentile female and child sized dummies modeling various ages and stages of development. These differently sized ATDs allow for surrogate testing of biomechanical responses more representative of the population as a whole, but exhibit the same anatomical inaccuracy as the original 50<sup>th</sup> percentile male head form. The Hybrid III 50<sup>th</sup> percentile male dummy and head form are still used more frequently than any of the other Hybrid III ATDs.



Figure 1. Hybrid III 50th percentile male head form

The head form of the Hybrid III dummy was originally instrumented with an accelerometer array that provided researchers with the necessary data to calculate the head injury criteria (HIC) value experienced by the ATD in a particular crash mode. The HIC value was used to determine if a car passed or failed the standards for sale in the United States. As ATD instrumentation became more advanced, the Hybrid III became useful in evaluating a wide variety of biomechanical responses to different stimuli. The Hybrid III ATD has been used in published research investigating the effects of restraint performance and airbag interactions [5,6]. Additional research has been conducted comparing the relative responses of the Hybrid III dummy and post mortem human surrogates (PMHS), validating the biomechanical response of the Hybrid III to another type of human surrogate [7].

As sports concussion moved into public and research focus in the early 2000's, the Hybrid III ATD, including the head form, was used by Pellman and Viano to reconstruct impacts thought to cause concussion during NFL game play [8-14]. Although the authors used the entire head, body and extremities of the Hybrid III in their reconstructions of game impacts, 100% of the concussions observed came from direct head impacts, as opposed to body impacts that resulted in head movement. In 2012, Viano conducted a study using only the Hybrid III head form to investigate the response of the head form to impact on different field types at different temperatures [15]. The ability of the Hybrid III head form to be used independently or with an attached surrogate neck allows a broad array of biomechanical research to be performed to using the Hybrid III.

The Hybrid III head form was used by the Virginia Tech – Wake Forest Center for Injury Biomechanics and other institutions to validate the Riddell HIT System (Head Impact Telemetry

System) and the custom 6 degree of freedom helmet impact sensor system designed at Virginia Tech [16,17]. The validation of these two systems using the Hybrid III head form is the foundation for a large data set of concussive and non-concussive head impacts collected from 2003 to 2012 from 11 collegiate football teams and several high school and youth football teams [16,18-40]. This data set in turn contributed to the development of the Virginia Tech – Wake Forest Center for Injury Biomechanics Summation of Tests for the Analysis of Risk (STAR) system for evaluating commercially available football helmets [31].

In addition to the major football studies, the Hybrid III head form has also been used with the attached Hybrid III dummy to test the efficacy of different styles of neck collars to prevent stingers in football [41]. The Hybrid III head form has been used without the Hybrid III dummy in studies designed to measure the efficacy of catcher's masks to reduce head accelerations in baseball [42,43].

### NOCSAE

The head form used by the National Operating Committee on Standards for Athletic Equipment (NOCSAE) is named for the organization itself. The NOCSAE head form was developed by Dr. Voigt Hodgson at Wayne State University to accurately simulate human head response to impact [44]. The NOCSAE head form is considered more anatomically correct than

the Hybrid III and includes appropriate facial features and bone structure. However, because the NOCSAE head form was designed to be mounted to a rigid arm rather than a surrogate neck, it cannot be used to study the effects of a neck strength and anisotropic bending of the neck on head acceleration.

The NOCSAE head form is available in three different adult sizes;  $6\frac{5}{8}$  (small),  $7\frac{1}{4}$  (medium) and  $7\frac{5}{8}$  (large). The medium NOCSAE head form (**Figure 2**) is constructed to approximately the same dimension as a 50<sup>th</sup> percentile male and fits a large size football helmet [45,46]. The NOCSAE head form is instrumented with an array of accelerometers to measure acceleration in the anterior-posterior direction, the superior-inferior direction and the left-right direction [45]. Accelerations measured during a helmet test are used to calculate the Gadd Severity Index (GSI) of a particular impact. NOCSAE tests helmets under a variety of different impact conditions and passes, or certifies, only



Figure 2. Medium NOCSAE head form

helmets that maintain GSI values of less than a given value, determined by NOCSAE. Football helmets must reduce the head form acceleration to a GSI of less than 1200 for all impact types tested in order to gain NOCSAE certification [46].

In 2011, Rowson and Duma of the Virginia Tech – Wake Forest Center for Injury Biomechanics used the medium NOCSAE medium head form in conjunction with the football

impact exposure data collected using the HIT system to develop the STAR evaluation system for football helmets [31,47]. Linear acceleration data collected from the HIT system was used to quantify impact exposure and concussion risk of football players. The NOCSAE head form and NOCSAE style drop tower were used to perform drop tests at varying heights and impact locations on commercially available helmet models to quantify their relative performances [47].

Revised concussion risk functions were developed by Rowson and Duma in 2012 that take into account rotational accelerations of the head [24]. In 2013, Rowson and Duma published combined probability of concussion contours, based on both rotational and linear head accelerations [48]. These risk functions can be used with a modified STAR equation to better characterize the relative performances of different football helmet models.

## FOCUS

The Facial and Ocular Countermeasures Safety (FOCUS) head form (**Figure 3**) was developed through a collaboration between the U.S. Army Aeromedical Research Laboratory, Virginia Tech-Wake Forest Center for Injury Biomechanics, and Denton, Inc. to allow for testing of facial and ocular protective equipment without the use of cadavers [49]. The FOCUS head form models the 50<sup>th</sup> percentile male soldier in all head dimensions, and is compatible with the Hybrid III surrogate neck. The neck and body attachment capabilities and biofidelic facial structure are two major strengths of the Hybrid III and NOCSAE head forms respectively combined into one surrogate head form. However, the FOCUS head form is not currently manufactured in any additional sizes and is therefore not useful in studies that may emphasize particular sub groups of the general population.



Figure 3. FOCUS head form

The surrogate skull of the FOCUS head form is unique in that it consists of 8 separate pieces representing the left and right frontal bones, the left and right zygoma, the left and right maxilla, the nasal bone and the mandible [49]. Each segment is instrumented separately with a three-axis load cell capable of measuring up to 1000 pounds. Data from the load cells of each skull segment can be used in conjunction with carefully developed risk functions for fracture to predict injury to a human in a given loading scenario [50-54].

The eyes of the FOCUS head form are also unique among ATDs [49,55]. Each synthetic eyeball rests in a cup of synthetic extraocular tissue, held by a simulated orbit. Each eye assembly is mounted to the face of a load cell. Force measurements obtained during testing by the eye socket load cells can be used to predict injury according to risk functions developed by Kennedy et al. Extensive work to validate the response of the FOCUS synthetic eye to the response of human cadaver eyes was conducted by the Virginia

Tech – Wake Forest Center for Injury Biomechanics and other colleagues to create the most biofidelic eyes possible [55-67]. In addition to its distinct facial instrumentation, the FOCUS head form is also instrumented similarly to the Hybrid III with an accelerometer array located at the center of gravity of the head form. Data from these accelerometers can be used to determine the biomechanical response of the head form to impact.

Although the FOCUS head form contains all of the appropriate instrumentation to be used in concussion and head injury research, it has primarily been used to study facial and ocular injury because of its specialized additional features and instrumentation. At the Virginia Tech – Wake Forest Center for Injury Biomechanics, extensive eye injury research has been done using the FOCUS head form. Alphonse et al. have used the head form to study eye injury resulting from fireworks and Duma et al. used the head form to study risk of injury from different types of impact, including water streams and high speed projectiles [58,60,68-71]. The FOCUS head form has been used in portions of studies conducted by Weaver et al. on modeling the human eye orbit [72-74]. Much of the continuing research on eye orbit anthropometry may be incorporated into future iterations of the FOCUS head form.

It is important to note that because of the particular technological features and geometrical properties of each of the different head forms, they cannot be considered interchangeable. Careful consideration of the biomechanical features of the system to be tested is necessary in choosing the ideal head form for any study of head and mild traumatic brain injury mechanisms.

## REFERENCES

- [1] Langlois JA, Rutland-Brown W, Wald MM. The epidemiology and impact of traumatic brain injury: a brief overview. *J Head Trauma Rehabil.* Sep-Oct 2006;21(5):375-378.
- [2] Iverson GL. Clinical and methodological challenges with assessing mild traumatic brain injury in the military. *The Journal of head trauma rehabilitation.* 2010;25(5):313-319.
- [3] Warden D. Military TBI during the Iraq and Afghanistan wars. *Journal of Head Trauma Rehabilitation.* Sep-Oct 2006;21(5):398-402.
- [4] Hubbard RP, McLeod DG. Definition and Development of A Crash Dummy Head. *Proceedings of the 18th Stapp Car Crash Conference.* 1974;SAE 741193.
- [5] Duma SM, Crandall JR, Rudd RW, Kent RW. Small female head and neck interaction with a deploying side airbag. *Accident; analysis and prevention.* 2003;35(5):811.
- [6] Kent R, Crandall J, Bolton J, Duma S. Comparison and evaluation of contemporary restraint systems in the driver and front-passenger environments. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering.* 2001;215(11):1147-1159.
- [7] Beeman SM, Kemper AR, Madigan ML, Duma SM. Kinetic and kinematic responses of post mortem human surrogates and the hybrid III ATD in high-speed frontal sled tests. *Accident Analysis & Prevention.* 2013.
- [8] Pellman EJ, Powell JW, Viano DC, et al. Concussion in professional football: epidemiological features of game injuries and review of the literature--part 3. *Neurosurgery.* Jan 2004;54(1):81-94; discussion 94-86.
- [9] Pellman EJ, Viano DC, Casson IR, et al. Concussion in professional football: repeat injuries--part 4. *Neurosurgery.* Oct 2004;55(4):860-873; discussion 873-866.

- [10] Pellman EJ, Viano DC, Tucker AM, Casson IR. Concussion in professional football: location and direction of helmet impacts-Part 2. *Neurosurgery*. Dec 2003;53(6):1328-1340; discussion 1340-1321.
- [11] Pellman EJ, Viano DC, Tucker AM, Casson IR, Waeckerle JF. Concussion in professional football: reconstruction of game impacts and injuries. *Neurosurgery*. Oct 2003;53(4):799-812; discussion 812-794.
- [12] Pellman EJ, Viano DC, Withnall C, Shewchenko N, Bir CA, Halstead PD. Concussion in professional football: helmet testing to assess impact performance--part 11. *Neurosurgery*. Jan 2006;58(1):78-96; discussion 78-96.
- [13] Viano DC, Casson IR, Pellman EJ. Concussion in professional football: biomechanics of the struck player--part 14. *Neurosurgery*. Aug 2007;61(2):313-327; discussion 327-318.
- [14] Viano DC, Pellman EJ. Concussion in professional football: biomechanics of the striking player--part 8. *Neurosurgery*. Feb 2005;56(2):266-280; discussion 266-280.
- [15] Viano DC, Withnall C, Wonnacott M. Football Helmet Drop Tests on Different Fields Using an Instrumented Hybrid III Head. *Ann Biomed Eng*. Jan 2012;40(1):97-105.
- [16] Beckwith JG, Greenwald RM, Chu JJ. Measuring Head Kinematics in Football: Correlation Between the Head Impact Telemetry System and Hybrid III Headform. *Ann Biomed Eng*. Jan 2012;40(1):237-248.
- [17] Rowson S, Beckwith JG, Chu JJ, Leonard DS, Greenwald RM, Duma SM. A six degree of freedom head acceleration measurement device for use in football. *J Appl Biomech*. Feb 2011;27(1):8-14.
- [18] Beckwith JG, Greenwald RM, Chu JJ, et al. Timing of Concussion Diagnosis is Related to Head Impact Exposure prior to Injury. *Med Sci Sports Exerc*. 2012.
- [19] Beckwith JG, Greenwald RM, Chu JJ, et al. Head impact exposure sustained by football players on days of diagnosed concussion. *Med Sci Sports Exerc*. 2012.
- [20] Daniel RW, Rowson S, Duma SM. Head Impact Exposure in Youth Football. *Ann Biomed Eng*. Apr 2012;40(4):976-981.
- [21] Duhaime A-C, Beckwith JG, Maerlender AC, et al. Spectrum of acute clinical characteristics of diagnosed concussions in college athletes wearing instrumented helmets: Clinical article. *Journal of neurosurgery*. 2012;117(6):1092-1099.
- [22] Rowson S, Duma SM. The temperature inside football helmets during head impact: a five-year study of collegiate football games. *Proceedings of the Institution of Mechanical Engineers, Part P: Journal of Sports Engineering and Technology*. 2013;227(1):12-19.
- [23] Rowson S, Duma SM. The virginia tech response. *Annals of biomedical engineering*. 2012:1-7.
- [24] Rowson S, Duma SM, Beckwith JG, et al. Rotational head kinematics in football impacts: an injury risk function for concussion. *Ann Biomed Eng*. Jan 2012;40(1):1-13.
- [25] Crisco JJ, Wilcox BJ, Beckwith JG, et al. Head impact exposure in collegiate football players. *J Biomech*. Oct 13 2011;44(15):2673-2678.
- [26] Crisco JJ, Wilcox BJ, Machan JT, et al. Magnitude of head impact exposures in individual collegiate football players. *J Appl Biomech*. May 2012;28(2):174-183.
- [27] Duma SM, Rowson S. Past, present, and future of head injury research. *Exerc Sport Sci Rev*. Jan 2011;39(1):2-3.
- [28] Funk JR, Rowson S, Daniel RW, Duma SM. Validation of Concussion Risk Curves for Collegiate Football Players Derived from HITS Data. *Ann Biomed Eng*. Jan 2012;40(1):79-89.

- [29] Kimpapa H, Nakahira Y, Iwamoto M, Rowson S, Duma S. Head Injury Prediction Methods Based on 6 Degree of Freedom Head Acceleration Measurements during Impact. *International Journal of Automotive Engineering*. 2011;2(2):13-19.
- [30] Rowson S, Brolinson G, Goforth M, Dietter D, Duma SM. Linear and angular head acceleration measurements in collegiate football. *J Biomech Eng*. Jun 2009;131(6):061016.
- [31] Rowson S, Duma SM. Development of the STAR Evaluation System for Football Helmets: Integrating Player Head Impact Exposure and Risk of Concussion. *Ann Biomed Eng*. Aug 2011;39(8):2130-2140.
- [32] McAllister T, Flashman L, Maerlender A, et al. Cognitive effects of one season of head impacts in a cohort of collegiate contact sport athletes. *Neurology*. 2012;78(22):1777-1784.
- [33] Duma SM, Manoogian SJ, Bussone WR, et al. Analysis of real-time head accelerations in collegiate football players. *Clin J Sport Med*. Jan 2005;15(1):3-8.
- [34] Crisco JJ, Fiore R, Beckwith JG, et al. Frequency and location of head impact exposures in individual collegiate football players. *J Athl Train*. Nov-Dec 2010;45(6):549-559.
- [35] Broglio SP, Sosnoff JJ, Shin S, He X, Alcaraz C, Zimmerman J. Head impacts during high school football: a biomechanical assessment. *J Athl Train*. Jul-Aug 2009;44(4):342-349.
- [36] Broglio SP, Surma T, Ashton-Miller JA. High school and collegiate football athlete concussions: a biomechanical review. *Ann Biomed Eng*. Jan 2012;40(1):37-46.
- [37] Crisco JJ, Chu JJ, Greenwald RM. An algorithm for estimating acceleration magnitude and impact location using multiple nonorthogonal single-axis accelerometers. *J Biomech Eng*. Dec 2004;126(6):849-854.
- [38] Guskiewicz KM, Mihalik JP, Shankar V, et al. Measurement of head impacts in collegiate football players: relationship between head impact biomechanics and acute clinical outcome after concussion. *Neurosurgery*. Dec 2007;61(6):1244-1253.
- [39] Mihalik JP, Bell DR, Marshall SW, Guskiewicz KM. Measurement of head impacts in collegiate football players: an investigation of positional and event-type differences. *Neurosurgery*. Dec 2007;61(6):1229-1235; discussion 1235.
- [40] Mihalik JP, Guskiewicz KM, Marshall SW, Blackburn JT, Cantu RC, Greenwald RM. Head impact biomechanics in youth hockey: comparisons across playing position, event types, and impact locations. *Annals of Biomedical Engineering*. 2012;40(1):141-149.
- [41] Rowson S, McNeely DE, Brolinson PG, Duma SM. Biomechanical analysis of football neck collars. *Clin J Sport Med*. Jul 2008;18(4):316-321.
- [42] Beyer JA, Rowson S, Duma SM. Concussions experienced by major league baseball catchers and umpires: field data and experimental baseball impacts. *Ann Biomed Eng*. Jan 2012;40(1):150-159.
- [43] Shain KS, Madigan ML, Rowson S, Bisplinghoff J, Duma SM. Analysis of the ability of catcher's masks to attenuate head accelerations on impact with a baseball. *Clin J Sport Med*. Nov 2010;20(6):422-427.
- [44] Hodgson VR. National Operating Committee on Standards for Athletic Equipment football helmet certification program. *Medicine and science in sports*. 1975;7(3):225.
- [45] NOCSAE. Standard Test Method and Equipment Used in Evaluating the Performance Characteristics of Protective Headgear/Equipment. National Operating Committee on Standards for Athletic Equipment; 2011.

- [46] NOCSAE. Standard Performance Specification for Newly Manufactured Football Helmets. National Operating Committee on Standards for Athletic Equipment; 2011.
- [47] Rowson S, Duma SM. National Impact Database - Adult Football Helmet Ratings - May 2012. 2012; <http://www.sbes.vt.edu/nid.php>.
- [48] Rowson S, Duma SM. Brain injury prediction: assessing the combined probability of concussion using linear and rotational head acceleration. *Annals of Biomedical Engineering*. 2013;1-10.
- [49] Crowley JS, Brozoski FT, Duma SM, Kennedy EA. Development of the Facial and Ocular Countermeasures Safety (FOCUS) headform. *Aviation, space, and environmental medicine*. 2009;80(9):831.
- [50] Cormier J, Duma S. The epidemiology of facial fractures in automotive collisions. Paper presented at: Annual Proceedings/Association for the Advancement of Automotive Medicine2009.
- [51] Cormier J, Manoogian S, Bisplinghoff J, et al. The tolerance of the nasal bone to blunt impact. *Ann Adv Automot Med*. 2010;54:3-14.
- [52] Cormier J, Manoogian S, Bisplinghoff J, et al. Biomechanical Response of the Human Face and Corresponding Biofidelity of the FOCUS Headform. *SAE Int. J. Passeng. Cars - Mech. Syst*. 2010;3(1):842-859.
- [53] Cormier J, Manoogian S, Bisplinghoff J, et al. The tolerance of the frontal bone to blunt impact. *J Biomech Eng*. Feb 2011;133(2):021004.
- [54] Cormier J, Manoogian S, Bisplinghoff J, et al. The tolerance of the maxilla to blunt impact. *J Biomech Eng*. Jun 2011;133(6):064501.
- [55] Kennedy EA, Inzana JA, McNally C, et al. Development and validation of a synthetic eye and orbit for estimating the potential for globe rupture due to specific impact conditions. *Stapp Car Crash J*. 2007;51:381.
- [56] Kennedy E, Duma S. The effects of the extraocular muscles on eye impact force–deflection and globe rupture response. *J Biomech*. 2008;41(16):3297-3302.
- [57] Duma SM, Crandall JR. Eye Injuries from Air Bags With Seamless Module Covers. Paper presented at: Annual Proceedings/Association for the Advancement of Automotive Medicine1999.
- [58] Duma SM, Jernigan MV. The effects of airbags on orbital fracture patterns in frontal automobile crashes. *Ophthalmic Plastic & Reconstructive Surgery*. 2003;19(2):107-111.
- [59] Duma SM, Kress TA, Porta DJ, et al. Airbag-induced eye injuries: a report of 25 cases. *The Journal of Trauma and Acute Care Surgery*. 1996;41(1):114-119.
- [60] Duma SM, Ng TP, Kennedy EA, Stitzel JD, Herring IP, Kuhn F. Determination of significant parameters for eye injury risk from projectiles. *The Journal of Trauma and Acute Care Surgery*. 2005;59(4):960-964.
- [61] Duma Sm JMSJD, et al. THE effect of frontal air bags on eye injury patterns in automobile crashes. *Archives of Ophthalmology*. 2002;120(11):1517-1522.
- [62] Stitzel J, Kemper A, Duma S. Myopia and hyperopia's effect on probability of globe rupture due to a foreign body impact. *Investigative Ophthalmology and Visual Science*. 2005;46(5):5028.
- [63] Stitzel Jd HGAHIPDSM. Blunt trauma of the aging eye: Injury mechanisms and increasing lens stiffness. *Archives of Ophthalmology*. 2005;123(6):789-794.
- [64] Bisplinghoff JA, McNally C, Manoogian SJ, Duma SM. Dynamic material properties of the human sclera. *J Biomech*. 2009;42(10):1493-1497.



- [65] Bisplinghoff JA, MCDERMOTT SM. High-rate internal pressurization of human eyes to predict globe rupture. *Archives of Ophthalmology*. 2009;127(4):520-523.
- [66] Power ED, Duma SM, Stitzel JD, et al. Computer modeling of airbag-induced ocular injury in pilots wearing night vision goggles. *Aviation, space, and environmental medicine*. 2002;73(10):1000-1006.
- [67] Vinger PF, DERMOTT SM. Baseball hardness as a risk factor for eye injuries. *Archives of Ophthalmology*. 1999;117(3):354-358.
- [68] Alphonse VD, Kemper AR, Duma SM. Exposure to Fireworks and Eye Injuries—Reply. *Jama*. 2012;308(15):1523-1524.
- [69] Alphonse VD, Kemper AR, Strom BT, Beeman SM, Duma SM. Mechanisms of eye injuries from fireworks. *JAMA: The Journal of the American Medical Association*. 2012;308(1):33-34.
- [70] Duma SM, Bisplinghoff JA, Senge DM, McNally C, Alphonse VD. Evaluating the risk of eye injuries: intraocular pressure during high speed projectile impacts. *Current eye research*. 2012;37(1):43-49.
- [71] Duma SM, Bisplinghoff JA, Senge DM, McNally C, Alphonse VD. Eye Injury Risk from Water Stream Impact: Biomechanically Based Design Parameters for Water Toy and Park Design. *Current eye research*. 2012;37(4):279-285.
- [72] Weaver AA, Kennedy EA, Duma SM, Stitzel JD. Evaluation of different projectiles in matched experimental eye impact simulations. *J Biomech Eng*. 2011;133(3):031002.
- [73] Weaver AA, Loftis KL, Duma SM, Stitzel JD. Biomechanical modeling of eye trauma for different orbit anthropometries. *J Biomech*. 2011;44(7):1296-1303.
- [74] Weaver AA, Loftis KL, Tan JC, Duma SM, Stitzel JD. CT based three-dimensional measurement of orbit and eye anthropometry. *Investigative ophthalmology & visual science*. 2010;51(10):4892-4897.