

TABLE OF CONTENTS

Chapter 1. Introduction.....	1
1.1 The Acoustic Disturbance and Some Solutions.....	2
1.2 Motivation and Requirements for Active Control of Payload Fairings.....	5
1.3 Active Structural/Acoustic Control.....	6
1.4 Active Control Research Related to Payload Fairings.....	8
1.5 Is the Piezoelectric (PZT) Actuator a Feasible Choice to Control PFs?.....	9
1.6 Approach and its Significance	10
1.7 Structural Modeling Performed on the PZT Actuation of Cylinders.....	11
1.8 Internal Acoustic Response of Cylinders.....	12
1.9 Overview of Dissertation	12
Chapter 2. Simply-Supported Cylinder Structural Response	14
2.1 PZT Actuator Model and Structural Response for a SS Cylinder	14
2.2 Creation of the Cylinder Simply-Supported Boundary Condition	19
2.2.1 Various Boundary Conditions Tested.....	19
2.2.2 Synopsis of Boundary Conditions Tested.....	22
2.3 Modal Evaluation of the Cylinder.....	23
2.4 Comparison with Finite Element Analysis	25
2.5 Response to Various Actuator Locations.....	26
2.6 Analytical and Experimental Response	26
2.7 Concluding Remarks on the Structural Model.....	31
Chapter 3. Simply-Supported Cylinder Acoustic Response	32
3.1 Kirchoff-Helmholtz Integral Applied to a Cylinder	32
3.2 Internal Acoustic Response of a Cylinder Having a Single Mode Structural Vibration	35
3.3 Internal Acoustic Response of a Cylinder Using Boundary Element Analysis	37
3.4 Analytical and Boundary Element Model Comparison for the Internal Acoustic Response of a Cylinder.....	39
3.5 Variation of the Internal SPL with Applied Voltage	43
Chapter 4. Experiment: Verification of the Acoustic Model and Determination of the Acoustic Loss Factor	45
4.1 Experimental Determination of the Cylinder Structural Operating Shape	45
4.2 Results of the Cylinder Operating Shape.....	46
4.3 Some Experimental Issues and Additional Tests.....	47
4.4 Description of the Acoustic Experimental Setup.....	50
4.5 Description of the Acoustic Measurements	50

4.6 Results of the Acoustic Natural Frequencies for the Cylinder	52
4.7 Determination of the Acoustic Modes	56
4.8 Effect of Changes to the Acoustic Loss Factor.....	61
4.9 Comparison of the Model with Experiment.....	61
4.10 Concluding Remarks on the Acoustic Model	68

Chapter 5. Simulation of a Payload Fairing69

5.1 Properties of the Payload Fairing.....	69
5.2 Choice of Parameters for a Large Scale SS Cylinder	69
5.2.1 Cylinder Size.....	69
5.2.2 Cylinder Mass and Stiffness	71
5.2.3 Cylinder Damping.....	71
5.2.4 Baseline PZT Actuator: Material and Physical Properties	72
5.2.5 PZT Actuator Location	73
5.2.6 Acoustic Field Point Location	73
5.2.7 Summary of the Simulation Test Cases	73
5.3 Results of the Simulations	73
5.3.1 Effect of Cylinder Stiffness and Mass Changes	74
5.3.2 Effect of Actuator Applied Voltage.....	74
5.3.3 Effect of Cylinder Damping Changes on the Acoustic Response	77
5.3.4 Implications to Active Structural Acoustic Control of Payload Fairings	77
5.3.5 Baseline Actuator Acoustic Authority.....	78
5.3.6 The Importance of Actuator Current Consumption.....	78
5.3.7 Baseline Actuator Current Consumption.....	79
5.3.8 Payload Fairing Acoustic Authority and Current Consumption.....	79
5.4 Conclusions of the Simulations	80

Chapter 6. Practical Considerations and Limitations90

6.1 Mode Shape Orientation	90
6.2 Applications to Larger Fairings	90
6.3 Control Issues.....	90
6.4 PZT Actuator Non-linearity.....	91
6.5 PZT Actuator Tensile Properties	91
6.6 Single or Co-located Actuators.....	92
6.7 Fairing and Cylinder Modal Density	92
6.8 Potential Sources of Error.....	92
6.9 Convergence Test.....	93

Chapter 7. Conclusions94

7.1 Structural Model	94
7.2 Acoustic Model.....	94
7.3 Simulations	95
7.4 Future Work.....	96

References	98
Appendix A MATLAB Code to Compute Structural Response.....	106
Appendix B MATLAB Code to Compute the Acoustic Response.....	114
Appendix C Miscellaneous Cylinder Operating Shapes	121
Appendix D Calibration of the Microphones	127
Appendix E Miscellaneous Cylinder Acoustic Fields	131
Appendix F Cylinder Natural Frequencies for Cases 1-7	175
Appendix G Summary of Simulations Performed.....	186
Appendix H Miscellaneous Phase Plots for the Cylinder.....	188
Appendix I Modal Assurance Criterion for the Cylinder.....	191
Vita.....	193

LIST OF FIGURES

1.1 Contour of equal overall SPL (Eldred, 1971).	3
1.2 Titan IV rocket fairing SPLs (Elliot, 1990).	4
1.3 Typical absorption coefficients for a fairing (Weissman, et al., 1994).....	4
1.4 Effect of blankets on internal SPL (Lee, 1992).	5
1.5 Huygen’s Surface: Secondary Sources Produce a Region of Silence (Stevens and Ahuja, 1991).	6
2.1 Cylinder with mounted actuators.	14
2.2 Transfer of actuator forces to equivalent mid-plane loading.	15
2.3 Interaction between the PZT and the cylinder via the structural impedance.	16
2.4 Instrumented cylinder.	20
2.5 Tested boundary conditions: (a) test 1, 2, & 3: (b) test 4: (c) test 5.	21
2.6 Response of the cylinder for different boundary conditions (tests 1-5).	22
2.7 Response of the cylinder at different axial locations.	23
2.8 FRF of accelerance with respect to force.	24
2.9. Spatial FRF magnitude at 950 Hz (2,1): (a) circumferential at $x = 237$ mm: (b) circumferential at $x = 67.8$ mm: (c) axial at $\theta = 0^\circ$: (d) circumferential phase at $x = 67.8$ mm.	24
2.10 Spatial FRF at 1838 Hz (3,2): (a) circumferential at $x = 237$ mm: (b) circumferential at $x = 67.8$ mm: (c) axial at $\theta = 0^\circ$: (d) circumferential phase at $x = 67.8$ mm.	25
2.11 Comparison of analytical, FEA, and experimental natural frequencies.	28
2.12 Analytical displacement magnitude driven by actuator A, B, and C.	28
2.13 Experimental displacement magnitude driven by actuator A, B, and C.	29
2.14 Analytical/experimental displacement magnitude for PZT A at 25 Vrms.	29
2.15 Analytical/experimental displacement magnitude for PZT B at 25 Vrms.	30
2.16 Analytical response at 1533 Hz (4,1).	30
2.17 Analytical response at 2021 Hz (3,2).	31
3.1 Example of the location of nodal accelerance points on the cylinder surface.	38
3.2 Corresponding example of the partitioned surface elements.	38
3.3 Magnitude of the cylinder accelerance (phase adjusted) for case 1.	40
3.4 Radial acoustic response at $x = 0.3l$ for case 1 (SPL dB).	41
3.5 Horizontal acoustic response for case 1, except $t_o = 0^\circ$ (SPL dB).	41
3.6 Magnitude of the cylinder accelerance (phase adjusted) for case 2.	42
3.7 Radial acoustic response at $x = 0.3l$ for case 2 (SPL dB).	42
3.8 Vertical acoustic response for case 2 (SPL dB).	43
3.9 Normalized internal SPL for varying voltage, linear scale.	44
3.10 Normalized internal SPL for varying voltage, semi-log scale.	44
4.1 Schematic representation of the structural experiment.	46
4.2 Cylinder displacement magnitude at various axial locations, $\theta = 0^\circ$	47
4.3 Cylinder operating shape at 948 Hz (2,1).	48
4.4 Cylinder operating shape at 948 Hz, (displacement magnitude, m).	48

4.5 Cylinder operating shape at 976 Hz (3,1).	49
4.6 Cylinder operating shape at 976 Hz, (displacement magnitude, m).	49
4.7 Cross section of the acoustic test set up.	51
4.8 Schematic of the microphone and actuator signal conditioning.	51
4.9 Vertical plane of acoustic field measurements.	53
4.10 Radial planes of acoustic field measurements.	53
4.11 Acoustic response of the cylinder at $\theta = 0^\circ$ for microphones A, B, & C; near the endplate, at $L/2$, and $L/3$ (S=structural mode, A=acoustic mode, B=Bessel mode, ?=unknown).	54
4.12 Comparison of analytical and experimental acoustic natural frequencies.	55
4.13 Error between the analytical and experimental acoustic natural frequencies.	56
4.14 Axial internal acoustic field (SPL in dB) at 948 Hz.	57
4.15 Radial internal acoustic field near endplate (SPL in dB) at 948 Hz.	57
4.16 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 948 Hz.	58
4.17 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 948 Hz.	58
4.18 Axial internal acoustic field (SPL in dB) at 1552 Hz.	59
4.19 Radial internal acoustic field near endplate (SPL in dB) at 1552 Hz.	59
4.20 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1552 Hz.	60
4.21 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1552 Hz.	60
4.22 Model acoustic response for various acoustic loss factors (1, 0.5 and 0.1%).	62
4.23 Comparison of the acoustic simulation with experiment $\{x_a = 19.05 \text{ mm (0.75 in.)}\}$.	63
4.24 Comparison of the acoustic simulation with experiment $\{x_a = 130.56 \text{ mm (5.14 in.)}\}$.	63
4.25 Comparison of the acoustic simulation with experiment $\{x_a = 195.83 \text{ mm (7.71 in.)}\}$.	64
4.26 Axial internal acoustic simulation (SPL in dB) at 948 Hz.	64
4.27 Radial internal acoustic simulation near endplate (SPL in dB) at 948 Hz.	65
4.28 Radial internal acoustic simulation at 1/3 cylinder length (SPL in dB) at 948 Hz.	65
4.29 Radial internal acoustic simulation at 1/2 cylinder length (SPL in dB) at 948 Hz.	66
4.30 Axial internal acoustic simulation (SPL in dB) at 1552 Hz.	66
4.31 Radial internal acoustic simulation near endplate (SPL in dB) at 1552 Hz.	67
4.32 Radial internal acoustic simulation at 1/3 cylinder length (SPL in dB) at 1552 Hz.	67
4.33 Radial internal acoustic simulation at 1/2 cylinder length (SPL in dB) at 1552 Hz.	68
5.1 Minotaur fairing approximate dimensions and modeled cylinder section.	70
5.2 Cylinder displacement response actuated at $x = l/2, \eta = 0.007$, cases 1a-7a.	75
5.3 Cylinder displacement response actuated at $x = l/4, \eta = 0.007$, cases 1d-7d.	75
5.4 Pressure within the cylinder actuated at $x = l/2, \eta = 0.007$, cases 1a-7a.	76
5.5 Pressure within the cylinder actuated at actuated at $x = l/4, \eta = 0.007$, cases 1d-7d.	76
5.6 Cylinder displacement response actuated at $x = l/2$, case 1a, $\eta = 0.007$; case 1b, $\eta = 0.0206$; case 1c, $\eta = 0.052$.	82
5.7 Cylinder SPL actuated at $x = l/2$, case 1a, $\eta = 0.007$; case 1b, $\eta = 0.0206$; case 1c, $\eta = 0.052$.	82
5.8 Cylinder displacement response actuated at $x = l/4$, case 1d, $\eta = 0.007$; case 1e, $\eta = 0.0206$; case 1f, $\eta = 0.052$.	83
5.9 Cylinder SPL actuated at $x = l/4$,	

case 1d, $\eta = 0.007$; case 1e, $\eta = 0.0206$; case 1f, $\eta = 0.052$	83
5.10 Cylinder displacement response actuated at $x = l/2$, case 7a, $\eta = 0.007$; case 7b, $\eta = 0.0206$; case 7c, $\eta = 0.052$	84
5.11 Cylinder SPL actuated at $x = l/2$, case 7a, $\eta = 0.007$; case 7b, $\eta = 0.0206$; case 7c, $\eta = 0.052$	84
5.12 Cylinder displacement response actuated at $x = l/4$, case 7d, $\eta = 0.007$; case 7e, $\eta = 0.0206$; case 7f, $\eta = 0.052$	85
5.13 Cylinder SPL actuated at $x = l/4$, case 7d, $\eta = 0.007$; case 7e, $\eta = 0.0206$; case 7f, $\eta = 0.052$	85
5.14 Baseline PZT actuator current draw for harmonic excitation.	86
5.15 Baseline PZT actuator current at the 1/3 octave-band center frequencies.	86
5.16 Cylinder internal acoustic levels and 1/3 octave-band representation for case1.	87
5.17 Cylinder internal acoustic levels and 1/3 octave-band representation for case7.	87
5.18 Additional SPL required to achieve 130 dB, case1.	88
5.19 Additional SPL required to achieve 130 dB, case7.	88
5.20 Required number of baseline PZT actuators to achieve 130 dB.	89
5.21 Required current amplitude to achieve 130 dB.	89
C.1 Cylinder operating shape at 1528 Hz (4,1).	121
C.2 Cylinder operating shape at 1528 Hz, (displacement magnitude, m).	121
C.3 Cylinder operating shape at 1836 Hz (3,2).	122
C.4 Cylinder operating shape at 1836 Hz, (displacement magnitude, m).	122
C.5 Cylinder operating shape at 2044 Hz (4,2).	123
C.6 Cylinder operating shape at 2044 Hz, (displacement magnitude, m).	123
C.7 Cylinder operating shape at 2116 Hz (2,2).	124
C.8 Cylinder operating shape at 2116 Hz, (displacement magnitude, m).	124
C.9 Cylinder operating shape at 2208 Hz (1,1).	125
C.10 Cylinder operating shape at 2208 Hz, (displacement magnitude, m).	125
C.11 Cylinder operating shape at 2388 Hz (5,1).	126
C.12 Cylinder operating shape at 2388 Hz, (displacement magnitude, m).	126
D.1 Comparison of B&K and RSO microphone “A” at four different acoustic levels.	128
D.2 Absolute error between the B&K and RSO microphone “A” at four acoustic levels.	128
D.3 Comparison of B&K and RSO microphone “B” at four different acoustic levels.	129
D.4 Absolute error between the B&K and RSO microphone “B” at four acoustic levels.	129
D.5 Comparison of B&K and RSO microphone “C” at four different acoustic levels.	130
D.6 Absolute error between the B&K and RSO microphone “C” at four acoustic levels.	130
E.1 Axial internal acoustic field (SPL in dB) at 832 Hz.	131
E.2 Radial internal acoustic field near endplate (SPL in dB) at 832 Hz.	131
E.3 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 832 Hz.	132
E.4 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 832 Hz.	132
E.5 Axial internal acoustic field (SPL in dB) at 876 Hz.	133
E.6 Radial internal acoustic field near endplate (SPL in dB) at 876 Hz.	133

E.7 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 876 Hz.....	134
E.8 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 876 Hz.....	134
E.9 Axial internal acoustic field (SPL in dB) at 972 Hz.....	135
E.10 Radial internal acoustic field near endplate (SPL in dB) at 972 Hz.....	135
E.11 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 972 Hz.....	136
E.12 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 972 Hz.....	136
E.13 Axial internal acoustic field (SPL in dB) at 1208 Hz.....	137
E.14 Radial internal acoustic field near endplate (SPL in dB) at 1208 Hz.....	137
E.15 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1208 Hz.....	138
E.16 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1208 Hz.....	138
E.17 Axial internal acoustic field (SPL in dB) at 1316 Hz.....	139
E.18 Radial internal acoustic field near endplate (SPL in dB) at 1316 Hz.....	139
E.19 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1316 Hz.....	140
E.20 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1316 Hz.....	140
E.21 Axial internal acoustic field (SPL in dB) at 1388 Hz.....	141
E.22 Radial internal acoustic field near endplate (SPL in dB) at 1388 Hz.....	141
E.23 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1388 Hz.....	142
E.24 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1388 Hz.....	142
E.25 Axial internal acoustic field (SPL in dB) at 1452 Hz.....	143
E.26 Radial internal acoustic field near endplate (SPL in dB) at 1452 Hz.....	143
E.27 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1452 Hz.....	144
E.28 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1452 Hz.....	144
E.29 Axial internal acoustic field (SPL in dB) at 1532 Hz.....	145
E.30 Radial internal acoustic field near endplate (SPL in dB) at 1532 Hz.....	145
E.31 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1532 Hz.....	146
E.32 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1532 Hz.....	146
E.33 Axial internal acoustic field (SPL in dB) at 1636 Hz.....	147
E.34 Radial internal acoustic field near endplate (SPL in dB) at 1636 Hz.....	147
E.35 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1636 Hz.....	148
E.36 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1636 Hz.....	148
E.37 Axial internal acoustic field (SPL in dB) at 1760 Hz.....	149
E.38 Radial internal acoustic field near endplate (SPL in dB) at 1760 Hz.....	149
E.39 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1760 Hz.....	150
E.40 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1760 Hz.....	150
E.41 Axial internal acoustic field (SPL in dB) at 1800 Hz.....	151
E.42 Radial internal acoustic field near endplate (SPL in dB) at 1800 Hz.....	151
E.43 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1800 Hz.....	152
E.44 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1800 Hz.....	152
E.45 Axial internal acoustic field (SPL in dB) at 1840 Hz.....	153
E.46 Radial internal acoustic field near endplate (SPL in dB) at 1840 Hz.....	153
E.47 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1840 Hz.....	154
E.48 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1840 Hz.....	154
E.49 Axial internal acoustic field (SPL in dB) at 1900 Hz.....	155
E.50 Radial internal acoustic field near endplate (SPL in dB) at 1900 Hz.....	155
E.51 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1900 Hz.....	156
E.52 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1900 Hz.....	156

E.53 Axial internal acoustic field (SPL in dB) at 1908 Hz.....	157
E.54 Radial internal acoustic field near endplate (SPL in dB) at 1908 Hz.....	157
E.55 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1908 Hz.....	158
E.56 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1908 Hz.....	158
E.57 Axial internal acoustic field (SPL in dB) at 1964 Hz.....	159
E.58 Radial internal acoustic field near endplate (SPL in dB) at 1964 Hz.....	159
E.59 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 1964 Hz.....	160
E.60 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 1964 Hz.....	160
E.61 Axial internal acoustic field (SPL in dB) at 2048 Hz.....	161
E.62 Radial internal acoustic field near endplate (SPL in dB) at 2048 Hz.....	161
E.63 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2048 Hz.....	162
E.64 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2048 Hz.....	162
E.65 Axial internal acoustic field (SPL in dB) at 2088 Hz.....	163
E.66 Radial internal acoustic field near endplate (SPL in dB) at 2088 Hz.....	163
E.67 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2088 Hz.....	164
E.68 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2088 Hz.....	164
E.69 Axial internal acoustic field (SPL in dB) at 2124 Hz.....	165
E.70 Radial internal acoustic field near endplate (SPL in dB) at 2124 Hz.....	165
E.71 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2124 Hz.....	166
E.72 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2124 Hz.....	166
E.73 Axial internal acoustic field (SPL in dB) at 2172 Hz.....	167
E.74 Radial internal acoustic field near endplate (SPL in dB) at 2172 Hz.....	167
E.75 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2172 Hz.....	168
E.76 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2172 Hz.....	168
E.77 Axial internal acoustic field (SPL in dB) at 2208 Hz.....	169
E.78 Radial internal acoustic field near endplate (SPL in dB) at 2208 Hz.....	169
E.79 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2208 Hz.....	170
E.80 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2208 Hz.....	170
E.81 Axial internal acoustic field (SPL in dB) at 2304 Hz.....	171
E.82 Radial internal acoustic field near endplate (SPL in dB) at 2304 Hz.....	171
E.83 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2304 Hz.....	172
E.84 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2304 Hz.....	172
E.85 Axial internal acoustic field (SPL in dB) at 2328 Hz.....	173
E.86 Radial internal acoustic field near endplate (SPL in dB) at 2328 Hz.....	173
E.87 Radial internal acoustic field at 1/3 cylinder length, (SPL in dB) at 2328 Hz.....	174
E.88 Radial internal acoustic field at 1/2 cylinder length, (SPL in dB) at 2328 Hz.....	174
H.1 Phase of displacement wrt. force for hammer strike at $x = 4"$, $\theta = 0^\circ$	188
H.2 Phase of displacement wrt. force for hammer strike at $x = 8"$, $\theta = 0^\circ$	189
H.3 Comparison of the acoustic simulation with experiment { $x_a = 19.05$ mm (0.75 in.)}.....	189
H.4 Comparison of the acoustic simulation with experiment { $x_a = 130.56$ mm (5.14 in.)}.....	190
H.5 Comparison of the acoustic simulation with experiment { $x_a = 195.83$ mm (7.71 in.)}.....	190
I.1 Comparison of the MAC of the cylinder operating shape for the different modes.....	192

LIST OF TABLES

2.1 Cylinder and actuator properties.....	20
2.2 Cylinder analytical, FEA, and experimental natural frequencies	27
3.1 Case properties comparing analytical and BEA	40
4.1 Radio Shack Optimus microphone properties	50
4.2 Comparison of analytical and experimental natural frequencies	55
5.1 Mechanical properties of AGS composite material	70
5.2 Physical properties of an equivalent cylinder.....	72
5.3 Properties of the PSI-5H-S2 PZT actuator.....	72
5.4 Increase in sound for a given actuation.....	81
F.1 Structural natural frequencies and modal indices for Case 1	175
F.2 Cylinder acoustic natural frequencies and modal indices for Case 1.....	176
F.3 Structural natural frequencies and modal indices for Case 2.....	178
F.4 Structural natural frequencies and modal indices for Case 3.....	179
F.5 Structural natural frequencies and modal indices for Case 4.....	180
F.6 Structural natural frequencies and modal indices for Case 5.....	181
F.7 Structural natural frequencies and modal indices for Case 6.....	182
F.8 Structural natural frequencies and modal indices for Case 7.....	183
F.9 Cylinder acoustic natural frequencies and modal indices for Case 7.....	184
G.1 Test cases for the cylinder actuated at $l/2$	186
G.2 Test cases for the cylinder actuated at $l/4$	187
I.1 Comparison of modal properties for the cylinder.....	191