

LIST OF REFERENCES

Aicher, S., Schmidt, J. and Brunold, S. (1995). "Design of Timber Beams with Holes by Means of Fracture Mechanics," *CIB – W18: International Council for Building Research Studies and Documentation, Working Commission W18 – Timber Structures, Meeting 28, Copenhagen, Denmark, April 1995*, 1-28.

Akamatsu, A. (1990). "Effects of Withdrawal Resistance, Screw-Shank Diameter, Screw Length, and Specific Gravity on the Lateral Resistance of Screw-Wood Joints with Steel Side-Members," *Mokuzai Gakkaishi*, 36(1), 15-21.

American Forest & Paper Association (1991a). *National Design Specification for Wood Construction, 1991 edition*. ANSI/NSI/NF&PA NDS[®]-1991, American Forest and Paper Association, Washington, D.C., 121 pp.

American Forest & Paper Association (1991b). *Commentary on the National Design Specification for Wood Construction, 1991 edition*. NDS[®]-1991 Commentary, American Forest and Paper Association, Washington, D.C., 173 pp.

American Forest & Paper Association (1996). *LRFD Load and Resistance Factor Design Manual for Engineered Wood Construction, 1996 edition*, American Forest and Paper Association and American Wood Council, Washington, D.C., 124 pp.

American Forest & Paper Association (1997). *National Design Specification for Wood Construction, 1997 edition*. ANSI/NSI/NF&PA NDS[®]-1997, American Forest and Paper Association, Washington, D.C., 174 pp.

American Forest & Paper Association (1999). *General Dowel Equations for Calculating Lateral Connection Values – Technical Report 12*, American Forest and Paper Association, Inc., Washington, D.C., 18 pp.

American Society of Civil Engineers (1996). "Standard for Load and Resistance Factored Design for Engineered Wood Construction," ASCE, New York, New York.

American Society of Mechanical Engineers (1996). *Square and Hex Bolts and Screws (Inch Series)*, ASME B18.2.1, ASME, New York.

American Society for Testing and Materials (1999a). "D 143-94: Standard Methods of Testing Small Clear Specimens of Timber," in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.

American Society for Testing and Materials (1999b). "E 399-90: Standard Test Method for Plane-Strain Fracture Toughness of Metallic Materials," in *1999 Annual Book of*

Standards, Section 3, Vol. 03.01: Metals – Mechanical Testing; Elevated and Low-Temperature Tests; Metallography, ASTM, West Conshohocken, Pennsylvania.

American Society for Testing and Materials (1999c). “D 1761-88: Standard Test Methods for Mechanical Fasteners in Wood,” in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.

American Society for Testing and Materials (1999d). “D 5764-97a: Standard Test Method for Evaluating Dowel-Bearing Strength of Wood and Wood-Based Products,” in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.

American Society for Testing and Materials (1999e). “D 5045-96: Standard Test Methods for Plane-Strain Fracture Toughness and Strain Energy Release Rate of Plastic Materials,” in *1999 Annual Book of ASTM Standards*, Section 8, Vol. 08.03: Plastics (III), ASTM, West Conshohocken, Pennsylvania.

Anderson, G.T. (2001). “Experimental Investigation of Group Action Factor for Bolted Wood Connections,” *Master of Science Thesis*, Department of Civil & Environmental Engineering, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, December 18, 2001, 299 pp.

Ansell, M.P. (1982). “Acoustic Emission from Softwoods in Tension,” *Wood Science and Technology*, 16(1), 35-57.

Ansell, M.P. (1983). “Acoustic Emission as a Technique for Monitoring Fracture Processes in Wood, in *Structural Use of Wood in Adverse Environments*, R.W. Meyer and R.M. Kellog, eds., Society of Wood Science and Technology, Van Nostrand Reinhold Co., New York, N.Y., 451-466.

Ansell, M.P. and Harris, B. (1979). “The Relationship Between Toughness and Fracture Surface Topography in Wood and Composites,” *Mechanical Behaviour of Materials, Proceedings of the Third International Conference, Cambridge, England, August 20-24, 1979*, 309-318.

Ashby, M.F., Easterling, K.E., Harrysson, R. and Maiti, S.K. (1985). “The Fracture and Toughness of Woods,” *Proceedings of the Royal Society of London*, A398, 261-280.

Attack, D., May, W.D., Morris, E.L. and Sproule, R.N. (1961). “The Energy of Tensile and Cleavage Fracture of Black Spruce,” *Tappi*, 44(8), 555-567.

Atkins, A.G. and Mai, Y.W. (1985). *Elastic and Plastic Fracture: Metals, Polymers, Ceramics, Composites, Biological Materials*, John Wiley & Sons, New York.

- Atluri, S.N., Kobayashi, A.S. and Nakagaki, M. (1975). "A Finite Element Program for Fracture Analysis of Composite Material," *Fracture Mechanics of Composites, ASTM STP 593*.
- Aune, P. (1993). "Design Concepts for Nailed and Screwed Joints," *Proceedings of the International Workshop on Wood Connectors, Portland, Oregon, Forest Products Society, 1993, 67-77*.
- Aune, P. and Patton-Mallory, M. (1986). "Lateral Load-bearing Capacity of Nailed Joints Based on the Yield Theory," *Forest Products Laboratory Research Paper 470, U.S. Department of Agriculture, Forest Service, Forest Products Laboratory, Madison, Wisconsin*.
- Bao, G. and Suo, Z. (1992). "Remarks on Crack-Bridging Concepts," *Applied Mechanics Reviews, ASME, 45(8), 355-366*.
- Barenblatt, G.I. (1961). "On Some Basic Ideas of the Theory of Equilibrium Cracks, Forming During Brittle Fracture," *Problems of Continuum Mechanics, SI A M, 1961, 21-38*.
- Barrett, J.D. (1976). "Effect of Crack-Front Width on Fracture Toughness of Douglas-Fir," *Engineering Fracture Mechanics, 8(4), 711-717*.
- Barrett, J.D. (1981). "Fracture Mechanics and the Design of Wood Structures," *Philosophical Transactions of the Royal Society of London, A299(1446), 217-226*.
- Barrett, J.D. and Foschi, R.O. (1977). "Mode II Stress-Intensity Factors for Cracked Wood Beams," *Engineering Fracture Mechanics, Vol. 9, 371-378*.
- Barrett, J.D. and Foschi, R.O. (1979). "On the Application of Brittle Fracture Theory, Fracture Mechanics and Creep-rupture Models for the Prediction of the Reliability of Wood Structural Elements," *Proceedings of the First International Conference on Wood Fracture, Banff, Alberta, Canada, August 14-16, 1978, 1-38*.
- Bergander, A. and Salmen, L. (2002). "Cell Wall Properties and Their Effects on the Mechanical Properties of Fibers," *Journal of Materials Science, 37(1), 151-156*.
- Blass, H.J., Ehlbeck, J. and Rouger, F. (1999). "Simplified Design of Joints with Dowel-type Fasteners," *Proceedings of Pacific Timber Engineering Conference, Rotorua, New Zealand, March, 14-18, 1999 (Forest Research Bulletin 212), Vol. 3, 275-279*.
- Biblis, E.J. (1965). "Shear Deflection of Wood Beams," *Forest Products Journal, 15(11), 492-498*.
- Blicblau, A.S. and Cook, D.J. (1986). "Aspects of Wood Fracture Toughness at Various Testing Speeds," *Institute of Eng. Aust. Civil Engineering Transactions, CE28(2)*.

- Boatright, S.W.J. and Garrett, G.G. (1980). "On the Statistical Approach to the Fracture Toughness Variations with Specimen Size in Wood," *Engineering Fracture Mechanics*, 13(1), 107-110.
- Boatright, S.W.J. and Garrett, G.G. (1983). "The Effect of Microstructure and Stress State on the Fracture Behaviour of Wood," *Journal of Materials Science*, 18(7), 2181-2199.
- Bodig, J. and Jayne, B.A. (1982). *Mechanics of Wood and Wood Composites*, Van Nostrand Reinhold Company, New York, New York.
- Boone, T.J., Wawrzynek, P.A. and Ingraffea, A.R. (1987). "Finite Element Modelling of Fracture Propagation in Orthotropic Materials," *Engineering Fracture Mechanics*, 26(2), 185-201.
- Bostrom, L. (1990). "Application of Fracture Mechanics to Timber Structures, State-of-the-Art Report, Part 2," *Meeting of International Union of Forestry Research Organisations: Wood Engineering Group, Proceedings Vol. 1, St. John, New Brunswick and Montreal, Quebec, Canada, July/August 1990*, 170-207.
- Bostrom, L. (1992). "Method for Determination of the Softening Behaviour of wood and the Applicability of a Nonlinear Fracture Mechanics Model," *Report TVBM-1012 (Doctoral Thesis)*, Lund Institute of Technology, Lund, Sweden.
- Boyd, G.M. (1972). "From Griffith to COD and Beyond," *Engineering Fracture Mechanics*, 4(3), 459-482.
- Brokaw, M.P. and Foster, G.W. (1958). "Effect of Rapid Loading and Duration of Stress on the Strength Properties of Wood Tested in Compression and Flexure," *Report No. 1518*, U.S. Forest Products Laboratory, Madison, Wisconsin, 17 pp.
- Call, R.D. and Bjorhovde, R. (1990). "Wood Connections with Heavy Bolts and Steel Plates," *Journal of Structural Engineering*, ASCE, 106(11), 3090-3107.
- Carroll, J.D. (1988). "Withdrawal and Combined Load Capacity of Threaded Fastener Wood Joints," *Master of Science in Wood Science and Forest Products Thesis*, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, December 1988, 143 pp.
- Carroll, M.N. (1970). "Relationship Between Driving Torque and Screwholding Strength in Particleboard and Plywood," *Forest Products Journal*, 20(3), 24-29.
- Chen, D.L., Weiss, B. and Stickler, R. (1992). *International Journal of Fracture*, 55, R19-R22.

- Chen, D.L., Weiss, B. and Stickler, R. (1993a). "Geometric Correction Factors Determined by Force Balance Method for Center Cracked Specimens. V. Loaded by a Pair of Tensile Forces Acting at Some Distance from the Crack," *International Journal of Fracture*, 62(4), R71-R79.
- Chen, D.L., Weiss, B. and Stickler, R. (1993b). "Geometric Correction Factors Determined by Force Balance Method for Center Cracked Specimens. VI. Loaded by a Pair of Splitting Forces Acting at an Arbitrary Location on the Crack," *International Journal of Fracture*, 64(4), R89-R96.
- Chiang, Y.J. and Rowlands, R.E. (1991). "Finite Element Analysis of Mixed-mode Fracture of Bolted Joints in Composites," *Journal of Composite Technology and Research*, 13(4), 227-235.
- Chow, C.L. and Woo, C.W. (1979). "Orthotropic and Mixed Mode Fracture in Wood," *Proceedings of the First International Conference on Wood Fracture, Banff, Alberta, Canada, August 1978*, 39-52.
- Chu, Y.P. (1978). "Strength of Nailed Joints," *Malaysian Forester*, 41(1), 53-73.
- Cline, M. (1908). "Forest Service Tests to Determine the Influence of Different Methods and Rates of Loading on the Strength and Stiffness of Timber," *Proceedings of ASTM*, Vol. 8, 535 pp.
- Cockrell, R.A. (1933). "A Study of the Screw Holding Properties of Wood," *Technical Publication 44, Bulletin of the New York State College of Forestry*, Syracuse, New York, 27 pp.
- Conrad, M.P.C., Smith, G.D. and Fernlund, G. (2002). an unpublished article, "Fracture of Solid Wood: a Review".
- Cook, T.S. and Rau, C.A., Jr. (1974). "A Critical Review of Anisotropic Fracture Mechanics," in *Prospects of Fracture Mechanics*, Sih, Van Elst, and Broek, eds., 509-523.
- Cote, W.A. and Hanna, R.B. (1983). "Ultrastructural Characteristics of Wood Fracture Surfaces," *Wood and Fiber Science*, 15(2), 135-163.
- Cousins, W.J. (1974). "Effects of Strain-Rate on the Transverse Strength of Pinus Radiata Wood," *Wood Science and Technology*, 8(4), 307-321.
- Cramer, S.M. and Goodman, J.R. (1986). "Failure Modeling: A Basis for Strength Prediction of Lumber," *Wood and Fiber Science*, 18(3), 446-459.

- Cramer, S.M. and McDonald, K.A. (1989). "Predicting Lumber Tensile Stiffness and Strength with Local Grain Angle Measurements and Failure Analysis," *Wood and Fiber Science*, 21(4), 393-410.
- Daudeville, L. and Yasumura, M. (1996). "Failure Analysis of Timber Bolted Joints by Fracture Mechanics," *Materials and Structures*, 29(191), 418-425.
- Dawicke, D.S., Phillips, E.P., Swenson, D.V. and Gondhalekar, S. (1992). "Crack Growth from Loaded Countersunk Rivet Holes," in *Durability of Metal Aircraft Structures, Proceedings of the International Workshop on Structural Integrity of Aging Airplanes, Atlanta, Georgia, March 31 – April 2, 1992*, Atlanta Technology Publications, S.N. Atluri, C.E. Harris, A. Hoggard, N. Miller and S.G. Sampath, eds., 75-90.
- DeBaise, G.R., Porter, A.W. and Pentoney, R.E. (1966). "Morphology and Mechanics of Wood Fracture," *Materials Research & Standards*, 6(10), 493-499.
- DeBaise, G.R. (1972). "Morphology of Wood Shear Fracture," *Journal of Materials*, JMLSA, 7(4), 568-572.
- DeBonis, A.L. and Bodig, J. (1975). "Nailed Wood Joints Under Combined Loading," *Wood Science and Technology*, 9(2), 129-144.
- Desch, H.E. (1981). *Timber: Its Structure, Properties, and Utilisation*, revised by J.M. Dinwoodie, 6th Edition, Timber Press, Forest Grove, Oregon.
- Dinwoodie, J.M. (1975). "Timber – A Review of the Structure – Mechanical Property Relationship," *Journal of Microscopy*, 104(1), 3-32.
- Eckelman, C.A. (1975). "Screwholding Performance in Hardwoods and Particleboard," *Forest Products Journal*, 25(6), 30-35.
- Ehlbeck, J. and Larsen, H.J. (1981). "Load-Slip Relationship of Nailed Joints," *CIB – W18: International Council for Building Research Studies and Documentation, Working Commission W18 – Timber Structures, Meeting 14, Warsaw, Poland, May 1981*, 1-6.
- ENV 1995-1 Eurocode 5. (1994). *Design of Timber Structures, Part 1*, Comite Europeen de Normalisation, Brussels, Belgium.
- Ewing, P.D. and Williams, J.G. (1979). "Thickness and Moisture Content Effect in the Fracture Toughness of Scots Pine," *Materials Science*, 14(12), 2959-2966.
- Fairchild, I.J. (1926). "Holding Power of Wood Screws," *Technologic Papers of the Bureau of Standards, No. 319*, Vol. 20, Department of Commerce, Washington, D.C., 553-580.

Feng, X.O. and Gross, D. (2000). "On the Coalescence of Collinear Cracks in Quasi-Brittle Materials," *Engineering Fracture Mechanics*, 65(5), 511-524.

Finn, W.L. and Gohl, W.B. (1992). "Response of Model Pile Groups to Strong Shaking, in Piles Under Dynamic Loads," *ASCE Geotechnical Special Publication No. 34*, American Society of Civil Engineers: New York, New York, 27-55.

Finn, W.L., Wu, G. and Thavaraj, T. (1997). "Soil-Pile-Structure Interactions, in Seismic Analysis and Design for Soil-Pile-Structure Interactions, *ASCE Geotechnical Special Publication 70*, American Society of Civil Engineers: New York, New York, 1-22.

Fonselius, M. (1986). "Fracture Mechanics of Spruce and PLV," *Report 80*, Helsinki University of Technology, Division of Structural Engineering, Helsinki, Finland.

Forest Products Laboratory (1987). *Wood Handbook: Wood as an Engineering Material*, USDA Forest Service Agricultural Handbook No. 72, Forest Products Laboratory, Washington, D.C.

Forest Products Laboratory (1999). *Wood Handbook: Wood as an Engineering Material*, USDA Forest Service Agricultural Handbook No. 72, Forest Products Laboratory, Washington, D.C.

Foschi, R.O. (1974). "Load-Slip Characteristics of Nails," *Wood Science*, 7(1), 69-76.

Foschi, R.O. (2000). "Modeling the Hysteretic Response of Mechanical Connections for Wood Structures," *Proceedings of the World Conference on Timber Engineering, Whistler Resort, British Columbia, Canada, July 31-August 3, 2000*, 11 pp.

Foschi, R.O. and Barrett, J.D. (1976). "Stress Intensity Factors in Anisotropic Plates Using Singular Isoparametric Elements," *International Journal for Numerical Methods in Engineering*, 10(6), 1281-1287.

Foschi, R.O. and Bonac, T. (1977). "Load-Slip Characteristics for Connections with Common Nails," *Wood Science*, 9(3), 118-123.

Gallagher, R.H. (1978). "A Review of Finite Element Techniques in Fracture Mechanics," *Proceedings of the International Conference on Numerical Methods in Fracture Mechanics, Swansea*, 1-25.

Garrett, G.A. (1931). *The Mechanical Properties of Wood*, Chapman and Hall, London, England, 1931.

Gerhards, C.C. (1970). "Effect of Fire Retardant Treatment of Bending Strength of Wood," *Research Paper FPL 145*, U.S. Department of Agriculture, Forest Products Laboratory.

- Gerstle, W.H. (1985). "Finite and Boundary Element Modelling of Crack Propagation in Two- and Three-Dimensions Using Interactive Computer Graphics," *PhD Dissertation*, Cornell University, Ithaca, New York.
- Gilman, J.J. (1959). *Fracture*, B.L. Averbach, ed., Wiley: New York, New York.
- Girhammar, U.A. and Andersson, H. (1988). "Effect of Loading Rate on Nailed Timber Joint Capacity," *Journal of Structural Engineering*, ASCE, 114(11), 2439-2456.
- Gohl, W.B. (1991). "Response of Pile Foundations to Simulated Earthquake Loading: Experimental and Analytical Results," *PhD Dissertation*, Department of Civil Engineering, University of British Columbia, Vancouver, British Columbia, Canada.
- Grashof, F. (1878). *Elastizitat und Festigkeit*, 2nd ed., Auflage der "Festigkeitslehre," Berlin, Germany.
- Griffith, A.A. (1920). "The Phenomena of Rupture and Flow in Solids," *Philosophical Transactions of the Royal Society of London*, A221(582-593), 163-198.
- Gu, P., Dao, M. and Asaro, R.J. (1999). "A Simplified Method for Calculating the Crack-tip Field of Functionally Graded Materials Using the Domain Integral," *Journal of Applied Mechanics*, 66(1), 101-108.
- Gustafsson, P.J. (1988). "A Study of Strength of Notched Beams," , *CIB – W18: International Council for Building Research Studies and Documentation, Working Commission W18 – Timber Structures, Meeting 21, September 1988, Paper No. 21-10-1*.
- Gustafsson, P.J. (1990). "Application of Fracture Mechanics to Timber Structures, State-of-the-Art Report, Part 3," *Meeting of International Union of Forestry Research Organisations: Wood Engineering Group, Proceedings Vol. 1, St. John, New Brunswick and Montreal, Quebec, Canada, July/August 1990*, 208-233.
- Gutshall, S.T. (1994). "Monotonic and Cyclic Short-term Performance of Nailed and Bolted Timber Connections," *Master of Science Thesis*, Virginia Polytechnic Institute and State University, Blacksburg, Virginia.
- Hankinson, R.L. (1921). "Investigation of Crushing Strength of Spruce at Various Angles to the Grain," *Air Service Information Circular*, 3(259), Materials Section Paper No. 130.
- Harding, N. and Fowkes, A.H.R. (1984). "Bolted Timber Joints," *Proceedings of Pacific Timber Engineering Conference, Auckland, New Zealand, May, 1984*, Vol. III Wood Science, 872-883.
- Hasebe, K. and Usuki, S. (1989). "Application of Orthotropic Failure Criteria to Wood," *Journal of Engineering Mechanics*, 115(4), 867-872.

- Heine, C.P. (2001). "Cyclic Response of Multiple-Bolt Connections," *PhD Dissertation*, Wood Science and Forest Products Department, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, August 2001.
- Henshell, R.D. and Shaw, K.G. (1975). "Crack Tip Finite Elements are Unnecessary," *International Journal for Numerical Methods in Engineering*, 9(3), 495-507.
- Hilson, B.O. (1969). "The Behavior of Softwoods Loaded in Compression Parallel to the Grain and Supported Against Lateral Movement," *Journal of the Institute of Wood Science*, 4(4), 11-23.
- Hilson, B.O. (1995). "Joints with Dowel-type Fasteners – Theory," *Paper C3: Timber Engineering Step 1: Basis of Design, Material Properties, Structural Components and Joints*, Almere, The Netherlands, Centrum Hout, 1995, C3/1-C3/11.
- Hilson, B.O., Whale, L.R.J. and Smith, I. (1990). "Characteristic Properties of Nailed and Bolted Joints under Short-term Lateral Load. Part 5: Appraisal of Current Design Data in BS5268: Part 2: 1984 Structural Use of Timber," *Journal of the Institute of Wood Science*, 11(6), 208-212.
- Hirai, T. and Sawada, M. (1982a). "Lateral Resistance of Bolted Wood-Joints with Wood Side Members Loaded Parallel to the Grain," *Mokuzai Gakkaishi*, Journal of Japan Wood Research Society, 28(11), 695-698.
- Hirai, T. and Sawada, M. (1982b). "Lateral Resistance of Bolted Wood-Joints with Steel Side Members Loaded Parallel to the Grain," *Mokuzai Gakkaishi*, Journal of Japan Wood Research Society, 28(11), 685-694.
- Hirai, T. and Sawada, M. (1982c). "Linear Load-slip Relationship of Bolted Joints of Glue-Laminated Lumber," *Mokuzai Gakkaishi*, Journal of Japan Wood Research Society, 28(10), 609-613.
- Hirai, T. and Sawada, M. (1982d). "Nominal Bearing-Stresses of Bolted Wood-Joints at Apparent Proportional Limits," *Mokuzai Gakkaishi*, Journal of Japan Wood Research Society, 28(9), 543-547.
- Hoadley, R.B. (1977). "Comparison of Lag Screws and Threaded Nails in a Typical Structural Joint," *Forest Products Journal*, 27(12), 40-47.
- Hu, J. (1990). "Strength Analysis of Wood Single Bolted Joints," *PhD Dissertation*, Department of Civil Engineering, University of Wisconsin, Madison, Wisconsin, 144 pp.
- Humphrey, P.E. and Ostman, L.J. (1989). "Bolted Timber Connections Part II: Bolt Bending and Associated Wood Deformation," *Wood and Fiber Science*, 21(4), 354-366.

- Hunt, R.D. and Bryant, A.H. (1990). "Laterally Loaded Nail Joints in Wood," *Journal of Structural Engineering*, ASCE, 116(1), 111-124.
- Hyer, M.W., Klang, E.C. and Cooper, D.E. (1987). "The Effects of Pin Elasticity, Clearance, and Friction on the Stresses in a Pin-loaded Orthotropic Plate," *Journal of Composite Materials*, 21(3), 190-206.
- Ifju, G. (1964). "Tensile Strength Behavior as a Function of Cellulose in Wood," *Forest Products Journal*, 14(8), 366-372.
- Inglis, C.E. (1913). "Stresses in a Plate Due to the Presence of Cracks and Sharp Corners," *Proceedings of the Institute of Naval Architects*, Vol. 60.
- International Organization for Standardization (1998). "Timber Structures – Dowel-type Fasteners, Part I: Determination of Bending Strength," *Draft International Standard ISO/DIS 10984-1*, 5 pp.
- Irwin, G.R. (1957). "Analysis of Stresses and Strains Near the End of a Crack Traversing a Plate," *Journal of Applied Mechanics*, Vol. 24, 361-364.
- Irwin, G.R. (1958). "Fracture," in *Handbuch der Physik*, Vol. VI, Springer, Berlin, Germany.
- Irwin, G.R. (1960). "Fracture Mechanics," in *Structural Mechanics*, Pergamon Press, New York, New York.
- Irwin, G.R. (1962). "Analytical Aspects of Crack Stress Field Problems," *T&AM Report No. 213*, University of Illinois, Champaign, Illinois.
- Ishimaru, Y., Arai, K., Mizutani, M., Oshima, K. and Iida, I. (2001). "Physical and Mechanical Properties of Wood After Moisture Conditioning," *Journal of Wood Science*, The Japan Wood Research Society, Springer, 47(3), 185-191.
- James, W.L. (1962). "Dynamic Strength and Elastic Properties of Wood," *Forest Products Journal*, 12(6), 253f.
- Jayne, B.A. and Hunt, M.O. (1969). "Plane Stress and Plane Strain in Orthotropic and Anisotropic Media," *Wood and Fiber*, 1(3), 236-247.
- Jenkins, C.F. (1920). "Report on Materials of Construction Used in Aircraft and Aircraft Engines," Min. Munitions – Aircraft Production Department – Aeronautical Research Committee, 162 pp.
- Jessome, A.P. (1962). "Strength Properties of Wood Treated with Fire Retardants," *Report No. 193*, Canadian Forest Products Laboratory.

Johansen, K.W. (1949). "Theory of Timber Connections," *International Association for Bridge and Structural Engineering Publication*, Vol. 9, 249-262.

Johnson, J.A. (1973). "Crack Initiation in Wood Plates," *Wood Science*, 6(2), 151-158.

Jorissen, A. (1998). "Double Shear Timber Connections with Dowel Type Fasteners," *PhD Dissertation*, Delft University of Technology, Delft, The Netherlands, December 1998.

Jorissen, A. (1999). "Multiple Fastener Timber Connections with Dowel Type Fasteners," *Proceedings of Pacific Timber Engineering Conference, Vol. 3, Rotorua, New Zealand, March 14-18, 1999, Forest Research Bulletin No. 212*, G.B. Walford and D.J. Gaunt, eds., 267-274.

Kanninen, M.F., Rybicki, E.F. and Brinson, H.F. (1977). "A Critical Look at Current Applications of Fracture Mechanics to the Failure of Fibre-reinforced Composites," *Composites*, 8(1), 17-22.

Karacabeyli, E., Fraser, H. and Deacon, W. (1998). "Lateral and Withdrawal Load Resistance of Glulam Rivet Connections Made with Sawn Timber," *Canadian Journal of Civil Engineering*, 25(1), 128-138.

Keenan, F.J., Lepper, M.M. and Marshall, C.M. (1982). "Improved Design of Fastenings in Timber Structures Based on Limit States Design Procedures," Canadian Forestry Service, Hull, Quebec, Canada.

Kellog, R.M. and Ifju, G. (1962). "Influence of Specific Gravity and Certain Other Factors on the Tensile Properties of Wood," *Forest Products Journal*, 10(12), 463-470.

Kharouf, N., McClure, G. and Smith, I. (1999). "Fracture Modeling of Bolted Connections in Wood and Composites," *Journal of Materials in Civil Engineering*, ASCE, 11(4), 345-352.

Klauditz, W. (1952). "Zur Biologisch-Mechanischen Wirkung des Lignins im Stammholz der Nadelund Laubholzer," *Holzforsch*, Vol. 6, 70-82.

Klauditz, W. (1957). "Zur Biologisch-Mechanischen Wirkung der Cellulose und Hemicellulose im Festigungsgewebe der Laubholzer," *Holzforsch*, Vol. 11, 110-116.

Kretschmann, D.E., Green, D.W. and Nelson, W.J. (1990). "The Effect of Moisture Content on Mode I Fracture Toughness in Southern Pine," *IUFRO S5.02, Timber Engineering: Proceedings of the 1990 Conference, Vol. I*, St. John, New Brunswick and Montreal, Quebec, Canada, July/August 1990, 274-303.

Kuenzi, E.W. (1955). "Theoretical Design of a Nailed or Bolted Joint Under Lateral Load," *Research Paper No. D1951*, USDA, Forest Service, Forest Products Laboratory, Madison, Wisconsin.

Kuipers, J. (1960). *Research into Split Ring Connections: Elements Connected at an Angle* (in Dutch) Rapport 4-60-1HV-18, Stevin Laboratorium, Delft University Press, Delft, Netherlands, 264 pp.

Kuipers, J. and Vermeyden, P. (1965). "Research on Timber Joints in the Netherlands," *Proceedings CIB-TRADA International Symposium on Joints in Timber Structures*, London, England.

Lantos, G. (1969). "Load Distribution in a Row of Fasteners Subjected to Lateral Load," *Wood Science*, 1(3), 129-136.

Larsen, H.J. (1973). "The Yield Load of Bolted and Nailed Joints," *Meeting of International Union of Forestry Research Organisations: Wood Engineering Group, Proceedings Vol. 2, Pretoria, South Africa, 1973*, 646-654.

Larsen, H.J. (1975). "Determination of Load-slip Curves for Bolts and Nails," *Meeting of International Union of Forestry Research Organisations: Wood Engineering Group, Proceedings Vol. 1, Delft, Holland, April 1975*, 1-11.

Larsen, H.J. and Reestrup, V. (1969). "Tests on Screws in Wood," *Bygningsstatistiske Meddelelser*, 40(1), 3-36.

Lau, P.W.C. (1990). "Factors Affecting Crack Formation in Wood as a Result of Nailing," *IUFRO S5.02, Timber Engineering: Proceedings of the 1990 Conference, Vol. I*, St. John, New Brunswick and Montreal, Quebec, Canada, July/August 1990, 250-259

Lau, P.W.C. (1992). "Rationalizing Spacing Requirements for Nailed Wood Connections by Induced Wood Splitting," *Canadian Journal of Civil Engineering*, 19(5), 842-846.

Lau, P.W.C. and Tardif, Y. (1990). "A Computer-Aided Image System for Analyzing Cracks Created by Nailing in Wood," *Journal of Testing and Evaluation*, ASTM, 18(2), 131-137.

Lawn, B.R. and Wilshaw, T.R. (1975). *Fracture of Brittle Solids*, Cambridge University Press, Cambridge, England, 1975, 204 pp.

Lei, Y.K. and Wilson, J.B. (1979). "Fracture Toughness of Parallel-laminated Veneer," *Forest Products Journal*, 29(8), 28-32.

Leicester, R.H. (1974). "Application of Linear Fracture Mechanics to the Design of Timber Structures," *1974 Conference of the Australian Fracture Group, Melbourne, Australia, October 23, 1974*, 157-164.

Leicester, R.H. (1983). "The Fracture Strength of Wood," *Workshop on Timber Engineering, Melbourne, Australia*, Vol. 11, 24 pp.

Lekhnitskii, S.G., Tsai, S.W. and Cheron, T. (1968). *Anisotropic Plates*, Gordon and Breach Science Publishers: New York, New York, 534 pp.

Li, F.Z., Shih, C.F. and Needleman, A. (1985). "A Comparison of Methods for Calculating Energy Release Rates," *Engineering Fracture Mechanics*, 21(2), 405-421.

Liska, J.A. (1955). "Effect of Rapid Loading on the Compressive and Flexural Strength of Wood," *U.S. Forest Service Research Paper No. R1767*, U.S. Forest Products Laboratory, Madison, Wisconsin.

Liu, J.Y. and Soltis, L.A. (1984). "Lateral Resistance of Nailed Joints – A Test Method," *Forest Products Journal*, 34(1), 55-60.

Liu, C.H., Wong, J.Y., Chen, D.L., Weiss, B. and Stickler, R. (1996). "Numerical Evaluation of Stress Distributions Ahead of Crack Tip for Finite-Width Center Cracked Specimens. IV. Loaded by a pair of Splitting Forces Acting at an Arbitrary Location on the Crack," *International Journal of Fracture*, 76(1), R3-R9.

Longworth, J. and McMullin, A.E. (1963). "Effect of Moisture Content on Strength of Bolted Timber Connections," *Forest Products Journal*, 13(3), 104-107.

Luxford, R.F. and MacLean, J.D. (1951). "Effect of Pressure Treatment with Coal-tar Creosote on the Strength of Douglas-fir Structural Timber," *Report No. 1798*, U.S. Department of Agriculture, Forest Products Laboratory.

Mack, J.J. (1960). "The Strength of Nailed Timber Joints I," *Division of Forest Products Technological Paper No. 9*, Division of Forest Products Commonwealth Scientific and Industrial Research Organization, Melbourne, Australia.

Mack, J.J. (1966). "The Strength and Stiffness of Nailed Joints under Short-Duration Loading," *Division of Forest Products Technological Paper No. 40*, Commonwealth Scientific and Industrial Research Organization, Melbourne, Australia, 1-28.

Madsen, B. (1975). "Duration of Load Tests for Wood in Tension Perpendicular to Grain," *Forest Products Journal*, 25(8), 48-53.

Madsen, B. (2000). *Behaviour of Timber Connections*, Timber Engineering Ltd., North Vancouver, British Columbia, Canada.

Mai, Y.W. (1975). "On the Velocity-Dependent Fracture Toughness of Wood," *Wood Science*, 8(1), 364-367.

Mall, S., Murphy, J.F. and Shottafer, J.E. (1983). "Criterion for Mixed-mode Fracture in Wood," *Journal of Engineering Mechanics*, 109(3), 680-690.

Markwardt, L.J. and Liska, J.A. (1955). "The Influence of Rate of Loading on the Strength of Wood and Wood-Base Materials," *Symposium on Speed of Testing of Non-metallic Materials*, 3-18.

Markwardt, L.J. and Wilson, T.R.C. (1935). "Strength and Related Properties of Woods Grown in the United States," *Technical Bulletin No. 479*, USDA, Washington, D.C., 1-99.

Markwardt, L.J. and Youngquist, W. G. (1956). "Tension Test Methods for Wood, Wood-Base Materials, and Sandwich Constructions," *FPL-2055*, Forest Products Laboratory, Forest Service, USDA, Madison, Wisconsin.

Masse, D.I., Salinas, J.J. and Turnbull, J.E. (1988). "Lateral Strength and Stiffness of Single and Multiple Bolts in Glued-Laminated Timber Loaded Parallel to Grain," Unpublished Report, Engineering and Statistics Research Centre, Agric Canada, Ottawa, Ontario, Canada.

McLain, T.E. (1976). "Curvilinear Load-Slip Relations in Laterally Loaded Nailed Joints," *Recent Research with Mechanical Fasteners in Wood: Proceedings of the Forest Products Research Society, No. P-76-16*, Toronto, Ontario, Canada, July 1976, 33-51.

McLain, T.E. (1984). "Lag Screw Joint Design," *Fastener Technology International*, 7(6), 43-46.

McLain, T.E. (1992). "Strength of Lag-Screw Connections," *Journal of Structural Engineering*, ASCE, 118(10), 2855-2871.

McLain, T.E. (1997). "Design Axial Withdrawal Strength from Wood: I. Wood Screws and Lag Screws," *Forest Products Journal*, 47(5), 77-84.

McLain, T.E. and Carroll, J.D. (1990). "Combined Load Capacity of Threaded Fastener-Wood Connections," *Journal of Structural Engineering*, ASCE, 116(9), 2419-2432.

McLain, T.E. and Thangjitham, S. (1983). "Bolted Wood Joint Yield Model," *Journal of the Structural Division*, ASCE, 109(8), 1820-1835.

Mindess, S. and Nadeau, J.S. (1975). "Slow Crack Growth in Wood," *Meeting of International Union of Forestry Research Organisations: Wood Engineering Group, Proceedings Vol. 1, Delft, Holland, 1975*, 1-21.

Moller, T. (1951). "En ny Metod for Berakning av Spikforband," *Report No. 117*, Chalmers University of Technology, Sweden.

Moran, B. and Shih, C.F. (1987). "A General Treatment of Crack Tip Contour Integrals," *International Journal of Fracture*, Vol. 35, 295-310.

Morgner, W., Niemz, P. and Theis, K. (1980). "Use of Acoustic Emission Analysis for the Investigation of Failure and Creep Processes in Wood Product.," *Holztechnologie*, 21(2), 77-82.

Moss, P.J. (1997). *Multiple-Bolted Joints in Wood Members: A Literature Review, General Technical Report FPL-GTR-97*, USDA and Forest Products Laboratory, Washington, D.C.

Mostovoy, S., Crosley, P.B. and Rippling, E.J. (1967). *Journal of Materials*, Vol. 2, 425-428.

Murphy, J.F. (1988). "Mode II Wood Test Specimen: Beam with Center Slit," *Journal of Testing and Evaluation*, 16(4).

NFPA (1986). *National Design Specification for Wood Construction*, National Forest Products Association, Washington, D.C., 87 pp.

Nadeau, J.S. (1979). "Fracture Mechanics: An Overview," *Proceedings of the First International Conference on Wood Fracture, Banff, Alberta, Canada, 14-16 August, 1978*, Forintek Canada Corp., Western Forest Products Laboratory, Vancouver, British Columbia, Canada, July 1979, 175-186.

Newlin, J.A. and Gahagan, J.M. (1938). *Lag-Screw Joints: Their Behavior and Design, Technical Bulletin No. 597*, USDA, Washington, D.C.

Newlin, J.A. and Trayer, G.W. (1924). "Deflection of Beams with Especial Reference to Shear Deformations," National Advisory Committee for Aeronautics, Report No. 180, Washington, D.C.

Niemz, P. (1993). *Physik des Holzes und der Holzwerkstoffe*, DRW-Verlag Weinbrenner GmbH & Co., Leinfelden-Echterdingen.

Nordtest (1981a). *Nails in Wood: Bending Strength, NT Build 136*, Stockholm, Sweden: Nordtest, Box 5103, S-102 43.

Nordtest (1981b). *Nails in Wood: Embedding Strength, NT Build 135*, Stockholm, Sweden: Nordtest, Box 5103, S-102 43.

Nordtest (1981c). *Nails in Wood: Lateral Strength, NT Build 133*, Stockholm, Sweden: Nordtest, Box 5103, S-102 43.

Nordtest (1981d). *Nails in Wood: Withdrawal Strength, NT Build 134*, Stockholm, Sweden: Nordtest, Box 5103, S-102 43.

Noren, B. (1951). *Strength of Bolted Wood Joints, Especially the Influence of Washer Size on Strength and Stiffness in Single Shear*, Australia, CSIRO, Translation 9373. (Translated from Svenska Traforskning Institutet, Meddelande, 22b.)

Noren, B. (1954). "Relation Between Compressive Strength and Rate of Deformation in Testing Swedish Fir," *ASTM Bulletin No. 202*, 43 pp.

Noren, B. (1961). "Nailed Joints: A Contribution to the Theoretical Analysis of Yield and Strength," *Proceedings of the International Conference on Timber Engineering, Southampton, England, 1961*, 66-76.

Noren, B. (1974). *Formulas Indicating the Strength of Mechanical Wood Joints*, Swedish Forest Products Research Laboratory, Stockholm, Sweden, Series B, No. 226, 20 pp.

Osherovich, L. (1955). "Tensile Tests on Timber Perpendicular to Grain," *Zarodskaya Laboratoriya, Transl. No. 3128, C.S.I.R.O.*, Vol. 21, Melbourne, Australia, 3 pp.

Ott, R.L. and Longnecker, M. (2001). *An Introduction to Statistical Methods and Data Analysis, 5th ed.*, Duxbury Thomson Learning, Pacific Grove, California, 1152 pp.

Palka, L.C. (1973). "Predicting the Effect of Specific Gravity, Moisture Content, Temperature and Strain rate on the Elastic Properties of Softwoods," *Wood Science and Technology*, 7(2), 127-141.

Panshin, A.J. and De Zeeuw, C. (1970). *Textbook of Wood Technology, Vol. I*, McGraw Hill, New York, New York, 1970, 226 pp.

Parhizgar, S., Zachary, L.W., and Sun, C.T. (1982). "Application of the Principles of Linear Fracture Mechanics to the Composite Materials," *International Journal of Fracture*, Vol 20, 3-15.

Paris, P.C. and Sih, G.C. (1964). "Stress Analysis of Cracks," in *Fracture Toughness Testing and its Applications, ASTM Special Technical Publication No. 381*, Sixty-seventh Annual Meeting of the American Society of Testing and Materials, Chicago, Illinois, June 21-26, 1964, 30-81.

Patton-Mallory, M. (1989). "Yield theory of bolted connections compared with current U.S. design criteria," *Proceedings of the Pacific Timber Engineering Conference, Wellington, New Zealand*, Institute of Professional Engineers, 323-329.

Patton-Mallory, M. (1996). "The Three-dimensional Mechanics and Failure of Single Bolt Wood Connections," *PhD Dissertation*, Civil Engineering Department, Colorado State University, Ft. Collins, Colorado, March 1996.

Patton-Mallory, M. and Cramer, S.M. (1987). "Fracture Mechanics: A Tool for Predicting Wood Component Strength," *Forest Products Journal*, 37(7/8), 39-47.

Patton-Mallory, M., Pellicane, P.J. and Smith, F.W. (1997b). "Modeling Bolted Connections in Wood: Review," *Journal of Structural Engineering*, 123(8), 1054-1062.

Pearson, R.G. (1974). "Application of Fracture Mechanics to the Study of the Tensile Strength of Structural Lumber," *Holzforschung*, 28(1), 11-19.

Pellicane, P.J. (1980). "Ultimate Tensile Strength Analysis of Wood," *PhD Dissertation*, Dept. of Forest and Wood Science, Colorado St. University, Ft. Collins, Colorado, Fall, 1980.

Pellicane, P.J., Bodig, J. and Goodman, J.R. (1983). "Simulation of the Tensile Strength-Fracture Toughness Relationship," *Wood Science*, 14(4), 168-177.

Petterson, R.W. and Bodig, J. (1983). "Prediction of Fracture Toughness of Conifers," *Wood and Fiber Science*, 15(4), 302-316.

Petterson, R.W., Bodig, J., Smith, F.W., Goodman, J.R. and Pellicane, P.J. (1981). "Prediction of Mode I TL Fracture Toughness for Conifers," *Structural Research Report No. 39*, Civil Engineering Department, Colorado State University, Ft. Collins, Colorado.

Plumier, A. (1994). "Behavior of Connections," *Journal of Construction Steel Research*, 29(1-3), 95-119.

Porter, A.W. (1964). "On the Mechanics of Fracture in Wood," *Forest Products Journal*, 14(8), 325-331.

Price, A.T. (1928). "A Mathematical Discussion on the Structure of Wood in Relation to Its Elastic Properties," *Philosophical Transactions of the Royal Society of London*, Series A:228, 1-62.

Prokopski, G. (1993). "The Application of Fracture Mechanics to the Testing of Wood," *Journal of Materials Science*, 28(22), 5995-5999.

ProModel Corporation (1999). *ProModel 4.2, Stat:Fit, version 110.06.2*, Geer Mountain Softward Corp.

Pugel, A.D. (1986). "Fracture Mechanics-Based Failure Criterion for the Tensile Strength of Wood," *Ph.D. Dissertation*, Dept. of Forest and Wood Science, Colorado State University, Fort Collins, Colorado, Summer, 1986.

Rammer, D.R., Winistorfer, S.G. and Bender, D.A. (2001). "Withdrawal Strength of Threaded Nails," *Journal of Structural Engineering*, 127(4), 442-449.

Rammer, D.R. and Winistorfer, S.G. (2001). "Effect of Moisture Content on Dowel-Bearing Strength," *Wood and Fiber Science*, 33(1), 126-139.

Rance, H.F. (1948). "Some New Studies on the Strength Properties of Paper," *Proceedings of the Papermakers Association*, G.B.I..

Rankine, W.J.M. (1895). *Applied Mechanics*, 15th ed., Griffin and Company, London, England.

Rice, J.R. (1968). "A Path Independent Integral and the Approximate Analysis of Strain Concentration by Notches and Cracks," *ASME Journal of Applied Mechanics*, Vol. 35, 379-386.

Riipola, K. and Fonselius, M. (1988). "Evaluation of Critical J-integral for Wood Material," *VTT Report 528*, Espoo, Finland.

Rodd, P.D. (1988). "Timber Joints Made with Improved Circular Dowel Fasteners," *Proceedings of the International Timber Engineering Conference, Seattle, Washington*, Vol. 1, 26-37.

Rodd, P.D. (1999). "Improvement of the Structural Behavior of Timber Joints," *COST C1: Control of the Semi-Rigid Behaviour of Civil Engineering Structural Connections: Proceedings of the International Conference, September 17-19, 1998, Liege*, Office for Official Publications of the European Communities, 285-294.

Rubio-Gonzalez, C. and Mason, J.J. (2001). "Green's Functions for the Stress Intensity Factor Evolution in Finite Cracks in Orthotropic Materials," *International Journal of Fracture*, 108(4), 317-336.

Saada, A.S. (1974). *Elasticity Theory and Applications*, Robert E. Krieger Publishing Company, Malabar, Florida.

Salmon, C.G. and Johnson, J.E. (1980). *Steel Structures – Design and Behavior*, 2nd Edition, Harper and Row, New York, New York, 1007 pp.

Samarasinghe, S. and Kulasiri, D. (1999). "Fracture Toughness of Wood Based on Experimental Near-Tip Displacement Fields and Orthotropic Theory," *Proceedings of Pacific Timber Engineering Conference, Vol. 1, Rotorua, New Zealand, March 1999*, 292-299.

Saouma, V.E. (1980). "Interactive Finite Element Analysis of Reinforced Concrete: A Fracture Mechanics Approach," *PhD Dissertation*, Cornell University, Ithaca, New York.

Saouma, V.E. and Sikiotis, E.S. (1986). "Stress Intensity Factors in Anisotropic Bodies Using Singular Isoparametric Elements," *Engineering Fracture Mechanics*, 25(1), 115-121.

Sa`Ribeiro, R.A. and Sa`Ribeiro, M.G. (1991). "Load Slip Behavior of Nailed Joints: An Improved Model," *Proceedings of the 1991 International Timber Engineering Conference, Vol. 3, London, U.K., Sept. 2-5, 1991*, Trada, 3.03-3.10.

Sato, K., Fushitani, M. and Noguchi, M. (1984). "Discussion of Tensile Fracture of Wood Using Acoustic Emissions. Estimation of Tensile Strength and Consideration of AE Generation Based on Fracture Mechanics," *Mokuzai Gakkaishi*, Japan Wood Research Society, 30(2), 117-123.

Schachner, H., Reiterer, A. and Stanzl-Tschegg, S.E. (2000). "Orthotropic Fracture Toughness of Wood," *Journal of Materials Science Letters*, 19(20), 1783-1785.

Schniewind, A.P. (1962). "Tensile Strength Perpendicular to Grain as a Function of Moisture Content in California Black Oak," *Forest Products Journal*, 12(5), 249-252.

Schniewind, A.P. and Centeno, J.C. (1973). "Fracture Toughness and Duration of Load Factor I. Six Principal Systems of Crack Propagation and the Duration Factor for Cracks Propagating Parallel to Grain," *Wood and Fiber*, 5(2), 152-159.

Schniewind, A.P. and Lyon, D.E. (1973). "A Fracture Mechanics Approach to the Tensile Strength Perpendicular to Grain of Dimension Lumber," *Wood Science and Technology*, 7(1), 45-59.

Schniewind, A.P., Ohgama, T., Aoki, T. and Yamada, T. (1982). "Effect of Specific Gravity, Moisture Content, and Temperature on Fracture Toughness of Wood," *Wood Science*, 15(2), 101-109.

Schniewind, A.P. and Pozniak, R.A. (1971). "On the Fracture Toughness of Douglas Fir Wood," *Engineering Fracture Mechanics*, 2(3), 223-233.

Shah, R.C. (1974). "Fracture Under Combined Modes in 4340 Steel," in *Fracture Analysis, ASTM STP560, in Proceedings of the 1973 National Symposium on Fracture Mechanics, Part II, University of Maryland, College Park, Maryland, August 27-29, 1973*, American Society for Testing and Materials, Philadelphia, Pennsylvania, 29-52.

Shaw, R.D. and Pitchen, R.G. (1978). "Modifications to the Suhara-Fukuda Method of Network Generation," *International Journal for Numerical Methods in Engineering*, Vol. 12, 93-99.

Shih, C.F., Moran, B. and Nakamura, T. (1986). "Energy Release Rate along a Three-Dimensional Crack Front in a Thermally Stressed Body," *International Journal Fracture*, Vol. 30., 79-102.

Showalter, J., Line, P. and Douglas, B.K. (1999). "Calculation of Lateral Connection Values Using General Dowel Equations," *Presentation at the 1999 ASAE/CSAE-SCGR Annual International Meeting, Toronto, Ontario, Canada, July 1999*, 1-11.

Sih, G.C. (1973). *Handbook of Stress Intensity Factors*, George C. Sih, ed.

Sih, G.C., Paris, P.C. and Irwin, G.R. (1965). "On Cracks in Rectilinearly Anisotropic Bodies," *International Journal of Fracture Mechanics*, 1(3), 189-203.

Skelton, J. (1970). "The Tensile Behavior of Fibrous Materials at High Rates of Strain and Subambient Temperatures," *Materials Research Standards*, 10(6), 20-25.

Skulteti, M.J., Bender, D.A., Winistorfer, S.G. and Pollock, D.G. (1997). "Withdrawal Strength of Ring-shank Nails Embedded in Southern Pine Lumber," *Transactions of the ASAE*, 40(2), 451-456.

Smart, J.V. (2002). "Capacity Resistance and Performance of Single-Shear Bolted and Nailed Connections: An Experimental Investigation," *M.S. Thesis*, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, August 2002.

Smart, J.V., Kelley, T.H. and Dolan, J.D. (2001). "Verification of the European Yield Model for Nailed Connections with Reduced Fastener Penetration," *Virginia Polytechnic Institute and State University Timber Engineering Report, No. TE-2001-001*, June 2001, Department of Wood Science and Forest Products, Brooks Center Products Center, Blacksburg, Virginia, 15 pp.

Smith, I. (1980). "A Review of Analytical and Empirical Models Used to Predict the Strength and Stiffness Characteristics of Timber Joints with Dowel Type Connectors," *Research Report 1/80*, Timber Research and Development Association, Stocking Lane, Hughenden Valley, High Wycombe, Bucks, England, August 1980, 41 pp.

Smith, I. (1982a). "Analysis of Mechanical Timber Joints with Dowel Type Connectors Subject to Short-term Lateral Loading by Finite Element Approximation," *Timber Research and Development Association, Research Report 2/82*.

Smith, I. (1982b). "Failure Criteria for Timber Subjected to Complex Stress States due to Short Term Loading," *Timber Research and Development Association, Research Report 3/82*, High Wycombe, Bucks.

Smith, I. and Chui, Y.H. (1991). "Mode I Fracture Energy of Plantation-Grown Red Pine," *Proceedings of the 1991 International Timber Engineering Conference, Vol. 3, London, U.K., September 1991*, 3.399-3.406.

Smith, I. and Chui, Y.H. (1994). "Factors Affecting Mode I Fracture Energy of Plantation-Grown Red Pine," *Wood Science and Technology*, 28(2), 147-157.

Smith, I. and Foliente, G. (2002). "Load and Resistance Factor Design of Timber Joints: International Practice and Future Direction," *Journal of Structural Engineering*, ASCE, 128(1), 48-59.

Smith, I. and Hu, L.J. (1994). "Fracture Analysis of Bolted Timber Connections," *Proceedings of Structures Congress XII, Atlanta, Georgia, April 25-27, 1994*, ASCE, 912-917.

Smith, I., Whale, L.R.J., Anderson, C., Hilson, B.O. and Rodd, P.D. (1988). "Design Properties of Laterally Loaded Nailed or Bolted Wood Joints," *Canadian Journal of Civil Engineering*, 15(4), 633-643.

Snedden, I.N. (1946). "The Distribution of Stress in the Neighborhood of a Crack in an Elastic Solid," *Proceedings of the Royal Society of London*, Vol. A-187.

Sobue, N., Bajolet, D. and Pluinage, G. (1985). "Effect of Drying Stress on the Fracture Toughness of Wood," *Mokuzai Gakkaishi*, 31(7), 528-531.

Soltis, L.S., Hubbard, F.K. and Wilkinson, T.L. (1986). "Bearing Strength of Bolted Timber Joints," *Journal of Structural Engineering*, 112(9), 2141-2154.

Soltis, L.A., Karnasuidja, S. and Little, J.K. (1987). "Angle to Grain Strength of Dowel-Type Fasteners," *Wood and Fiber Science*, 19(1), 68-80.

Soltis, L.A. and Wilkinson, T.L. (1987). "Bolted Connection Design," *General Technical Report FPL-GTR-54*, USDA, Forest Service, Forest Products Laboratory, Madison, Wisconsin.

Stahl, D.C., Cramer, S.M. and McDonald, K. (1990). "Modeling the Effect of Out-of-Plane Fiber Orientation in Lumber Specimens," *Wood and Fiber Science*, 22(2), 173-192.

Stanzl-Tschegg, S.E., Tan, D.M. and Tschegg, E.K. (1995). "New Splitting Method for Wood Fracture Characterization," *Wood Science and Technology*, 29(1), 31-50.

Stanzl-Tschegg, S.E., Tschegg, E.K. and Teischinger, A. (1994). "Fracture Energy of Spruce Wood After Different Drying Procedures," *Wood and Fiber Science*, 26(4), 467-478.

Stern, E.G. (1959). "Wood Screws for Building Construction and Wood Products Assembly," *Wood Research Laboratory Bulletin, Series 39*, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, 11 pp.

- Stluka, R.T. (1960). "Theoretical Design of a Nailed or Bolted Joint under Load, *M.S. Thesis*, University of Wisconsin, Madison, Wisconsin, 1960.
- Strickler, M.D. and Pellerin, R.F. (1973). "Rate of Loading Effect on Tensile Strength of Wood Parallel to the Grain," *Forest Products Journal*, Vol. 23, 34-36.
- Tan, D.M., Stanzl-Tschegg, S.E. and Tschegg, E.K. (1995). "Models of Wood Fracture in Mode I and Mode II," *Holz als Roh- und Werkstoff*, 53(3), 159-164.
- Theilen, R., Bender, D.A., Pollock, D.G. and Winistorfer, S. (1997). "Lateral Performance of Ring-shank Nails in Southern Pine Lumber," *Frame Builder News*, January 1997, 62-71.
- Thomas, B. and Malhotra, S.K. (1985). "Behavior of Timber Joints with Multiple Nails," *Journal of Structural Engineering*, ASCE, 111(5), 973-991.
- Thuvander, F., Sjudahl, M. and Berglund, L.A. (2000). "Measurements of Crack Tip Strain Field in Wood at the Scale of Growth Rings," *Journal of Materials Science*, 35(24), 6267-6275.
- Tiemann, H.D. (1908). "The Effect of Speed of Testing and Rate of Deformation in Testing Swedish Fir," *ASTM Bulletin*, No. 202, 43 pp.
- Timoshenko, S. (1955). *Strength of materials, 3rd ed., Part I. Elementary Theory and Problems*, Van Nostrand, New York, New York.
- Timoshenko, S. and Goodier, J. (1951). *Theory of Elasticity, 2nd ed.*, McGraw-Hill, New York, New York.
- Tokuda, M, Hirashima, A. and Matsubara, H. (1989a). "The Strength of Lag-Screw Joints. I. Lateral Strength Parallel-to-Grain," *Journal of the Japan Wood Research Society*, 35(6), 473-481 (in Japanese).
- Tokuda, M. Hirashima, A. and Miyakoshi, M. (1989b). "The Strength of Lag-Screw Joints. II. Lateral Strength Perpendicular-to-Grain," *Journal of the Japan Wood Research Society*, 35(6), 482-488 (in Japanese).
- Tomin, M. (1971). "Influence of Wood Orthotropy on Basic Equations of Linear Fracture Mechanics," *Drevarsky Vyskum*, 16(4), 219-230.
- Tomin, M. (1972). "Influence of Anisotropy on Fracture Toughness of Wood," *Wood Science*, 5(2), 118-121.
- Trayer, G.W. (1932). "The Bearing Strength of Wood Under Bolts," *Technical Bulletin No. 332*, USDA, Forest Service, Forest Products Laboratory, Washington, D.C., 1-40.

Triboulot, P., Jodin, P. and Pluvinage, G. (1984). "Validity of Fracture Mechanics Concepts Applied to Wood by Finite Element Calculation," *Wood Science and Technology*, 18(1), 51-58.

Tschegg, E.K., Fruhmann, K. and Stanzl-Tschegg, S.E. (2001). "Damage and Fracture Mechanisms during Mode I and III Loading of Wood," *Holzforschung*, 55(5), 525-533.

Valentin, G.H. and Adjanooun (1992). "Applicability of Classical Isotropic Fracture Mechanics Specimens to Wood Propagation Studies," *Materials and Structures*, 25(145), 3-13.

Valentin, G.H., Bostrom, L., Gustafsson, P.J., Ranta-Maunus, A. and Gowda, S. (ed.) (1991). *Application of Fracture Mechanics to Timber Structures: RILEM State-of-the-Art Report, Espoo, Sweden, July 1991*, Valtion teknillinen tutkimuskeskus, Tiedotteita – Statens tekniska forskningscentral, Meddelanden – Technical Research Centre of Finland, Research Notes 1262, 142 pp. + app. 2 pp.

Valentin, G.H. and Caumes, P. (1989). "Crack Propagation in Mixed Mode in Wood: A New Specimen," *Wood Science Technology*, Vol. 23, 43-53.

Valentin, G. and Morlier, P. (1982). "A Criterion of Crack Propagation in Timber," *Materials and Structures*, 15(88), 291-298.

Vasic, S. and Smith, I. (1996a). "On the Influence of Ultrastructure and Fibres Bridging in Mode I Fracture of Wood," *KWSF '96, Proceedings of the 2nd International Conference on the Development of Wood Science/Technology and Forestry, The Buckinghamshire College, U.K. and University of Sopron, Sopron, Hungary, April 10-12, 1996*.

Vasic, S. and Smith, I. (1996b). "The Brittleness of Wood in Tension Perpendicular to the Grain: Micromechanical Aspects," *Proceedings of the International COST 508 Wood Mechanics Conference, Stuttgart, Germany, May 14-16, 1996*, 555-569.

Vasic, S. and Smith, I. (1999a). "Contact-crack Problem in Wedge-splitting of Wood," *RILEM Symposium on Timber Engineering, Stockholm, Sweden, September 13-15, 1999*, 10 pp.

Vasic, S. and Smith, I. (1999b). "Fracture Analysis of Tensile Strength Perpendicular to the Grain," *RILEM Symposium on Timber Engineering, Stockholm, Sweden, September 13-15, 1999*, 10 pp.

Vasic, S. and Smith, I. (1999c). "The Effect of Bridging Stresses on Fracture Toughness of Wood," *RILEM Symposium on Timber Engineering, Stockholm, Sweden, September 13-15, 1999*, 10 pp.

Vasic, S. and Smith, I. (2002). "Bridging Crack Model for Fracture of Spruce," *Engineering Fracture Mechanics*, Vol. 69, 745-760.

Vasic, S., Smith, I. and Landis, E. (2002). "Fracture Zone Characterization – Micro-mechanical Study," *Wood and Fiber Science*, 34(1), 42-56.

Wangaard, F.F. (1950). *The Mechanical Properties of Wood*, John Wiley & Sons, New York, New York.

Weibull, W. (1939). *Ing. Vetenskaps Akad. Hanal, No. 151*.

Weibull, W. (1951). *Journal of Applied Mechanics*, Vol. 18, p. 293.

Westergaard, H.M. (1939). "Bearing Pressures and Cracks," *Transactions ASME: Journal of Applied Mechanics*, Vol. 6, A-49 – A-53.

Wilkinson, T.L. (1971). "Theoretical Lateral Resistance of Nailed Joints," *Journal of the Structural Division*, 97(ST5), 1381-1398.

Wilkinson, T.L. (1972). "Analysis of Nailed Joints with Dissimilar Members," *Journal of the Structural Division*, 98(ST9), 2005-2013.

Wilkinson, T.L. (1986). "Load Distribution Among Bolts Parallel to Load," *Journal of Structural Engineering*, 112(4), 835-852.

Wilkinson, T.L. (1991). "Dowel Bearing Strength," *Research Paper FPL-RP-505*, USDA, Forest Service, Forest Products Laboratory, Madison, Wisconsin.

Wilkinson, T.L. and Rowlands, R.E. (1981). "Analysis of Mechanical Joints in Wood," *Experimental Mechanics*, 21(11), 408-414.

Williams, J.G. (1988). "On the Calculation of Energy Rates for Cracked Laminates," *International Journal of Fracture*, Vol. 36, 101-119.

Williams, J.G. and Birch, M.W. (1976). "Fracture in Anisotropic Media, Cracks, and Fracture," *STP 601*, ASTM, 125-137.

Williams, M.L. (1957). "On the Stress Distribution at the Base of a Stationary Crack," *Transactions of the American Society of Mechanical Engineers, Journal of Applied Mechanics*.

Wills, B.L., Winistorfer, S.G., Bender, D.A. and Pollock, D.G. (1996). "Threaded-nail Fasteners – Research and Standardization Needs," *Transactions of the ASAE*, 39(2), 661-668.

Winistorfer, S.G. (1992). "Mechanical Fasteners in Wood," *Fastener Technology International*, 15(6), 39-41.

Winistorfer, S.G. (1995). "Practical Considerations of Dowel Bearing Strength and Annular Ring/Fastener Orientation," *Forest Products Journal*, 45(7/8), 64-68.

Wnuk, M.P. (1990). "Mathematical Modelling of Nonlinear Phenomena in Fracture Mechanics," *Nonlinear Fracture Mechanics: CISM Courses and Lectures No. 314*, International Centre for Mechanical Sciences, M.P. Wnuk, ed., Springer-Verlag, New York, 359-451.

Wood, L.W. (1947). "Behavior of Wood under Continued Loading," *Engineering News-Record*, 139(24), 804.

Wood Engineering and Construction Handbook (1999). Keith F. Faherty and Thomas G. Williamson, eds., 3rd Edition, McGraw-Hill, Inc., New York, New York.

Woodward, C. and Minor, J. (1988). "Failure Theories for Douglas-Fir in Tension," *Journal of Structural Engineering*, ASCE, 114(12), 2808-2813.

Wright, K. and Fonselius, M. (1986). "Fracture Toughness of Wood – Mode I," *CIB – W18: International Council for Building Research Studies and Documentation, Working Commission W18 – Timber Structures, Meeting 19, Dublin, Ireland, September 1986*, 1-14.

Wright, K. and Fonselius, M. (1987). "Fracture Mechanics Testing of Wood Methods for Mode I and Mode II," *Proceedings of the First International RILEM Congress, Versailles, France, Sept. 7-11, 1987*, Vol. 2, J.C. Maso, Ed., Chapman and Hall, New York, 764-771.

Wu, E.M. (1963). "Application of Fracture Mechanics to Orthotropic Plates," *T&AM Report No. 248*, Department of Theoretical and Applied Mechanics, University of Illinois, Urbana, Illinois.

Wu, E.M. (1967). "Application of Fracture Mechanics to Anisotropic Plates," *Journal of Applied Mechanics*, 34e(4), 967-974.

Yamauchi, T. and Hirano, H. (2000). "Examination of the Onset of Stable Crack Growth Under Fracture Toughness Testing of Paper," *Journal of Wood Science*, 46(1), 79-84.

Ylinen, A. (1962). "Comparative Investigation of the Influence of Loading and Deformation Rate on the Ultimate Strength of Wood," *Transl. FPL-562*, U.S. Department of Agriculture, Forest Products Laboratory, Madison, Wisconsin, 11 pp.

Youngs, R.L. (1957). "Mechanical Properties of Red Oak Related to Drying," *Forest Products Journal*, 7(10), 315-324.

Yuhara, T. and Kortshot, M.T. (1993). "A Simplified Determination of the J-integral for Paper," *Journal of Materials Science*, Vol. 28, 3571-3580.

Zahn, J.J. (1991). "Design Equation for Multiple Fastener Wood Connections," *Journal of Structural Engineering*, 117(11), 3477-3486.

Zahn, J.J. (1992). "Reliability of Bolted Wood Connections," *Journal of Structural Engineering*, ASCE, 118(12), 3362-3376.

Zanbergs, J.G. and Smith, F.W. (1988). "Finite Element Fracture Prediction for Wood with Knots and Cross Grain," *Wood and Fiber Science*, 20(1), 97-106.

Zikmunda, W. (1992). "Bruchmechanische Charakterisierung des Haftvemogens Zementgebundener Werkstoffe," *PhD Dissertation*, TU, Wien.