

---

## LIST OF TABLES

<b>TABLE</b>		<b>PAGE</b>
3.1	Molecular weight characteristics for the three PMP resins studied.	81
3.2	Summary of melt-extrusion conditions for Resin A.	82
3.3	Summary of melt-extrusion conditions for Resin B.	83
3.4	Summary of melt-extrusion conditions for Resin C.	83
3.5	The crystalline orientation ( $f_a$ and $f_c$ ), percent crystallinity, and melting points for the resin A films.	95
3.6	The crystalline orientation ( $f_a$ and $f_c$ ), percent crystallinity, & melting points for the resin B films.	99
3.7	The crystalline orientation ( $f_a$ and $f_c$ ), percent crystallinity, and melting points for the resin C films.	102
4.1	Molecular weight characteristics for the three PMP resins studied.	119
4.2	Pertinent characteristics of the precursor films utilized in this study.	122
4.3	Pertinent film characteristics of selected A1 annealed films.	137
4.4	The Gurley numbers and the %TS (top left corner of each cell) for A1 membranes. These membranes were products of different %CS and %HS combinations. All other annealing/stretching parameters remained intact with the standard condition.	156
4.5	The effect of different $T_{cs}$ and $T_{hs}$ combinations on the resulting A1 microporous film Gurley number – all other annealing/stretching parameters remained constant with the standard condition.	166
4.6	Final A1 film Gurley numbers, film thickness, and normalized Gurley numbers as a function of the %CS – all other annealing/stretching parameters remained constant with the standard condition.	167
5.1	Summary of melt-extrusion conditions for Resin D.	178
5.2	Summary of melt-extrusion conditions for Resin E.	179

---

5.3	Summary of melt-extrusion conditions for Resin F.	179
5.4	Molecular weight characteristics for the three POM resins studied.	187
5.5	The crystalline orientation ( $f_c$ ), total birefringence ( $\Delta_T$ ), long spacing ( $\ell$ ), mass fraction percent crystallinity ( $X_c$ ), and melting point ( $T_m$ ) for the resin D precursors.	191
5.6	The crystalline orientation ( $f_c$ ), total birefringence ( $\Delta_T$ ), long spacing ( $\ell$ ), mass fraction percent crystallinity ( $X_c$ ), and melting point ( $T_m$ ) for the resin E precursors.	203
5.7	The crystalline orientation ( $f_c$ ), total birefringence ( $\Delta_T$ ), long spacing ( $\ell$ ), mass fraction percent crystallinity ( $X_c$ ), and melting point ( $T_m$ ) for the resin F precursors.	209
6.1	Molecular weight characteristics for the two POM resins studied.	231
6.2	Pertinent characteristics for the melt-extruded films F1, F2, F3, & D1.	234
6.3	Pertinent film characteristics of selected D1 annealed films.	240
6.4	Pertinent annealed F1 film properties at different $t_a$ (min), $T_a$ ( $^{\circ}$ C), and percent tension combinations.	241
6.5	Pertinent annealed F1 film properties at different $t_a$ (min), $T_a$ ( $^{\circ}$ C), and percent tension combinations, where all other annealing/stretching parameters remained constant with the standard condition.	259
6.6	The Gurley number results from membranes of different %CS and $T_{cs}$ combinations. All other annealing/stretching parameters remained constant with the standard condition.	262
6.7	The Gurley number results from membranes of different %HS and $T_{hs}$ combinations. All other annealing/stretching parameters remained constant with the standard condition.	264
6.8	The Gurley number results from F1 microporous films, which were a product of different %CS and %HS combinations. The %TS is displayed in the top left corner of each cell. The other annealing/stretching parameters remained constant with the standard condition.	267

---

<b>8.1</b>	<b>Molecular weight characteristics &amp; thermal transition of the resins utilized in this study.</b>	<b>294</b>
<b>8.2</b>	<b>Contributions to the total haze for the polyethylene blown films utilized in this study.</b>	<b>294</b>
<b>8.3</b>	<b>Spherulitic Diameters based upon SALS patterns for some samples studied.</b>	<b>303</b>
<b>8.4</b>	<b>Contributions to total haze and spherulitic diameter for H cast roll films with P blend</b>	