

TABLE OF CONTENTS

ABSTRACT	ii
ACKNOWLEDGMENT	vi
TABLE OF CONTENTS	vii
LIST OF FIGURES	xi
LIST OF TABLES	xv
1. INTRODUCTION	1
1.1 Background	1
1.2 Problem Description	4
1.3 Purpose and Broad Objectives	6
1.4 Plan of Research	7
2. LITERATURE REVIEW	10
2.1 Introduction	10
2.2 U.S. Maglev Efforts	10
2.3 Superconductivity	11
2.4 Guideway Considerations	12
2.5 Status of AHS	13
2.6 Automatic Longitudinal Control	14
2.6.1 Car-Following Models	14
2.6.2 Autonomous Intelligent Cruise Control (AICC) Concept	15
2.6.3 Point-Following Control (PFC) Concept	16
2.7 Deterministic Control Systems	17
2.8 Vehicle Dynamics	18
2.8.1 Propulsive Force	18
2.8.2 Braking Resistance	19
2.8.3 Fluid Resistance	19
2.8.4 Rolling Resistance	20
2.8.5 Curve Resistance	20

2.8.6 Grade Resistance	20
2.9 AHS Schematics	21
2.10 Platooning on the AHS	25
3. TRANSPORTATION FOR SUSTAINABLE DEVELOPMENT	27
3.1 Introduction	27
3.2 Magnetic Levitation Systems	28
3.3 Maglev Vehicle Characteristics	33
3.4 Need for a Broader System Architecture	35
3.5 Decision Support System (DSS)	37
3.6 System Dynamics	39
3.7 Scenario Analysis	41
3.8 Sensitivity Analysis	41
3.9 Model Validation	42
4. THE AHS MAGLEV LAND USE TRANSPORTATION SYSTEM	44
4.1 Introduction	44
4.2 Intelligent Transportation Infrastructure (ITI)	47
4.3 Sustainable Development	50
4.4 Creating Accessible Cities	54
4.5 The Land Use and Transportation Subsystems	57
4.6 Application of the UTPP	61
4.7 The Supply Function	66
4.8 Economic Analysis	73
4.9 Nonuser Benefit Analysis	84
4.10 Impact on Air Travel	94
5. GUIDEWAY TRAFFIC FLOW RELATIONSHIPS	97
5.1 Introduction	97
5.2 The Macroscopic Approach	98
5.3 Platooning and Safe Following Distance	99
5.4 Network Assignment	106

5.5 Car Maneuvering	110
5.6 Platooning	117
5.7 Merging and Weaving	119
5.7.1 Ideal Gap	121
5.7.2 Delay-Oriented Approach	122
5.7.3 Multiple Merge Approach	124
5.7.4 Finite Capacity Queuing	125
5.7.5 State Depending Queuing	128
5.8 Summary of Merging	129
6. THREE-DIMENSIONAL CONTROL MODEL	135
6.1 Introduction	135
6.2 Vertical Control Model	135
6.3 Lateral Position Control	144
6.4 Lateral Position Control on Horizontal Curve	146
6.5 Longitudinal Control	150
6.6 Three-Dimensional Control Model	152
6.7 Longitudinal Control Model	156
6.7.1 Car Maneuvering Control Model	156
6.7.2 Spacing Dependent Control Model	159
6.7.3 Magnetic Coupling Control Model	177
6.7.4 Combinations of Longitudinal Control Models	177
6.8 Vehicle Motion on Curve	183
6.9 Integration of 3-D Models	190
7. SUMMARY AND DISCUSSION	193
7.1 Search for Perspective	193
7.2 Purpose, Premise and Approach	195
7.3 Overcoming Congestion with AHS Maglev	198
7.4 Preserving Stream Stability	200
7.5 Recommendations for Further Studies	202

7.6 The Future of High Speed Transportation	204
REFERENCES	207
APPENDIX A	214
APPENDIX B	231
VITA	236

LIST OF FIGURES

Figure 2.1 Autonomous Intelligent Cruise Control	16
Figure 2.2 Point Following Control	17
Figure 2.3 AHS Guideway and freeway roadways	22
Figure 2.4 Guideway-freeway interchange	23
Figure 2.5 Guideway-guideway interchange	24
Figure 2.6 Guideway stream dynamics	26
Figure 3.1 Comparison between two types of maglev vehicles currently in use	30
Figure 3.2 Magnetic levitation system for electrodynamic levitation	30
Figure 3.3 Drag forces versus speed	32
Figure 3.4 AHS Maglev Levitation, Propulsion and Guidance	34
Figure 3.5 Decision support system elements	38
Figure 3.6 Vehicle longitudinal feedback control diagram based on GM's car following model	40
Figure 4.1 Magway metropolitan structure	56
Figure 4.2 Application of UTPP	62
Figure 4.3 Supply performance functions for work trips	70
Figure 4.4 Supply performance functions for long trips	70
Figure 4.5 Supply performance function for trucks	71
Figure 4.6 Determination of user benefits in transportation improvement	74
Figure 4.7 User benefits for Expansion Alternative (work trips)	76

Figure 4.8 User benefits for AHS Maglev Alternative (work trips)	77
Figure 4.9 User benefits for Extension Alternative (long trips)	78
Figure 4.10 User benefits for AHS Maglev Alternative (long trips)	79
Figure 4.11a Assumed condition for Alternative 2	85
Figure 4.11b Assumed condition for Alternative 3	85
Figure 4.12 Causal diagram for nonuser benefits	89
Figure 4.13 DYNAMO program for nonuser benefits	90
Figure 4.14 Gross National Product for Alternative 1	92
Figure 4.15 Gross National Product for Alternative 2	92
Figure 4.16 Gross National Product for Alternative 3	92
Figure 4.17 Summary of comparison of nonuser benefits	93
Figure 4.18 Mode competitiveness based on travel time	96
Figure 4.19 Modal split between air travel & AHS Maglev	96
Figure 5.1 Platoon spacing on the guideway	100
Figure 5.2 Dynamics of platoon flow	101
Figure 5.3 Relationship between platoon spacing and velocity	103
Figure 5.4 Guideway practical capacities	107
Figure 5.5 Maglev traffic network ($a = 3$)	108
Figure 5.6 Traffic Impedance	109
Figure 5.7 Relationship between total traffic volume and guideway volume	112
Figure 5.8 Relationship between total traffic volume and freeway volume	113
Figure 5.9 Determination of variables for car maneuvering theory	115
Figure 5.10 Relationship of platoon size to longitudinal control	120

Figure 5.11 Time-space diagram of freeway merging maneuver	121
Figure 5.12 Merging Vehicles	131
Figure 5.13 Relationship between guideway flow and ramp capacity by delay approach.	132
Figure 5.14 Relationship between guideway flow and ramp capacity by multiple merge approach.	132
Figure 5.15 Probability that a ramp is fully loaded versus ramp capacity	133
Figure 6.1 Free body diagram of a maglev vehicle on a curvature path	147
Figure 6.2 Causal diagram for four vehicles under the 3-phase control rule	151
Figure 6.3 Vehicle Characteristics under Three Dimensional Control Law	153
Figure 6.4a Vehicle Characteristics under Car Maneuvering Model (T = 0.2 seconds)	160
Figure 6.4b Vehicle Characteristics under Car Maneuvering Model (T = 0.1 seconds)	162
Figure 6.4c Vehicle Characteristics under Car Maneuvering Model (T = 0.1 seconds)	164
Figure 6.5a Vehicle Characteristics under Spacing Dependent Law (b = 0.01)	167
Figure 6.5b Vehicle Characteristics under Spacing Dependent Law (b = 0.005)	169
Figure 6.5c Vehicle Characteristics under Spacing Dependent Law (b = 0.001)	171
Figure 6.5d Vehicle Characteristics under Spacing Dependent Law (b = 0.0005)	173
Figure 6.5e Vehicle Characteristics under Spacing Dependent Law (b = 0.0001)	175
Figure 6.6 Vehicle Characteristics under Magnetic Coupling Control Law	178
Figure 6.7 Vehicle Characteristic under Stepwise Longitudinal Control Law	181

Figure 6.8 Vehicle Characteristics under Cooperative Longitudinal Control Model	184
Figure 6.9 Vehicle Motion on a 90-Degree Curve	187
Figure 6.10 Vehicle Tilting and Superelevation in a Curvature Motion	190
Figure 6.11 Distance traveled by four vehicles under integrated model	191
Figure 6.12 Headway between four vehicles under integrated model	191
Figure 6.13 First vehicle's longitudinal velocity under integrated model	192
Figure 6.14 First vehicle's longitudinal acceleration under integrated model	192

LIST OF TABLES

Table 4.1 Calculations of user benefit	81
Table 4.2 Calculations of costs for Alternative 3	82
Table 4.3 Calculations of Benefit Cost Ratio	83
Table 5.1 Network Assignment: Sample of Calculation (Cars, a =3)	110
Table 5.2 Results of regression analysis for relationship between q and q^g	111