

List of Illustrations

1.1	Nonlinear elastic behavior of stiffened panels	3
1.2a	Existing geometric imperfections treatment	17
1.2b	Design process with imperfection model for uncertainties	17
1.2c	Projected closed loop design scheme	17
2.1	Element geometry and nodal degrees of freedom	24
2.2	Kirchoff thin plate deformation model	25
2.3	Element natural coordinate system and node numbering	31
2.4	Load-deflection curve by piecewise linear incremental approach	44
2.5	Square plate with all edges clamped (a quarter of total region)	45
2.6	Finite element mesh employed	46
2.7	Load-deflection curve at point O of a square plate with all edges clamped under uniform load	47
2.8	Upper and lower stress at point O of the square plate	47
2.9	Maximum deflection convergence as the number of load increments is increased	48
2.10	Center deflection of CCCC square plates with imperfections	49
2.11	Square plate with two edges clamped and the other two free	50
2.12	Load deflection curves at points A and B of a square plate under concentrated load	50
2.13	Finite element mesh and boundary conditions	54
2.14	Postbuckling response characteristics: End shortening	55
2.15	Postbuckling response characteristics: Out-of-plane deflection	55

3.1	Panel geometry and finite element model	58
3.2	The applied genetic algorithm	63
3.3	Roulette wheel distribution for 3 laminates and parent selection using random numbers	64
4.1	Geometry of the composite-bleeder system	71
4.2	Process-induced curvatures modeling flow diagram	84
4.3	Panel discretization and global coordinates	85
4.4a	Third ply fiber orientation angle as function of position	89
4.4b	Passes of tow placement for the third ply from the top	90
4.5	Temperature curing cycle for the variable stiffness panel	91
4.6	Predicted profile for the cured variable stiffness panel	92
4.7	Actual cured profile for the variable stiffness panel	92
4.8	Manufacturer's recommended cure cycle for Hercules AS/3501-6 prepreg	94
4.9	Imperfect profile convergence	95
4.10	Effect of fiber orientation angle on the final panel profile	96
4.11	Effect of the number of layers on the panel cured profile	97
4.12	Effect of the position of the 45° layer on the panel cured profile	98
5.1	Nonlinear elastic behavior of stiffened panels	103
5.2	Typical compressively loaded prismatic linked-plate structures	104
5.3	Stiffened panel showing plate strip and labeling convention	106
5.4	Existing geometric imperfections treatment	108
5.5	Design process with imperfection model for uncertainties	108
5.6	Elastic limit load variation with first mode shape amplitude	115

5.7	Predictions of the convex model for the minimum elastic limit load along with the minimum of the response surface	116
5.8a	Elastic limit load from the convex model and the probabilistic analysis for negative first mode amplitudes	119
5.8b	Elastic limit load from the convex model and the probabilistic analysis for positive first mode amplitudes	120
6.1	First proposed closed loop design scheme	123
6.2	Second suggested design scheme	125
6.3	Imperfection profile used to initialize the design process	126
6.4	Predicted nominal imperfection profile for the first optimum design	128
6.5	Predicted nominal imperfection profile for the second optimum design	128
6.6	Predicted nominal imperfection profile for the third optimum design	130
6.7	Predicted nominal imperfection profile for the new optimum design	131