10.0 REFERENCES

Adalier, K. (1996). *Mitigation of earthquake-induced liquefaction hazards*. Ph.D. Thesis Rensselaer Polytechnic Institute, Troy, NY.

Anderson, M.P. and Woessner, W.W. (1992). *Applied Groundwater Modeling: Simulation of Flow and Advective Transport*, Academic Press, Inc., San Diego, California, 381 p.

Ata, A. and Vipulanandan, C. (1997). "Silica fume in cement and silicate grouts and grouted sands." C. Vipulanandan, ed., *Grouting: Compaction, Remediation, Testing*, ASCE GSP No. 66, pp. 242-257.

Avanti International (1999). Personal communication.

Borglis, S.E., Moridis, G.J., and Becker, A. (1998). *Experimental Studies of Magnetically Driven Flow of Ferrofluids in Porous Media*. Lawrence Berkeley National Laboratory Report LBNL-40126 Berkeley, CA.

Bruce, D.A., Littlejohn, G.S. and Naudts, A.M. (1997). "Grouting Materials for Ground Treatment: A Practitioner's Guide." C. Vipulanandan, ed., *Grouting: Compaction, Remediation, Testing*, ASCE GSP No. 66, pp. 306-334.

Bruere (1966). "Set-retarding effects of sugars in Portland cement pastes." *Nature*, 212, 502-503.

Cantrell, K.J. and Kaplan, D.I. (1997). "Zero-valent iron colloid emplacement in sand columns." *Journal of Environmental Engineering*, 123(5), 499-505.

Cantrell, K.J., Kaplan, D.I., and Gilmore, T.J. (1997). "Injection of colloidal Fe⁰ particles in sand with shear-thinning fluids." *Journal of Environmental Engineering*, 123(8), 786-791.

Chan, C.K. (1985). Instruction Manual, CKC E/P Cyclic Loading Triaxial System Users Manual. Soil Engineering Equipment Company, San Francisco, CA.

Clarke, W.J. (1984). "Performance characteristics of microfine cement." Preprint 84-023, ASCE Geotechnical Conference, Atlanta, GA, May 14-18.

Clarke, W.J. (1987). "Microfine cement technology." 23rd International Cement Seminar, December 6-9, Atlanta, GA.

Clementz, D.M., Patterson, D.E., Aseltine, R.J., and Young, R.E. (1982). "Stimulation of water injection wells in the Los Angeles basin by using sodium hypochlorite and mineral acids." *Journal of Petroleum Technology*, 34, 2087-2096.

Clough, G.W., Iwabuchi, J., Rad, N.S. and Kuppusamy, T. (1989). "Influence of cementation of liquefaction of sands." *Journal of Geotechnical Engineering*, ASCE, Vol. 115, No. 8, pp. 1102-1117.

Collepardi, M.M. (1995). "Water Reducers/Retarders." *Concrete Admixtures Handbook: Properties, Science, and Technology, 2nd Edition*, V.S. Ramachandran, ed., Noyes Publications, Park Ridge, NJ.

Cooke, H.G. (2000). *Ground Improvement for Liquefaction Mitigation at Existing Highway Bridges*, Ph.D. Dissertation, Virginia Tech, Blacksburg, Virginia.

Cusack, F., Singh, S., McCarthy, C., Greico, J., DeRocco, M., Nguyen, D., Lappin-Scott, H. and Costerton, J.W. (1992). "Enhanced oil recovery – three-dimensional sandpack simulation of ultramicrobacteria resuscitation in reservoir formation." *Journal of General Microbiology*, 138, 647-655.

Deere, D. U. and Lombardi, G. (1985). "Grout slurries – thick or thin?" *Issues in Dam Grouting*, W.H. Baker, ed., ASCE, New York, 156-164.

Dennis, M.L. and Turner, J.P. (1998). "Hydraulic conductivity of compacted soil treated with biofilm." *Journal of Geotechnical and Geoenvironmental Engineering*, ASCE, 124(2), 120-128.

DePaoli, B., Bosco, B., Granata, R. and Bruce, D.A. (1992). "Fundamental observations on cement based grouts (1): traditional materials." R.H. Borden, R.D. Holtz and I. Juran, eds., *Grouting, Soil Improvement and Geosynthetics*, ASCE GSP No. 30, pp. 474-485.

Dillard, J.G., Glanville, J.O., Collins, W.D., Weyers, R.E. and Al-Qadi, I.L. (1993). Concrete Bridge Protection and Rehabilitation: Chemical and Physical Techniques. Feasibility Studies of New Rehabilitation Techniques, Strategic Highway Research Program, National Research Council, Washington, DC.

Domenico, P.A. and Schwartz, F.W. (1990). *Physical and Chemical Hydrolgeology*. John Wiley and Sons, Inc., New York, NY, 824 p.

DuPont (1997). *Ludox Colloidal Silica: Properties, Uses, Storage, and Handling*. Product Information, DuPont, Wilmington, DE, 19 p.

Fann (1995). *Series 300 API Filter Press Instruction Manual*. Fann Instrument Company, Houston, TX, 37 p.

Fetter, C.W. (1993). *Contaminant Hydrology*. Prentice-Hall, Inc., Upper Saddle River, NJ, 458 p.

Finsterele, S., Moridis, G.J., and Pruess K. (1994). A TOUGH2 Equation of State Module for the Simulation of Two-Phase Flow of Air, Water, and a Miscible Gelling Liquid. LBL Report LBL-36086, Lawrence Berkeley National Laboratory, Berkeley, CA.

Finsterle, S. Oldenburg, C.M., James, A.L., Pruess, K. and Moridis, G.J. (1997). "Mathematical modeling of permeation grouting and subsurface barrier performance." *1997 International Containment Technology Workshop Proceedings*, St. Petersburg, FL, pp. 438-444.

Freeze, R.A. and Cherry, J.A. (1979). *Groundwater*. Prentice-Hall, Inc., Englewood Cliffs, NJ 604 p.

Gause, C. and Bruce, D.A. (1997). "Control of fluid properties of particulate grouts: part 1 – general concepts." C. Vipulanandan, ed., *Grouting: Compaction, Remediation, Testing*, ASCE GSP No. 66, pp. 212-229.

Gavaskar, A.R., Gupta, N., Sass, B.M., Janosy, R.J., and O'Sullivan, D. (1998). *Permeable Barriers for Groundwater Remediation.*, Battelle Press, Columbus, OH, 176 p.

Gillham, R.W., Blowes, D.W., Ptacek, C.J., and O'Hannesin, S.F. (1994). "Use of zero-valent metals in in-situ remediation of contaminated groundwater." *In Situ Remediation: Scientific Basis for Current and Future Technologies, Proceedings of the 33rd Hanford Symposium on Health and the Environment*, November 7-11, Pasco, WA, Vol. 2, pp. 913-930.

Hapka, A.M. and Whang, J.M. (1996). "In-situ precipitation of an iron based grout." *Environmental Geotechnology, Proceedings of the 3rd International Symposium*, Vol. 1, pp. 375-378.

Houlsby, A.C. (1982). "Cement Grouting for Dams." *Proceedings of the Conference on Grouting in Geotechnical Engineering*, New Orleans, ASCE, pp. 1-34.

Iler, R.K. (1979). *The Chemistry of Silica: Solubility, Polymerization, Colloid and Surface Properties, and Biochemistry*, John Wiley & Sons, 866 p.

Ishihara, K. (1985). "Stability of natural deposits during earthquakes." *Proceedings*, 11th *International Conference on Soil Mechanics and Foundation Engineering*, San Francisco, Vol.1, pp. 321-376

Jack, T.R., Stehmeier, L.G., Islam, M.R. and Ferris, F.G. (1991). "Microbial selective plugging to control water channeling." *Microbial Enhancement of Oil Recovery – Recent Advances*, Elsevier Science Publishers, B.V., Amsterdam, The Netherlands, pp. 433-440.

Johnson, T.L. and Tratnyek, P.G. (1994). "A column study of geochemical factors affecting reductive dechlorination of chlorinated solvents by zero-valent iron." *In Situ Remediation: Scientific Basis for Current and Future Technologies, Proceedings of the 33rd Hanford Symposium on Health and the Environment*, November 7-11, Pasco, WA, Vol. 22, pp. 931-947.

Jurinak, J.J., Summers, L.E. and Bennett, K.E. (1989). "Oilfield application of colloidal silica gel." *Society of Petroleum Engineers International Symposium on Oil Field Chemistry*, Houston, TX, February 8-10.

Kaplan, D.I., Cantrell, K.J., Wietsma, T.W., and Potter, M.A. (1994). "Formation of a barrier to GW contaminants by the injection of zero-valent ion colloids: suspension properties." *In Situ Remediation: Scientific Basis for Current and Future Technologies, Proceedings of the 33rd Hanford Symposium on Health and the Environment*, November 7-11, Pasco, WA, Vol. 22, pp. 821-837.

Karol, R. (1990). *Chemical Grouting*, 2nd Ed., Marcel Dekker, Inc, NY, 465 p.

Khayat, K.H. (1995). "Effects of antiwashout admixtures on fresh concrete." ACI Materials Journal, 92, 2, 164-171.

Kramer, S.L. (1996). *Geotechnical Earthquake Engineering*, Prentice-Hall, Upper Saddle River, NJ, 653 p.

Ladd, R.S. (1978). "Specimen preparation and liquefaction of sands." *Journal of the Geotechnical Engineering Division*, ASCE, 100 (10), 1180-1184.

Lappin-Scott, H.M., Cusack, F. and Costerton, J.W. (1988). "Nutrient resuscitation and growth of starved cells in sandstone cores: a novel approach to enhanced oil recovery." *Applied and Environmental Microbiology*, 54(6), 1373-1382.

Lappin-Scott, H.M. and Costerton, J.W. (1990). "Starvation and penetration of bacteria in soils and rocks." *Experientia*, Birkhauser Verlag, 46, 807-812.

Lombardi, G. (1985). "The role of cohesion in cement grouting." 15th International Congress On Large Dams, Lausanne, Switzerland, Q.58-R.13, pp.235-260.

MacLeod, F.A., Lappin-Scott, H.M. and Costerton, J.W. (1988). "Plugging of a model rock system by using starved bacteria." *Applied and Environmental Microbiology*, 54(6), 1365-1372.

Maher, M.H., Ro, K.S. and Welsh, J.P. (1994a). "High strain modulus and damping of chemically grouted sand." *Soil Dynamics and Earthquake Engineering* (13), Elsevier Science Limited, Great Britain, pp. 131-138

Maher, M.H., Ro, K.S. and Welsh, J.P. (1994b). "Cyclic undrained behavior and liquefaction potential of sand treated with chemical grouts and microfine cement (MC-500)." *Geotechnical Testing Journal*, ASTM, Vol. 17, No. 2, June, pp. 159-170.

Mangold, D.C. and Tsang, C.-F. (1991). "A summary of subsurface hydrological and hydrochemical models." *Reviews of Geophysics*, American Geophysical Union, 29(1), 51-79.

Martin, G.R., Yen, T.F., Karimi, S. (1996). "Application of Biopolymer Technology in Silty Soil Matrices to Form Impervious Barriers." *Proceedings*, 7th Australia-New Zealand Geomechanics Conference, Adelaide, Australia, July.

McDonald, M.G. and Harbaugh, A.W. (1988). A Modular Three-Dimensional Finite-Difference Ground-Water Flow Model: Techniques of Water-Resources Investigations of the United States Geological Survey. Book 6.

Milestone, N.B. (1979). "Hydration of tricalcium silicate in the presence of lignosulfates, glucose, and sodium gluconate." *Journal of the American Ceramic Society*, 62(7-8), 321-324.

Mitchell, J.K. (1981). "Soil improvement: state-of-the-art." *Tenth International Conference on Soil Mechanics and Foundation Engineering*, Stockholm, Sweden, June 15-19.

Mitchell, J.K. (1993). *Fundamentals of Soil Behavior*. John Wiley & Sons, Inc., New York, NY, 437 p.

Mitchell, R. and Nevo, Z. (1964). "Effect of bacterial polysaccharide accumulation on infiltration of water through sand." *Applied Microbiology*, 12(3), 219-223.

Mongilardi, E. and Tornaghi, R. (1986). "Construction of large underground openings and use of grouts." *Proceedings of the International Conference on Deep Foundations*, Sept., Beijing, 19 p.

Moridis, G.J., Apps, J., Persoff, P., Myer, L., Muller, S., Yen, P. and Pruess, K. (1996). "A field test of a waste containment technology using a new generation of injectable barrier liquids." *Spectrum '96*, Seattle WA, August 18-23.

Moridis, G.J., Pruess K., Persoff, P., and Apps, J.A. (1995). "Performance and properties of colloidal silica and polysiloxane grouts." Note presented at the International Containment Technology Workshop, Baltimore, Maryland. (As cited in Whang 1995).

Moridis, G.J., Borglin, S.E., Oldenburg, C.M., and Becker, A. (1998). *Theoretical and Experimental Investigation of Ferrofluids for Guiding and Detecting Liquids in the Subsurface.* Lawrence Berkeley National Laboratory Report LBNL-41069 Berkeley, CA.

Morrison, S.J. and Spangler, R.R. (1993). "Chemical barriers for controlling groundwater contamination." *Environmental Progress*, 12(3),175-181.

Morrison, S.J., Spangler, R.R. and Morris, S.A. (1996). "Subsurface injection of dissolved ferric chloride to form a chemical barrier: laboratory investigations." *Ground Water*, January-February, 34(1), 75-83.

Naudts, A.M.C. (1996). "Grouting to improve foundation soil." *Practical Foundation Engineering Handbook*, R.W. Brown, ed., McGraw-Hill, New York, NY.

NAVFAC (1983). *Dewatering and Groundwater Control, Navy NAVFAC P-418*. Departments of the Army, the Air Force and the Navy, Washington, D.C.

NCEER (1997). *Proceedings of the NCEER Workshop on Evaluation of Liquefaction Resistance of Soils*, Technical Report NCEER-97-0022, edited by T.L Youd and I.M. Idriss, National Center for Earthquake Engineering Research, Buffalo, NY.

Nitao, J. (1998). *Reference Manual for the NUFT Flow and Transport Code, Version 2.0.* URCL-MA-130651, Lawrence Livermore National Laboratory, CA.

Noll, M.R., Bartlett, C. and Dochat, T.M. (1992). "In situ permeability reduction and chemical fixation using colloidal silica." *Proceedings of the 6th National Outdoor Action Conference*, National Ground Water Association, Las Vegas, NV, pp. 443-457.

Noll, M.R., Epps, D.E., Bartlett, C.L. and Chen, P.J. (1993). "Pilot field application of a colloidal silica gel technology for in situ hot spot stabilization and horizontal grouting." *Proceedings of the 7th National Outdoor Action Conference*, National Ground Water Association, Las Vegas, NV, pp. 207-219.

Parkhurst, D.L. (1995). User's Guide to PHREEQC- A Computer Program for Speciation, Reaction-Path, Advective-Transport, and Inverse Geochemical Calculations, USGS 95-4227, Lakewood, CO.

Persoff, P., Moridis, G.J., Apps, J., Pruess, K., and Muller, S.J. (1994). "Designing injectable colloidal silica barriers for waste isolation at the Hanford site." *In Situ Remediation: Scientific Basis for Current and Future Technologies, Proceedings of the 33rd Hanford Symposium on Health and the Environment*, November 7-11, Pasco, WA, Vol. 1, pp. 87-101.

Persoff, P., Apps, J., Moridis, G., and Whang, J.M. (1997). "Effect of dilution and contaminants on strength and hydraulic conductivity of sand grouted with colloidal silica gel." *1997 International Containment Technology Proceedings*, pp. 578-584.

Persoff, P., Apps, J., Moridis, G. and Whang, J.M. (1999). "Effect of dilution and contaminants on strength and hydraulic conductivity of sand grouted with colloidal silica gel." *Journal of Geotechnical and Geoenvironmental Engineering*, Vol. 125, No. 6., pp. 461-469.

Polito, C.P. (1999). *The Effects Of Non-Plastic and Plastic Fines On The Liquefaction Of Sandy Soils*, Ph.D. Dissertation, Virginia Tech, Blacksburg, Virginia.

Pollock, D.W. (1989). Documentation of Computer Programs to Compute and Display Pathlines using Results from the U.S. Geological Survey Modular Three-Dimensional Finite-Difference Ground-Water Flow Model. U.S. Geological Survey Open-File Report 89-381.

Pruess, K (1991). *TOUGH2 – A General Purpose Numerical Simulator for Multiphase Fluid and Heat Flow.* Report No. LBL-29400, Lawrence Berkeley National Laboratory, Berkeley, CA.

Rad, N.S. and Clough, G.W. (1982). "New procedure for saturating sand specimens." *Journal of Geotechnical Engineering*, ASCE, Vol. 110, No. 9, pp. 1205-1218.

Ramachandran, V.S. and Lowery, M.S. (1992). "Conduction calorimetric investigation of the effect of retarders on the hydration of Portland cement." *Thermochimica Acta*, 195, 373-387.

Ramachandran, V.S., Lowery, M.S., Wise, T., and Polomark, G.M. (1993). "The role of phosphonates in the hydration of Portland cement." *Materials and Structures*, 26, 425-432.

Reardon, E.J. (1995). "Anaerobic corrosion of granular iron: measurement and interpretation of hydrogen evolution rates." *Environmental Science & Technology*, 29(12), 2936-2945.

Rosenfarb, J.L and Hackman, R.E. (1981). "The cyclic loading behavior of grouted sand." *International Conference on Recent Advances in Geotechnical Earthquake Engineering and Soil Dynamics*, University of Missouri-Rolla, April 26-May 3, 1981, pp. 81-86.

Rosensweig, R.E. (1985). *Ferrohydrodynamics*. Cambridge University Press, New York, NY, 344 p.

Saxena, S.K., Reddy, K.R., and Avramidia, A.S. (1988). "Liquefaction resistance of artificially cemented sand." *Journal of Geotechnical Engineering*, ASCE, Vol. 114, No. 12, December, pp. 1395-1413.

Schaeffer, J.A. (1998). "Excess Pore Water Pressure Migration and Dissipation in Densified Sand Zones During and After Earthquakes," Master's Project Report, Department of Civil Engineering, Virginia Polytechnic Institute and State University, Blacksburg, VA, 63 pp.

Schuhmacher, T., Odziemkowski, M.S., Reardon, E.J. and Gillham, R.W. (1997). "Identification of precipitates formed on zero-valent iron in anaerobic aqueous solutions." *1997 International Containment Technology Conference Proceedings*, pp.801-805.

Schwarz, L.G. and Krizek, R.J. (1992). "Effects of mixing on rheological properties of microfine cement grout." *Grouting, Soil Improvement and Geosynthetics*, Geotechnical Special Publication No. 30, R.H. Borden, R.D. Holtz, and I. Juran, eds., ASCE, New York, New York, pp. 512-525.

Seed, H.B. and Idriss, I.M. (1982). *Ground Motions and Soil Liquefaction During Earthquakes*, Earthquake Engineering Research Institute, 134 p.

Shaw, J.C., Bramhill, B., Wardlaw, N.C. and Costerton, J.W. (1985). "Bacterial fouling in a model core system." *Applied and Environmental Microbiology*, 49(3), 693-701.

Sydansk, R.D. (1990). "A newly developed chromium (III) technology." *SPE Reservoir Engineering*, August, pp. 346-352.

Thomas, N.L. and Birchall, J.D. (1983). "The Retarding Action of Sugars on Cement Hydration." *Cement and Concrete Research*, Vol. 13, pp. 830-842.

Thomas, N.L., Jameson, D.A. and Double D.D. (1981). "The effect of lead nitrate on the early hydration of Portland cement." *Cement and Concrete Research*, Vol. 11, pp. 143-153.

Turner, J.P., Dennis, M.L., Osman, Y.A., Chase, J., and Bulla, L.A. (1997). "Biofilm treatment of soil for waste containment and remediation." *1997 International Containment Technology Conference Proceedings*, February 9-12, St. Petersburg, FL, pp. 672-678.

Vipulanandan, C. and Ata, A. (2000). "Cyclic and damping properties of silicate-grouted sand." *Journal of Geotechnical and Geoenvironmental Engineering*, ASCE, Vol. 126, No. 7, July, pp. 650-656.

Voss, C.I. (1984). A Finite-Element Simulation Model for Saturated-Unsaturated, Fluid-Density-Dependent Ground-Water Flow with Energy Transport or Chemically-Reactive Single Species Solute Transport. U.S. Geological Survey Water-Resources Investigations Report 84-4369, 409 p.

Weaver, K. (1991). Dam Foundation Grouting, ASCE, New York, New York, 178 p.

Whang, J.M. (1995). "Section 9 – Chemical-based barrier materials." *Assessment of Barrier Containment Technologies for Environmental Remediation Applications*, R. R. Rumer and J.K. Mitchell, eds., NTIS, Springfield, VA, 211-247.

Wu, J., Gui, S., Stahl, P., and Zhang, R. (1997). "Experimental study on the reduction of soil hydraulic conductivity by enhanced biomass growth." *Soil Science*, 162(10), 741-748.

Yang, I.C.-Y., Li, Y., Park, J.K. and Yen, T.F. (1992). "The use of slime-forming bacteria to enhance the strength of the soil matrix." *Microbial Enhancement of Oil Recovery – Recent Advances, Proceedings of the 1992 International Conference on Microbial Enhanced Oil Recovery*, Developments in Petroleum Science, 39, 89-96.

Yeh, G.T. and Salvage, K.M. (1997). *HYDROGEOCHEM 2.0: A Coupled Model of HYDROlogic Transport and Mixed GEOCHEMical Kinetic/Equilibrium Reactions in Saturated Unsaturated Media.*

Yonekura, R. and Miwa, M. (1993). "Fundamental Properties of Sodium Silicate Based Grout." *Eleventh Southeast Asia Geotechnical Conference*, May 4-8, Singapore, pp. 439-444.

Zheng, C. (1990). A Modular Three-Dimensional Transport Model for Simulation of Advection, Dispersion and Chemical Reactions of Contaminants in Groundwater Systems. S.S. Papadopulos & Associates, Inc., Rockville, MD.

Zheng, C. and Wang, P.P. (1998). *MT3DMS: A Modular Three-Dimensional Multispecies Transport Model for Simulation of Advection, Dispersion and Chemical Reactions of Contaminants in Groundwater Systems. Documentation and User's Guide.* Departments of Geology and Mathematics, University of Alabama, Tuscaloosa, AL.