

## LIST OF FIGURES

<b>Figure 1.1</b> Definition of supercritical region for a pure substance. CP: critical point (where the distinction between liquid and vapor disappears), TP: triple point (where liquid, solid and vapor coexist), $T_c$ : critical temperature, $P_c$ : critical pressure. ....	1
<b>Figure 1.2</b> Critical line for a simple binary mixture of component 1 and 2. $P_{c1}$ , $P_{c2}$ , $T_{c1}$ , $T_{c2}$ correspond to pure component critical pressures and critical temperatures. ....	3
<b>Figure 1.3</b> Variation of density with pressure for a pure fluid above and below the critical temperature ( $T_c$ ). $T_1 > T_c > T_2$ . The shaded area is the vapor-liquid two-phase region. ....	4
<b>Figure 1.4</b> Structures for PMMA, PCL, poly (MDO-co-MMA), poly (MDO-co-ST), poly (MDO-co-AN), and 2-methylene-1,3-dioxepane (MDO). ....	6
<b>Figure 1.5</b> The phase behavior in polymer solutions as a function of carbon dioxide content of solvent. The solid lines are the liquid-liquid phase boundaries. Shaded sides depict the two-phase regions. ....	8
<b>Figure 1.6</b> Schematic diagrams showing polymerization-induced phase separation (top). With the progress of polymerization, the lower critical solution temperature may be lowered or the upper critical solution temperature may increase, upon which homogeneous system enters two-phase region. ....	10
<b>Figure 1.7</b> Schematic diagram for variation of transmitted light intensity, $I_{tr}$ with polymerization time in homogeneous or heterogeneous polymerizations. In heterogeneous polymerizations, phase separation occurs at time = $t_1$ and thereafter the polymerization proceeds in two phase region. ....	11
<b>Figure 1.8</b> Interrelations among different parts of the present program .....	14
<b>Figure 2.1</b> Paths for solid-fluid (S-F) (crystallization) (path A) and liquid-liquid (L-L) (path B) phase separation. The dashed boundaries represent the phase boundaries for solvents with decreased solvent power (higher carbon dioxide content). ....	19
<b>Figure 2.2</b> Schematic diagram of temperature versus concentration of polymer solutions at different pressures or with different solvent power. The shaded regions in these diagrams represent the immiscible regions. ....	19
<b>Figure 2.3</b> Schematic diagrams for polymer particle formation. ....	38
<b>Figure 3.1</b> Schematic diagram of phase separation during viscosity measurement. Generally, the viscosity increases with pressure. When the phase separation takes place, the viscosity	

shows decrease with pressure, which can be used to detect the phase separation in the system. .... 47

**Figure 4.1** Schematic diagram of the view cell system. SL: solvent line, PL: pressure line, CO<sub>2</sub> C: CO<sub>2</sub> cylinder, SR: solvent reservoir, RPH: right pump head, LPH: left pump head, PG: pressure gauge, CV: check valve, RD: rupture disk, PGN: pressure generator, LVDT/PRU: linear variable differential transformer / position readout unit, VVP: variable volume part, HE: cartridge heater, MS: magnetic stirring, P/T S: pressure/temperature sensor, V1-V7: valves, E1-E6: exits. .... 69

**Figure 4.2** Schematic diagram of the view-cell for density and phase behavior determinations. PFL: pressurized fluid line, PPS LVDT: piston position sensor linear variable differential transformer, FS: ferromagnetic slug, PI: piston, SL: solvent line, TC: temperature controller, CH: cartridge heater, VVP: variable volume part housing the piston, P = pressure; T = temperature, FOL: fiber optical illuminator, SW: sapphire window, PS/*I<sub>tr</sub>*: photo sensor/transmitted light intensity, MS: magnetic stirrer. .... 70

**Figure 4.3** Illustration of the different paths followed to determine phase boundaries and the corresponding changes in temperature (T), pressure (P) and transmitted light intensity (*I<sub>tr</sub>*) with time. The lower part of this figure demonstrates the incipient demixing pressure (*P<sub>i</sub>*) and temperature (*T<sub>i</sub>*) and the condition corresponding to transmitted light intensity going to minimum (*P<sub>f</sub>* and *T<sub>f</sub>*). Path A: constant temperature, Path B: constant pressure, Path C: variable pressure and temperature. .... 71

**Figure 4.4** Variation of temperature, pressure, and transmit light intensity with time during depressurization at constant temperature of 354.7 K in the view cell for the solution of 5 wt % PCL in acetone containing 40 wt % CO<sub>2</sub>. .... 72

**Figure 4.5** Flow sheet of the viscometer system. VC: view cell, FT: falling tube, MP: movable piston, V's: valves, E's: exit valves, CV: check valve, RD: rupture disk, PG: pressure gauge, SL: solvent line, PL: pressurized line, LPH: left pump head, RPH: right pump head, PGN: pressure generator, CP: circulation pump. .... 73

**Figure 4.6** Schematic diagram of the viscometer and the data processing procedure. SL: solvent line, PFL: pressurizing fluid line, PM: pull-up magnet, TLP: top loading port, FLP: front loading port, SW: sapphire window, EMS: electromagnetic stirrer, PI: movable piston, FS: ferromagnetic slug, PPS LVDT: piston position sensor linear variable differential transformer, S: sinker, V: LVDT signal; D: sinker fall distance. .... 74

**Figure 4.7** Sinker LVDT signal (V) versus time during viscosity determination for acetone at 35 MPa and 100 °C. .... 75

**Figure 4.8** Working diagram for data processing software package ..... 75

**Figure 4.9** Calibration voltage-distance relations for the sinker position in the falling tube of the instrument. Raw calibration voltage-distance data (a); normalized calibration voltage-

distance data (b). The normalized data (b) are derived from the raw data by 1) divide all the data into 6 sections according to the 6 peak areas; 2) find maximum for each peaks; 3) normalize all the data by being divided by the 6 maximum for the 6 peak areas, respectively. Some points that are at the beginning are deleted in the normalized figure (b). -..... 76

**Figure 4.10** Sinker travel distance (D) versus time during viscosity determination for acetone at 35 MPa and 100 °C. The sinker terminal velocity determined from the response of the 2<sup>nd</sup> and 3<sup>rd</sup> LVDT coils (the slope of the fitted line) is 0.274 cm/s. .... 77

**Figure 4.11** (a). Sinker LVDT signal (V) versus time, and (b). Sinker travel distance (D) versus time during viscosity determination for system of acetone + PMMA (10 wt%, 15 K) at 35 MPa and 100 °C. The sinker terminal velocity is 0.152 cm/s. .... 78

**Figure 4.12** (a). Sinker LVDT signal (V) and (b). Sinker travel distance (D) versus time during viscosity determination for system of acetone + PMMA (10 wt%, 540 K) at 35 MPa and 100 °C. The sinker terminal velocity is 0.062 cm/s. .... 79

**Figure 5.1** Variation of density with pressure at the nominal temperature of 323 K for acetone, carbon dioxide, and acetone + carbon dioxide mixtures containing 10, 25, 50, and 75 wt % carbon dioxide. (See Table 5.1 for exact temperature for each mixture). .... 106

**Figure 5.2** Variation of density with pressure at the nominal temperature of 348 K for acetone, carbon dioxide, and acetone + carbon dioxide mixtures containing 10, 25, 50, and 75 wt % carbon dioxide. .... 107

**Figure 5.3** Variation of density with temperature for acetone + carbon dioxide mixtures containing 10 wt % carbon dioxide at 7, 14, 21, 28, and 35 MPa. .... 108

**Figure 5.4** Variation of viscosity with pressure at 323 K for acetone, carbon dioxide, and acetone + carbon dioxide mixtures containing 10, 25, 50, and 75 wt % carbon dioxide. .... 109

**Figure 5.5** Variation of viscosity with temperature for acetone + carbon dioxide mixture containing 10 wt % carbon dioxide at 7, 14, 21, 28, and 35 MPa. .... 110

**Figure 5.6** Variation of viscosity with density for acetone, carbon dioxide, and acetone + carbon dioxide mixtures containing 10, 25, 50, and 75 wt % carbon dioxide. .... 111

**Figure 5.7** Variation of excess volume with carbon dioxide content for acetone + carbon dioxide mixture at 323 K and at 14, 21, 28, and 35 MPa. Excess volumes at 35 and 55 MPa are from literature (Pohler and Kiran, 1997a). .... 112

**Figure 5.8** Variation of excess volume with carbon dioxide content for acetone + carbon dioxide mixture at 373 K and 28 and 35 MPa. .... 113

<b>Figure 5.9</b> Variation of viscosity with carbon dioxide content for acetone + carbon dioxide mixture at 323 K and 28 MPa. The viscosities include the experimental data and data calculated from 4 different mixing rules. See text for the mixing rules. ....	114
<b>Figure 5.10</b> Variation of viscosity with carbon dioxide content for acetone + carbon dioxide mixture at 373 K and 28 MPa. The viscosities include the experimental data and data calculated from 4 different mixing rules. See text for the mixing rules. ....	115
<b>Figure 5.11</b> Variation of excess viscosity with carbon dioxide content (mass %) for acetone + carbon dioxide mixture at 323 K and at 14, 21, 28, and 35 MPa. ....	116
<b>Figure 5.12</b> Variation of excess viscosity with carbon dioxide content (mass %) for acetone + carbon dioxide mixture at 373 K and at 28 and 35 MPa. ....	117
<b>Figure 5.13</b> Variation of excess viscosity with excess volume for acetone + carbon dioxide mixtures containing 0, 10, 25, 50, 75, and 100 wt % carbon dioxide at 323 K and 373 K at 28 MPa. ....	118
<b>Figure 5.14</b> <i>Top</i> : Electron donor-acceptor complexes between acetone and carbon dioxide (Cabaco et. al., 2005) <sup>35</sup> where $\alpha_1 = 132.8^\circ$ , $r_1 = 2.745 \text{ \AA}$ ; $\alpha_2 = 180.0^\circ$ , $r_2 = 2.774 \text{ \AA}$ . <i>Bottom</i> : Dimer structures of carbon dioxide: the slipped parallel arrangement with C-C distance of $3.6 \text{ \AA}$ ( $d_1 = 3.6 \text{ \AA}$ , $d_{11} = 1.9 \text{ \AA}$ , $d_{12} = 3.1 \text{ \AA}$ ) and T-shaped arrangement with C-C distance of $4.2 \text{ \AA}$ . ( $d_2 = 4.2 \text{ \AA}$ ) (Fedchenia and Schröder, 1997) .....	119
<b>Figure 5.15</b> Visualization of compositional variations in carbon dioxide – acetone mixtures. The diagrams consider possibilities for different forms of CO <sub>2</sub> dimers, and CO <sub>2</sub> -acetone complexes for different CO <sub>2</sub> :acetone ratios in the mixtures. ....	120
<b>Figure 5.16</b> Variation of viscosity with excess volume for acetone + carbon dioxide mixture at 323 K and 14, 21, 28, and 35 MPa. On each curve, from top to the bottom, the carbon dioxide contents for every point are 0, 10, 25, 50, 75, and 100 wt %. ....	121
<b>Figure 7.17</b> Variation of viscosity with excess volume for acetone + carbon dioxide mixture at 373 K and 28 and 35 MPa. On each curve, from top to the bottom, the carbon dioxide contents for every point are 0, 10, 25, 50, 75, and 100 wt %. ....	122
<b>Figure 5.18</b> Correlation results for acetone using all the experimental data. ....	123
<b>Figure 5.19</b> Correlation results. In this correlation, the parameters that were determined from data at 398 K were used to predict the viscosity at T = 373, 348, and 323 K. ....	124
<b>Figure 5.20</b> Correlation results. In this correlation, the parameters that were determined from data at 373 K were used to predict the viscosity at T = 398, 348, and 323 K. ....	125

<b>Figure 5.21</b> Variations of model parameters, $l$ and $E_0$ , with pressure. The parameters were determined at fixed pressure. ....	126
<b>Figure 6.1</b> (a). Sinker LVDT signal (V) versus time, and (b) Sinker travel distance (D) versus time during viscosity determination for acetone at 35 MPa and 100 °C. The sinker terminal velocity determined from the response of the 2 <sup>nd</sup> and 3 <sup>rd</sup> LVDT coils (the slope of the fitted line) is 0.274 cm/s. ....	150
<b>Figure 6.2</b> (a). Sinker LVDT signal (V) versus time, and (b) Sinker travel distance (D) versus time during viscosity determination for system of acetone + PMMA (10 wt%, 15 K) at 35 MPa and 100 °C. The sinker terminal velocity is 0.152 cm/s. ....	151
<b>Figure 6.3</b> (a). Sinker LVDT signal (V) and (b). Sinker travel distance (D) versus time during viscosity determination for system of acetone + PMMA (10 wt%, 540 K) at 35 MPa and 100 °C. The sinker terminal velocity is 0.062 cm/s. ....	152
<b>Figure 6.4</b> Variation of density with pressure at 50, 75, 100, and 125 °C for acetone. Literature data are from references (Lit. data (1): Pohler and Kiran, 1997a; Lit. data (2): Azevedo et. al., 2004). ....	153
<b>Figure 6.5</b> Variation of viscosity with pressure at 50, 75, 100, and 125 °C for acetone. ....	154
<b>Figure 6.6</b> Variation of density with pressure for PMMA (10 wt %, $M_w = 15$ K) in acetone at 50, 75, 100, and 125 °C. ....	155
<b>Figure 6.7</b> Variation of viscosity with pressure for PMMA (10 wt %, $M_w = 15$ K) in acetone at 50, 75, 100, and 125 °C. ....	156
<b>Figure 6.8</b> Comparison of the variation of density with pressure for PMMA ( $M_w = 15$ K) solutions (0, 10, 20 wt %) in acetone at 100 °C. ....	157
<b>Figure 6.9</b> Comparison of variation of viscosity with pressure for PMMA ( $M_w = 15$ K) solutions (0, 10, 20 wt %) in acetone at 100 °C. ....	158
<b>Figure 6.10</b> Variation of density with pressure for PMMA (10 wt %, $M_w = 540$ K) in acetone at 50, 75, 100, and 125 °C. ....	159
<b>Figure 6.11</b> Variation of viscosity with pressure for PMMA (10 wt %, $M_w = 540$ K) in acetone at 50, 75, 100, and 125 °C. ....	160
<b>Figure 6.12</b> Comparison of variation of density with pressure for PMMA ( $M_w = 540$ K) solutions (0, 5, 10, 20 wt %) in acetone at 100 °C. ....	161

<b>Figure 6.13</b> Comparison of the variation of viscosity with pressure for PMMA ( $M_w = 540$ K) solutions (0, 5, 10, 20 wt %) in acetone at 100 °C. ....	162
<b>Figure 6.14</b> Comparison of the variation of viscosity with pressure for solutions of PMMA (20 wt %) in acetone at 100 °C. ....	163
<b>Figure 6.15</b> Variation of density with pressure for solutions of PMMA (5 wt %, $M_w = 540$ K) in acetone + CO <sub>2</sub> mixtures at different CO <sub>2</sub> levels at 100 °C. ....	164
<b>Figure 6.16</b> Variation of Viscosity with pressure for solutions of PMMA (5 wt %, $M_w = 540$ K) in acetone + CO <sub>2</sub> mixtures at different CO <sub>2</sub> levels at 100 °C. ....	165
<b>Figure 6.17</b> Variation of viscosity with density for PMMA ( $M_w = 15$ K) solutions (0, 10, 20 wt %) in acetone. ....	166
<b>Figure 6.18</b> Variation of viscosity with density and concentration for PMMA ( $M_w = 540$ K) solutions (0, 2, 5, 10, 20 wt %) in acetone. (a). Viscosity versus density; (b) 3-D representation. ....	167
<b>Figure 6.19</b> Variation of viscosity with density and composition for PMMA (5 wt %, $M_w = 540$ K) solutions in acetone + CO <sub>2</sub> mixtures at CO <sub>2</sub> addition levels of 0, 1, 2, 4 wt %. (a). Viscosity versus density; (b) 3-D representation. ....	168
<b>Figure 6.20</b> Variation of the viscosity with concentration for PMMA (540 K) solutions in acetone. The pressure/temperature conditions are as indicated in the figure inset. A significant jump in viscosity takes place in the concentration range between 0.4 to 0.8 g/cm <sup>3</sup> which is interpreted to be related to the onset of entanglements. ....	169
<b>Figure 7.1.</b> Variation of temperature, pressure, and transmitted light intensity with time (top three figures), and the determination of the phase separation (demixing) pressure from variation of $I_{tr}$ with pressure (lower figure) during depressurization at constant temperature of 354.7 K in the view cell for 5 wt % PCL solution in acetone. ....	186
<b>Figure 7.2</b> Variation of density with pressure at 323, 348, 373, and 398 K for 5 wt % solution of PCL in acetone. ....	187
<b>Figure 7.3</b> Variation of viscosity with pressure at 323, 348, 373, and 398 K for 5 wt % solution of PCL in acetone. ....	188
<b>Figure 7.4</b> Variation of density with pressure at 323, 348, 373, and 398 K for mixtures of PCL (5 wt%) + acetone + CO <sub>2</sub> (1 wt %). ....	189
<b>Figure 7.5</b> Variation of viscosity with pressure at 323, 348, 373, and 398 K for mixtures of PCL (5 wt%) + acetone + CO <sub>2</sub> (1 wt %). ....	190

<b>Figure 7.6</b> Variation of density with pressure at 323, 348, 373, and 398 K MPa for mixtures of PCL (5 wt%) + acetone + CO <sub>2</sub> containing 0, 1, 2, 4, 40 wt % CO <sub>2</sub> . .....	191
<b>Figure 7.7</b> Variation of viscosity with pressure at 323, 348, 373, and 398 K MPa for mixtures of PCL (5 wt%) + acetone + CO <sub>2</sub> containing 0, 1, 2, 4, 40 wt % CO <sub>2</sub> . .....	192
<b>Figure 7.8</b> Liquid-liquid phase boundary for mixture of PCL (5 wt %, 14 K) + acetone + CO <sub>2</sub> (40 wt %) as determined in the view cell. ....	193
<b>Figure 7.9</b> Variation of density with pressure at 323, 348, 373, and 398 K MPa for mixtures of PCL (5 wt%) + acetone + CO <sub>2</sub> (40 wt %). (The demixing points are also included). .....	194
<b>Figure 7.10</b> Variation of viscosity with pressure at 323, 348, 373, and 398 K MPa for mixtures of PCL (5 wt%, 14 K) + acetone + CO <sub>2</sub> (40 wt %). (The demixing points are also included). ....	195
<b>Figure 7.11</b> Variation of viscosity with density for mixtures of PCL (5 wt %, 14 K) + acetone + CO <sub>2</sub> (0, 1, 2, 4, 40 wt %). The solid curves are correlations based on Doolittle equation. ....	196
<b>Figure 7.12</b> Comparison of the variation of density with pressure at T = 373 K for the mixtures of PMMA (15 K) + acetone + CO <sub>2</sub> , PMMA (540 K) + acetone + CO <sub>2</sub> , and PCL (15K) + acetone + CO <sub>2</sub> . ....	197
<b>Figure 7.13</b> Comparison of the variation of viscosity with pressure at T = 373 K for the mixtures of PMMA (15 K) + acetone + CO <sub>2</sub> , PMMA (540 K) + acetone + CO <sub>2</sub> , and PCL (15K) + acetone + CO <sub>2</sub> . ....	198
<b>Figure 8.1</b> Demixing pressures for PCL ( $M_w = 14$ K) solutions in acetone + CO <sub>2</sub> containing 40 wt % CO <sub>2</sub> at different polymer compositions. The inserts are T-composition and P-composition diagrams generated from the P-T data at 15 and 20 MPa, and 370 and 380 K, respectively. ....	225
<b>Figure 8.2</b> Demixing pressures for 5 or 10 wt % PCL ( $M_w = 14$ K) solutions in acetone + CO <sub>2</sub> containing 40 or 50 wt % CO <sub>2</sub> . ....	226
<b>Figure 8.3</b> Demixing pressures for 10 wt % PCL solutions in acetone + CO <sub>2</sub> containing 40 wt % CO <sub>2</sub> for different polymer molecular weights ( $M_w = 14$ K or 65 K). ....	227
<b>Figure 8.4</b> Variation of demixing pressure with temperature for 5 wt % PCL ( $M_w = 14$ K) solutions in DME, HCFC-22, acetone + carbon dioxide (40 wt %), DME + carbon dioxide (37 wt %), and HCFC-22 + carbon dioxide (44 wt %) mixtures. (The data for systems other than acetone + CO <sub>2</sub> are from literature (Liu and Kiran, 2006)). ....	228

<b>Figure 8.5</b> Variation of density with pressure for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + 10 wt % CO <sub>2</sub> at 323, 348, 373, and 398 K. ....	229
<b>Figure 8.6</b> Variation of density with temperature for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + 10 wt % carbon dioxide at 7, 14, 21, 28, 35, 42, and 49 MPa. ....	230
<b>Figure 8.7</b> Variation of density with pressure for 10 wt % PCL ( $M_w = 65$ K) solution in acetone + 40 wt % carbon dioxide at 323, 348, 373, and 398 K. (The liquid-liquid phase separation points are shown with symbol “+”) ....	231
<b>Figure 8.8</b> Variation of density with pressure for mixtures of PCL ( $M_w = 14$ K) + acetone + CO <sub>2</sub> (40 wt %) containing 5, 10, and 20 wt % PCL at 373 K. ....	232
<b>Figure 8.9</b> Variation of density with pressure for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixtures containing 0, 5, 10, 20, 40, 50, 60 wt % CO <sub>2</sub> at 348 K. ....	233
<b>Figure 8.10</b> Variation of isothermal compressibility with pressure for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 10 wt % CO <sub>2</sub> and the polymer-free solvent mixture acetone + carbon dioxide (~10 wt %) at 323, 348, 373, and 398 K. ....	234
<b>Figure 8.11</b> Variation of isobaric expansivity with temperature for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 10 wt % CO <sub>2</sub> at 7, 14, 21, 28, 35, 42, and 49 MPa and the polymer-free solvent mixture acetone + carbon dioxide (~10 wt %) at 7, 14, 21, 28, 35 MPa. ....	235
<b>Figure 8.12</b> Schematic diagrams for intermolecular interactions in the PCL solutions (top row) and acetone + carbon dioxide solvent mixture (second row) at different temperatures. Acetone – CO <sub>2</sub> interactions are stronger than PCL- CO <sub>2</sub> interactions at lower temperatures which undergoes a reversal at a crossover temperature around 373 K. ....	236
<b>Figure 8.13</b> Variation of isothermal compressibility difference between 5 wt % PCL ( $M_w = 14$ K) solution in acetone + 10 wt % carbon dioxide and the polymer-free solvent mixture acetone + carbon dioxide (~10 wt %) with temperature at 7, 14, 21, 28, and 35 MPa. ....	237
<b>Figure 8.14</b> Variation of isobaric expansivity difference between 5 wt % PCL ( $M_w = 14$ K) solution in acetone + 10 wt % carbon dioxide mixture and the polymer-free solvent mixture acetone + carbon dioxide (~10 wt %) with pressure at 323, 348, 373, and 398 K. ....	238
<b>Figure 8.15</b> Variation of isothermal compressibility with pressure for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 40 wt % CO <sub>2</sub> and the polymer-free solvent mixture acetone + carbon dioxide (~42 wt %) at 323, 348, 373, and 398 K. ....	239

<b>Figure 8.16</b> Variation of isothermal compressibility with pressure for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 10 and 40 wt % CO <sub>2</sub> at 323, 348, 373, and 398 K. ....	240
<b>Figure 8.17</b> Variation of isothermal compressibility with pressure for 5 and 10 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 40 wt % CO <sub>2</sub> at 323, 348, 373, and 398 K. ....	241
<b>Figure 8.18</b> Variation of isothermal compressibility with pressure for 10 wt % PCL solutions in acetone + carbon dioxide mixture containing 40 wt % CO <sub>2</sub> with two different molecular weights of 14 K and 65 K at 323, 348, 373, and 398 K. ....	242
<b>Figure 8.19</b> Variation of isobaric expansivity with temperature for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 40 wt % CO <sub>2</sub> at 14, 21, 28, 35, 42, and 49 MPa and for the polymer-free solvent acetone + carbon dioxide (42 wt %) at 14, 21, 28, and 35 MPa. ....	243
<b>Figure 8.20</b> Variation of isobaric expansivity with temperature for 5 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 10 and 40 wt % CO <sub>2</sub> at 7, 14, 21, 28, 35, 42, and 49 MPa. ....	244
<b>Figure 8.21</b> Variation of isobaric expansivity with temperature for 5 and 10 wt % PCL ( $M_w = 14$ K) solution in acetone + carbon dioxide mixture containing 40 wt % CO <sub>2</sub> at 7, 14, 21, 28, 35, 42, and 49 MPa. ....	245
<b>Figure 8.22</b> Variation of isobaric expansivity with temperature for 10 wt % PCL solutions in acetone + carbon dioxide mixture containing 40 wt % CO <sub>2</sub> with two different molecular weights of 14 K and 65 K at 7, 14, 21, 28, 35, 42, and 49 MPa. ....	246
<b>Figure 9.1</b> The schematic of phase separation process in forming the blends. ....	262
<b>Figure 9.2</b> Variation of demixing pressure with temperature for 10 wt % PCL, PCL / PMMA blends, and PMMA (15 K) solutions in acetone (50 wt %) + carbon dioxide (40 wt %) mixture. Molecular weight: $M_w = 14,000$ (PCL); $15,000$ (PMMA). ....	263
<b>Figure 9.3</b> Variation of demixing pressure with temperature for 10 wt % PCL (14 K), PCL (14 K)/ PMMA (540 K) blend, and PMMA (540 K) solutions in acetone (50 wt %) + carbon dioxide (40 wt %) mixture. ....	264
<b>Figure 9.4</b> Variation of demixing pressure with temperature for solutions of 5 wt % PCL (14 K) + 5 wt % PMMA (15 K) and 5 wt % PCL (14 K) + 5 wt % PMMA (540 K) in acetone (50 wt %) + carbon dioxide (40 wt %) mixture. ....	265
<b>Figure 9.5a</b> First heating scans for original PMMA samples ( $M_w = 15,000$ and $540,000$ ). The heating rates are 10 K/min. The glass transition temperatures are indicated by the arrows. ....	266

<b>Figure 9.5b</b> First heating scan for original PCL samples ( $M_w = 14,000$ ). The heating rate is 10 K/min. The doublet peaks represent the melting transitions. ....	267
<b>Figure 9.5c</b> First heating scan for 75/25 PCL (14 K)/PMMA (15 K) blend. The heating rate is 10 K/min. The doublet peaks represent the melting transitions. ....	268
<b>Figure 9.5d</b> First heating scan for 50/50 PCL (14 K)/PMMA (15 K) blend. The heating rate is 10 K/min. A $T_g$ is suggested at around 100 °C in the enlarged insert. ....	269
<b>Figure 9.5e</b> First heating scan for 25/75 PCL (14 K)/PMMA (15 K) blend. The heating rate is 10 K/min. The enlarged insert indicates a $T_g$ at around 90 °C. ....	270
<b>Figure 9.5f</b> First heating scan for 50/50PCL (14 K)/PMMA (540 K) blend. The heating rate is 10 K/min. A $T_g$ is detected at around 105 °C. ....	271
<b>Figure 9.6</b> Comparative of DSC scans (first heating scans) for PCL ( $M_w = 14$ K), PMMA ( $M_w = 15$ K), PMMA ( $M_w = 540$ K) and their blends. ....	272
<b>Figure 9.7a</b> First cooling scans for the original PMMA samples ( $M_w = 15$ K and 540 K) showing the $T_g$ 's. The cooling rate is 10 K/min. ....	273
<b>Figure 9.7b</b> First cooling scans for the original PCL samples ( $M_w = 14$ K). The cooling rate is 10 K/min. ....	274
<b>Figure 9.7c</b> First cooling scans for the 75/25 PCL (14 K)/PMMA (15 K) blend sample. The cooling rate is 10 K/min. ....	275
<b>Figure 9.7d</b> First cooling scans for the 50/50 PCL (14 K)/PMMA (15 K) blend sample. The cooling rate is 10 K/min. ....	276
<b>Figure 9.7e</b> First cooling scans for the 25/75 PCL (14 K)/PMMA (15 K) blend sample. The cooling rate is 10 K/min. ....	277
<b>Figure 9.7f</b> First cooling scans for the 50/50 PCL (14 K)/PMMA (540 K) blend sample. The cooling rate is 10 K/min. ....	278
<b>Figure 9.8</b> Comparative DSC scans (first cooling scans) for PCL ( $M_w = 14$ K), PMMA ( $M_w = 15$ K), PMMA ( $M_w = 540$ K) and their blends. ....	279
<b>Figure 9.9</b> Variation of liquid-liquid phase boundary with PCL concentration for PCL ( $M_w = 14$ K) + PMMA (15 K) blend (10 wt % total polymer) solutions in acetone (50 wt %) + carbon dioxide (40 wt %) at 15 and 20 MPa. The ambient pressure crystallization temperatures of the PCL + PMMA blends in the absence of solvent are also included. This is depicted as $T_c^*$ in the insert figure. $T_c$ represents the crystallization curve in the presence of	

solvent fluid. Starting at homogeneous conditions, increasing the temperature leads to L-L phase separation, and lowering the temperature leads to S-F phase separation.....	280
<b>Figure 9.10</b> FTIR spectrum for original PCL sample. ....	281
<b>Figure 9.11</b> FTIR spectrum for original PMMA sample. ....	282
<b>Figure 9.12</b> Comparison of FTIR spectra for PCL + PMMA blend samples. ....	283
<b>Figure 9.13</b> Comparison of FTIR spectra for PCL ( $M_w = 14$ K), PMMA ( $M_w = 15$ K), and their blends. ....	284
<b>Figure 9.14</b> Comparison of FTIR spectra for PCL ( $M_w = 14$ K), PMMA ( $M_w = 15$ K), and their blends in the wavenumber range $600\text{-}2000\text{ cm}^{-1}$ . The band at $1295\text{ cm}^{-1}$ is used to characterize the crystallinity of the PCL and its blends with PMMA. ....	285
<b>Figure 10.1</b> GPC tests for PMMA samples formed from the MMA polymerizations in acetone at (i) $P = 28$ MPa; (ii). $P = 35$ MPa. ....	304
<b>Figure 10.2</b> Variation of temperature, pressure, density, and viscosity with time during polymerization at 21 MPa (Initial reactant mixture is MMA (10 wt %) + Acetone (90 wt %) + AIBN (0.04 wt %)). ....	305
<b>Figure 10.3</b> Variation of temperature, pressure, density, and viscosity with time during polymerization at 42 MPa (Initial reactant mixture is MMA (10 wt %) + Acetone (90 wt %) + AIBN (0.04 wt %)). ....	306
<b>Figure 10.4</b> Variation of density with time during polymerization at different pressures (Initial reactant mixture is MMA (10 wt %) + Acetone (90 wt %) + AIBN (0.04 wt %)). ....	307
<b>Figure 10.5</b> Variation of viscosity with time at different pressures during polymerization. ....	308
<b>Figure 10.6</b> Variation of Density with time during polymerization at different pressures. ....	309
<b>Figure 10.7</b> Variation of viscosity with time during polymerization at different pressures. ....	310
<b>Figure 10.8</b> Variation of viscosity increasing-rate with pressure for two stages. ....	311
<b>Figure 10.9</b> Density comparisons between present reactant mixtures and other three systems (acetone, 10 wt % PMMA ( $M_w = 15$ K) solution in acetone, 10 wt % PMMA ( $M_w = 540$ K) solution in acetone). ....	312

<b>Figure 10.10</b> Viscosity comparisons between present reactant mixtures and other three systems (acetone, 10 wt % PMMA ( $M_w = 15$ K) solution in acetone, 10 wt % PMMA ( $M_w = 540$ K) solution in acetone). .....	313
<b>Figure 10.11</b> Variation of density with MMA concentration for MMA + acetone mixture and PMMA + MMA + acetone mixture at 7, 14, 21, 28, 35, and 42 MPa. ....	314
<b>Figure 10.12</b> Variation of viscosity with MMA concentration for MMA + acetone mixture and PMMA + MMA + acetone mixture at 7, 14, 21, 28, 35, and 42 MPa. ....	315
<b>Figure 10.13</b> Comparison of the GPC elution times for 5 wt % PMMA solutions ( $M_w = 15$ K and $M_w = 540$ K) with the elution times for 5 wt % MMA solutions in acetone that were kept in the viscometer at 343 K for 24 hours. For the GPC runs, the solutions were diluted 3 times with THF.....	316
<b>Figure 10.14</b> Variation of MMA concentration with time derived from density data at different pressures. ....	317
<b>Figure 10.15</b> Variation of MMA concentration with time derived from viscosity data at different pressures. ....	318
<b>Figure 10.16</b> Comparison of density-derived and viscosity-derived variation of MMA concentration with time at 35 MPa. ....	319
<b>Figure 10.17</b> Variations of MMA concentration with time for polymerizations at different pressures. The MMA concentrations are derived from density information of the reaction mixtures. (See also Figure 10.14) .....	320
<b>Figure 10.18</b> Variations of $\ln [M]$ with time for polymerizations at different pressures. ....	321
<b>Figure 10.19</b> Evaluations of slopes of the $\ln [M]$ versus time plots for polymerizations in the initial 300 mins at different pressures from density data. Pressures are in MPa, and rate constants are in $\text{min}^{-1}$ units. ....	322
<b>Figure 10.20</b> Variations of MMA concentration with time for polymerizations at different pressures. The MMA concentrations are derived from viscosity information of the reaction mixtures. ....	323
<b>Figure 10.21</b> Variations of $\ln [M]$ with time for polymerizations at different pressures. ....	324
<b>Figure 10.22</b> Evaluations of slopes of the $\ln [M]$ versus time plots for polymerizations in the initial 300 mins at different pressures from viscosity data. ....	325
<b>Figure 11.1</b> Molecular structure for poly ( $\epsilon$ -caprolactone) .....	326

<b>Figure 11.2</b> Catalyzed ring-opening polymerization of $\epsilon$ -caprolactone ( $\epsilon$ -CL) to produce poly ( $\epsilon$ -caprolactone) (PCL). .....	327
<b>Figure 11.3</b> Ring opening polymerization of 2-methylene-1,3-dioxepane (MDO) to produce poly ( $\epsilon$ -caprolactone). .....	328
<b>Figure 11.4</b> Branch formations in the free-radical polymerization of MDO .....	329
<b>Figure 11.5</b> Copolymerization of MDO with MMA. ....	330
<b>Figure 11.6</b> Copolymerization of MDO with ST. ....	331
<b>Figure 11.7</b> Copolymerization of MDO with AN. ....	331
<b>Figure 11.8</b> Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical homopolymerizations of MDO in CO <sub>2</sub> at high pressure (P = 28 MPa, T = 323 K, polymerization time = 24 hrs, concentration of MDO = 20.9 wt %, and AIBN concentration = 2.79 wt %).[Polymerization # 2 in Table 11.1] .....	347
<b>Figure 11.9</b> <sup>1</sup> H NMR spectrum for PCL from MDO polymerization (No. 3 in Table 11.1). .....	348
<b>Figure 11.10</b> <sup>13</sup> C NMR spectrum for PCL from MDO polymerization (No. 3 in Table 11.1). .....	349
<b>Figure 11.11</b> Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical copolymerization of MDO with MMA (50/50) in CO <sub>2</sub> at high pressure (P = 28 MPa, T = 343 K, polymerization time = 24 hrs, concentration of MDO = 9.0 wt %, MMA= 9.0 wt %, and AIBN = 2.8 wt % (relative to amount of comonomers)) [Polymerization # 1 in Table 11.3]. ....	350
<b>Figure 11.12</b> Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical copolymerization of MDO with MMA (20/80) in CO <sub>2</sub> at high pressure (P = 28 MPa, T = 343 K, polymerization time = 24 hrs, concentration of MDO = 3.6 wt %, MMA= 13.6 wt %, and AIBN = 3.4 wt % (relative to amount of comonomers)). [Polymerization # 2 in Table 11.3] .....	351
<b>Figure 11.13</b> Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical copolymerization of MDO with MMA	

(10/90) in CO<sub>2</sub> at high pressure (P = 28 MPa, T = 343 K, polymerization time = 24 hrs, concentration of MDO = 1.9 wt %, MMA= 15.3 wt %, and AIBN = 3.0 wt % (relative to amount of comonomers)). [Polymerization # 3 in Table 11.3] ..... 352

**Figure 11.14** Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical copolymerization of MDO with MMA (5/95) in CO<sub>2</sub> at high pressure (P = 28 MPa, T = 343 K, polymerization time = 24 hrs, concentration of MDO = 0.9 wt %, MMA= 16.2 wt %, and AIBN = 3.0 wt % (relative to amount of comonomers)). [Polymerization # 4 in Table 11.3] ..... 353

**Figure 11.15** Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical copolymerization of MDO with styrene (50/50) in CO<sub>2</sub> at high pressure (P = 28 MPa, T = 343 K, polymerization time = 24 hrs, concentration of MDO = 9.0 wt %, ST= 8.8 wt %, and AIBN = 2.8 wt % (relative to amount of comonomers)). [Polymerization # 5 in Table 11.3] ..... 354

**Figure 11.16** Polymerization temperature, pressure, and transmitted light intensity as a function of polymerization time for free-radical copolymerization of MDO with acrylonitrile (50/50) in CO<sub>2</sub> at high pressure (P = 28 MPa, T = 343 K, polymerization time = 24 hrs, concentration of MDO = 10.1 wt %, AN= 9.6 wt %, and AIBN = 4.1 wt % (relative to amount of comonomers)). [Polymerization # 6 in Table 11.3] ..... 355

**Figure 11.17** <sup>1</sup>H NMR spectrum for PMMA. .... 356

**Figure 11.18** <sup>13</sup>C NMR spectrum for PMMA. .... 357

**Figure 11.19** <sup>1</sup>H NMR spectrum for MDO-MMA copolymer (No. 1 in Table 11.3).  
..... 358

**Figure 11.20** <sup>13</sup>C NMR spectrum for MDO-MMA copolymer (No. 1 in Table 11.3).  
..... 359

**Figure 11.21** DSC tests for the 50/50, 20/80, 10/90, 5/95 MDO-MMA copolymers. The second heating scans are shown and the heating rate is 10 K/min. .... 360

**Figure 11.22** DSC test for 50/50 MDO-ST copolymer sample (No. 5 in Table 13.3).  
..... 361

**Figure 11.23** DSC test for 50/50 MDO-AN copolymer sample (No. 6 in Table 13.3).  
..... 361