

SAVANNAH RIVER SITE
AIKEN, S. CAROLINA

LINE SRS-27

MIGRATED STACK
DATUM 80 METERS

NORTHWEST

RECORDING PARAMETERS

DATE RECORDED : APRIL 1988 SOURCE ARRAY : 200/1.0 M (660 FT)
CONTRACTOR : CONCO NO. 28V130 SHOT INTERVAL : 24.4 M (80 FT)
GROUP INTERVAL : 12.2 M (40 FT) PAV OFFSET : 604 M (1980 FT)
NEAR OFFSET : 30.2 M (100 FT) SPREAD RATE : 2 MSEC
INSTRUMENTS : NIS-10 RECORD LENGTH : 14 SEC (4 SEC)
CHANNELS : 96 RECORD FILTERS : 30 HZ & 120 HZ
ENERGY SOURCE : 2 NO. 15 V10 SHOOT FREQ. : 20-120 HZ
SHEEP LENGTH : 18 SEC RECEIVER ARRAY: 14/12.2 M (40 FT)

SPREAD CONFIGURATION
TR 1 TR 40 TR 80
604 M 31 M VP 31 M 604 M

PROCESSING SEQUENCE

DEMULTIPLIXING
VERGOSIS WHITENING - 10000 MS AGC
RECORD PAD - TO 25 SEC
XCOR W/ RECORDED SHEEP (RL=13 SEC.)
TRACE EDITS/DATUM STATICS
30 MS BULK SHIFT APPLIED
80 M DATUM W/ CORR. VEL. 900 M/S
COMMON MIDPOINT SORT
DECONVOLUTION - STREPPED
10 MS GAP 70 MS OPERATOR
AUTOCOR. GATE 10-1000 MS
VELOCITY ANALYSIS - CONSTANT VEL. STKS.
RESIDUAL STATICS - SURFACE CONSISTENT
ITERATIVE W/ VEL. ANALYSIS
3 ITERATIONS STATICS W/ VELOCITY
ITER 1-2 EVERY 2ND TR 15 TR PILOT 10 SHFT
ITER 3 EVERY TR 30 TR PILOT 6 SHFT
NND/MUTE/250 MS AGC
COMMON MIDPOINT STACK - 24 FOLD NOM.
DECONVOLUTION - ZERO PHASE
30 FT SMOOTH DESIGN & OPERATOR
SPECTRUM SHAPE 15-20-120-130 HZ
DESIGN GATE 9-500, 350-1000 MS
FILTER 30-95-110-120 HZ 0-1.0 SEC
AGC - 250 MS
MIGRATION - FINITE DIFFERENCE
100% STACKING VELOCITY
DECIMATE 1 IN 3
MIGRATE 0-12000 MS
FILTER 30-95-110-120 HZ 0-1.0 SEC
SIGNAL
WINDOW : 15 TR
INCREMENT : 5 TR
TIME GATE : 164 MS
DIP RANGE : - 30 MS/TR
DIGISITK 50-50 MIX WITH SIGNAL TRACE
AGC - 250 MS

DISPLAY PARAMETERS

TRACES PER INCH: 40.0 DATE PROCESSED: MAR 1992
INCHES PER SEC: 10.0 POLARITY: NORMAL

VIRGINIA POLYTECHNIC INSTITUTE
AND STATE UNIVERSITY

REGIONAL GEOPHYSICS LABORATORY

PROCESSED BY: W. J. DOMORACKI

