

List of Figures

| | |
|--|----|
| Figure 1-1. Objective of this project: inter-relate the three properties shown above using information based upon the chemical structure of a penetrant | 2 |
| Figure 3-1. DSC Thermogram of R/flex 410 Adhesive | 14 |
| Figure 3-2. Schematic of shear “sandwich” geometry | 18 |
| Figure 3-3. Schematic of shear stud | 18 |
| Figure 4-1. Schematic of the evanescent wave formed at the internal reflection element-sample surface. d_p is defined as the penetration depth (equ. 10). | 22 |
| Figure 4-2 & 4-3. Absorbance ratio A1708/A1165 (Mylar backing/PP) and A1708/A1490 (Mylar/PS) and electric field amplitude decay at 1708cm-1 as a function of thickness of polypropylene layer measured via KRS-5 at 45°. (ref 7) | 24 |
| Figure 4-4. Effect of contact pressure on polypropylene spectra on KRS-5 at 45°. Values refer to torque wrench settings. (ref.8) | 25 |
| Figure 4-5. Plot of n and k spectra during an absorption band at frequency ω_0 . | 27 |
| Figure 4-6. ATR-IR Absorption Near Critical Angle of Polypropylene on KRS-5 IRE. (ref.11) | 28 |
| Figure 4-7. Simulated absorbance spectra $k_{\max}=0.25$ intensity. Band separation distance is designated as Δv . (ref.20) | 30 |
| Figure 4-8. A Plot of Intensity Ratio as Function of Band Separation, Δv . (ref.20) | 30 |
| Figure 4-9: Schematic of the Liquid ATR Diffusion Cell | 44 |
| Figure 4-10. Continued Schematic of the Liquid ATR Diffusion Cell | 44 |
| Figure 4-11. Cross-section of the Liquid ATR-Diffusion Cell with Adhesive Film Shown | 45 |
| Figure 4-12. External schematic of entire ATR setup | 45 |
| Figure 4-13. R/flex 410 Spectrum Variation with Angle of Incidence. Transition from normal absorption to refractive index dispersion. | 47 |
| Figure 4-14. Minimization in the number of terms n for the ATR - Diffusion Model | 48 |

| | |
|--|----|
| Figure 4-15. Plot of log residual (S) vs. Diffusivity and A_{∞} . Note that the x and y axes are arbitrary units for illustration. | 49 |
| Figure 4-16. Simplex Fit of PAN 102°C Literature Data (ref. 32) | 49 |
| Figure 4-17. Transmission IR Spectra of R/flex 410 Adhesive Material | 50 |
| Figure 4-18. Overlay of Isodecyl Pelargonate and R/flex 410 Adhesive Material | 51 |
| Figure 4-19. Simulation of Thickness Dependence | 51 |
| Figure 4-20. In-situ Monitoring of Ester Diffusion (IDP at 23°C) | 52 |
| Figure 4-21. Optimized Fit of IDP + Polymer Experimental Data (23°C) | 52 |
| Figure 4-22. Plot of log S (residual error) vs. Diffusivity and A_{∞} for IDP Diffusion. Note that the x and y-axes are arbitrary units | 53 |
| Figure 4-23. Experimental Data and Curve Fit for Ethyl Myristate (23°C) | 53 |
| Figure 4-24. Experimental Data and Curve Fit for Ethyl Undecanoate (23°C) | 54 |
| Figure 4-25. Experimental Data and Curve Fit for Ethyl Heptanoate (23°C) | 54 |
| Figure 4-26. Experimental Data and Curve Fit for Propyl Butyrate (23°C) | 55 |
| Figure 4-27. Diffusivity vs. Molecular Size of Ester Penetrants (23°) | 57 |
| Figure 4-28. Equilibrium IR Absorbance vs. Solubility Parameters of Esters | 57 |
| Figure 4-29. Chemical Shifts of Amide I Absorption (~1640 cm ⁻¹) as a Function of Exposure Time to Ester Penetrants. | 58 |
| Figure 4-30. Chemical Shifts of Amide II Absorption (~1547 cm ⁻¹) as a Function of Exposure Time to Ester Penetrants | 58 |
| Figure 5-1. Fractional Mass Uptake for n-alkanes at 23°C as a Function of Linear Time | 63 |
| Figure 5-2. Fractional Mass Uptake for n-alkanes at 23°C as a Function of Normalized Time | 63 |
| Figure 5-3. Fractional Mass Uptake for n-alkanes at 45°C as a Function of NormlizedTime | 64 |

| | |
|---|----|
| Figure 5-4. Fractional Mass Uptake for n-alkanes at 55°C as a Function of Normalized Time | 64 |
| Figure 5-5. Fractional Mass Uptake for n-alkanes at 65°C as a Function of Normalized Time | 65 |
| Figure 5-6. Fractional Mass Uptake for n-alkanes at 85°C as a Function of Normalized Time | 65 |
| Figure 5-7. Nonlinear Curve Fit of equation (3) to experimental data of Heptadecane at 23°C | 66 |
| Figure 5-8. Structural and temperature dependence of the parameter K for the n-alkanes | 67 |
| Figure 5-9. Equilibrium sorption for n-alkanes and its dependence upon temperature | 67 |
| Figure 5-10. Equilibrium sorption as a function of solubility parameter for n-alkanes | 68 |
| Figure 5-11. Evaluation of diffusion coefficient for undecane penetrant at 23°C is shown above. The initial slope of the fractional mass uptake versus the square root of time is proportional to the diffusivity. Red line shows the result of a linear fit. | 69 |
| Figure 5-12. Error analysis involving decane at 45°C. The average value for D was $9.1 (\pm 0.4) \times 10^{-9} \text{ cm}^2/\text{sec}$. A deviation of 4.4% is given for all 11 experiments. | 70 |
| Figure 5-13. Molecular weight dependence of diffusivity for alkanes | 81 |
| Figure 5-14. Plot of Log D (cm^2/sec) as a function of molar volume for the n-alkanes | 82 |
| Figure 5-15. Arrhenius analysis for n-alkanes. Plot shows log D (cm^2/sec) as a function of 1/T. | 83 |
| Figure 5-16. Molar volume dependence of the activation energy of diffusion for n-alkanes | 86 |
| Figure 5-17. Relationship between the Arrhenius diffusion front factor (D_0) and the activation energy of diffusion (E_d) for the n-alkanes | 87 |
| Figure 5-18. Arrhenius analysis of n-alkane permeability (cm^2/sec) | 89 |
| Figure 5-19. Kinetic plot of tridecane sorption at 23°C | 93 |

| | |
|---|-----|
| Figure 5-20. van't Hoff analysis of n-alkane solubility as a function of temperature | 96 |
| Figure 5-21. Fractional mass uptake for ester penetrants at 23°C | 97 |
| Figure 5-22. Fractional mass uptake for ester penetrants at 45°C | 98 |
| Figure 5-23. Fractional mass uptake for ester penetrants at 55°C | 98 |
| Figure 5-24. Fractional mass uptake for ester penetrants at 65°C | 99 |
| Figure 5-25. Fractional mass uptake for ester penetrants at 85°C | 99 |
| Figure 5-26. K versus the number of carbon atoms in the ester penetrants for temperature isotherms. | 106 |
| Figure 5-27. Equilibrium weight uptake versus molar mass of the esters | 107 |
| Figure 5-28. Equilibrium weight percent uptake for esters as a function of their solubility parameters. | 107 |
| Figure 5-29. Weight percent uptake versus temperature for esters | 108 |
| Figure 5-30. Fractional mass uptake for ester penetrants at 23°C versus square root of normalized time | 109 |
| Figure 5-31. Fractional mass uptake for ester penetrants at 45°C versus square root of normalized time | 109 |
| Figure 5-32. Fractional mass uptake for ester penetrants at 55°C versus square root of normalized time | 110 |
| Figure 5-33. Fractional mass uptake for ester penetrants at 65°C versus square root of normalized time | 110 |
| Figure 5-34. Fractional mass uptake for ester penetrants at 85°C versus square root of normalized time | 111 |
| Figure 5-35. Power law fit to molecular weight of ester penetrants | 113 |
| Figure 5-36. Log D versus molar volume for ester penetrants | 114 |
| Figure 5-37. Arrhenius plots for the ester penetrants | 115 |
| Figure 5-38. Activation energy of diffusion, E_d , versus molar volume of esters | 116 |

| | |
|---|-----|
| Figure 5-39. Plot of Arrhenius front factor, D_0 , versus activation energy of diffusion, E_d , for ester penetrants | 117 |
| Figure 5-40. Arrhenius analysis of permeability coefficients for ester penetrants | 118 |
| Figure 5-41. Van't Hoff analysis of ester solubility as a function of temperature | 120 |
| Figure 5-42. Log-Log plot of D and molecular weight for alkanes and esters | 132 |
| Figure 5-43. Simplified view of Log-Log plot of Figure 5-45 showing 23° and 65°C data | 132 |
| Figure 5-44. Composite graph showing the penetrant size effects for both penetrant series. A plot of Log diffusivity (cm^2/sec) versus the molar volume of each penetrant at each test temperature. | 134 |
| Figure 5-45. Comparison between the molecular weight dependence of activation energies for diffusion for the n-alkane and ester penetrants | 134 |
| Figure 5-46. Comparison between the molar volume dependence of the activation energy for diffusion of the n-alkane and ester series of penetrants | 135 |
| Figure 5-47. Plot of $\log D$ (cm^2/sec) versus the number of carbon atoms for n-alkanes | 136 |
| Figure 5-48. Plot of $\log D$ (cm^2/sec) versus number of carbon atoms for ester penetrants | 137 |
| Figure 5-49. Plot of aspect ratios calculated for select n-alkanes and esters from the geometric dimensions provided by Monte-Carlo simulations | 141 |
| Figure 5-50. CPK images from Monte-Carlo simulations of hexane | 142 |
| Figure 5-51. CPK images from Monte-Carlo simulations of nonane | 143 |
| Figure 5-52. CPK images from Monte-Carlo simulations for decane | 144 |
| Figure 5-53. CPK images from Monte-Carlo simulations for tridecane | 145 |
| Figure 5-54. CPK images from Monte-Carlo simulations for pentadecane | 146 |
| Figure 5-55. CPK images from Monte-Carlo simulations for hexadecane | 147 |
| Figure 5-56. CPK images from Monte-Carlo simulations for heptadecane | 148 |
| Figure 5-57. Monte-Carlo simulations for ethyl propionate | 149 |

| | |
|--|-----|
| Figure 5-58. Monte-Carlo simulations for ethyl heptanoate | 150 |
| Figure 5-59. Monte-Carlo simulations for ethyl nonoate | 151 |
| Figure 5-60. Monte-Carlo simulations for ethyl myristate | 152 |
| Figure 5-61. Monte-Carlo simulations for isopropyl myristate | 153 |
| Figure 5-62. Monte-Carlo simulations for isodecyl pelargonate | 154 |
| Figure 5-63. Temperature dependence of Flory-Huggins interaction parameter for n-alkanes | 155 |
| Figure 5-64. Temperature dependence of Flory-Huggins interaction parameter for esters | 156 |
| Figure 5-65. Equilibrium sorption versus Flory-Huggins interaction parameter for n-alkanes | 156 |
| Figure 5-66. Equilibrium sorption versus Flory-Huggins interaction parameter for ester penetrants | 157 |
| Figure 5-67. Activation energy of diffusion for the n-alkane and ester penetrants versus the Flory-Huggins interaction parameter | 158 |
| Figure 5-68. Log Diffusivity (cm^2/sec) versus Flory-Huggins interaction parameter for n-alkane penetrants | 159 |
| Figure 5-69. Log Diffusivity (cm^2/sec) versus molecular weight for n-alkane penetrants | 159 |
| Figure 5-70. Log Diffusivity (cm^2/sec) versus Flory-Huggins interaction parameter for ester penetrants | 160 |
| Figure 5-71. Log Diffusivity (cm^2/sec) versus Flory-Huggins interaction parameter for n-alkanes and esters at 23°C | 161 |
| Figure 5-72. Plot of Log D (cm^2/sec) versus $(\text{Chi} \cdot \text{Vm})^{-1}$ for esters and alkanes. Esters are designated with open symbols. Data have been shifted along the y-axis for the sake of clarity. | 164 |
| Figure 5-73. Activation energy of diffusion (E_d , kJ/mole) for both n-alkanes and esters versus $(\text{Chi} \cdot \text{Vm})$. A first-order exponential decay has been fit to aid in visualization. | 165 |

| | |
|--|-----|
| Figure 6-1: Schematic Plot of Cole-Cole Model | 180 |
| Figure 6-2. Schematic of Cole-Davidson Model | 180 |
| Figure 6-3. ACF for poly(hydroxybutyrate) at temperatures increasing from 25°C to 33°C (left to right) in increments of 2°C. | 183 |
| Figure 6-4. Dynamic loss moduli as a function of frequency for polymer sample exposed to decane penetrant for 10 ⁵ minutes | 185 |
| Figure 6-5. Frequency-temperature master curve of polymeric adhesive after exposure to decane for 10 ⁵ minutes | 187 |
| Figure 6-6. Temperature-shift factor plot for polymeric adhesive exposed to decane for 10 ⁵ minutes. C1 and C2 values are 8.03 and 76.0, respectively. | 188 |
| Figure 6-7. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to decane penetrant for 10 ² minutes. (legend same as in Figure 6-5) | 191 |
| Figure 6-8. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to decane penetrant for 10 ⁰ minute. (legend same as in Figure 6-5) | 192 |
| Figure 6-9. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to tridecane penetrant for 10 ¹ minutes. (legend same as in Figure 6-5) | 193 |
| Figure 6-10. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to tridecane penetrant for 10 ³ minutes. (legend same as in Figure 6-5) | 194 |
| Figure 6-11. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to tridecane penetrant for 10 ⁵ minutes. (legend same as in Figure 6-5) | 195 |
| Figure 6-12. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to ethyl propionate penetrant for 10 ⁰ minutes. (legend same as in Figure 6-5) | 196 |
| Figure 6-13. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to ethyl propionate penetrant for 10 ¹ minutes. (legend same as in Figure 6-5) | 197 |

| | |
|--|-----|
| Figure 6-14. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to ethyl propionate penetrant for $10^{3.70}$ minutes. (legend same as in Figure 6-5) | 198 |
| Figure 6-15. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to propyl butyrate penetrant for 10^0 minutes. (legend same as in Figure 6-5) | 199 |
| Figure 6-16. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to propyl butyrate penetrant for 10^1 minutes. (legend same as in Figure 6-5) | 200 |
| Figure 6-17. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to propyl butyrate penetrant for 10^3 minutes. (legend same as in Figure 6-5) | 201 |
| Figure 6-18. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to ethyl myristate penetrant for 10^0 minutes. (legend same as in Figure 6-5) | 202 |
| Figure 6-19. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to ethyl myristate penetrant for 10^1 minutes. (legend same as in Figure 6-5) | 203 |
| Figure 6-20. Frequency-temperature dynamic loss modulus master curve and the corresponding temperature shift-factor plot of adhesive exposed to ethyl myristate penetrant for $10^{3.70}$ minutes. (legend same as in Figure 6-5) | 204 |
| Figure 6-21. Frequency-temperature master curves for exposure times of 10^2 and 10^5 minutes to decane penetrant | 214 |
| Figure 6-22. Normalized frequency-temperature master curves for various penetrant exposure times to decane (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, decane (bottom). | 216 |
| Figure 6-23. Diffusion-time shift factors, $\log a_{Dt}$, for adhesive exposed to decane at various times. | 217 |
| Figure 6-24. Normalized frequency-temperature master curves for various penetrant exposure times to hexane (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, hexane (bottom). | 218 |
| Figure 6-25. Normalized frequency-temperature master curves for various penetrant exposure times to tridecane (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, tridecane (bottom). | 219 |

| | |
|--|-----|
| Figure 6-26. Normalized frequency-temperature master curves for various penetrant exposure times to hexadecane (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, hexadecane (bottom). | 220 |
| Figure 6-27. Normalized frequency-temperature master curves for various penetrant exposure times to ethyl propionate (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, ethyl propionate (bottom). | 221 |
| Figure 6-28. Normalized frequency-temperature master curves for various penetrant exposure times to propyl butyrate (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, propyl butyrate (bottom). | 222 |
| Figure 6-29. Normalized frequency-temperature master curves for various penetrant exposure times to isopropyl myristate (top). Doubly reduced temperature and diffusion-time master-master curves for penetrant, isopropyl myristate (bottom). | 223 |
| Figure 6-30. Diffusion-time shift factors for n-alkanes as a function of normalized time | 224 |
| Figure 6-31. Diffusion-time shift factors for esters as a function of normalized time | 224 |
| Figure 6-32. Diffusion-time shift factors as a function of penetrant composition for n-alkane penetrants | 226 |
| Figure 6-33. Diffusion-time shift factors as a function of penetrant composition for ester penetrants | 226 |
| Figure 6-34. Autocorrelation decay functions, $\Phi(t)$, for polymer-penetrant system of heptadecane at various exposure times. | 228 |
| Figure 6-35. KWW Beta parameter as a function of exposure time to n-alkane penetrants | 230 |
| Figure 6-36. KWW Beta parameter as a function of exposure time to ester penetrants | 230 |
| Figure 6-37. Evaluated KWW tau as a function of normalized time for polymer adhesive exposed to n-alkane penetrants. | 233 |
| Figure 6-38. Evaluated mean relaxation time, $\langle \tau \rangle$, as a function of normalized time for polymer adhesive exposed to n-alkane penetrants. | 233 |
| Figure 6-39. Evaluated KWW tau as a function of normalized time for polymer adhesive exposed to ester penetrants. | 234 |

| | |
|--|-----|
| Figure 6-40. Evaluated mean relaxation time, $\langle \tau \rangle$, as a function of normalized time for polymer adhesive exposed to ester penetrants. | 234 |
| Figure 7-1. Arrhenius parameters for the diffusion of n-alkanes and esters | 240 |
| Figure 7-2. Fractional Composition as a function of Normalized time for various Diffusivities | 241 |
| Figure 7-3. Equilibrium weight percent uptake for both series of penetrants as a function of the Flory-Huggins interaction parameter χ | 242 |
| Figure 7-4. Diffusion-time shift factors for both n-alkane and ester penetrants as a function of weight percent uptake | 243 |