

List of Illustrations

Chapter 1: Introduction.....	(1-15)
Figure 1.2.1: Schematic of a Blackbody Cavity High Temperature Sensor..	5
Figure 1.2.2: Illustration of the Principle of a FO/ATR Spectroscopic Sensor.....	6
Figure 1.2.3: Intensity-Based Sensor Schematic.....	7
Figure 1.2.4: Sapphire Rod Displacement Sensor.....	8
Figure 1.2.5: Sapphire Extrinsic Fabry-Perot Interferometer.....	9
Figure 1.2.6: Absolute Strain Sensor and Illustrative Output.....	10
Figure 1.2.7: Determination of Fringe Visibility.....	11
Figure 1.2.8: Sapphire-Based Intrinsic Fabry-Perot Interferometer.....	12
Figure 1.2.9: (a) General Design of a Polarimetric Sensor System, (b) Non-Birefringence Balanced Sensor Head Design, (c) Birefringence Balanced Sensor Head.....	13
Figure 1.2.10: System Used to Test Viability of a Sensor Based on the Principle of Spatial Modulation.....	14
 Chapter 2: Sapphire Optical Fiber.....	 (16-30)
Figure 2.1.1: The Laser Heated Pedestal Growth Process.....	18
Figure 2.2.1: Measured and Theoretical Attenuation in Bulk Sapphire.....	22
Figure 2.2.2: Measured Attenuation in Bulk Sapphire and in Sapphire Fiber.....	23
Figure 2.2.3: One Hour Bend Survival Strengths, Fast-Fracture Tensile Strengths, and Bend Strengths Versus Temperature.....	27
 Chapter 3: White-Light Michelson Interferometry with Optical Fibers	 (31-59)
Figure 3.1.1: Michelson Interferometer.....	33
Figure 3.1.2: Fringes From Bulk-Optic Michelson Interferometer.....	34
Figure 3.2.1: Young's Interference Experiment.....	42
Figure 3.2.2: Propagation of a Wavefront.....	43
Figure 3.4.1: Normalized Sample Fringe Visibility for Source with Gaussian Spectrum.....	47
Figure 3.4.2: Normalized Sample Fringe Visibility for Source with Lorentzian Spectrum.....	48
Figure 3.5.1: Basic Schematic of a WSFMI Fiber Sensor.....	57
Figure 3.5.2: Interferogram Detected at Output of WSFMI.....	59

Chapter 4: The WSFMI with a Sapphire Fiber Sensing Head.....(60-107)

Figure 4.1.1:	Basic Configuration of the WSFMI System.....	62
Figure 4.1.2:	WSFMI Interferogram Generated Using a Sensing Head Composed of Silica Graded Index Multimode Fiber. Highlight of the Reference Fiber Fringe Group.....	64
Figure 4.1.3:	WSFMI Interferogram Generated Using a Sensing Head Composed of Silica Graded Index Multimode Fiber. Highlight of the Sensing Fiber Fringe Group.....	65
Figure 4.1.4:	Generation of EFPI Fringes Using the Isolated WSFMI Sensing Head.....	66
Figure 4.2.1:	WSFMI System Without a Sensing Fiber in the Sensing Head.....	68
Figure 4.2.2:	Interferogram Generated When a Sensing Head Consisting of Solely a Sapphire Reference Fiber is Used in the Basic WSFMI System.....	69
Figure 4.2.3:	Propagation of a Mode of Width W Around a Bend of Radius R	71
Figure 4.2.4:	Interferogram Generated After Bend Loss is Used to Strip Higher Order Modes.....	72
Figure 4.2.5:	Geometry of a Linear Taper.....	73
Figure 4.2.6:	Interferogram Generated After a Fiber Taper is Used to Strip Higher Order Modes.....	75
Figure 4.2.7:	Faraday Rotators Used in a Michelson Interferometer Configuration.....	77
Figure 4.2.8:	Inflexible Apparatus Used to Couple Light From a Singlemode Fiber to a Multimode Fiber.....	79
Figure 4.2.9:	Flexible Apparatus Used to Couple Light From a Singlemode Fiber to a Multimode Fiber.....	80
Figure 4.3.1:	Optimized Interferogram Generated Using a Sapphire Reference Fiber in the Sensing Head of the Modified WSFMI System.....	85
Figure 4.3.2:	Optimized Interferogram Generated Using a Sapphire Reference Fiber and an Aluminum Coated Sensing Fiber in the Sensing Head of the Modified WSFMI System.....	87
Figure 4.3.3:	Typical Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at Room Temperature.....	88
Figure 4.3.4:	Measured Gap Length Plotted Against the Indicated Transverse Stage Demarcations.....	89
Figure 4.3.5:	Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at Room Temperature. There is a Bend of 90 Degrees in the Reference Fiber.....	90

Figure 4.3.6: Test 1. Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at Room Temperature.....	92
Figure 4.3.7: Test 1. Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at 500 Degrees Celsius.....	93
Figure 4.3.8: Test 2. Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at Room Temperature.....	95
Figure 4.3.9: Test 2. Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at 800 Degrees Celsius.....	96
Figure 3.4.10: Test 2. Representative Intensity Variations Detected Between 700 and 800 Degrees Celsius While Using a Sapphire Fiber Sensing Head in the Modified WSFMI System.....	97
Figure 4.3.11: Test 3. Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at Room Temperature.....	99
Figure 4.3.12: Test 3. Optimized Interferogram Obtained Using a Sapphire Fiber Sensing Head in the Modified WSFMI System at 800 Degrees Celsius.....	100
Figure 4.3.13: Sapphire Fiber EFPI Fringes Generated After Using the Modified WSFMI System to Align the Sensing and Reference Fibers.....	102
Figure 4.3.14: Sapphire Fiber EFPI Fringes Generated After Detuning the Optimal the Modified WSFMI System Alignment Laterally by 5 Micrometers.....	103