

## ABSTRACT

Nitrification performance of three, fluidized-bed filters was investigated. Each filter contained 10 L of plastic bead medium (near neutral specific gravity and 2-4 mm diameter and length) and was loaded under conditions of various flow rates and ammonia levels. Bead settled depth and biofilter diameter (12.7, 15.2 and 17.8 cm) were the factors differing among the filters. The experiments were conducted with three replicate recirculating systems. Each system included one of the three different biofilter types, connected in parallel to a reservoir containing 500 L of water. Systems were allowed to acclimate using a synthetic nutrient substrate, which was followed by a comparative analysis of biofilter performance. To evaluate filter performance, ammonia inflow concentration, ammonia loading rates, nitrite, nitrate, temperature, pH, dissolved oxygen levels, hardness, alkalinity and flow rates were monitored. Initially, four different flow rates, ranging from 6 Lpm–12 Lpm, were tested at constant ammonia feed level (8.4 g/day). Here, biofilter D<sub>3</sub> (17.8 cm diameter) showed the best ammonia removal performance at a flow rate of 6 Lpm, followed by the performance of D<sub>1</sub> (12.7 Lpm) and D<sub>2</sub> (15.2 Lpm). The difference in ammonia and nitrite removal performance decreased among the biofilters, as flow rate increased. An increase in flow rate also lowered ammonia level in the systems at a constant ammonia loading, but did not affect the nitrite concentration. Five different ammonia feed rates, ranging from 8.4 – 16.8 g/day, were tested in the second part of the study, at a constant flow rate of 12 Lpm in each column. Different ammonia and nitrite removal performance was observed between biofilter sizes. Ammonia accumulated in the tanks as ammonia loading increased, but nitrite concentration remained relatively constant. The results indicated that nitrification performance improved by 17 % as the applied flow rate was increased. Ammonia concentration decreased slightly, from 0.6 mg/L to 0.5 mg/L. The performance appeared to be limited at higher ammonia loadings, at which time ammonia concentration increased from 0.5 to 0.99 mg/L. Data on biofilm development indicates a reduction in biofilm thickness as flow rate was increase, and significant biofilm accumulation as ammonia supply increased. The results of this work were compared to performance data generated using a steady state biofilm model, developed by Rittmann and McCarty

(1980). The model predicted higher values of biofilm thickness ( $L_f$ ) than those seen in this study.

Fluidized bed filters with plastic bead medium proved to be effective in removing ammonia and nitrite from a synthetic aquaculture water.

## BIBLIOGRAPHY

- Antonie, R.L. 1976. Fixed biological surface wastewater treatment: the rotating biological contactor. CRC Press Inc., Cleveland, Ohio. 200p.
- Atkinson, B., G.M. Black and A. Pinches, 1981. The characteristics of solid supports and biomass supports particles when used in fluidized beds. Pp. 75 – 106. In Biological fluidized bed treatment of water and wastewater, Chichester, England.
- Atkinson, B. and A. J. Knights. 1975. Microbial film fermenters: Their present and future applications. *Biotechnology and Bioengineering*, 17: 1245.
- Atkinson, B. and H.B. Fowler. 1974. The significance of microbial film in fermenters. *Advances in Biochemical Engineering*, 3: 221 – 227.
- Atkinson, B. and I. J. Daves. 1972. The completely mixed microbial film fermenter. *Transactions of the Institution of Chemical Engineers*, 50: 208.
- Brune, D.E. and D.C. Gunther. 1981. The design of a new high rate nitrification filter for aquaculture water reuse. *Journal of World Mariculture Society*, 12 (1): 20 – 31.
- Characklis, W.G. 1973. Attached microbial growth – I. Attachment and growth. *Water Research*, Washington D.C., Vol. 7, 1113 p.
- Chen, S., D.E. Coffin and R.F. Malone. 1993. Production, characteristics, and modeling of aquacultural sludge from a recirculating aquacultural system using a granular media biofilter. Pp.16-25. In J.K. Wang, editor. *Techniques for modern aquaculture*. American Society of Agricultural Engineers, St. Joseph, Michigan.
- Cook, E.E. and O.F. Kincannon. 1971. An evaluation of trickling filter performance. *Proceedings of the 25<sup>th</sup> Industrial Waste Conference*, Engineering Bulletin of Purdue University, Extension Series No. 137. Pp. 230 – 235.

- Easter, C.C. 1992. Water chemistry characterization and component performance of a recirculating aquaculture system producing hybrid striped bass. M.S. Thesis, Department of Environmental Engineering. Virginia Polytechnic Institute and State University, Blacksburg, Virginia.
- Fan, L., K. Fujie, T. R. Long and W. T. Tang. 1987. Characteristics of draft tube gas-liquid-solid fluidized-bed bioreactor with immobilized living cells for phenol degradation. *Biotechnology and Bioengineering* 30: 498 – 504.
- Gaudy, A. F. and E.T. Gaudy. 1988. *Elements of Environmental Engineering*. Engineering Press Inc., San Jose, California: 592.
- Grady, C.P.L. and H.C. Lim. 1980. A conceptual model of RBC performance. *Proceedings, First National Symposium/Workshop on Rotating Biological Contactor Technology*, E.D. Smith, R.D. Miller, and Y.C. Wu, editors. University of Pittsburg, Pittsburg, pp. 829 – 859.
- Gujer W. and M. Boller. 1986. Design of nitrifying tertiary trickling filter based on theoretical concepts. *Water Research*, 20 (11): 1353 – 1362.
- Hall, A.G. 1999. A comparative analysis of three biofilter types treating wastewater produced in recirculating aquaculture systems. M.S. Thesis, Fisheries and Wildlife Department, Virginia Polytechnic Institute and State University, Blacksburg, Virginia.
- Haug, R.T. and P.L. McCarty. 1972. Nitrification with submerged filters. *Journal Water Pollution Control Federation* 44 (11): 2086 – 2102.
- Hochheimer, J.N. 1990. Trickling filter model for closed system aquaculture. Unpublished. PhD. Dissertation. University of Maryland. College Park, Maryland.
- Jeris, J.S., C. Beer, and J.A. Muller. 1974. High rate biological denitrification using a granular fluidized bed. *Journal Water Pollution Control Federation* 46(9): 2118 –2128.
- Jones R.D. and R.Y. Morita. 1985. Low temperature growth and whole cell kinetics of a marine ammonia oxidizer. *Marine Ecology Progress Series* 21: 239 – 243.
- Kaiser, G.E. and F. W. Wheaton. 1983. Nitrification filters for aquatic culture systems: state of the art. *Journal of the World Mariculture Society* 14: 302 – 324.
- Klontz, G.W. 1979. Recent advances in evaluating biofilter performance. Pp. 90 – 91.

- In L.J. Allen and E.C. Kinney, editors. Bioengineering symposium for fish culture. American Fisheries Society, Bethesda, Maryland.
- Lazarova, V. and J. Manem. 1994. Advances in biofilm aerobic reactors ensuring effective biofilm activity control. *Water Science and Technology* 29 (10/11): 319 – 327.
- Libey, G.S. 1996. How to evaluate a “paper system”. Pp. 363 – 372. In G.S. Libey and M.B. Timmons, editors. *Aquaculture Engineering Society Proceedings II: Successes and failures in commercial aquaculture*. Northeast Regional Agricultural Engineering Service, Ithaca, New York.
- Libey, G.S. and G.E. Miller. 1985. Evaluation of three biological filters suitable for aquacultural applications. *Journal of the World Mariculture Society* 16: 158-168.
- Losordo, T.M. 1991. Engineering considerations in closed recirculating systems. Pp. 58-69. In *Aquaculture systems engineering*. American Society of Agricultural Engineers, St. Joseph, Michigan.
- Losordo, T.M. and M.B. Timmons. 1994. An introduction to water reuse systems. Pp. 1-7. In M.B. Timmons and T.M. Losordo, editors. *Aquaculture water reuse systems: Engineering design and management*. *Developments in aquaculture and fisheries science*, vol. 27. Elsevier Science, Amsterdam.
- Malone, R.F., B.S. Chitta and D.G. Drennan II. 1993. Optimizing nitrification in bead filters for warmwater recirculating aquaculture. Pp. 315-325. In J.K. Wang, editor. *Techniques for modern aquaculture*. American Society of Agricultural Engineers, St. Joseph, Michigan.
- Malone, R.F. and D.G. Burden. 1988. Design of recirculating blue crab shedding systems. Department of Civil Engineering, Louisiana State University, Baton Rouge, Louisiana.
- Nagel, C.A. and J.G. Havorth. 1969. Operational factors affecting nitrification in the activated sludge process. Presented at the 42<sup>nd</sup> Annual Conference of the Eater Pollution Control Federation, Dallas, Texas.
- O’Shaughnessy, J.C., F.C. Blanc and T.G. Barker. 1982. Fixed film nitrification kinetics. *Proceedings of the First International Conference on Fixed-film Biological processes*, Kingsland, Ohio: 1363 – 1388.
- Owsley, D.E. 1993. Status of U.S. Fish and Wildlife Service hatcheries with reuse systems in region 1: 278 –283. In J. K. Wang, editor. *Techniques for Modern Aquaculture*. American Society of Agricultural Engineers, St. Joseph, Michigan.

- Rittmann B.E. and P.L. McCarty. 1978. Variable-order model of bacterial-film kinetics. *Journal of the Environmental Engineering Division, ASCE*, Vol. 104, (EE5): 889 - 900.
- Rittmann, B.E. 1982. Comparative performance of biofilm reactor types. *Biotechnology and Bioengineering* 24: 1341 – 1370.
- Rittmann B.E. and P.L. McCarty. 1980. Model of steady-state biofilm. *Biotechnology and Bioengineering* 22: 2343 – 2357.
- Roberts, J. 1985. Mathematical models for trickling filter process. Pp. 112 – 116. In *Mathematical Models in Biological Wastewater Treatment*, E. Jorgensen and M.J. Gromiec, Editors. Elsevier, Amsterdam.
- Rosenthal, H.R. 1994. Aquaculture and the Environment. *World Aquaculture* 25: 4 –11.
- Saez, P. and Rittmann B.E. 1987. Improved pseudoanalytical solution for steady-state biofilm kinetics. *Biotechnology and Bioengineering* 32: 379 – 385.
- Spotte, S. 1979. Fish and invertebrate culture: Water management in closed systems, 2<sup>nd</sup> ed. Wiley-Interscience, New York.
- Van Gorder, S.D. 1994. Operating and managing water reuse systems. Pp. 281 – 306. In M.B. Timmons and T.M. Losordo, editors. *Aquaculture water reuse system: Engineering design and management. Developments in Aquaculture and Fisheries Science*, vol. 27. Elsevier Science, Amsterdam.
- Youngs, W.D. and M.B. Timmons. 1991. A historical perspective of raceway design. Pp. 160 – 169. In *Engineering Aspects of Intensive Aquaculture*. Northeast Regional Agricultural engineering Service, Ithaca, New York.
- Water Pollution Control Federation. 1983. Nutrient control, manual of practice. Publication Number FD-7. Washington, D.C.
- Wedemeyer, A. 1996. *Physiology of fish in intensive culture systems*. Chapman and Hall, New York.
- Westerman, P.W., T.M. Losordo and M.L. Wildhaber. 1996. Evaluation of various

biofilters in an intensive recirculating fish production facility. Transactions of the American Society of Agricultural Engineers 39: 723-727.

Wheaton, F.W., J.N. Hochheimer, G.E. Kaiser, R.F. Malone, M.J. Krones, G.S. Libey and C.C. Easter. 1994. Nitrification filter design methods. Pp. 127 – 171. In M.B. Timmons and T.M. Losordo editors. Aquaculture water reuse systems: Engineering Design and Management. Developments in aquaculture and fisheries science, vol. 27. Elsevier Science, Amsterdam.

Wheaton, F.W., J. Hochheimer and G.E. Kaiser. 1990. Fixed film nitrification filters for aquaculture. Pp. 272 – 303. In Proceedings Aquaculture Water Quality Symposium. World Aquaculture Society, Baton Rouge, Louisiana.

Williamson, K. and P. McCarty. 1976. Verification studies of the biofilm model for bacterial substrate utilization. Journal of the Water Pollution Control Federation 48 (2): 281 – 296.

Zhu, S. and S. Chen. 1999. An experimental study on nitrification biofilm performances using a series reactor system. Aquacultural Engineering 20: 245 - 259.