

List of Tables

Table	Page
2.1. New design earthquakes and performance objectives in the new LRFD guidelines	6
3.1. Definition of foundation modeling method	22
3.2. Multiple presence factors	26
3.3. Dynamic load allowance	26
3.4. Load combinations and load factors	27
3.5. Values of F_a as a function of site class and mapped short-period spectral acceleration	29
3.6. Values of F_v as a function of site class and mapped one second period spectral acceleration	29
3.7. Seismic Hazard Levels	30
3.8. Seismic Design and Analysis Procedures (SDAP) and Seismic Design Requirements (SDR)	30
3.9. Base response modification factors (R) for substructures	41
3.10. Results of the detailing requirement checks for the bridge using Seismic Design Requirement 3	45
4.1. Results of the detailing requirement checks for the West Bound steel girder bridge using Seismic Design Requirement 5	77
4.2. Results of the detailing requirement checks for the East Bound steel girder bridge using Seismic Design Requirement 5	79
5.1. Periods of vibration in the transverse direction for the parametric study	88
5.2. Periods of vibration in the longitudinal direction for the parametric study	88

III-1. Coordinates of the joints of the RISA 3D model of the prestressed concrete girder bridge	108
III-2. Member numbers of the RISA 3D model of the prestressed concrete girder bridge	109
IV-1. Results of the calculation to determine the column cracked section properties of the prestressed concrete girder bridge	110
V-1. Calculation for the maximum positive and negative moments in the pier cap beam of the prestressed concrete girder bridge	117
VIII-1. Complete results of the dead load, live load and earthquake load effects for the prestressed concrete girder bridge	120
XI-1. Estimate for the construction cost of the prestressed concrete girder bridge	136
XIV-1. Joint coordinates of the West Bound and East Bound steel girder bridges	157
XIV-2. Member numbers of the steel girder bridge	158
XV-1. Results of the calculation to get the column cracked section properties of the steel girder bridges	159
XVI-1. Calculation for the maximum positive and negative moments in the pier cap beams of the steel girder bridges	164
XVIII-1. Calculation to get the period of vibration and equivalent lateral loads for the West Bound of the steel girder bridge using the single mode spectral analysis method	173
XVIII-2. Calculation to get the period of vibration and equivalent lateral loads for the East Bound of the steel girder bridge using the single mode spectral analysis method	174
XIX-1. Complete results of the dead load, live load and earthquake load effects for the West Bound of the steel girder bridge	175
XIX-2. Complete results of the dead load, live load and earthquake load effects for the East Bound of the steel girder bridge	175
XXII-1. Estimate for the construction cost of the two steel girder bridges	213
XXIII-1. Period of vibration in the transverse direction for the parametric study bridge	245

XXIII-2. Period of vibration in the longitudinal direction for the parametric study bridge	245
XXIII-3. Spectral accelerations in the longitudinal direction for a bridge in Vienna, VA	252
XXIII-4. Equivalent longitudinal earthquake loads in kips for a bridge in Vienna, VA	252
XXIII-5. Spectral accelerations in the longitudinal direction for a bridge in Richmond, VA	253
XXIII-6. Equivalent longitudinal earthquake loads in kips for a bridge in Richmond, VA	253
XXIII-7. Spectral accelerations in the longitudinal direction for a bridge in Bristol, VA	254
XXIII-8. Equivalent longitudinal earthquake loads in kips for a bridge in Bristol, VA	254