

List of Figures

2.1	Schematic of Bunsen burner	19
2.2	Photograph of Bunsen Type Burner	19
2.3	Schematic of Honeycomb burner	21
2.4	Photograph of Honeycomb burner	21
2.5	Photograph of Honeycomb material	22
2.6	Schematic of optical system	24
2.7	Radial variation of percentage of light collected from a differential element of the flame	25
2.8	Schematic top-view of the monochrometer with attached hardware	29
4.1	Chemiluminescence spectrum for a Bunsen burner flame	46
4.2	Optical system efficiency	47
4.3	Chemiluminescence spectrum for a Bunsen burner flame with CO ₂ * continuum estimate	49
4.4	OH* integrand scale factor variation with equivalence ratio	50
4.5	CH* integrand scale factor variation with equivalence ratio	51
5.1	OH* chemiluminescence yield as a function of equivalence ratio	56
5.2	OH* chemiluminescence yield as a function of air-flow	56
5.3	Normalized OH* chemiluminescence yield as a function of equivalence ratio	57
5.4	CH* chemiluminescence yield as a function of equivalence ratio	58
5.5	CH* chemiluminescence yield as a function of air flow-rate	59

5.6	Normalized CH* chemiluminescence yield as a function of equivalence ratio	60
5.7	Ratio of OH* to CH* chemiluminescence yields as a function of equivalence ratio	61
5.8	Radial variation of OH* chemiluminescence with equivalence ratio at an air flow-rate of 60 cc/sec	62
5.9	Radial Variation of OH* chemiluminescence with air flow-rate at an equivalence ratio of 1.0	63
5.10	Radial Variation of CH* chemiluminescence with equivalence ratio at an air flow-rate of 60 cc/sec	63
5.11	Radial Variation of CH* chemiluminescence with air flow-rate for an equivalence ratio of 0.80	64
5.12	Radial Variation of the ratio of OH* to CH* chemiluminescence for several equivalence ratios	65
5.13	Variation of OH* chemiluminescence with equivalence ratio	66
5.14	Variation of normalized OH* chemiluminescence with fuel flow-rate	67
5.15	Variation of CH* chemiluminescence with equivalence ratio	68
5.16	Variation of normalized CH* chemiluminescence with fuel flow-rate	69
5.17	Variation of OH* to CH* chemiluminescence ratio with equivalence ratio	69
5.18	Spectral wavelength scan of the honeycomb burner	70
7.1	Illustration of Bunsen burner experimental flame	87
7.2	Photograph of stoichiometric Bunsen type flame	88
7.3	Illustration of Bunsen burner flame model	88
7.4	Flame temperature as a function of heat-loss	91
7.5	Flame-speed as a function of heat-loss	92
7.6	OH* modeling results and experimental data at an air flow-rate of 60 cc/sec	93
7.7	OH* modeling results and experimental data at an equivalence ratio of 0.90	94

7.8	Local OH* chemiluminescence intensity modeling results at an equivalence ratio of 0.90 and an air flow-rate of 60 cc/sec	96
7.9	CH* modeling results and experimental data at an air flow-rate of 60 cc/sec	97
7.10	CH* modeling results and experimental data at an equivalence ratio of 0.90	97
7.11	Local CH* chemiluminescence intensity modeling results at an equivalence ratio of 0.90 and an air flow-rate of 60 cc/sec	98
7.12	OH* to CH* chemiluminescence ratio modeling results and experimental data vs. mainstream equivalence ratio	99
7.13	Radial variation of the modeled OH* to CH* chemiluminescence ratio at an equivalence ratio of 0.9 with an air flow-rate of 60 cc/sec	100
7.14	Variation of mixing parameters with mainstream equivalence ratio	101
7.15	Variation of heat transfer parameters with mainstream equivalence ratio	103
7.16	Schematic of CFD geometry for Bunsen type burner	104
7.17	Contour plot of the methane consumption reaction rate in Bunsen type burner CFD simulation	105
7.18	Contour plot of axial velocity in Bunsen type burner CFD simulation	106
7.19	Streamlines in the Bunsen type burner CFD simulation	107
7.20	Radial velocity profile through center of wake region in the Bunsen type burner CFD simulation	108
8.1	Side-on photograph of honeycomb burner flame	110
8.2	Schematic illustrating honeycomb computational domain	111
8.3	Schematic illustrating honeycomb gas heat balance	112
8.4	Schematic illustrating honeycomb solid material heat balance	114
8.5	Volumetric heat-loss and chimney outside wall temperature as a function of flame temperature	115
8.6	Area factor governing radiation exchange between a gas layer and the honeycomb surface	118

8.7	Area factor governing radiation exchange between honeycomb surface and the interior honeycomb sides	119
8.8	Comparison between experimental OH* chemiluminescence data and OH* chemiluminescence modeling results using the OH* formation path through CH	123
8.9	Comparison between experimental OH* chemiluminescence data and OH* chemiluminescence modeling results using the formation path through HCO	125
8.10	Comparison between experimental CH* chemiluminescence data and CH* chemiluminescence modeling results	126
8.11	Computed gas temperatures through the entire computational domain for four flow-rates at an equivalence ratio of 0.75	128
8.12	Computed gas temperatures through the entire computational domain for four equivalence ratios at an air flow-rate of 170 cc/sec	129
8.13	Computed honeycomb solid and gas temperatures inside the honeycomb channel at an air flow-rate of 170 cc/sec and an equivalence ratio of 0.75	129
8.14	Computed honeycomb solid temperatures for four equivalence ratios at an air flow-rate of 170 cc/sec	130
8.15	Computed honeycomb solid temperatures for four air flow-rates at an equivalence ratio of 0.75	131
8.16	Computed gas temperatures in vicinity of flame at an equivalence ratio of 0.75 for four air flow-rates	132
8.17	Computed gas temperatures in vicinity of flame at an air flow-rate of 170 cc/sec for four equivalence ratios	133
8.18	Computed gas temperatures and chemiluminescent species mole fraction in the vicinity of the flame for an air flow-rate of 170 cc/sec and an equivalence ratio of 0.90	134

8.19	Computed gas temperatures, OH*, HCO and O species mole fractions in the vicinity of the flame for an air flow-rate of 170 cc/sec and an equivalence ratio of 0.90	135
8.20	Computed axial variation of OH* mole fraction in the vicinity of the flame for four equivalence ratios at an air flow-rate of 170 cc/sec . . .	136
8.21	Computed axial variation of OH* mole fraction in the vicinity of the flame for four flow-rates at an equivalence ratio of 0.75	136
8.22	Computed gas temperatures, CH* C ₂ H and O species mole fractions in the vicinity of the flame for an air flow-rate of 170 cc/sec and an equivalence ratio of 0.75	137
8.23	Computed axial variation of CH* mole fraction in the vicinity of the flame for four equivalence ratios at an air flow-rate of 170 cc/sec . . .	138
8.24	Computed axial variation of CH* mole fraction in the vicinity of the flame for four air flow-rates at an equivalence ratio of 0.75 cc/sec . .	139
8.25	Variation of the difference between the altered chemical mechanism and the original GRIMECH chemical mechanism with OH* reactions with equivalence ratio for an air flow-rate of 130 cc/sec	140
8.26	Variation of the difference between the reduced chemical mechanism (Smooke, 1991) and the modified GRIMECH 3.0 mechanism with equivalence ratio for an air flow-rate of 200 cc/sec	141
8.27	OH* chemiluminescence emissions predicted by the reduced and large chemical mechanism at an air flow-rate of 200 cc/sec for varying equivalence ratio	142
9.1	Methane oxidation reaction path diagram (Najm et al., 1998)	145
9.2	Chemiluminescence formation path diagram	151
10.1	Heat-release rate as a function of OH* chemiluminescence	157
10.2	OH* chemiluminescence sensitivity to changes in heat-release rate . .	157
10.3	Heat-release rate as a function of CH* chemiluminescence	158
10.4	CH* chemiluminescence sensitivity to changes in heat-release rate . .	159

10.5	Ideal dynamic response with in-phase variation of equivalence ratio and mass-flow at amplitudes of 0.01 and 2 scc/sec respectively	161
10.6	Ideal dynamic response with in-phase variation of equivalence ratio and mass-flow at amplitudes of 0.01 and 4 scc/sec respectively	161
10.7	Ideal dynamic response with a 45 degree phase shift between the oscillations of equivalence ratio and mass-flow of amplitudes of 0.01 and 4 scc/sec respectively	162
10.8	Ideal dynamic response with in-phase variation of equivalence ratio and mass-flow at amplitudes of 0.02 and 2 scc/sec respectively	163
10.9	Ideal dynamic response with a 180 degree phase shift between the oscillations of equivalence ratio and mass-flow of amplitudes of 0.02 and 2 scc/sec respectively	164
10.10	Ideal dynamic response with in-phase variation of equivalence ratio and mass-flow at amplitudes of 0.02 and 4 scc/sec respectively	164
10.11	Ideal dynamic response with a 90 degree phase shift between the oscillations of equivalence ratio and mass-flow of amplitudes of 0.02 and 4 scc/sec respectively	165
10.12	Heat-release rate as a function of OH* chemiluminescence for four air flow-rates and varying equivalence ratio	166
10.13	Heat-release rate as a function of CH* chemiluminescence for four air flow-rates and varying equivalence ratio	167
10.14	Heat-release rate as a function of OH* chemiluminescence for four equivalence ratios and varying flow-rate	168
10.15	Heat-release rate as a function of CH* chemiluminescence for four equivalence ratios and varying flow-rate	169
10.16	Chemiluminescence formation path diagram	170
C.1	Schematic of ray-tracing technique	202
C.2	The two-lens type optical system	203
C.3	Illustration of calculations involving the percentage of light collected .	205

C.4	Relative fraction of light collected from incremental area	208
-----	--	-----

List of Tables

2.1	Optical system distances (ref. Figure 2.6)	27
6.1	Comparison of chemiluminescence quenching models	78
6.2	Example chemiluminescence mechanism	80