

List of Figures

Figure 2-1: Release Drain Installed on Two New Tubes.....	9
Figure 2-2: Release Drain Installed on Existing Tube.....	10
Figure 2-3: End Cap and Connecting Hose Used in Leveling Trough.....	11
Figure 2-4: Inflow Drip Line with Adjustable Valve.....	12
Figure 2-5: Outflow Drip Line with Fixed Head Location.....	12
Figure 2-6: Aligning of the Measurement Beam in Vertical Direction.....	13
Figure 2-7: Measurement Tool for Obtaining Measurements Under the Tubes.....	14
Figure 2-8: Measurement Procedure Using Plumb Bob.....	15
Figure 2-9: Typical Cross Section of Three-Tube Configuration.....	16
Figure 2-10: Locations of Straps along Longitudinal Length of Tubes.....	17
Figure 2-11: Cross Section of Trial 1 Setup.....	20
Figure 2-12: Strapping System for Trial 1.....	20
Figure 2-13: Tube #2 Rolling Away from Headwater at 7.5-Inch Water Height in Trial 1.....	21
Figure 2-14: Cross Section of Trial 2 Setup.....	22
Figure 2-15: Rotation of Tube #2 Against Sidewall of Box at 10-Inch Water Height in Trial 2.....	23
Figure 2-16: Strapping System for Trial 3.....	25
Figure 2-17: Bentonite Paste Applied to Tube #2 and Tube #3 in Trial 3.....	26
Figure 2-18: Valve on Tube #2 Nearly Sheared Off by Tube #3 in Trial 3.....	27
Figure 2-19: Strapping System for Trial 4.....	28
Figure 2-20: No-Slip Buckle.....	28
Figure 2-21: Ratcheting Device.....	28
Figure 2-22: Bentonite Paste Applied to Strap Locations on Tube #2 and Tube #3 in Trial 4.....	28
Figure 2-23: Foam Material under Strapping System in Trial 5.....	30
Figure 2-24: Piping Failure at Strap Locations in Trial 5.....	31
Figure 2-25: Flat Plate Hand Compactor in Operation.....	32

Figure 2-26: Bentonite Cutoff Trenches to Prevent Piping under Strap Locations in Trial 6.....	33
Figure 2-27: Bentonite Cutoff Trench after Tube #2 Installed.....	34
Figure 2-28: Trial 6 at Headwater Elevation of 12 ½-inches.....	34
Figure 2-29: Cross Section of Trial 7 Setup.....	36
Figure 2-30: Foam Material Placed under Strap Locations for Trial 7.....	36
Figure 2-31: Strapping System for Trial 8.....	38
Figure 2-32: Cross Section of Trial 9 Setup.....	39
Figure 2-33: Beginning of Piping Failure on Tailwater Side of Tubes in Trial 9.....	40
Figure 2-34: Cross Section of Trial 10 Setup.....	41
Figure 2-35: Cross Section of Trial 11 Setup.....	43
Figure 2-36: Trial 11 at a Headwater Elevation of 16-Inches.....	43
Figure 2-37: Trial 11 Just After Sliding Failure.....	44
Figure 2-38: Cross Section of Trial 12 Setup.....	45
Figure 2-39: Trial 12 Just After Sliding Failure.....	46
Figure 2-40: Cross Section of Trial 13 Setup.....	47
Figure 2-41: Trial 13 at Headwater Elevation of 15-Inches.....	47
Figure 2-42: Shear Box with Upper and Lower Ring Prepared for Testing.....	50
Figure 2-43: Strapping Material Attached to the Wooden Block.....	51
Figure 2-44: Setup of the Shear Box Prior to Testing.....	52
Figure 2-45: Plot of Shear Stress vs. Normal Stress for Reinforced PVC against Reinforced PVC.....	54
Figure 2-46: Plot of Shear Stress vs. Normal Stress for Reinforced PVC against Strapping Material.....	54
Figure 3-1: Freestanding Tube.....	57
Figure 3-2: Shapes of Freestanding Tube with Varying h_{int} Values.....	59
Figure 4-1: Tube with an Apron Attached.....	61
Figure 4-2: Apron.....	61
Figure 4-3: Tube with Apron Attached and $h_{int} = 0.2$ is Constant.....	66

Figure 4-4: Tension vs. h_{ext} for a Tube with Apron Attached; $h_{int} = 0.2$ is Constant.....	67
Figure 4-5: y_E vs. h_{ext} for a Tube with Apron Attached; $h_{int} = 0.2$ is Constant.....	67
Figure 4-6: Tube with Apron Attached and $h_{int} = 0.3$ is Constant.....	68
Figure 4-7: Tube with Apron Attached and $h_{int} = 0.4$ is Constant.....	68
Figure 4-8: Tube with Apron Attached and $h_{int} = 0.5$ is Constant.....	69
Figure 5-1: Freestanding Tube.....	71
Figure 5-2: Tube With an Apron Attached and $\theta_E < \theta_J < \pi/2$	73
Figure 5-3: Tube With an Apron Attached and $\theta_E < \pi/2$ and $\theta_J > \pi/2$	74
Figure 5-4: Tube With an Apron Attached and $\theta_J > \theta_E > \pi/2$	76
Figure 5-5: Tube With an Apron Attached and Drain Directly Beneath.....	77
Figure 5-6: Free Body Diagram of the Apron.....	78
Figure 5-7: Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.2$	81
Figure 5-8: h_{int} vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.2$	82
Figure 5-9: h vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.2$	82
Figure 5-10: Tension vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.2$	83
Figure 5-11: y_E vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.2$	83
Figure 5-12: Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.31903$	84
Figure 5-13: h_{int} vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.31903$	85
Figure 5-14: Tension vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.31903$	85
Figure 5-15: y_E vs. h_{ext} for a Tube with Apron Attached; Constant Area, Initial $h_{int} = 0.31903$	86

Figure 6-1: Tube with Apron Attached: initial hint = 0.31903,
hext = 0.05172 (3 in.)..... 88

Figure 6-2: Tube with Apron Attached: initial hint = 0.31903,
hext = 0.10345 (6 in.)..... 89

Figure 6-3: Tube with Apron Attached: initial hint = 0.31903,
hext = 0.15517(9 in.)..... 89

Figure 7-1: Typical Cross Section of Trial Setup..... 91

Figure 7-2: Critical Headwater Height vs. Location of Drain..... 91