

## List of Figures

Figure 1.1 IVDS System Diagram .....	3
Figure 2.1 Autocorrelation Function of ML Sequence (N=15) .....	14
Figure 2.2 Power Spectral Density of ML Sequence (N=15).....	15
Figure 2.3 Spread Spectrum Transmission Procedures .....	17
Figure 2.4 Spread Spectrum Reception Procedures .....	18
Figure 2.5 Signal After Demodulation and Matched Filtering (Direct Path) .....	20
Figure 2.6 Laboratory Hardware for Testing .....	22
Figure 2.7 Laboratory Hardware with VCR in Signal Path.....	23
Figure 2.8 Signal After Demodulation and Matched Filtering (VCR in Path).....	25
Figure 2.9 Signal After Demodulation and Matched Filtering (Phase Test).....	27
Figure 2.10 Phase at Peaks of Matched Filter Output.....	27
Figure 2.11 Unwrapped Phase at Peaks of Matched Filter Output.....	28
Figure 2.12 1st Difference of Phase at Peaks of Matched Filter Output.....	28
Figure 2.13 Change in Carrier Frequency .....	29
Figure 2.14 Change in Carrier Frequency in Percent.....	29
Figure 2.15 Histogram of the Percent Change in Carrier Frequency .....	30
Figure 2.16 CDF of Percent Change in Carrier Frequency .....	30
Figure 2.17 Sinusoidal Frequency Variation (2 ms) .....	32
Figure 2.18 Sinusoidal Frequency Variation in Percent (2 ms).....	33
Figure 2.19 Histogram of Wow and Flutter in Percent (2 ms) .....	33
Figure 2.20 CDF of Wow and Flutter in Percent (2 ms) .....	34
Figure 2.21 Sinusoidal Frequency Variation (5 ms) .....	37
Figure 2.22 Sinusoidal Frequency Variation in Percent (5 ms).....	38
Figure 2.23 Histogram of Wow and Flutter in Percent (5 ms) .....	38
Figure 2.24 CDF of Wow and Flutter in Percent (5 ms) .....	39
Figure 2.25 Spectral Estimate for 2 ms (32 Sample) Block .....	39
Figure 2.26 Spectral Estimate for 5 ms (80 Sample) Block .....	40
Figure 2.27 Sinusoidal Frequency Variation Estimation Via AR Modeling (2 ms).....	42
Figure 2.28 Sinusoidal Frequency Variation Estimation Via AR Modeling (5 ms).....	42
Figure 2.29 Coding by Spectral Changes .....	46
Figure 3.1 Sinusoid Detection Process .....	51
Figure 3.2 FFT of Sinusoid, Rectangular Window .....	53
Figure 3.3 FFT of Shifted Sinusoid, Rectangular Window .....	53
Figure 3.4 FFT of Sinusoid, Hanning Window .....	55
Figure 3.5 FFT of Shifted Sinusoid, Hanning Window .....	55
Figure 3.6 FFT of Sinusoid, Blackman Window .....	56
Figure 3.7 FFT of Shifted Sinusoid, Blackman Window .....	56
Figure 3.8 Sinusoid Detection by FFT Magnitude Results .....	58
Figure 3.9 Control Function for Synchronization .....	59
Figure 3.10 Code Comparisons.....	64

Figure 3.11	Frequency Domain Matched Filter for Frequency Shift Detection.....	70
Figure 3.12	Matched Filter Output for Frequency Shift Detection.....	71
Figure 3.13	Psychoacoustic Masking.....	74
Figure 3.14	Frequency Response of Bandstop Audio Filter.....	77
Figure 3.15	Impulse Response of Bandstop Audio Filter.....	77
Figure 3.16	Time-Averaged Power Spectral Density of the Original Audio Signal.....	79
Figure 3.17	Time-Averaged Power Spectral Density of the Composite Signal.....	79
Figure 3.18	Sloping of Sinusoids for Code Insertion.....	80
Figure 3.19	Spectrogram of Original Audio Signal.....	83
Figure 3.20	Spectrogram of Modified Audio Signal.....	83
Figure 5.1	Signal PSD – AudioLink Powered by Switching Power Supply.....	119
Figure 5.2	Signal PSD – AudioLink Powered by Dry-Cell Batteries.....	120
Figure 5.3	Signal PSD – AudioLink Powered by Switching Power Supply (Microphone Input Shorted).....	121
Figure 5.4	Signal PSD – AudioLink Powered by Dry-Cell Batteries (Microphone Input Shorted).....	121
Figure 5.5	Simple Bandpass Filter.....	123
Figure 5.6	Double Bandpass Audio Amplifier and Filter.....	126
Figure 5.7	Magnitude Response of Double Bandpass Filter Cascade: a) Overall, b) Passband, c) Stopband.....	127
Figure 5.8	Elliptic Filter Magnitude Response. a) Overall, b) Passband, c) Stopband..	131
Figure 5.9	Magnitude Responses of Stages: a) Buffer, b) Elliptic, c) Gain.....	132
Figure 5.10	Passband Magnitude Response of Stages: a) Buffer, b) Elliptic, c) Gain..	133
Figure 5.11	Stopband Magnitude Responses of Stages: a) Buffer, b) Elliptic, c) Gain.	134
Figure 5.12	Resulting Magnitude Response of Cascade: a) All Frequencies, b) Passband, c) Stopband.....	135
Figure 5.13	Microphone Buffer Stage.....	136
Figure 5.14	Highpass Elliptic Filter Stage.....	137
Figure 5.15	Highpass Elliptic Filter and Gain Stages.....	138
Figure 5.16	FIR Compensation and Pre-Emphasis Filter Magnitude Response: a) All Frequencies, b) Stopband, c) Passband.....	140
Figure 5.17	General Input/Output Characteristics of the Compressor.....	143
Figure 6.1	Power of Received Signal Versus Microphone Distance.....	161
Figure 7.1	Example Slide from the WOW Conference Channel.....	187
Figure 7.2	Example Slide from the Commercial Channel.....	189
Figure 8.1	Example Phase Spectra.....	202
Figure 8.2	Block Synchronization by Error Detection.....	204
Figure 8.3	Time-Averaged PSD of Audio Signal.....	205
Figure 8.4	Phase Errors from Quantization vs. Frequency.....	206
Figure 9.1	Template for Automatic Selection of Code Insertion Locations.....	218