



US009266121B2

(12) **United States Patent**  
**Yoon et al.**

(10) **Patent No.:** **US 9,266,121 B2**

(45) **Date of Patent:** **\*Feb. 23, 2016**

(54) **FLOTATION MACHINE ROTOR**

(71) Applicant: **Virginia Tech Intellectual Properties, Inc.**, Blacksburg, VA (US)

(72) Inventors: **Roe-Hoan Yoon**, Blacksburg, VA (US); **Gerald Luttrell**, Blacksburg, VA (US); **Saad Ragab**, Blacksburg, VA (US); **Demetri Telionis**, Blacksburg, VA (US); **Abdel-Halim Said**, Zagazig (EG); **Sanja Miskovic**, Salt Lake City, UT (US); **Aaron Noble**, Lenoir City, TN (US); **Yihong Yang**, Salt Lake City, UT (US)

(73) Assignee: **Virginia Tech Intellectual Properties, Inc.**, Blacksburg, VA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/405,215**

(22) PCT Filed: **May 8, 2013**

(86) PCT No.: **PCT/US2013/040057**  
§ 371 (c)(1),  
(2) Date: **Dec. 3, 2014**

(87) PCT Pub. No.: **WO2014/003894**  
PCT Pub. Date: **Jan. 3, 2014**

(65) **Prior Publication Data**

US 2015/0151309 A1 Jun. 4, 2015

**Related U.S. Application Data**

(63) Continuation of application No. 13/535,566, filed on Jun. 28, 2012.

(51) **Int. Cl.**  
**B03D 1/16** (2006.01)  
**B03D 1/20** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **B03D 1/16** (2013.01); **B01F 3/04539** (2013.01); **B01F 7/00241** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... B03D 1/16; B03D 1/20; B01F 7/00241; B01F 3/04539; B01F 2003/04546; B01F 2003/04567  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,342,331 A \* 9/1967 Maxwell ..... 209/170  
3,843,101 A 10/1974 Green  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 2912802 Y \* 6/2007  
EA 014815 B1 2/2011  
(Continued)

OTHER PUBLICATIONS

International Search Report for PCT/US2013/040057 dated Sep. 12, 2013.  
(Continued)


*Primary Examiner* — Thomas M Lithgow

(74) *Attorney, Agent, or Firm* — Buchanan Ingersoll & Rooney PC

(57) **ABSTRACT**

A rotor for flotation machines or flotation cells of flotation machines includes blades that are configured to provide improved bubble flow and bubble generation performance while also reducing the power requirements for rotating the rotor to generate bubble flow within a tank of a flotation cell used to generate froth. Embodiments of the rotor may also be configured to be smaller than conventional rotor designs, which may help reduce the costs of manufacturing the rotor or flotation machines using such embodiments of the rotor.

**10 Claims, 9 Drawing Sheets**



(51)	<b>Int. Cl.</b>		6,805,243 B1 10/2004 Kallioinen et al.
	<b>B01F 3/04</b>	(2006.01)	7,980,824 B2 7/2011 Niitti
	<b>B01F 7/16</b>	(2006.01)	2008/0063523 A1 3/2008 Niitti

	<b>B01F 7/18</b>	(2006.01)
	<b>F01D 5/14</b>	(2006.01)
	<b>B01F 7/00</b>	(2006.01)

FOREIGN PATENT DOCUMENTS

(52)	<b>U.S. Cl.</b>	
	CPC .....	<b>B01F 7/163</b> (2013.01); <b>B03D 1/20</b> (2013.01); <b>F01D 5/141</b> (2013.01); <b>B01F</b> <b>2003/04546</b> (2013.01); <b>B01F 2003/04553</b> (2013.01)

FR	1474582 B3	4/1966
GB	1028590	5/1966
SU	599848 B3	3/1978
SU	747530 B3	7/1980
SU	852366 B3	8/1981
SU	1720724 A2 *	3/1992
SU	1745342 A1	7/1992
WO	9706892	2/1997
WO	2008062097 A1	5/2008

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,425,232 A	1/1984	Lawrence et al.	
4,800,017 A	1/1989	Krishnaswamy et al.	
5,045,246 A *	9/1991	Dorr .....	261/93
5,205,926 A	4/1993	Lawrence	
6,789,788 B2	9/2004	Belke	

OTHER PUBLICATIONS

Written Opinion of the International Searching Authority for PCT/US2013/040057 dated Sep. 12, 2013.  
European Search Report for PCT/US2013/040057 dated May 26, 2015.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

**FLOTATION MACHINE ROTOR**CROSS-REFERENCE TO RELATED  
APPLICATIONS

The present application claims priority to U.S. patent application Ser. No. 13/535,566, which was filed on Jun. 28, 2012. The entirety of U.S. patent application Ser. No. 13/535,566 is incorporated by reference herein.

## FIELD OF INVENTION

The present invention relates to devices and methods used to agitate slurry retained in flotation machines. One example of a flotation machine is a machine that utilizes one or more flotation cells that have tanks that retain a slurry, or pulp, to recover particles of material such as ore, minerals, metal, or other material that is within solid material suspended in a liquid of the slurry, or pulp.

## BACKGROUND OF THE INVENTION

Flotation machines often include a tank that retains a slurry, or pulp. Examples of such machines may be appreciated from U.S. Pat. Nos. 4,425,232, 4,800,017, and 5,205,926. The entirety of U.S. Pat. Nos. 4,425,232, 4,800,017, and 5,205,926 are incorporated by reference herein. The slurry retained by such tanks may include solid material such as ore or minerals that is mixed in a liquid such as water. For example, the material present in the slurry may include particles of copper bearing minerals, coal, iron minerals, phosphate rock, potash, silica, base metal sulfide or precious metal.

The slurry retained in the tank may be aerated to generate froth to suspend solid particles in the froth. The froth may be a large amount of bubbles formed at the top of the slurry in the tank. For instance, froth may be generated via a forced air technology to create bubbles and generate the froth. Alternatively, bubbles may be generated via a self-aspirated technology to create the froth. The tanks are designed so that the froth, which contains the solid particles, may be passed into one or more launders adjacent to the tank to separate the valuable minerals from the other liquid and other material. It should be understood that after the material is sent to the one or more launders, it may be further processed to recover the desired material.

Rotors may be included in each flotation cell of a flotation machine to agitate the slurry for purposes of forming air bubbles that capture particles and rise to the top of the slurry to form froth. Air may be forced through the rotor and expelled out adjacent blades located at the bottom of the rotor that is rotated so that air is mixed with the slurry to generate bubbles for forming the froth above the slurry retained in the tank. Such a froth so generated, however, may be difficult to maintain unless the rotor is rotated at relatively fast speed and may also require a rotor to be relatively large. Such size and speed constraints increase the cost of fabricating such flotation machines and operating such machines.

Further, such rotors typically include blades that generate a velocity spike in an exit stream of slurry that consumes a relatively significant amount of power used to rotate the rotor but fails to provide any meaningful improvement to froth formation performance. This design feature also increases the costs associated with operating the flotation machines.

A new rotor design is needed for flotation cells of flotation machines. The new rotor design preferably reduces the cost of manufacturing rotors and reduces the operating costs associ-

ated with moving of the rotors during operation of the flotation cells. Preferably, such a rotor design also improves the bubble generation performance of the rotors as compared to conventional rotors.

## SUMMARY OF INVENTION

A flotation machine and flotation machine rotor are provided that can provide improved mineral recovery performance and reduced operating costs as compared to conventional designs.

In one embodiment, the flotation machine includes at least one flotation cell. Each flotation cell includes a tank that is sized to retain slurry comprised of a liquid mixed with at least one solid material and a rotor positioned in the tank that is rotated to agitate the slurry to facilitate formation of bubbles. The rotor includes a body that has outer blades that extend outwardly from the body, an inner channel, inner blades positioned adjacent the inner channel and a plurality of conduits in communication with the inner channel. Each of the conduits extends from the inner channel to an external surface of the body so that the slurry pulled into an opening of the body via rotation of the rotor passes through the inner channel and is ejected, or emitted, from the external surface of the body via the conduits.

In other embodiments, the rotor of the flotation machine includes a rotor positioned in the tank that is rotated to agitate the slurry to facilitate formation of a bubbly flow used to generate froth. The rotor is attached to a column and includes a body having a plurality of outer blades that extend outwardly from the body. Each of the outer blades has an outer edge that extends outwardly from an upper portion of the rotor to an outermost position located below the upper portion of the rotor. The outer edge extends inwardly from the outermost position to which the outer edge extends to a lower portion of the rotor. The lower portion of the rotor is located below the outermost position to which the outer edge extends and is positioned inward relative to the outermost position of the outer edge.

Embodiments of a rotor for flotation machines are also provided. One embodiment of the rotor includes a body that has outer blades that extend outwardly from the body, an inner channel, inner blades positioned adjacent the inner channel and a plurality of conduits in communication with the inner channel. Each of the conduits extends from the inner channel to an external surface of the body so that the slurry pulled into an opening of the body via rotation of the rotor subsequently passes through the inner channel and is then ejected, or emitted, from the external surface of the body via the conduits.

The body of the rotor may also include passageways for receiving at least one gas such as air. Each of the passageways may include an inlet to receive at least one gas and an outlet to emit the at least one gas received via the inlet. The outlet of each passageway is spaced apart from the outlets of other passageways. The outlet of each passageway may be positioned in the body between immediately adjacent outer blades. The outer blades may be spaced apart from one another along the external surface of the body of the rotor and the inner blades may be spaced apart from each other and may at least partially define the conduits.

The body of the rotor may be formed so that the inner blades and outer blades are integral with the body or are attached to the body. In one embodiment, the inner blades may be formed by casting or molding the body of the rotor and the outer blades may be welded to the rotor body or formed when the rotor body is casted or molded. The outer blades may be offset relative to the inner blades. The body

may be structured in some embodiments so that no gas is injected into the inner channel of the body.

Other embodiments of the rotor for flotation machines can include a plurality of outer blades that extend outwardly from the body. Each of the outer blades has an outer edge that extends outwardly from an upper portion of the rotor to an outermost position located below the upper portion of the rotor. The outer edge extends inwardly from the outermost position to which the outer edge extends to a lower portion of the rotor. The lower portion of the rotor is located below the outermost position to which the outer edge extends and is positioned inward relative to the outermost position of the outer edge.

The outer edges of the outer blades may be curved. In some embodiments of the rotor, the outer edges define smooth outer surfaces of the outer blades and at least partially define the shape of the outer blades so that the outer blades are each generally half-heart shaped. The rotor may also include one or more outlets for emitting air. Each outlet may be positioned between immediately adjacent outer blades.

In one embodiment, the lower portion of the rotor is the bottom of the rotor and the outer blades are sized and shaped so that the rotor suppresses a velocity spike in an exit stream of agitated slurry formed via rotation of the rotor. Preferably, the rotor is shaped so that rotation of the rotor at steady state defines a uniform turbulence profile within the slurry.

Other details, objects, and advantages of the invention will become apparent as the following description of certain present preferred embodiments thereof and certain present preferred methods of practicing the same proceeds.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Present preferred embodiments of flotation machines that utilize embodiments of rotors that rotate for generating froth in flotation cells of such machines, embodiments of the rotor and methods of making and using the same are shown in the accompanying drawings. It should be understood that like reference numbers used in the drawings may identify like components.

FIG. 1 is top schematic view of an exemplary flotation machine that may utilize one or more embodiments of the rotor.

FIG. 2 is a top schematic view of another exemplary flotation machine that may utilize one or more embodiments of the rotor.

FIG. 3 is a perspective view of a first exemplary embodiment of a rotor.

FIG. 4 is a perspective cross sectional view of the first exemplary embodiment of the rotor taken along line IV-IV in FIG. 3.

FIG. 5 is a cross sectional view of the first exemplary embodiment of the rotor taken along line V-V in FIG. 3 that includes indicia illustrating slurry and gas flows that may be generated by the rotor when the rotor is rotated.

FIG. 6 is a perspective view of a second exemplary embodiment of a rotor.

FIG. 7 is a side perspective view of the second exemplary embodiment of the rotor.

FIG. 8 is a schematic side view of the second exemplary embodiment of the rotor that includes indicia illustrating slurry-gas flow patterns from rotation of the rotor.

FIG. 9 is a graph illustrating the curved path defined by the outer edges of the outer blades of the second exemplary embodiment of the rotor. The x and y values of the graph are normalized by rotor radius.

#### DETAILED DESCRIPTION OF PRESENT PREFERRED EMBODIMENTS

Referring to FIGS. 1 and 2, a flotation machine 1 used to recover minerals from slurry may have a plurality of flotation cells 2. The number of flotation cells used in embodiments of the flotation machine 1 may range from one cell to a large number of cells. The number of cells needed for any particular flotation machine may be dependent on design requirements for the mineral or material recovery that the flotation machine is designed to meet. In some embodiments, the flotation machine may be a flotation column.

For example, a flotation machine may include a number of cells that are Dorr-Oliver® unit cells to process finely sized particles and cells upstream or downstream of these cells may be WEMCO® or MixedRow™ cells for larger sized particle recovery such as middlings. Of course, it should be understood that other type of cells could be used as substitutes of the above referenced Dorr-Oliver®, WEMCO®, or Mixed-Row™ cells.

Each flotation cell 2 has a tank that retains slurry, which may also be referred to as pulp, within the tank 3. The tank 3 may have any of a number of different shapes. For example, each tank 3 may be shaped similarly to a large rectangular tank or may be a generally cylindrical tank as may be appreciated from U.S. Pat. No. 5,205,926 (the entirety of which is incorporated by reference herein).

A feed box 13 may be adjacent to one or more of the flotation cells 2 and may be where material is mixed with liquid to form the slurry, or pulp, that is subsequently fed into the tanks 3 of the cells 2. The liquid may be water, salt water, or a solution. The material that is mixed with the liquid may include rock, stone or dirt that includes one or more minerals or metals that are desired to be recovered from the material.

Froth may be generated in the tank above the slurry retained in the tank by a rotation mechanism 8 that is positioned in the tank 3 of a flotation cell. The rotation mechanism 8 may include a column that is attached to a rotor. Air or another type of gas or mixture of gases may be forced through the column and the rotor so that air is ejected from the rotor to help facilitate agitation of the slurry and formation of the bubbles. The column may be positioned so that the rotor is near the bottom of the tank, at the bottom of the tank, or in another position within the tank that is desirable for generating bubbles sufficiently to form a froth for the particular mineral recovery process a flotation cell of the flotation machine may be configured to meet. The column may a part of a drive mechanism or attached to a drive mechanism so that the column may be rotated to rotate the rotor in the slurry to agitate the slurry within the tank to generate bubbles. The rotor of the rotation mechanism 8 may have any of a number of different designs as discussed more fully below with reference to FIGS. 3-8. The bubbles that are formed float upwardly within the tank and accumulate on the top of the slurry to form a foam. Often, water or other liquid of the slurry may drain back into the slurry when the foam is formed at the top of the slurry. When solid particles of the slurry are trapped in the bubbles that form the foam, the foam is referred to as a froth.

Launders 6 may be positioned on the top lips of the tank or adjacent the top lips of each tank around at least some of the sides of the tank 3 of each flotation cell 2 to receive froth that may flow over the sides of the tank. The launders 6 may have discharge outlets 7 for discharging froth received by the launders. The discharged froth may then be processed to separate the fine particles of the material that is within the froth to extract, or recover, desirable portions of this material, such as

5

metal, a mineral, or other desirable material. A cross launder **5** may be positioned between the adjacent flotation cells **2** to divide the cells **2**.

Referring to FIGS. **3-5**, one embodiment of a rotor **21** that may be used in embodiments of the flotation machine include rotor **21**. Rotor **21** has a body **22** that has an upper portion sized and configured for attachment to a column of a rotation mechanism **8**. The body **22** includes outer blades **24** that extend from the body. The outer blades may be members such as projecting walls, plates, or profiled fins that agitate the slurry in the tank when the rotor **21** is rotated. The outer blades **24** may be formed on the body, adhered to the body, cast with the body, integrally attached to the body or otherwise attached to the body via one or more fastening mechanisms such as welding, rivets, or other fasteners.

The body **22** of the rotor **21** may be formed from metal and have an opening **26** formed therein at the bottom of the rotor below the outer blades **24** or adjacent the bottom of the outer blades **24**. An inner channel **27** may be formed in the body **22** that is in communication with the opening **26** so that slurry may pass through the opening **26** and into the inner channel **27**. A plurality of inner blades **25** are attached to the body **22**. For instance, the inner blades **25** may be attached such that the inner blades are integral with the body **22** or are defined in the body **22**. The inner blades **25** are positioned adjacent to the inner channel **27** or in the inner channel **27**. The inner blades may be members such as plates, inwardly projecting walls, or other structure that is positioned in the body adjacent the inner channel to provide a pumping force or pressure differential, for pulling slurry into the inner channel **27** via opening **26** and out of conduits **28** when the rotor **21** is rotated.

The conduits **28** may be formed in the body **22** and be at least partially defined by the body **22**. Immediately adjacent inner blades **25** may also partially define the conduits **28** along with portions of the body **22**. For instance, immediately adjacent inner blades **25a** and **25b** in combination with the body **22** may define conduit **28a** as shown in FIG. **4**. It should be understood that inner blades **25** may be considered immediately adjacent if no other inner blade is positioned between two adjacent inner blades located adjacent to or along a periphery of the inner circumference **27**. The conduits **28** are in communication with the inner channel **27** so that slurry that passes into the inner channel **27** via opening **26** passes from the inner channel **27** and through inlets of the conduits **28** to be expelled out of the outlets of the conduits **28** located on the exterior surface of the body **22** of the rotor **21**. The inlets of the conduits may interface with the inner channel **27** and the outlets may be formed in the body **22** of the rotor in the exterior surface of the body. Each of the outlets of the conduits **28** are preferably positioned above the outer blades **24**.

The body **22** of the rotor **21** may also include a plurality of passageways **31** that are sized to receive air or other gas forced through a column attached to the rotor **21** for expelling out of the rotor body **22** by the outer blades **24**. The passageways **31** may include an inlet for receiving air and may be formed in the body **22** of the rotor **21** so that the receive air passes through the passageways **31** and out of outlets **29** of the passageways **31**. Each outlet **29** of a passageway is preferably spaced apart from other outlets **29** and each outlet **29** is preferably positioned between two immediately adjacent outer blades **24**. For instance, as may be seen in FIG. **4**, blades **24a** and **24b** may be considered to be immediately adjacent. It should be understood that outer blades **24** may be considered immediately adjacent if no other outer blade is positioned between two adjacent outer blades along a periphery of the rotor body **22**.

6

The outer blades **24**, inner blades **25** and rotor body **22** may be sized and shaped so that rotation of the rotor forces slurry along flows **A** and **B** shown in FIG. **5**. Air may be passed through the passageways **31** so that the air flows along flow path **C** shown in FIG. **5**. No air may be combined with the slurry of flow **B** that passes through the inner channel **27** and conduits **28**. The slurry passed out of the conduits is expelled above the slurry and air mixed together via air flow **C** emitted from outlets **29** and slurry flow **A** generated by rotation of the outer blades **24**. The air flow **C** being positioned between the combination of slurry flows **A** and **B** such that large gas bubbles cannot escape without breaking into smaller bubbles that must collide with particles in the slurry flows **A** and **B**. The layering of slurry flows **A** and **B** and air flow **C** created by the rotor **21** may be referred to as an "air sandwich."

Thus slurry flow **B** is denser because the slurry flow **B** is not mixed immediately with air as the slurry flow **A** because slurry flow **A** is generated by the outer blades **24** while air is expelled from outlets **29** positioned between immediately adjacent outer blades **24**. In embodiments where the conduits **28** feed the slurry flow **B** out above the air flow **C** passing out of outlets **29** and slurry flow **A** generated from the rotation of the outer blades **24**, the rotor triggers "Rayleigh-Taylor" instability that enhances slurry gas mixing. Further, small bubbles that could recirculate back to the rotor are more likely to be drawn in by the conduits **28**, which may improve the pumping capacity created by rotation of the inner blades **25** and shape of conduits **28**, and inner channel **27** since it is contemplated that only the slurry will be drawn into the conduits **28** and inner channel **27**.

Due to the shape and structure of the rotor **21**, the rotor may be sized to be a smaller diameter than conventional rotors. The rotors may also, or alternatively, be rotated at lower speeds than conventional rotors due to the improved hydrodynamic design and performance of agitating slurry provided by embodiments of the rotor **21**. Further, the rotor may provide improved flotation kinetics as compared to conventional rotor designs due at least in part to the use of multiple slurry flows generated by rotation of the inner blades **25** and outer blades **24** of the rotor **21**.

Embodiments of the rotor **21** were found to provide a substantially greater ability to recover minerals during flotation machine operations. Testing was conducted on an embodiment of the rotor **21** and found the embodiment of the rotor **21** greatly improved mineral collection from a tank of a flotation cell as compared to the same cell having a conventional rotor for the recovery of minerals in certain types of slurries. Embodiments of the rotor were found to be particularly effective for processing slurry containing minerals in conditions that are typically difficult to recover via flotation machines with conventional rotors. For example, embodiments of the rotor were found to be particularly effective for small bubble generation, which improved mineral recovery of fine particulates from the slurry retained in a flotation cell. It is contemplated that the improvements provided by embodiments of the rotor **21** in flotation cell performance also permit embodiments of the rotor **21** to be fabricated at smaller diameters than conventional rotors, which may help the rotor provide a further reduction in cost associated with the manufacture of the rotor and operation of the rotor.

Another embodiment of a rotor **41** that may be utilized in rotation mechanisms **8** used in flotation machines may be appreciated from FIGS. **6-9**. The rotor **41** may include a body **42** formed of metal that has an upper portion **44** sized and configured for attachment to a column **61** of a rotation mechanism **8** and a central duct **45** for receiving air or gas that may be passed through the column to which the rotor is attached.

The duct 45 may also be considered a central channel, conduit, or passageway. The air passes through the duct 45 and out one or more outlets 46 formed in the rotor body 42. Preferably there is an outlet positioned between immediately adjacent outer blades 48 that extend from the rotor body 42.

The outer blades 48 may be formed on the body, adhered to the body, cast with the body, integrally attached to the body or otherwise attached to the body via one or more fastening mechanisms such as welding, rivets, or other fasteners. The outer blades 48 may be members such as walls or profiled fins that agitate the slurry when the rotor 41 is rotated.

Each of the outer blades 48 has an outer edge 49. As shown in FIGS. 6-9, the outer edge 49 extends outwardly from adjacent the upper portion of the rotor body 42 at an upper portion 50 of the outer edge 49 to an outermost position 51. The outward extension from the upper portion 50 adjacent the rotor body 42 to the outermost position 51 should extend along a curved path to a location positioned below the upper portion 50. This location should be positioned such that the portion of the outer blade 48 that extends from the outermost position 51 to the upper portion 50 should be at least 30% of the overall height H of the outer blade 48. From the outermost position 51, the outer edge 49 extends generally inwardly to a lower position 53 and innermost position 55 located adjacent the rotor body 42. The overall height of the portion of the outer blade that extends from the outermost position 51 to the lower position 53 should be at least 50% of the height H of the outer blade 48. The height of the portion of the outer blade 48 that extends from the lower portion 53 to the innermost position 55 of the outer edge 49 should be 20% or less of the overall height H of the outer blade 48. The outer edge 49 is preferably curved to define a generally half-hearted shape as may be appreciated from FIGS. 6, 7, and 8. A generally half heart shape may be understood to be the shape of the outer blades 48 as shown in FIGS. 6-9.

The upper portion 50 of the outer edge tapers inwardly toward the rotor body 42 and the lower portion of the outer edge 49 is positioned below the outermost position 51 also tapers inwardly to the rotor body 42. An intermediate section 48a of each outer blade 48 that includes the outermost position 51 is therefore wider than the upper section 48b and lower section 48c of the outer blade 48. It should be understood that the upper portion 50 of the outer edge 49 may be a portion of the upper section 48c and the lower position 53 and inner position 55 of the outer edge 49 may be portions of the lower section 48c.

The shape of the outer edge 49 of each outer blade may be defined as a curved path along with the outer edge travels. As may be seen from FIG. 9, the curved path of outer edges 49 may be defined by a series of equations for different values of parameters x and y used in a formula. The values for parameters x and y are normalized by rotor radius. For instance, the upper portion 50 of the outer edge 49, which is referred to as Section 1 in FIG. 9, may be defined by the formula  $y=10.974*x^6+10.512*x^5-43.377*x^4+28.863*x^3-4.6993*x^2+0.3068*x+0.5459$ . The value of x ranges from 0 to 0.7 for the upper portion 50 and may define the height and width of the upper section 48b of the outer blade.

The outermost position 51 of the outer edge 49 may extend for a certain distance, or height, to define a portion of a certain height of the outer edge 49 that is in the outermost position. The outermost position 51 is referred to as Section 2 in FIG. 9. The value of y may equal 1 for a value of x that ranges for 0.7 to 0.96, which may define the height of the intermediate section 48a of the outer blade.

The lower section of the outer edge 49 of each outer blade, which is referred to as Section 3 in FIG. 9, may be defined by

the formula  $y=134.46*x^5-712.12*x^4+1500*x^3-1572.6*x^2+821.19*x-169.93$ . The values for parameters x and y are normalized by rotor radius. The value of x ranges from 0.96 to 1.37 for the lower section of the outer edge that extends from the outermost position 51 to the inner position 55 and may define the height and width of the upper section 48b of the outer blade.

It should be understood that the values of x for the above noted formulas may define a height of the outer blades and the values of y may define the width of the outer blades normalized for the maximum radius of the rotor, which is the radius as measured to the outermost position 51 of the outer blade. The height of the outermost position 51 of the outer edge may extend to 18.9% of the overall height of the outer blade and define the intermediate section 48a of the outer blade. The height of the upper portion 50 that tapers from the upper portion of the outer blade to the highest point of the outermost position 51 of the outer edge 49 may extend along 51.1% of the overall height of the outer blade and may define the upper section 48b of the outer blade. The lower section of the outer edge that tapers inwardly from the lowermost point of the outermost position 51 of the outer edge may extend generally inwardly from this position as may be appreciated from FIGS. 6-9 for 29.3% of the height of the outer blade and may define the lower section 48c of the outer blade.

As may be seen in FIG. 8, rotation of the rotor 41 may create a flow D of slurry that is pushed outwardly by the intermediate section 48a of the outer blades 48 and gas expelled from outlets 46 so that a flow of slurry E is pushed further away from the rotor and column 61 than flows generated by conventional rotor designs. The tapered shape and the width of the intermediate sections 48a of the outer blades help spread the gas and slurry jet generated by the gas exiting the outlets 46 and rotation of the outer blades 48 so that the jet is spread out over a much larger area than conventional designs so that a uniform turbulence profile is generated when the rotor rotates at steady state conditions. The uniform turbulence profile enhances gas dispersion, improves bubble-particle collisions, and reduces bubble-particle detachment. Additionally, the velocity spike in the exit stream E is suppressed. This is beneficial as the velocity spike experienced by conventional rotors consumes power but does little to improve flotation performance.

Embodiments of the rotor 41 were found to consume substantially less horsepower than conventional rotor designs. Indeed, testing was conducted on an embodiment of the rotor 41 compared to conventional rotors and the results of that testing found the embodiment of the rotor 41 consumes much less horsepower as compared to conventional rotors, which provides a substantial reduction in operational costs associated with operation of the rotor and flotation cell using such a rotor. Further, the testing showed that embodiments of the rotor 41 provided an improved recovery of coarse particles from a slurry of a flotation cell as compared to conventional rotor designs.

It should be understood that numerous changes may be made to the embodiments of the rotor and flotation machine discussed above while still being within the scope of the following claims. For instance, the shape and geometry of the tanks of the flotation cells may be any of a number of different shapes and sizes. As another example, the type of material to be recovered by the cells of a flotation machine may be any of a number of different minerals or metals such as, for example, copper, iron, coal, a base metal, a special metal, other minerals or other types of metal. As yet another example, the column used to rotate the rotor may be any of a number of rotatable members such as rods or shafts that are part of a

rotation mechanism used to rotate the rotor. As yet another example and as those of at least ordinary skill in the art will appreciate, the types of reagents, types of depressants/activators, use of different pH levels, use of different collectors, frothers, or modifiers in the slurry may be utilized as needed to meet different material recovery objectives, or other design objectives. As yet another example, the number of external blades for an embodiment of the rotor may be two, five, seven, eight or any other number that is more than two as needed to meet one or more design objectives. Similarly, the number of internal blades of an embodiment of the rotor that may be utilized may be any number that is needed to meet one or more design objectives. As yet another example, the body of the rotor and the external and internal blades may be formed of a metal such as steel or an alloy or may be formed from another material that is found to be suitable to meet a particular design objective.

While certain present preferred embodiments of the flotation machines, rotors and methods of making and using the same have been shown and described above, it is to be distinctly understood that the invention is not limited thereto but may be otherwise variously embodied and practiced within the scope of the following claims.

What is claimed is:

1. A flotation machine comprising:

at least one flotation cell, each of the at least one flotation cell comprising:

a tank that is sized to retain a slurry comprised of a liquid mixed with at least one solid material;

a rotor positioned in the tank, the rotor rotated to agitate the slurry to facilitate formation of a bubbly flow used to generate a froth, the rotor attached to a column, the rotor comprising:

a body having:

a plurality of outer blades that extend outwardly from the body, each of the outer blades having an outer edge, the outer edge extending outwardly from an upper portion of the rotor to an outermost position located below the upper portion of the rotor, the outer edge extending inwardly from the outermost position to which the outer edge extends to a lower portion of the rotor, the lower portion of the rotor located below the outermost position to which the outer edge extends and is positioned inward relative to the outermost position of the outer edge;

wherein the outer edge extends along a curved path defined by the formulas:

$$y=10.974*x^6+10.512*x^5-43.377*x^4+28.863*x^3-4.6993*x^2+0.3068*x+0.5459 \text{ when } x \text{ is valued from } 0 \text{ to } 0.7;$$

$$y=1 \text{ when } x \text{ is valued from } 0.7 \text{ to } 0.96;$$

$$y=134.46*x^5-712.12*x^4+1500*x^3-1572.6*x^2+821.19*x-169.93 \text{ when } x \text{ is from } 0.96 \text{ to } 1.37; \text{ and}$$

wherein x and y are normalized by a maximum radius of the rotor.

2. The flotation machine of claim 1 wherein each outer edge defines a smooth outer surface of the blade and at least partially defines a shape of the outer blade such that the outer blade is generally half-heart shaped.

3. The flotation machine of claim 1 wherein the outer blades are sized and shaped such that the rotor suppresses a velocity spike in an exit stream of agitated slurry formed via rotation of the rotor.

4. The flotation machine of claim 3 wherein rotation of the rotor at steady state defines a uniform turbulence profile within the slurry.

5. The flotation machine of claim 1 wherein the rotor has a plurality of outlets for emitting air, each of the outlets positioned between immediately adjacent outer blades.

6. A rotor for a flotation machine comprising:

a body having:

a plurality of outer blades that extend outwardly from the body, each of the outer blades having an outer edge; the outer edge extending outwardly from an upper portion of the rotor to an outermost position located below the upper portion of the rotor and the outer edge extending inwardly from the outermost position to which the outer edge extends to a lower portion of the rotor, wherein the outer edge extends along a curved path defined by the formulas:

$$y=10.974*x^6+10.512*x^5-43.377*x^4+28.863*x^3-4.6993*x^2+0.3068*x+0.5459 \text{ when } x \text{ is valued from } 0 \text{ to } 0.7;$$

$$y=1 \text{ when } x \text{ is valued from } 0.7 \text{ to } 0.96;$$

$$y=134.46*x^5-712.12*x^4+1500*x^3-1572.6*x^2+821.19*x-169.93 \text{ when } x \text{ is from } 0.96 \text{ to } 1.37; \text{ and}$$

wherein x and y are normalized by a maximum radius of the rotor; and

the lower portion of the rotor being located below the outermost position to which the outer edge extends.

7. The rotor of claim 6 wherein each outer edge defines a smooth outer surface of the blade and at least partially defines a shape of the outer blade such that the outer blade is generally half-heart shaped.

8. The rotor of claim 6 wherein the outer blades are sized and shaped such that the rotor suppresses a velocity spike in an exit stream of agitated slurry formed via rotation of the rotor.

9. The rotor of claim 6 wherein the rotor is shaped so that rotation of the rotor at steady state defines a uniform turbulence profile within the slurry.

10. The rotor of claim 6 wherein the rotor has a plurality of outlets for emitting air, each of the outlets positioned between immediately adjacent outer blades and wherein the lower portion of the rotor is a bottom portion.

\* \* \* \* \*