

LIST OF TABLES

Table	Page
2.1 Aluminum Bridges in the United States.....	10
3.1 Mechanical and Cross-sectional Properties of Two-Void Extrusion.....	30
3.2 Test Truck Plan Dimensions and Axle Weights	36
3.3 Truck Live Load Moments at Mid-span.....	38
3.4 Location of Deck Gauges	41
3.5 Load Cases in Test Set 3	43
4.1 Example Table of “Moving Average of Six”	48
4.2 Non-composite Section Properties	52
4.3 Full Composite Section Properties.....	52
4.4 Influence Zone Parameter for Each Girder	69
4.5 Available Deck Gauge Data	73
4.6 S-N Curve Constants for Detail Categories in SAS-ASD (1994).....	75
4.7 S-N Curve Constants for Detail Categories in AASHTO LRFD (1994)	79
5.1 Top Flange Strains from Load Cases 1 and 2	86
5.2 Bottom Flange Strains from Load Cases 1 and 2.....	87
5.3 Neutral Axis Locations from Load Cases 1 and 2.....	87
6.1 Average Load Fractions from “Time Responses” Load Fractions.....	101
6.2 “Max Responses” Load Fractions	101
6.3 Load Fractions from Load Cases 1 and 2.....	102
6.4 One-Lane Loaded Distribution Factors (DF’s) from Field Data.....	107
6.5 Two-Lanes Loaded Distribution Factors (DF’s) from Field Data	109
6.6 Distribution Factors (DF’s) for Typical Transverse Truck Locations	110
6.7 Distribution Factors (DF’s) for Non-typical Transverse Truck Locations.....	110
7.1 Maximum Responses from Girders 1 and 2.....	118
7.2 Dynamic Load Allowances form Field Data for Girders 1 and 2	119
7.3 Average Dynamic Load Allowances from Test Set 3.....	119

8.1	Stress Ranges from Field Data of TS Gauges	124
8.2	Stress Ranges from Field Data of LS Gauges	125
8.3	Allowable Fatigue Stress Ranges	126
8.4	Stress Ranges for the Mechanical Deck Splice Evaluation.....	128