

References

- Archie, G. E. (1942). "Electrical resistivity log as an aid in determining some reservoir characteristics." *Transactions American Institute of Mining Engineers*, 146, 54-61.
- Arulanandan, K. (1982). "In situ characterization of saturated sands and silts for the prediction of dynamic shear modulus and shear wave velocity. Report to the Air Force Office of Scientific Res." *Grant No. AFOSR-82, 0216*, Dept. of Civil and Environ. Eng., Univ. of California, Davis, Calif.
- Arulanandan, K. (1991). "Dielectric method for prediction of porosity of saturated soil." *Journal of Geotechnical Engineering-ASCE*, 117(2), 319-330.
- Arulanandan, K. (2003). "Soil Structure: In Situ Properties and Behavior." Depart. of Civil and Environ. Eng., University of California, Davis, California. 352p.
- Arulanandan, K., Anandarajah, A. and Meegoda, N. J. (1983). "Soil characterization for non-destructive in situ testing." *Symposium Proceedings Part 2: The Interaction of Non-Nuclear Munitions with Structures, U.S. Air Force Academy, Colorado*, 69-75.
- Arulanandan, K. and Muraleetharan, K. K. (1988). "Level ground soil-liquefaction analysis using in-situ properties." *Journal of Geotechnical Engineering Division, ASCE*, 114(7), 771-790.
- Arulanandan, K., Yogachandran, C. (2001) "Dielectric dispersion method for non-destructive quantification of soil composition." *Computer simulation of earthquake effects*, Denver, Colorado.
- Arulmoli, K., Arulanandan, K., and Seed, H. B. (1985). "New method for evaluating liquefaction potential." *Journal of Geotechnical Engineering Division, ASCE*, 111(1), 95-114.
- ASTM, D6780-02. (2003). "Standard test method for water content and density of soil in place by time domain reflectometry (TDR)." *Annual book of ASTM standards*, Vol. 04.09.
- Aylmore, L. A. G., and Quirk, J. P. (1971). "Domain and quasi-crystalline regions in clay systems." *Soil Sci. Soc. Amer. Proc.*, 35, 652-654.
- Baker, J. M., and Spaans, E. J. A. (1993). "Time domain reflectometry measurements of water content and electrical conductivity of layered soil columns - comments." *Soil Sci. Society of America Journal*, 57(5), 1395-1396.
- Basu, R., and Arulanandan, K. (1973). "A new approach for the identification of swell potential of soils." *Proceedings of the Third International Conference on Expansive Soils*, Haifa, Israel, 1-11.
- Benson, C. H., and Bosscher, P.J. "Time-domain reflectometry (TDR) in Geotechnics: A review, nondestructive and automated testing for soil and rock properties." *ASTM SPT 1350*, West Conshohocken, Pa.
- Bromhead, E. N. (1979). "A simple ring shear apparatus." *Ground Engineering*, 12(5), 40-44.
- Bruggeman, D. A. G. (1935). "Dielektrizitätskonstanten und Leitfähigkeiten der Mischkörper aus isotropen Substanzen." *Ann. Phys. (Leipzig)*, 24, 636-664.
- Brunauer, S., Emmett, P.H., and Teller, E. (1938). "Adsorption of gases in multimolecular layers." *Journal of the American Chemical Society*, 60, 309-319.

- Call, F. (1957). "Soil fumigation, IV. Sorption of ethylene dibromide on soils at field capacity." *J. Sci. Food Agric*, 8, 137-142.
- Campbell, J. E. (1990). "Dielectric properties and influence of conductivity in soils at one to fifty megahertz." *Soil Science Society of American Journal*, 54, 332-341.
- Campbell, G. S., Mulla, D. J. (1990) "Measurement of soil water content and potential." *Irrigation of Agricultural Crops. Agronomy Monograph No. 30. ASA, CSSA, SSSA, Madison, WI*, 127-142.
- Carman, P. C. (1937). "Fluid flow through a granular bed." *Transactions of the Institute of Chemical Eng*, London.
- Carter, D. L., Heilman, M.D., and Gonzalez, C.L. (1965). "Ethylene glycol monoethyl ether procedure for assessment of surface area." *Soil Sci.*, 100, 356-360.
- Cerato, A. B., and Lutenegeger, A. J. (2002). "Determination of surface area of fine-grained soils by the ethylene (EGME) method." *Geotechnical Testing Journal*, 25(3), 315-321.
- Chen, G., P., J., Han, B., and Yan, H. (1999). "Adsorption of methylene blue on montmorillonite." *Journal of Dispersion Science and Technology*, 20(4), 1179-1187.
- Chen, Y. P., and Or, D. (2006). "Effects of Maxwell-Wagner polarization on soil complex dielectric permittivity under variable temperature and electrical conductivity." *Water Resources Research*, 42(6).
- Christensen, B. J., Coverdale, T. R., Olson, R. A., Ford, S. J., Garboczi, E. J., Jennings, H. M., Mason, T. O. (1994). "Impedance spectroscopy of hydrating cement-based materials: measurement, interpretation and application." *J. Am. Ceram. Soc.*, 77(11), 2789-2804.
- Churchman, G. J., and Burke, C. M. (1991). "Properties of subsoils in relation to various measures of surface area and water content." *J. of Soil Sci.*, 42(3), 463-478.
- Dafalias, Y. F., and Arulanandan, K. (1979). "The formation factor tensor in relation to structural characteristics of anisotropic granular soils." *Proceedings, Colloque International du C. N.R.S., Euromech Colloquium 115, Villard-pde-Laus, France*.
- Dafalias, Y. F., and Arulanandan, K. (1979). "Electrical characterization of transversely isotropic sands." *Archives of Mechanics*, 31(5), 723-739.
- Dahan, O., Rimon, Y., Tatarsky, B., and Talby, R. (2006). "Deep vadose zone monitoring system." *Proc. TDR 2006, Purdue University, West Lafayette, USA, No. 46*, 15 p.
- Dasberg, S., and Hopmans, J. W. (1992). "Time-domain reflectometry calibration for uniformly and non-uniformly wetted sandy and clayey loam soils." *Soil Sci. Soc. Am. J.*, 56(5), 1341-1345.
- Debye, P. (1929). *Polar Molecules*, New York.
- De Bruyn, C. M. A., Collins, L. F., and Williams, A. A. B. (1957). "The specific surface, water affinity, and potential expansiveness of clays." *Clay Mineralogy Bullitin*, 3, 120-128.
- de Jong, E. (1999). "Comparison of three methods of measuring surface area of soils." *Canadian Journal of Soil Science*, 79(2), 345-351.
- de Loor, G. P. (1968). "The dielectric properties of heterogeneous mixtures containing water." *J. of Microwave power*, 3(2), 67-73.
- Dirksen, C., and Dasberg, S. (1993). "Improved calibration of time-domain reflectometry soil-water content measurements." *Soil Sci. Soc. of Am. J.*, 57(3), 660-667.

- Dobson, M. C., Ulaby, F. T., Hallikainen, M. T., and Elrayes, M. A. (1985). "Microwave dielectric behavior of wet soil: 2. Dielectric Mixing Models." *IEEE Transactions on Geoscience and Remote Sensing*, 23(1), 35-46.
- Dong, X. B., Wang, Y.H. "EM-wave based characterizations of local void ratios in soils." *Geo-Frontier 2005*, Austin, Texas.
- Dyal, R. S., and Hendricks, S.B. (1950). "Total surface area of clays in polar liquids as a characteristic index." *Soil Sci.*, 69, 421-432.
- Fam, M. A., and Santamarina, J.C. (1996). "Study of clay-cement slurries with mechanical and electromagnetic waves." *J. of Geotech. Eng.*, 122(5), 365-373.
- Farrar, D. M., Coleman, J.D. (1967). "The correlation of surface area with other properties of nineteen British clay soils." *J. of Soil Sci.*, 18(1), 118-124.
- Feng, W., Lin, C. P., Deschamps, R. J., and Drnevich, V. P. (1999). "Theoretical model of multisection time domain reflectometry measurement system." *Water Resour. Res.*, 35(8), 2321-2331.
- Fernando, M. J., Burau, R.G., Arulanandan, K. (1977). "A new approach to determination of cation exchange capacity." *Soil Sci. Soc. of Am. J.*, 41(4), 818-820.
- Fricke, H. (1924). "A mathematical treatment of the electric conductivity and capacity of disperse systems." *Phys. Rev.*, 24, 575-587, 1924.
- Fricke, H. (1953). "The Maxwell-Wagner dispersion in a suspension of ellipsoids." *Journal of Chemical Physics*, 57, 934-937.
- Friedman, S. P. (1998). "A saturation degree-dependent composite spheres model for describing the effective dielectric constant of unsaturated porous media." *Water Resour. Res.*, 34(11), 2949-2961.
- Friedman, S. P. (2005). "Soil properties influencing apparent electrical conductivity: a review." *Computers and Electronics in Agriculture*, 46(1-3), 45-70.
- Frost, J. D. (2000). "Evolution of sand microstructure during shear." *J. of Geot. and Geoenviron. Eng.*, 126(2), 116-130.
- Jones, S. B., and Or, D. (2002). "Surface area, geometrical and configurational effects on permittivity of porous media." *Journal of Non-Crystalline Solids*, 305(1-3), 247-254.
- Gans, W. L., and Nahman, N. S. (1982). "Continuous and discrete Fourier transform of step-like waveforms." *IEEE Trans. Instrum. Meas.* (IM-31), 97-101.
- Geiman, C. M. (2005). "Stabilization of soft clay subgrades in Virginia," Virginia Tech, Blacksburg, VA.
- Gill, W. R., and Reaves, C. A. (1957). "Relationship of Atterberg limits and cation exchange capacity to some physical properties of soil." *Soil Sci. Soc. of Am. Proc.*, 21, 491-497.
- Hallikainen, M. T., Ulaby, F. T., Dobson, M. C., Elrayes, M. A., and Wu, L. K. (1985). "Microwave dielectric behavior of wet soil .1. empirical-models and experimental-observations." *IEEE Transactions on Geoscience and Remote Sensing*, 23(1), 25-34.
- Hammel, J. E., Sumner, M. E., and Burema, J. (1983). "Atterberg limits as indices of external surface areas of soils." *Soil Science Society of America Journal* (47), 1054-1056.

- Heilman, M. D., Carter, D. L. and Gonzalez, C. L. (1965). "The ethylene glycol monoethyl ether (EGME) technique for determining soil-surface area." *Soil Sci.*, 100, 409-413.
- Heimovaara, T. J. (1994). "Frequency-domain analysis of time-domain reflectometry wave-forms .1. measurement of the complex dielectric permittivity of soils." *Water Resources Research*, 30(2), 189-199.
- Heimovaara, T. J. (2001). "Frequency domain modeling of TDR wave forms in order to obtain frequency-dependent dielectric properties of soil samples: A theoretical approach." *Proc. Int. Symp. and Workshop on Time Domain Reflectometry for Innovative Geotechnical Applications*, 2nd.
- Heimovaara, T. J., Bouten, W., and Verstraten, J. M. (1994). "Frequency-domain analysis of time-domain reflectometry wave-forms: 2. A 4-component complex dielectric mixing model for soils." *Water Resources Research*, 30(2), 201-209.
- Hilhorst, M. A. (1998). "Dielectric Characterisation of Soil," Wageningen Agricultural University.
- Hill, N. E., Vaughan, W.E., Price, A.H., and Davies, M. (1969). *Dielectric Properties and Molecule Behavior*, London.
- Huisman, J. A., Bouten, W., Vrugt, J. A., and Ferre, P. A. (2004). "Accuracy of frequency domain analysis scenarios for the determination of complex dielectric permittivity." *Water Resources Research*, 40(2).
- Jacobsen, O. H., and Schjonning, P. (1993). "A laboratory calibration of time domain reflectometry for soil water measurement including effects of bulk density and texture." *J. Hydrol.*, 151(2-4), 147-157.
- Jones, S. B., and Or, D. (2002). "Surface area, geometrical and configurational effects on permittivity of porous media." *Journal of Non-Crystalline Solids*, 305, 247-254.
- Jones, S. B., and Or, D. (2003). "Modeled effects on permittivity measurements of water content in high surface area porous media." *Physica B-Condensed Matter*, 338, 284-290.
- Kaatze, U. (1996). "Microwave dielectric properties of water." *Microwave Aquametry*, A. Kraszewski, ed., IEEE press, New York.
- Kelleners, T. J., Robinson, D. A., Shouse, P. J., Ayars, J. E., and Skaggs, T. H. (2005). "Frequency dependence of the complex permittivity and its impact on dielectric sensor calibration in soils." *Soil Science Society of America Journal*, 69(1), 67-76.
- Kenney, T. C. (1967). "The influence of mineral composition on the residual shear strength of natural soils." *Proc. Geotechnical Conference*, Oslo, Norway, 123-129.
- Klein, K. (2006). "Electromagnetic properties of cemented paste backfill." *Journal of Environmental and Engineering Geophysics*, 11(1), 27-41
- Klein, K. (2004). "Permittivity measurements of high conductivity specimens using an open-ended coaxial probe - measurement limitations." *Journal of Environmental and Engineering Geophysics*, 9(4), 191-200.
- Klein, K., and Santamarina, J. C. (1997). "Methods for broad-band dielectric permittivity measurements (soil-Water mixtures, 5 Hz to 1.3 GHz)." *Geotechnical Testing Journal*, 20(2), 168-178.
- Klein, L. A., and Swift, C. T. (1977). "An improved model for the dielectric constant of sea water at microwave frequencies." *IEEE Trans. Antennas Propag.*, 25, 104-111.

- Lambe, T. W., and Whitman, R. V. (1969). *Soil Mechanics*, John Wiley & Sons, New York.
- Leroy, P., and Revil, A. (2004). "A triple-layer P model of the surface electrochemical properties of clay minerals." *Journal of Colloid and Interface Science*, 270(2), 371-380.
- Lin, C. P. (1999). "Time domain reflectometry for soil properties," Purdue University, West Lafayette, IN.
- Lin, C. P. (2003a). "Analysis of nonuniform and dispersive time domain reflectometry measurement systems with application to the dielectric spectroscopy of soil." *Water Resour. Res.*, 39(1), 1012.
- Lin, C. P. (2003b). "Frequency domain versus travel time analyses of TDR waveforms for soil moisture measurements." *Soil Science Society of America Journal*, 67(3), 720-729.
- Locat, J., Lefebvre, G., and Ballivy, G. (1984). "Mineralogy, chemistry, and physical properties interrelationships of some sensitive clays from Eastern Canada." *Canadian Geotechnical Journal*, 21, 530-540.
- Low, P. F. (1976). "Viscosity of interlayer water in montmorillonite." *Soil Science Society of America Journal*, 40(4), 500-505.
- Lyons, E. H. (1967). "Introduction to Electrochemistry." D.C. Heath and Company, Boston.
- Magnusson, P. C., Alexander, G. C., Tripathi, V. K., and Weisshaar, A. (2000). *Transmission Lines and Wave Propagation*, CRC, 250p.
- Marcum, R. B., Muccini, G. A. (1956). "Characteristics of porous beds and structures." *American Institute of Chemical Eng.*, 2(3), 393-403.
- Maxwell Garnett, J. C. (1904). "Colours in metal glasses and metal films." *Trans. of the Royal Society, (London)*, CCIII, 385-420.
- McCarter, W. J., and Afshar, A.B. (1984). "Some aspects of the electrical properties of cement paste." *J. Mat. Sci. Let.*, 3, 1083-1086.
- McGehee, G. A. (1988). "The layered-capacitor method for bridge measurements of conductive dielectrics." *IEEE Transactions on Electrical Insulation*, 23(3), 387-396.
- Meegoda, N. J. (1985). "Fundamental characterization of soils for the development of an expression for permeability for application in in-situ testing," University of California, Davis.
- Meegoda, N. J., King, I. P., and Arulanandan, K. (1989). "An expression for the permeability of anisotropic granular media." *International Journal for Numerical and Analytical Methods in Geomechanics*, 13(6), 575-598.
- Meehan, C. L. (2006). "An experimental study of the dynamic behavior of slickensided surfaces", Virginia Tech, Blacksburg.
- Mitchell, J. K. (1993). *Fundamentals of Soil Behavior, 2nd Edition*, John Wiley & Sons, 437p, New York.
- Mitchell, J. K. (2004). "Time - the fourth dimension of soil behavior in geotechnical engineering." *Seventeenth Nabor Carrillo Lecture*, Tiempo, Mexico.
- Mitchell, J. K., and Liu, N. (2006). "Usefulness of EM waves for site and soil property characterization in geotechnical engineering." *ASCE Geotechnical Special Publication No. 149*, Shanghai, China, 136-143.

- Nicolson, A. M. (1973). "Forming the fast Fourier transform of a step response in time-domain metrology." *Electron. Lett.*, 9, 317-318.
- Noborio, K. (2001). "Measurement of soil water content and electric conductivity by time domain reflectometry: a review." *Comput. Electron. Agric.*, 31(3), 213-237.
- O'Conner, K. M., Dowding, C.H. (1999). *GeoMeasurements by Pulsing TDR Cables and Probes*, CRC Press.
- O'Konski, C. T. (1960). "Electric properties of micromolecules, V. Theory of ionic polarization polyelectrolytes." *J. of Phy. Chem.*, 64, 605.
- Or, D., and Wraith, J. M. (1999). "Temperature effects on soil bulk dielectric permittivity measured by time domain reflectometry: A physical model." *Water Resources Research*, 35(7), 2283-2283.
- Parfitt, R. L., Whitton, J. S., and Theng, B. K. G. (2001). "Surface reactivity of A horizons towards polar compounds estimated from water adsorption and water content." *Australian Journal of Soil Research*, 39(5), 1105-1110.
- Penny, J. E. T., and Lindfield, G. R. (2000). *Numerical methods using Matlab*, Prentice Hall, Upper Saddle River, NJ.
- Persson, M., and Haridy, S. (2003). "Estimating water content from electrical conductivity measurements with short time-domain reflectometry probes." *Soil Science Society of America Journal*, 67(2), 478-482.
- Petersen, L. W., Moldrup, P., Jacobsen, O. H., Rolston, D. E. (1996). "Relations between specific surface area and soil physical and chemical properties." *Soil Science*, 161(1), 9-21.
- Polk, C., and Postow, E. (1986). *CRC Handbook of Biological Effects of Electromagnetic Fields*, CRC Press, Inc., Boca Raton, FL.
- Ponizovskiy, A. A., Korsunskaya, L. P., Polubesov, T. A., Salimgareyeva, O. A., Aleksane, Y. S., and Pachepskiy, Y. A. (1993). "Methods for determining the specific surface area of soil from water-vapor adsorption." *Eurasian Soil Science*, 25(6), 12-29.
- Prochnow, E. A., Remus, M. V. D., Ketzer, J. M., Gouvea, J. C. R., de Souza, R. S., and De Ros, L. F. (2006). "Organic-inorganic interactions in oilfield sandstones: Examples from turbidite reservoirs in the Campos Basin, offshore eastern Brazil." *Journal of Petroleum Geology*, 29(4), 361-379.
- Quirk, J. P. (1986). "Soil permeability in relation to sodicity and salinity." *Philosophical Transactions of the Royal Society of London Series a-Mathematical Physical and Engineering Sciences*, 316(1537), 297-317.
- Quirk, J. P., and Murray, R. S. (1991). "Towards a model for soil structural behavior." *Australian Journal of Soil Research*, 29(6), 829-867.
- Ramo, S., Whinnery, J. R., and Van Duzer, T. (1994). *Fields and Waves in Communication Electronics. 3rd ed.*, John Wiley, New York.
- Rinaldi, V. A., and Francisca, F. M. (1999). "Impedance analysis of soil dielectric dispersion (1 MHz-1 GHz)." *Journal of Geotechnical and Geoenvironmental Engineering*, 125(2), 111-121.
- Robinson, D. A. (2004). "Measurement of the solid dielectric permittivity of clay minerals and granular samples using a time domain reflectometry immersion method." *Vadose Zone Journal*, 3(2), 705-713.

- Roth, C. H., Malicki, M. A., and Plagge, R. (1992). "Empirical evaluation of the relationship between soil apparent dielectric constant and volumetric water content as the basis for calibrating soil moisture contents by TDR." *J. Soil Sci.*, 43(1), 1-13.
- Russell, E. R., Mickle, J.L. (1970). "Liquid limit values of soil moisture tension." *Journal of Soil Mechanics and Foundations Division, ASCE.*, 96, 967-987.
- Sachs, S. B., and Speigler, K.S. (1964). "Radio-frequency measurements of porous conductive plugs, ion-exchange resin-solution systems." *Journal of Physical Chemistry*, 68, 1214-1222.
- Sadek, M. S. (1993). "A comparative study of the electrical and hydraulic conductivities of compacted clay," University of California, Berkeley, Berkeley, California.
- Salgado, R., Bandini, P., and Karim, A. (2000). "Shear strength and stiffness of silty sand." *J. Geotech. Geoenviron. Eng.*, 126(5), 451-462.
- Sanjeevan, S. (1983). "Correlation of electrical properties of soils to permeability," Master Thesis, University of California, Davis, Davis.
- Santamarina, J. C., Klein, K. A., Wang, Y. H., and Prencke, E. (2002). "Specific surface: determination and relevance." *Canadian Geotechnical Journal*, 39(1), 233-241.
- Santamarina, J. C., Klein, K. and Fam, M. (2001). "Soils and Waves." J. Wiley and Sons, Chichester, UK, 488p.
- Santamarina, J. C., Rinaldi, V. A., Fratta, D., Klein, K., Wang, Y. H., Cho, G. C., and Cascante, G. (2005). "A survey of elastic and electromagnetic properties of near-surface soils."
- Sauck, W. A. (2000). "A model for the resistivity structure of LNAPL plumes and their environs in sandy sediments." *Journal of Applied Geophysics*, 44(2-3), 151-165.
- Saxon, J. A. "Dielectric dispersion in pure polar liquids at very high radio-frequencies, II, Relation of experimental results to theory." *Proc. R. Soc. London, Ser. A*, 213, 473-491.
- Schwarz, G. (1962). "A theory of the low-frequency dielectric dispersion of colloidal particles in electrolyte solution." *J. of physics and chemistry*, 66, 2626.
- Scott, J. H., Carroll, R.D. and Cunningham, D.R. (1967). "Dielectric Constant and Electrical Conductivity Measurements of Moist Rock: A New Laboratory Method." *Journal of Geophysical Research*, 72(20), 5101-5115.
- Seed, H. B., and Idriss, I.M. (1970). "Soil moduli and damping factors for dynamics response analysis, Report No. EERC 70-10." University of California, Berkeley.
- Sen, P. N., Scala, C., and Cohen, M. H. (1981). "A self-similar model for sedimentary rocks with application to the dielectric constant of fused glass beads." *Geophysics* 46(5), 781-795.
- Shaarawi, A. M., and Riad, S. M. (1986). "Computing the Complete Fft of a Step-Like Wave-Form." *IEEE Transactions on Instrumentation and Measurement*, 35(1), 91-92.
- Shang, J. Q., Rowe, R. K., Umana, J. A., and Scholte, J. W. (1999). "A complex permittivity measurement system for undisturbed compacted soils." *Geotechnical Testing Journal*, 22(2), 165-174.

- Siddiqui, S. I., and Drnevich, V. P. (1995). "A new method of measuring density and moisture content of soil using the technique of Time Domain Reflectometry." *FHWA/IN/JTRP-95/9, Joint Transportation Research Program*, Indiana Department of Transportation-Purdue University.
- Sihvola, A. and Lindell, I. V. (1990). "Polarizability and effective permittivity of layered and continuously inhomogeneous dielectric ellipsoids." *J. Electromagnetic Waves Appl.*, 4, 1-26.
- Sihvola, A. H. (1999). *Electromagnetic Mixing Formulas and Applications*, Institute of Electrical Engineers, London.
- Skempton, A. W. (1964). "Long-term stability of clay slopes." *Geotechnique*, 14(2), 75-102.
- Smith, S. S., and Arulanandan, K. (1981). "Relationship of Electrical Dispersion to Soil Properties." *Journal of the Geotechnical Engineering Division-ASCE*, 107(5), 591-604.
- Sridharan, A. "Engineering behavior of clays: Influence of mineralogy." *Chemo-Mechanical Coupling in Clays; From Nano-Scale to Engineering Applications*, Lisse, 3-28.
- Sridharan, A., Rao, S.M., and Murphy, N.S. (1988). "Liquid limit of kaolinite soils." *Geotechnique*, 38(2), 191-198.
- Stark, T. D., and Eid, H. T. (1994). "Drained residual strength of cohesive soils." *Journal of Geotechnical Engineering, ASCE*, 120(5), 856-871.
- Stogryn, A. (1971). "Equations for calculating the dielectric constant of saline water." *IEEE Transaction on Microwave Theory and Techniques*, 19, 733.
- Terzaghi, K., Peck, R. B., and Mesri, G. (1996). *Soil Mechanics in Engineering Practice*, Wiley, New York.
- Thevanayagam, S. (1993). "Electrical response of two-phase soil - theory and applications." *Journal of Geotechnical Engineering-ASCE*, 119(8), 1250-1275.
- Thevanayagam, S. (1995). "Frequency-domain analysis of electrical dispersion of soils." *Journal of Geotechnical Engineering-ASCE*, 121(8), 618-628.
- Thorp, J. M. (1959). "The dielectric behavior of vapours adsorbed on porous solids." *Transaction of the Faraday Society*, 55(3), 442-454.
- Tiller, K. G., Smith, L.H. (1990). "Limitations of EGME retention to estimate the surface area of soils." *Aust. J. Soil Res.*, 28, 1-26.
- Tinga, W. R., and Voss, W. A. G. (1973). "Generalized approach to multiphase dielectric mixture theory." *J. Appl. Phys.*, 44(9), 3897-3902.
- Topp, G. C., J. L. Davis, & A. P. Annan. (1980). "Electromagnetic determination of soil water content: Measurements in coaxial transmission lines." *Water Resour. Res.*, 16, 574-582.
- Topp, G. C., Zegelin, S., and White, I. (2000). "Impacts of the real and imaginary components of relative permittivity on time domain reflectometry measurements in soils." *Soil Science Society of America Journal*, 64(4), 1244-1252.
- USDA. (1982). "Procedures for collecting soil samples and methods of analysis for soil survey." USDA Soil Survey invest. Rep. No.1.
- van Olphen, H. (1977). *An Introduction to Clay Colloid Chemistry*, Wiley Interscience, New York.

- Wang, J. R., and Schmugge, T.J. (1980). "An empirical model for the complex dielectric permittivity of soils as a function of water content." *IEEE Transactions on Geoscience and Remote Sensing*, GE-18, 288-295.
- Weiler, R. A., and Chaussidon, J. (1968). "Surface conductivity and dielectrical properties of montmorillonite gels." *Clays and clay minerals*, 16, 147-155.
- Wensink, W. A. (1993). "Dielectric-Properties of wet soils in the frequency-range 1-3000 MHz." *Geophysical Prospecting*, 41(6), 671-696.
- Wetzel, A. (1990). "Interrelationships between porosity and other geotechnical properties of slowly deposited, fine-grained marine surface sediments." *Marine Geology*, 92, 105-113.
- White, W. A. (1949). "Atterberg plastic limits of clay minerals." *American Mineral.*, 34, 508-512.
- Whyte, I. L. (1982). "Soil plasticity and strength - a new approach using extrusion." *Ground Engineering*, 15(1), 16-24.
- Wobschall, D. (1977). "A theory of the complex dielectric permittivity of soil containing water, the semidisperse model." *IEEE Transactions on Geoscience and Remote Sensing*, 15(1), 49-58.
- Wraith, J. M., Or, D. and Jones, S. B. (2001). "Dielectric properties of bound water: application to porous media surface area and grain moisture determination." *TDR 2001*.
- Wroth, C. P., Wood, D.W. (1978). "The correlation of index properties with some basic engineering properties of soils." *Can. Geotech. J.*, 15(2), 137-145.
- Yu, X., and Drnevich, V. P. (2004). "Soil water content and dry density by time domain reflectometry." *Journal of Geotechnical and Geoenvironmental Engineering*, 130(9), 922-934.
- Yukselen, Y., and Kaya, A. (2006). "Comparison of methods for determining specific surface area of soils." *Journal of Geotechnical and Geoenvironmental Engineering*, 132(7), 931-936.