

References

- American Forest and Paper Association (AF&PA). 1997. National design specification for wood construction. AF&PA, Washington, D.C. 173 pp.
- American Forest and Paper Association (AF&PA). 1999. General dowel equations for calculating lateral connection values – Technical Report 12. AFPA, Washington, DC. 18 pp.
- American Society for Testing and Materials (ASTM). 2003a. Standard practice for exposing nonmetallic materials in accelerated test devices that use laboratory light sources. Annual Book of Standards, Vol. 14.10, G 151-00. ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003b. Standard specification for computing the reference resistance of wood-based materials and structural connections for load and resistance factor design. Annual Book of Standards, Vol. 04.10, D 5457-93. ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003c. Standard specification for driven fasteners: nails, spikes, and staples. Annual Book of Standards, Vol. 01.08, F 1667-03. ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003d. Standard test method for determining bending yield moment of nails. Annual Book of Standards, Vol. 01.08, F 1575-03. ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003e. Standard test method for evaluating dowel-bearing strength of wood and wood-based products. Annual Book of Standards, Vol. 04.10, D 5764-97a (Reapproved 2002). ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003f. Standard test methods for evaluating the properties of wood-base fiber and particle panel materials. Annual Book of Standards, Vol. 04.10, D 1037-99. ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003g. Standard test methods for mechanical fasteners in wood. Annual Book of Standards, Vol. 04.10, D 1761-88. ASTM, West Conshohocken, PA.
- American Society for Testing and Materials (ASTM). 2003h. Standard test methods for specific gravity of wood and wood-base materials. Annual Book of Standards, Vol. 04.10, D 2395-93 (Reapproved 1997). ASTM, West Conshohocken, PA.

- Anderson, C.A., J.R. Loferski, and F.E. Woeste. 2002. Wood Bits: Detecting early wood decay. *Building Standards* 71(4):6-7.
- APA – The Engineered Wood Association. 2001. Performance standards and policies for structural-use panels. PRP-108. APA, Tacoma, WA. 57 pp.
- Arima, T., M. Sato, and K. Mashita. 1981. Studies on the evaluation methods for long-Term performance of wood-based materials and elements. Report of the Building Research Institute. No.95, pp. 42-61.
- Arima, T. and S.I. Hong. 1996. Creep and mechano-sorptive deformation of mechanical joints in glulam and LVL. Proc. of International Wood Engineering Conference. Vol. 3, pp. 467-474.
- Aune, P. and M. Patton-Mallory. 1986. Lateral load-bearing capacity of nailed joints based on the yield theory: experimental verification. FPL-RP-470. U.S. Dept. of Agriculture, Forest Service. Forest Products Laboratory, Madison, WI.
- Baker, A. J. 1974. Degradation of wood by products of metal corrosion. FPL-RP-229. U.S. Dept. of Agriculture, Forest Service. Forest Products Laboratory. Madison, WI.
- Bennett, A., S. Clark, and C. Benge. 2001. Design for durability: a review of New Zealand practice. Proc. of CIB World Building Congress (CD-Rom). International Council for Research Innovation in Building and Construction (CIB), Wellington, New Zealand.
- Blass, H.J. 1994. Variation of load-slip behavior in nailed joints: variation parallel to the grain. *Forest Prod. J.* 44(1):15-20.
- Burch, D.M. and W.C. Thomas. 1993. MOIST: a PC program for predicting heat and moisture transfer in building envelopes. Release 2.0. National Institute of Standards and Technology, Special Publication 853. U.S. Government Printing Office, Washington, DC. 68 pp.
- Burch, D.M., R.R. Zarr, A.H. Fanney. 1995. Experimental verification of a moisture and heat transfer model in the hygroscopic regime. Proc. of Thermal Performance of Exterior Envelopes of Buildings VI. National Institute of Standards and Technology, Gaithersburg, MD. pp. 273-283.
- Burch, D.M. and J. Chi. 1997. MOIST: a PC program for predicting heat and moisture transfer in building envelopes. Special Publication 917. National Institute of Standards and Technology, Gaithersburg, MD.
- Burdock, E., M. Ritter, J. Livingston, and S. Carnes. 2001. Partnership for advancing technology in housing. *Forest Prod. J.* 51(3):8-14.

- Chow, P., J.D. McNatt, S.J. Lambrechts, and G.Z. Gertner. 1988. Direct withdrawal and head pull-through performance of nails and staples in structural wood-based panel materials. *Forest Prod. J.* 38(6):19-25.
- Chui, Y.H. and S. Craft. 2002. Fastener head pull-through resistance of plywood and oriented strand board. *Canadian J. of Civil Engineering* 29(3):384-389.
- Durrans, S.R., M.H. Triche, and S.K. Suddarth. 1998. Estimation of lower tail quantiles of Weibull probability distributions for lumber strength. *Forest Prod. J.* 48(1):96-101.
- Ellingwood, B. 1994. Probability-based codified design: past accomplishments and future challenges. *J. Structural Safety* 1(1):159-176.
- Farber, E. 1954. Chemical deterioration of wood in the presence of iron. *Industrial and Engineering Chemistry* 46(9):1968-1972.
- Feldborg, T. 1989. Timber joints in tension and nails in withdrawal under long-term load and alternating humidity. *Forest Prod. J.* 39(11/12):8-12.
- Fink, F.W. and W.K. Boyd. 1970. Corrosion of metals in marine environments. Report 245. Defense Materials Information Center, Batelle Memorial Institute, Columbus, OH. 6 pp.
- Foliente, G.C., R.H. Leicester, I. Cole, and C. Mackenzie. 1999. Development of a reliability-based durability design method for timber construction. *Proc. of 8th Inter. Conf. on Durability of Building Materials and Components (8dbmc)*. Vol. 2. M.A. Lacasse and D.J. Vanier, eds. NRC Research Press, Ottawa, ON, Canada. pp. 1289-1298.
- Foliente, G.C., R.H. Leicester, C. Wang, C. Mackenzie, I. Cole. 2002. Durability design for wood construction. *Forest Prod. J.* 52(1):10-19.
- Forest Products Laboratory. 1999. *Wood Handbook: Wood as an engineering material*. FPL-GTR-113. U.S. Dept. of Agriculture, Forest Service. Forest Products Laboratory. Madison, WI. 463 pp.
- Green, D.W. and J.W. Evans. 1987. *Mechanical properties of visually graded lumber*. Vols. 1-5. U.S. Dept. of Agriculture, Forest Service. Forest Products Laboratory. Madison, WI.
- Grenoble, H.S. 1925. Bearing strength of bolts in wood. Technical Note 147. Navy Department, Bureau of Aeronautics, Washington, DC.
- Groom, L.H. 1994. Effect of moisture cycling on truss-joist behavior. *Forest Prod. J.* 44(1):21-29.

- Hayashi, T., A. Miyatake, and M. Harada. 2002. Outdoor exposure tests of structural laminated veneer lumber I: evaluation of the physical properties after six years. *J. Wood Sci.* 48(1):69-74.
- International Conference of Building Officials (ICBO). 2002. Acceptance criteria for special roofing systems. AC07. ICBO, Whittier, CA.
- International Organization for Standardization (ISO). 1983. Timber structures – joints made with mechanical fasteners. General principles for the determination for strength and deformation characteristics. ISO 6891. Geneva, Switzerland.
- Jang, S.S., Y. Fujimoto, and Y. Mataka. 1993. Fatigue behavior of framing-to-sheathing nailed joints. *Forest Prod. J.* 43(4):63-69.
- Johansen, K.W. 1949. Theory of timber connections. Publications of the International Association for Bridge and Structural Engineering, Zurich, Switzerland. Vol. 9. pp. 249-262.
- Kalkert, R.E. and J.D. Dolan. 1997. Behavior of 8d nailed stud-to-sheathing connections. *Forest Prod. J.* 47(6):95-102.
- Kameda, H. and T. Koike. 1975. Reliability theory of deterioration in structures. *J. of Structures Division, American Society of Civil Engineers.* Vol. 101, pp. 295-310.
- Leicester, R.H. and G.C. Foliente. 1999. Models for timber decay and termite attack. *Proc. of Durability of Building Materials and Components VIII.* Vols. 1-4. pp. 756-765.
- Littell, R.D., J.R. McClave, and W.W. Offen. 1979. Goodness-of-fit test for the two-parameter Weibull or extreme-value distribution with unknown parameters. *Communications in Statistics, Part 2: simulation and computation.* Vol. 8. pp. 257-269.
- Liu, J.Y. and L.A. Soltis. 1984. Lateral resistance of nailed joints – A test method. *Forest Prod. J.* 34(1):55-60.
- Loferski, J.R. 2000. Technologies for wood preservation in historic preservation. *Science and Technology in Historic Preservation.* Williamson and Nickens, eds. Plenum Publishing. New York, NY. pp. 173-191.
- Marian, J.E. and A. Wissing A. 1960. The chemical and mechanical deterioration of wood in contact with iron, Part 1. Mechanical deterioration. *Svensk Papperstidning* 63(3):47-57.
- McLain, T.E. 1998. Connectors and fasteners: Research needs and goals. *Wood Engineering in the 21st Century: Research Needs and Goals.* K.J. Fridley, ed, American Society of Civil Engineers, Reston, VA. pp. 56-69.

- McNatt, J.D. and C.L. Link. 1989. Analysis of ASTM D 1037 accelerated aging test. *Forest Prod. J.* 39(10):51-57.
- McNatt, J.D. and D. McDonald. 1993. Two accelerated aging tests for wood-based panels. *Forest Prod. J.* 43(7-8):49-52.
- Mohammad, M.A.H., I. Smith. 1994. Stiffness of nailed OSB-to-lumber connections. *Forest Prod. J.* 44(11/12):37-44.
- Moller, T. 1950. En ny method for beräkning av spikförband: New method of estimating the bearing strength of nailed wood connections. (in Swedish with English Translation). No. 117. Chalmers Tekniska Hogskolas Handlingar, Gothenburg, Sweden.
- Morrell, J. J., C.S. Love, R.J. Leichti, and R.J. Scott. 2000. Predicting decay rates in structures: the effects of wood moisture content on decay rate. *Proc. of Durability and Disaster Mitigation In Wood-Frame Housing*, November 2000, 6-8. Madison, WI. pp. 43-49.
- National Association of Home Builders (NAHB) Research Center. 2001. Housing durability assessment and survey data. Prepared for the U.S. Dept. of Housing and Urban Development and National Association of Home Builders. Upper Marlboro, MD. 98 pp.
- National Association of Home Builders (NAHB) Research Center. 2002. Durability by design: a guide for residential builders and designers. Prepared for the U.S. Dept. of Housing and Urban Development and National Association of Home Builders. Upper Marlboro, MD. 75 pp.
- National Evaluation Service (NES). 2000. Protocol for durability assessment of building materials and systems. NES Inc., Falls Church, VA.
- Ocloo, J.K. and F.H. Potter. 1988. Predicting slip in nailed joints loaded perpendicular to the grain – comparison of three mathematical models. *J. Institute of Wood Sci.* 11(4):135-139.
- Okkonen, E.A. and B.H. River. 1996. Outdoor aging of wood-based panels and correlation with laboratory aging: Part 2. *Forest Prod. J.* 46(3):68-74.
- Ott, R.L. and M. Longnecker. 2001. An introduction to statistical methods and data analysis, 5th ed. Brooks/Cole Publishing, New York, NY. 1152 pp.
- Pellicane, P.J. 1978. Sampling for bending strength distribution of dimension lumber. MS Thesis. Dept. of Forest and Wood Sciences, Colorado State University. Fort Collins, CO.

- Pinion, L.C. 1970. The degradation of wood by metal fastenings and fittings. Timberlab Paper No. 27-1970. Forest Products Research Laboratory, Princes Risborough, Aylesbury, Bucks, England.
- River, B.H. 1994. Outdoor aging of wood-based panels and correlation with laboratory aging. *Forest Prod. J.* 44(11/12):55-65.
- Scheffer, T.C. 1971. A climate index for estimating potential for decay in wood structures above ground. *Forest Prod. J.* 21(10):25-31.
- Sharp, D.J., S. Suddarth, and C. Beaulieu. 2000. Length effect in prefabricated wood I-joists. *Forest Prod. J.* 50(5):29-42.
- Showalter, J., P. Line, and B.K. Douglas. 1999. Calculation of lateral connection values using general dowel equations. Presentation at the ASAE/CSAE-SCGR Annual International Meeting, July 1999, 18-21. Toronto, ON, Canada.
- Siimes, F.E., P.E. Johanson, and E. Niskanen. 1954. Investigations on the ultimate embedding stress and nail holding power of finish pine. *Tiedoitus* 122. Helsinki: The State Institute for Technical Research.
- Smart, J.V. 2002. Capacity resistance and performance of single-shear bolted and nailed connections: an experimental investigation. M.S. Thesis. Virginia Polytechnic Institute and State University, Blacksburg, VA.
- Smulski, S. 1992. Wood destroying insects. *J. of Light Construction.* 10(12):35-39.
- Smulski, S. 1993. Wood Fungi, Causes and Cures. *J. of Light Construction.* 11(8):22-28.
- Stern, E.G. 1956. Nail popping, its causes and prevention. Bulletin No. 24. Virginia Polytechnic Institute and State University, Blacksburg, VA. 12 pp.
- Stockwell, K. and B. Goodell. 1990. Design and construction of a low-cost automated, accelerated field simulator used in decay and preservative evaluation. *Forest Prod. J.* 40(1):15-17.
- TenWolde, A. 2000. Mold and decay in tristate homes. *Proc. of Durability and Disaster Mitigation In Wood-Frame Housing*, November 2000, 6-8. Madison, WI. pp. 53-57.
- Trayer, G.W. 1932. The bearing strength of wood under bolts. FPL-ATB-332. U.S. Dept. of Agriculture, Forest Service. Forest Products Laboratory, Madison, WI. 40 pp.
- Verall, A. and T. Amburgey. 1975. Prevention and control of decay in homes. IAA-25-75. U.S. Government Printing Office, Washington, DC.

- Wang, S. and P.M. Winistorfer. 2003. An optical technique for determination of layer thickness swell of MDF and OSB. *Forest Prod. J.* 53(9):64-71.
- Weibull, W. 1939. A statistical theory of the strength of materials. *Proc. of the Royal Swedish Institute, Engineering Research*, No. 151. Stockholm, Sweden.
- Wilkinson, T.L. 1991. Dowel bearing strength. FPL-RP-505. U.S. Dept. of Agriculture, Forest Service. Forest Products Laboratory. Madison, WI. 9 pp.
- Winistorfer, P.M., W.C. Davis, and W.W. Moschler, Jr. 1986. A direct scanning densitometer to measure density profiles in wood composite panel products. *Forest Prod. J.* 36(11/12):82-86.
- Winistorfer, P.M., W. Xu, and R. Wimmer. 1995. Application of a drill resistance technique for density profile measurement in wood composite panels. *Forest Prod. J.* 45(6):90-93.
- Winistorfer, S.G. 1995. Practical considerations of dowel bearing strength and annular ring/fastener orientation. *Forest Prod. J.* 45(7/8):64-68.
- Woodruff, B.W., A.H. Moore, E.J. Dunne, and R. Cortes. 1983. A modified Kolmogorov-Smirnov test for Weibull distributions with unknown location and scale parameters. *Institute of Electrical and Electronics Engineers (IEEE) Transactions on Reliability*. Vol. 2. pp. 209-121
- Wozniak, P.J. and W.G. Warren. 1984. Goodness-of-fit for the two-parameter Weibull distribution. Presented as the American Statistical Association National Meeting, August 1984, 13-16. Philadelphia, PA
- Yang, V.W., W.J. Nelson, B.L. Illman, and R.J. Ross. 2000. Nondestructive evaluation of biodegraded oriented strandboard: Laboratory results. *Proc. of Durability and Disaster Mitigation In Wood-Frame Housing*, November 2000, 6-8. Madison, WI. pp. 227-230