

A Sparsification Based Algorithm for Maximum-Cardinality Bipartite Matching in Planar Graphs

Mudabir Kabir Asathulla

Thesis submitted to the Faculty of the
Virginia Polytechnic Institute and State University
in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE

in

Computer Engineering

Anil Kumar S Vullikanti, Chair

Sharath Raghvendra, Co-Chair

Haibo Zeng

July 14, 2017

Blacksburg, Virginia

Keywords: Matching, maximum cardinality, bipartite, planar graph, planar separators

Copyright 2017, Mudabir Kabir Asathulla

A Sparsification Based Algorithm for Maximum-Cardinality Bipartite Matching in Planar Graphs

Mudabir Kabir Asathulla

(ABSTRACT)

Matching is one of the most fundamental algorithmic graph problems. Many variants of matching problems have been studied on different classes of graphs, the one of specific interest to us being the *Maximum Cardinality Bipartite Matching in Planar Graphs*. In this work, we present a novel sparsification based approach for computing maximum/perfect bipartite matching in planar graphs. The overall complexity of our algorithm is $O(n^{6/5} \log^2 n)$ where n is the number of vertices in the graph, bettering the $O(n^{3/2})$ time achieved independently by Hopcroft-Karp algorithm and by Lipton & Tarjan ‘divide and conquer’ approach using planar separators. Our algorithm combines the best of both these standard algorithms along with our sparsification technique and rich planar graph properties to achieve the speed up. Our algorithm is not the fastest, with the existence of $O(n \log^3 n)$ algorithm based on max-flow reduction.

A Sparsification Based Algorithm for Maximum-Cardinality Bipartite Matching in Planar Graphs

Mudabir Kabir Asathulla

(GENERAL AUDIENCE ABSTRACT)

A matching in a graph can be defined as a subset of edges without common vertices. A matching algorithm finds a maximum set of such vertex-disjoint edges. Many real life resource allocation problems can be solved efficiently by modelling them as a matching problem. While many variants of matching problems have been studied on different classes of graphs, the simplest and the most popular among them is the *Maximum Cardinality Bipartite Matching* problem. Bipartite matching arises in varied applications like matching applicants to job openings, matching ads to user queries, matching threads to tasks in OS scheduler, matching protein sequences based on their structures and so on.

In this work, we present an efficient algorithm for computing maximum cardinality bipartite matching in planar graphs. Planar graphs are sparse graphs and have interesting structural properties which allow us to design faster algorithms in planar setting for problems that are otherwise considered hard in arbitrary graphs. We use a new sparsification based approach where we maintain a compact and accurate representation of the original graph with a lesser number of vertices. Our algorithm combines the features of the best known bipartite matching algorithm for an arbitrary graph with the novel sparsification approach to achieve the speedup.

*To my beloved family,
Mom, Dad and Brother,
Thanks for endless love, support and sacrifices.*

Acknowledgments

I would like to express my gratitude to my advisor, Dr. Sharath Raghvendra for his exemplary guidance throughout my research work. His enthusiasm for algorithms is very contagious and the brainstorming sessions with him were highly rewarding. His expertise in the field greatly helped me validate my ideas and to stay on track. He was also easy to approach and made himself available for quick meetings and discussions, even on weekends. This enabled me to finish this work in a timely fashion. His attention to details helped me address any inconsistencies in my thesis write up, improving its quality immensely.

My sincere thanks to Dr. Anil Vullikanti for agreeing to chair my thesis committee and for taking the time to handle my graduate school paperwork and other administrative issues.

I am grateful to both Dr. Anil Vullikanti and Dr. Haibo Zeng for carefully reviewing my thesis and providing valuable feedback.

Apart from my committee members, I would like to thank my lab mate Nathaniel Lahn for all the enriching white board discussions. I am also grateful for the support and motivation that I received from my family and friends.

Contents

1	Introduction	1
1.1	Preliminaries	3
1.2	Previous Work	4
1.3	Our Contributions	7
1.4	Thesis Outline	9
2	Algorithmic Toolbox	10
2.1	Hopcroft Karp Algorithm Revisited	10
2.2	Planar Separator Theorem	13
2.3	Lipton-Tarjan Divide and Conquer Algorithm	15
2.4	r-division of Planar Graphs	16
2.5	Dense Distance Graphs	18

2.5.1	Monge property in Planar Graphs	19
2.5.2	Bipartite Monge Groups	20
2.5.3	Efficient Dijkstra Search in Dense Distance Graphs	23
2.5.4	Construction of DDG	25
3	New Matching Algorithm	27
3.1	Convention for Notation	28
3.2	Preprocessing	29
3.3	Compressed Residual Graph H	30
3.4	Projection and Lifting	34
3.4.1	Projecting a path.	34
3.4.2	Lifting a path.	35
3.5	Merge Algorithm	37
3.6	Proof of Correctness	40
3.6.1	Proof of Invariant	51
3.7	Algorithm Efficiency	53
3.7.1	Efficiency of BFS, FINDAUGPATH and AUGMENT procedures . . .	54
3.8	Hopcroft-Karp Equivalence of Our Algorithm	57

4	Improved Merge Algorithm	58
4.1	Choice of r	59
4.2	Faster BFS	61
4.2.1	Algorithm Overview	61
4.2.2	Algorithm Implementation	62
4.2.3	Analysis of FastBFS	65
4.3	Faster DFS	65
4.3.1	Algorithm Overview	66
4.3.2	Interval Construction	68
4.3.3	Range search tree	70
4.3.4	Algorithm Implementation	71
4.3.5	Analysis of FastDFS	74
4.4	Alternate BFS	74
5	Conclusion and Future Work	77
	List of Notations	80
	Bibliography	83

List of Figures

1.1	Bipartite Graph and its Residual Graph	3
2.1	Graph with partial matching and its layered graph	12
2.2	Planar Separation	14
2.3	Monge Crossing property for distances	19
2.4	Successive Bipartite Monge Decomposition	21
2.5	Intervals before and after vertex x_8 is activated	23
3.1	A path in G_M is lifted to H . An edge in H is projected to shortest path in G_M . 35	
3.2	Vertex disjoint paths in G (shown in red) have disjoint boundary vertices in H 37	
3.3	$L(u)$ and $L(v')$ can only increase or remain same after augmentation.	43
3.4	If z is marked visited by partial DFS from b_1 , P_1 is found before P_2	48
3.5	If $S(u)$ remains same after augmentation, v has to be of type A	50

3.6	Projection of 2 edges of augmenting path in H cannot intersect in G	52
4.1	(a) Single overlap, (b) two overlapping intervals, (c) No overlap	69
4.2	Monge Crossing Property for Connectivity	69
4.3	2-D Range Search Tree returns a vertex with specific layer number in the given interval	70

Chapter 1

Introduction

Matching theory is a widely studied area since the beginning of the twentieth century and has applications spanning diverse fields involving large scale resource allocation. Some of the classic examples of matching as stated in the survey by Gerards [14] are *the assignment problem*, *The oil well drilling problem* [6], *plotting street maps* ([17],[16]) and *scheduling* [13]. Matching problems also hold significance in the field of algorithms for several reasons that transcend their practical applications. Edmonds & Johnson [7] state that the matching problems can be positioned between the 'easier' problems like network flows and the hard (NP-hard) problems like general integer linear programming. Cunningham & Marsh [5] state that "Optimum matching problems constitute the only class of genuine integer programs for which a good solution is known". Owing to the significance of matching, hundreds of algorithms have been developed till date and there are still many open problems in this area.

Matching can be defined as dividing a collection of objects into pairs. Formally, matching M in an undirected graph G with node set V and edge set E can be defined as a subset of edges in E such that no two edges are incident to a common vertex. If all the vertices in V have a pairing in M , we call M a *perfect matching*. A matching problem consists of the graph G and the edge weights w . The *Maximum Cardinality Matching* problem is an easier problem with unit edge weights. Besides its own applications, maximum cardinality matching is often used as a subroutine for solving weighted matching problem, thus making it a compelling problem to study. If the graph G is bipartite, which is the case in many practical applications, we call it *bipartite matching*.

In our work, we present an algorithm to find maximum cardinality bipartite matching in a specific class of graphs called *planar graphs*. A planar graph is a graph that can be drawn on a plane such that edges don't cross each other and intersect only at their endpoints. A planar graph with n vertices and m edges obeys the property that if $n \geq 3$, then $m \leq 3n - 6$ and if there are no cycles of length 3, $m \leq 2n - 4$. In other words, planar graphs are sparse. Owing to the simplicity of their structure, planar graphs permit some algorithmic problems to be solved more efficiently than arbitrary graphs. For example, Max-cut is an NP-Complete problem for arbitrary graphs but has a polynomial time solution in the planar setting. In addition to being structurally simple, planar graphs are encountered in many real life situations like electronic circuit layouts, image processing, building construction plans, traffic maps etc., serving as a motivation to design faster algorithms specific to planar graphs.

1.1 Preliminaries

In this section, we will introduce some basic notations and definitions related to maximum cardinality bipartite matching henceforth referred to as bipartite matching.




Figure 1.1: Bipartite Graph and its Residual Graph

Consider a bipartite graph $G(A \cup B, E)$ with two disjoint vertex sets A and B and edges E between them as shown in Figure 1.1. The thick edges are part of partial matching M while other edges are not in the matching. The graph on the right is the *residual graph* G_M where all edges in the matching ($E \cap M$) are directed from $a \rightarrow b$ and all the other edges that are not in the matching are directed from $b \rightarrow a$. The residual graph is widely used for computing flows in a network. Bipartite matching is a special instance of network flow and G_M is the residual graph for this instance. Given a partial matching M , we define the *alternating path* as any path in the graph G which alternates between edges in the matching ($E \cap M$) and edges that are not in the matching ($E \setminus M$). It is easy to see that any directed

path in G_M is an alternating path in G . Similarly, an *alternating cycle* can be defined. An alternating path P between two free (unmatched) vertices is called an *augmenting path*. We can *augment* the matching M by one edge along P if we remove the edges of $P \cap M$ from M and add edges of $P \setminus M$ to M . After augmentation, the new matching is given by $M \leftarrow M \oplus P$, where $\oplus$ is the symmetric difference operator. BFS/DFS can be used to find an augmenting path in the residual graph and each augmentation increases the size of the matching $|M|$ by 1. Most matching algorithms start with an empty matching and iteratively augment the matching until a maximum matching is reached. When there are no augmenting paths left in the residual graph, the matching is said to be *maximum matching*. We state an important property of augmenting paths which was proved by Berge [1].

Theorem 1.1.1. *A matching M in a graph G is a maximum matching if and only if there is no augmenting path with respect to M in G .*

1.2 Previous Work

Major breakthroughs in bipartite matching began in the mid 50's. Ford and Fulkerson came up with the first polynomial time algorithm [11] for maximum flow problem in a single-source, single-sink flow network. In 1962, Ford and Fulkerson showed in their book [12] that maximum cardinality bipartite matching problem in an arbitrary graph can be reduced to a maximum flow problem in a single-source, single-sink flow network. Given a bipartite graph $G(A \cup B, E)$ and its residual graph G_M , we can construct a flow network $G'(s, t, c)$

from G_M by introducing a source vertex s and a sink vertex t and adding directed edges from s to all vertices of type B and also from all vertices of type A to t . The resulting flow network has unit edge capacities ($c = 1$). Ford and Fulkerson showed that maximum flow f in G' is equal to the size of the maximum matching $|M|$ in G and that max-flow residual graph of G' can be used to reconstruct maximum matching M in G .

Given a bipartite graph G with m edges and n vertices, Ford-Fulkerson algorithm runs $O(n)$ iterations of DFS where each DFS operation finds one augmenting path and has a run time of $O(m)$. Thus, the overall run time of the algorithm is $O(mn)$. Edmond and Karp's max-flow algorithm [8] and few other max-flow algorithms developed later could also solve the bipartite matching by reducing it to network flow problem. Their complexity for computing maximum matching is also $O(mn)$.

Hopcroft-Karp algorithm [15] introduced in 70's with a running time of $O(m\sqrt{n})$ remains the best combinatorial algorithm (based on augmenting paths) for bipartite matching in arbitrary graphs till date. It improves upon Ford-Fulkerson algorithm by finding a maximal set of vertex-disjoint shortest length augmenting paths in each iteration instead of just one augmenting path per iteration. Hopcroft-Karp algorithm uses a combination of BFS and DFS to find maximal set of augmenting paths in each iteration and it requires $O(\sqrt{n})$ iterations (section 2.1) to compute maximum matching.

In 2004, Mucha and Sankowski presented a randomized algorithm based on fast matrix multiplication [27] which gives $O(n^\omega)$ complexity ($\omega = 2.376$) for maximum cardinality matching in both bipartite and general graphs. This algorithm uses a Gaussian elimination approach and has the best run time in arbitrary graph settings till date.

Since planar graphs are sparse with m being $O(n)$, the complexities of Ford-Fulkerson algorithm and Hopcroft-Karp algorithm in planar graph setting become $O(n^2)$ and $O(n^{3/2})$ respectively. Mucha and Sankowski also came up with an improved randomized algorithm in planar setting [28] with $O(n^{\omega/2})$ time complexity. Just like their algorithm for arbitrary graphs [27], this algorithm again works for both bipartite and general matching and is based on Gaussian elimination approach.

Lipton and Tarjan's planar separator theorem [23] paved way to devise 'divide and conquer' algorithms [24] for planar graphs. Planar separator theorem states that by removing $O(\sqrt{n})$ vertices (*separator vertices*) from a n -vertex planar graph, we can partition the graph into two edge disjoint sub-graphs each with at most $\frac{2n}{3}$ vertices. Given the maximum matching in each sub-graph, the maximum matching in the original graph is computed by introducing the $O(\sqrt{n})$ separator vertices. Using Ford-Fulkerson algorithm in the *conquer* step of the divide and conquer approach, we can find maximum matching in $O(n^{3/2})$ time (section 2.3) which is the same complexity as Hopcroft-Karp algorithm.

Klein et al. [20] were able to give $O(n^{4/3} \log n)$ time algorithm for finding a maximum matching in bipartite planar graphs using the reduction of maximum flow with multiple sources and sinks to a single source shortest paths problem. In 2012, Borradaile et al. [4] came up with $O(n \log^3 n)$ time algorithm for the max-flow with multiple sources and sinks (single-source and sink reduction does not preserve planarity), thus also providing the first near linear time solution for finding a maximum matching in bipartite planar graphs.

1.3 Our Contributions

We present a new sparsification based approach to find a maximum matching in planar bipartite graphs. Our algorithm finds a maximal set of vertex-disjoint shortest length augmenting paths similar to Hopcroft-Karp algorithm and uses a ‘divide and conquer’ approach similar to Lipton-Tarjan algorithm. By combining these features and by exploiting planar graph properties, our algorithm performs faster than either of the above matching algorithms which take $O(n^{3/2})$ time individually.

It is known that we can use planar separators to partition an n -vertex planar graph G into $O(n/r)$ edge disjoint pieces, each of size $O(r)$ where $r < n$. This decomposition is referred to as r -division ([10],[22]). In addition, r -division (section 2.4) guarantees that each piece has only $O(\sqrt{r})$ vertices that participate in other pieces and such vertices are called boundary vertices. Therefore, in total, there are $O(n/\sqrt{r})$ boundary vertices.

We use Lipton-Tarjan ‘divide and conquer’ approach in our algorithm (section 2.3). At the beginning of the conquer/merge step of our algorithm, we are left with $O(\sqrt{n})$ augmenting paths. As a part of pre-processing in our merge algorithm, we perform r -division of our graph G and then find maximum matching in each each piece of G by running the Ford-Fulkerson algorithm in each piece. From the resulting residual graph G_M , we construct a compressed residual graph H from the boundary vertices of our r -division and unmatched internal vertices (not a boundary vertex) of each piece. H has $O(n/\sqrt{r})$ vertices and $O(n)$ edges as we will see in Section 3.3. After constructing H , we run a Hopcroft-Karp style algorithm on H instead of actual graph G to obtain the speed up.

Using fast implementations of BFS and DFS, we are able to speed up each iteration of our algorithm. We also reduce the number of iterations from $O(\sqrt{n})$ to $O(\sqrt{n}/r^{1/4})$ which is in the order of square root of number of vertices in H or number of boundary vertices in G , thus making the algorithm terminate faster. However, we cannot sparsify our graph beyond a limit as choosing a large value for r would increase the number of vertices in each region of r -division. After each augmentation, the residual graph G_M changes and as result, the compressed residual graph H changes. We need to reconstruct the edges of H in all the pieces that contributed an edge to the augmenting path. Total time spent in reconstructing H throughout the algorithm is directly proportional to $O(n\sqrt{r})$ as we will see in Chapter 3. By carefully choosing r to balance both competing factors namely (BFS + DFS + Number of iterations) and (reconstruction of H), we come up with $\tilde{O}(n^{6/5})$ time algorithm (Chapter 4).

The $\sim$ above O represents $\text{poly}(\log)$ term. Though our algorithm is not the fastest ([4],[28]), the sparsification approach for bipartite matching is novel and may potentially be extended to other matching problems in planar and non-planar graphs.

1.4 Thesis Outline

The rest of the thesis is organized as follows: We introduce the background, notations, and describe planar graph oracles/data structures used in the construction of compressed residual graph and for fast implementations of BFS/DFS in Chapter 2. We introduce our algorithm in Chapter 3 and we present the details of a simpler version of our algorithm which runs in $\tilde{O}(n^{4/3})$ time. Chapter 3 also covers the proof of correctness of our algorithm. At the end of the chapter, we highlight the similarity of our algorithm with the Hopcroft-Karp algorithm. In Chapter 4, we describe the faster BFS implementation in planar graphs which helps speed up the algorithm to $\tilde{O}(n^{5/4})$. We also describe a faster DFS technique which when combined with faster BFS implementation along with the right selection of r for r -division yields $\tilde{O}(n^{6/5})$ time complexity. We conclude and state future work in Chapter 5.

Chapter 2

Algorithmic Toolbox

In this chapter, we introduce advanced data structures and algorithms that we will use in our algorithm. We give an overview of the Hopcroft-Karp algorithm and Lipton-Tarjan divide and conquer algorithm. We then provide details of r -division and *Dense Distance Graphs* which are used for construction of a compressed residual graph H and for realizing faster implementations of the BFS and DFS in our algorithm.

2.1 Hopcroft Karp Algorithm Revisited

Our algorithm builds on top of the Hopcroft-Karp Algorithm [15] and we provide a summary of the Hopcroft-Karp algorithm in this section. Introduced in 1973, this algorithm outperforms previous methods such as Edmonds [8] and Ford-Fulkerson algorithm [12] by finding a maximal set of shortest length vertex disjoint augmenting paths instead of just

a single augmenting path per iteration. The pseudo code for Hopcroft-Karp Algorithm is shown in Algorithm 1.

Algorithm 1 Hopcroft Karp algorithm

```

1: procedure MAXIMUMMATCHING( $G(A \cup B, E)$ )
2:    $M \leftarrow \emptyset$ 
3:   while Augmenting Path Exists do ▷ Berge theorem 1.1.1
4:      $l \leftarrow$  length of shortest augmenting path
5:      $P \leftarrow \{P_1, P_2, \dots, P_k\}$  ▷  $|P_i| = l$ ,  $P$  is vertex disjoint
6:      $M \leftarrow M \oplus (P_1 \cup P_2 \dots \cup P_k)$ 
7:   return  $M$  ▷ Maximum Matching

```

The shortest augmenting paths $\{P_1, P_2, \dots, P_k\}$ are found using a combination of *breadth-first search* (BFS) and *depth-first-search* (DFS). Starting from free vertices of type B in a partial matching, we perform BFS to construct a *layered graph*. During the BFS search, each vertex being explored for the first time is added to the layered graph and is assigned a layer number indicating the length of the shortest path to that vertex from some free vertex of type B . Free vertices of type B have layer number 0. Layered graph comprises of free vertices of type B and all vertices which are reachable from any free vertex of type B with a distance less than or equal to the length of the shortest augmenting path. The BFS search terminates at the first layer where a free vertex of type A is found or when all the vertices have been added. After constructing the layered graph, DFS is done to find a maximal set of augmenting paths and the algorithm increases the matching by one after augmenting each path.

The graph on the left in Figure 2.1 represents a partial matching with matched vertices shown uncolored and matched edges shown as thick lines. The layered graph for this partial




Figure 2.1: Graph with partial matching and its layered graph

matching is shown in right side of Figure 2.1. The layered graph contains free vertices in the first and the last layers. All the vertices in the same column have the same layer number. Solid edges represent edges contributing to a maximal set of vertex disjoint augmenting paths while dashed edges are not part of a maximal set of augmenting paths in this iteration. BFS and DFS is repeated in each iteration till no augmenting paths are found.

Given a bipartite graph G with n vertices and m edges, Hopcroft-Karp algorithm takes $O(m)$ time for BFS and DFS and as a consequence of finding maximal set of shortest length augmenting paths every iteration, the authors show that only $O(\sqrt{n})$ iterations are needed for the algorithm to terminate.

Lemma 1. *The Hopcroft-Karp Algorithm runs in $O(m\sqrt{n})$ time.*

Proof. We prove this lemma using the property of Hopcroft-Karp algorithm that the length of the augmenting path strictly increases every iteration. Since any augmenting path is always of odd length, the length increases by at least 2 after each iteration. After $\sqrt{n}$ iterations, if the maximum matching is not found yet, the length of the shortest augmenting path is $\geq 2\sqrt{n} + 1$. Let M be the current matching and M^* be the maximum matching. $M^* \oplus M$ contains $|M^*| - |M|$ vertex-disjoint augmenting paths. Since each of these vertex disjoint augmenting paths is at least $2\sqrt{n} + 1$ in length, it implies that the number of augmenting paths remaining in $M^* \oplus M$ is $\leq \sqrt{n}/2$ as the total number of vertices is n . After first $\sqrt{n}$ iterations, even if only one augmenting path is found in each successive iteration, we can still find a maximum matching in $O(\sqrt{n})$ iterations. ■

Thus, the overall time complexity is $O(m\sqrt{n})$. In planar graphs, this comes to $O(n^{3/2})$. Hopcroft and Karp also showed that the total length of all augmenting paths found by the algorithm can be bounded by $O(n \log n)$. We use this idea to bound the total length of all augmenting paths in the compressed residual graph on which we run a modified version of Hopcroft-Karp algorithm.

2.2 Planar Separator Theorem

Lipton and Tarjan showed in [23] that a n -vertex planar graph can be divided into disjoint components of roughly equal size by removing a small set of vertices. Formally, Planar

Separator theorem can be stated as follows: Given a planar graph G with n vertices, there exists a partition of vertices of G into G_1 , G_2 and S such that

- $|G_1|, |G_2| \leq 2n/3$.
- $|S| \leq c\sqrt{n}$ where c is a constant.
- G_1 and G_2 are edge disjoint.




Figure 2.2: Planar Separation

Cycle Separator Extending Lipton-Tarjan's technique for finding separators, Miller [26] showed that it is possible to construct separators in planar graphs which are in the form of a cycle of small length ($O(\sqrt{n})$) such that the inside and the outside of the cycle each have at most $2n/3$ vertices. Cycle separator is also referred to as *Miller Separator*.

2.3 Lipton-Tarjan Divide and Conquer Algorithm

As one of many applications of planar separator theorem [24], Lipton and Tarjan showed that maximum cardinality matching problem in planar graphs can be solved efficiently in a divide and conquer fashion using planar separators. A planar separator can be used to subdivide the matching problem into two sub-problems, each of size at most $\frac{2n}{3}$. Maximum matching in each sub-problem is computed using a divide and conquer approach. When the sub-problem size becomes a small constant, we use Ford-Fulkerson algorithm to solve the sub-problem. Given the maximum matching for two sub-problems, the maximum matching for the current problem is computed in the merge step by introducing the boundary vertices. For ease of explanation, we will consider the merge step at the top most level of divide and conquer decomposition throughout this document in all chapters, unless stated otherwise. The same description for merge operation can be carried over to any sub-graph in the divide and conquer tree. The recurrence relation for this divide and conquer algorithm can be written as

$$T(n) = T(\alpha n) + T((1 - \alpha)n) + g(n)$$

where $\frac{1}{3} \leq \alpha \leq \frac{2}{3}$ and $g(n)$ is the merge time.

Consider a bipartite graph $G(A \cup B, E)$ divided by planar separators into sub-graphs X and Y by removal of a set of boundary vertices, S . Before the merge step, we recursively find a maximum matching in X and Y which imply that the residual graphs X_M and Y_M

have no augmenting paths. During the merge step, we compute a maximum matching M^* in G . The symmetric difference of the current matching $M(X) \cup M(Y)$ with the maximum matching M^* gives us a set of vertex-disjoint augmenting paths each passing through at least one vertex in S . This implies that $|M^*| - (|M(X)| + |M(Y)|) \leq |S|$ or in other words, the number of remaining augmenting paths in G is $O(\sqrt{n})$.

Lemma 2. *Number of augmenting paths remaining in G at the start of the merge step of Lipton-Tarjan Divide and Conquer algorithm is $O(\sqrt{n})$.*

Lipton and Tarjan showed that using Ford-Fulkerson algorithm to find one augmenting path at a time in merge step gives $g(n) = O(n^{3/2})$. The overall complexity of the recurrence relation above is dominated by merge time when $g(n)$ is $\tilde{O}(n^c)$ where $c > 1$. In such a case, the complexity of the algorithm is given by $g(n)$. Thus the overall complexity of Lipton-Tarjan algorithm for maximum cardinality matching is $O(n^{3/2})$.

2.4 r-division of Planar Graphs

Frederickson [10] showed that the planar separator theorem of Lipton and Tarjan [23] can be used to obtain an *r-division* of a planar graph G with n vertices, which is the division of G into $O(n/r)$ edge disjoint sub-graphs called *regions*, each with $O(r)$ vertices and $O(r)$ edges.

Let $\{R_1(V_1, E_1), \dots, R_l(V_l, E_l)\}$ be the disjoint regions obtained by *r-division* of $G(A \cup B, E)$ where l is $O(n/r)$. A vertex which is shared among two or more regions is a *boundary vertex*.

For a partition R_j , let $\mathcal{K}_j$ denote its set of boundary vertices. A vertex that belongs to just one region is called an *internal vertex* of that region. The division ensures that every edge of G is in exactly one region R_j . Specifically, the r -division $\{R_1(V_1, E_1), \dots, R_l(V_l, E_l)\}$ has the following properties:

- $\bigcup_j V_j = A \cup B$ and $E_j = \{(a, b) \mid (a, b) \in E, a, b \in V_j\}$. If vertices a, b are common boundary vertices in multiple regions, include the edge (a, b) in only one of the regions.
- $|V_j| = O(r)$ and $|\mathcal{K}_j| = O(\sqrt{r})$
- There are $O(n/r)$ partitions and $O(n/\sqrt{r})$ boundary vertices after r -division of G .
- All boundary vertices in a region R_j lie in constant number of faces in planar embedding of R_j (also called *holes*)

Like most algorithms which require cyclic ordering of boundary vertices in each region, we use Miller's cycle separator theorem [26] for the recursive decomposition (r -division). Fakcharoenphol and Rao [9] presented an $O(n \log n)$ time recursive decomposition using Miller's separator where each region has a constant number of holes. *Holes* of a region R are the bounded faces of R introduced by the cycle separators and are not faces of original graph G . Constant number of holes in each region is a necessity for our $\tilde{O}(n^{5/4})$ and $\tilde{O}(n^{6/5})$ algorithm as we will see in Chapter 4. Our $\tilde{O}(n^{4/3})$ algorithm is however immune to number of holes in each region.

2.5 Dense Distance Graphs

We use *dense distance graph* to answer connectivity queries between boundary vertices of a region (piece of r -division) for construction of edges of H . We maintain one DDG (D_j) for each region (R_j) of a r -division of G . The union $\bigcup_j D_j$ is called the DDG of entire graph G (with respect to that r -division).

D_j contains only the boundary vertices of R_j . D_j includes a directed edge from one boundary vertex u to another boundary vertex v in R_j if there is a directed path from u to v through edges within R_j^M (residual graph of R_j). The edge also carries a weight representing the shortest path length from u to v within R_j^M . Since there are $O(r)$ pairs of boundary vertices in D_j , it could have $O(r)$ edges. We can ignore the edge weights if we are only interested in the connectivity.

Before we go into the details of construction of DDG, we introduce the Monge property in Section 2.5.1 which is satisfied by all shortest length paths between boundary vertices in planar graphs. We provide high-level details of decomposition of DDG into bipartite Monge groups and the operations that can be performed on these groups using an associated data structures called Monge heaps. We also give an overview of implementing Dijkstra's algorithm using Monge heaps (FR-Dijkstra) that is in turn used to construct DDGs in divide and conquer fashion. For detailed analysis, refer [9], [19]. Some of the ideas in this section are borrowed for faster implementations of BFS and DFS which are described in Chapter 4.

2.5.1 Monge property in Planar Graphs

Given ordered sets of boundary vertices X and Y , we can define *Monge property* for shortest distances d between pairs of elements in X and Y as follows: The sum of the shortest distances when the pairs do not cross is at most the sum when the pairs cross. Consider




Figure 2.3: Monge Crossing property for distances

Figure 2.3 where $u, v \in X$, and $x, y \in Y$, order wise $u \leq v$ and $x \leq y$, then

$$d(u, x) + d(v, y) \leq d(u, y) + d(v, x)$$

. As a direct consequence of this, we can see that the shortest paths do not cross in a Bipartite group i.e. if $d(v, x) \leq d(u, x)$, then $d(u, y)$ has to be greater than or equal to $d(v, y)$ to satisfy the Monge inequality. Otherwise, we arrive at a contradiction (see Figure 2.3 (b)). Since the paths from $v \rightarrow x$ and $u \rightarrow x$ intersect at w and $d(v, x)$ is shorter than $d(u, x)$ by

our assumption, it also implies that $v \rightarrow w$ is shorter than $u \rightarrow w$. Thus, it is clear that $d(v, y) \leq d(u, y)$ if $d(v, x) \leq d(u, x)$. This is also called the *non-crossing* property.

2.5.2 Bipartite Monge Groups

To perform Dijkstra faster, the dense distance graph is decomposed into bipartite graphs. We know that in any dense distance graph, we can ensure that the boundary vertices lie in constant number of faces (holes) and have a cyclic ordering in the face they belong to. For the sake of simplicity, we will consider that the boundary vertices are in only one face and we can find a planar embedding such that the face becomes the infinite face. (Refer section 5 of [9] for handling constant number of holes). We split the boundary vertices into approximately two equal halves X and Y creating a *complete* bipartite graph on X and Y with edges going from X to Y . Using the same vertices, we define another bipartite graph with edges going from Y to X . The edges in the bipartite graph obey the Monge property i.e. the shortest paths do not cross. Therefore, every vertex x in X has a contiguous interval of vertices in Y , say I_x which have the shortest distance from x amongst all the vertices in X . We continue dividing X and Y into almost equal halves successively (see Figure 2.4) and end up with at most $O(k)$ bipartite groups for the piece, k being the number of boundary vertices in the piece. For a region R_j obtained from r -division, where k is $O(\sqrt{r})$, we have $O(\sqrt{r})$ bipartite Monge graphs with each boundary vertex in at most $O(\log r)$ groups and each edge in exactly one of the groups.





Figure 2.4: Successive Bipartite Monge Decomposition

We maintain a data structure for each Monge group which we call the Monge heap. We will use (X, Y) to represent both bipartite Monge group and Monge heap depending on the context used and where differentiation is needed, we use $\mathcal{M}(X, Y)$ to represent Monge heaps. The nodes on the left of Monge group have labels associated with them and the label of a vertex v on the right is given by $\delta(v) = \min_{u \in X} \{\delta(u) + w(u, v)\}$ where $w(u, v)$ is the weight of the edge from u to v in the DDG which is also the shortest path from u to v in the region R_j corresponding to the DDG that the Monge array is part of. When there is no edge from vertex u to v in DDG, it implies that there is no path from u to v in the the corresponding region of the original graph. In the Monge groups, we add an infinite weight edge from u to v when there is no path from u to v . Therefore, the bipartite Monge groups are complete on the node set $X \cup Y$.

Online bipartite Monge Search Before diving into FR-Dijkstra, we describe this important subroutine of FR-Dijkstra on DDGs. In every Monge groups, we maintain a set of

active nodes $A^* \subseteq X$, representing the frontier of Dijkstra search and set of *matched nodes* $M \subseteq Y$ representing nodes whose Dijkstra shortest path parent has been discovered. Each Monge heap supports three operations.

- **FINDMIN**: Returns minimum unmatched node $y \in Y \setminus M$ from the heap. ($O(1)$ time)
- **EXTRACTMIN**: Adds the current minimum y to M . For its parent $x \in A^*$, the interval $[i_-(x), i_+(x)]$ containing y is split into $[i_-(x), y)$ and $(y, i_+(x)]$ and the shortest edges (found using Least Common Ancestor/Range Minimum Query data structure) in these intervals are added to the heap. Instead of maintaining multiple intervals per vertex $x \in X$, whenever we split intervals, we can also replace x with two dummy nodes x' and x'' . One extra node is created in X whenever a node in Y is matched. This entire operation runs in $O(\log(|X| + |Y|))$ time.
- **ACTIVATE**($x_i, \delta(x_i)$): x_i is activated in all the bipartite groups where it occurs on X (left-hand side). Its interval in Y , I_{x_i} is computed and other intervals are adjusted and the heap is updated. If the vertex x_i is first to be activated in the group, its interval is whole of Y . Otherwise, walk up in A^* until first x_k whose $d(x_k, i_-(x_k)) < d(x_i, i_-(x_k))$. Do a binary search for $i_-(x_i)$ in the range $[i_-(x_k), i_+(x_k))$. Similarly, $i_+(x_i)$ can be found by walking down in A^* . After computing I_{x_i} , for nodes between x_i and x_k , all their intervals become empty and their corresponding min in $Y \setminus M$ are removed from the heap. Do the same for nodes whose intervals are affected by walking down. New min for x_k and for the corresponding node while walking down are updated in the heap.

Figure 2.5: Intervals before and after vertex x_8 is activated

ACTIVATE has an amortized run time $O(\log(|X| + |Y|))$ per operation. Figure 2.5 illustrates interval adjustment when vertex x_8 is activated. Note that y_3 and y_9 are not in any intervals implying that they have already been matched.

2.5.3 Efficient Dijkstra Search in Dense Distance Graphs

FR- Dijkstra is an efficient Dijkstra implementation on Dense distance graphs due to Fackcharoenphol and Rao. FR-Dijkstra algorithm constructs a single source shortest path tree on the vertices of the DDG (boundary vertices of the original graph) with some boundary

vertex as source in time proportional to number of vertices in DDG while the traditional Dijkstra algorithm runs in time proportional to the number of edges in the DDG.

By combining DDGs of all regions of r -division, we can perform FR-Dijkstra on the boundary vertices of the entire graph. The run time is proportional to $O(n/\sqrt{r})$ (the total number of boundary vertices) instead of $O(n)$ which is the number of edges between boundary vertices across all DDGs.

Each DDG is decomposed into bipartite monge groups. In addition to a heap for each bipartite group, FR-Dijkstra algorithm uses a global heap $\mathcal{Q}$ having vertices with smallest labels from each bipartite Monge group instance (X_i, Y_i) . In each iteration, a vertex v having smallest label in $\mathcal{Q}$ is extracted and the Monge heap (X, Y) that contributed v updates its new smallest vertex to the global heap $\mathcal{Q}$ after adding v to M . Since a vertex can be in $O(\log r)$ bipartite groups in every region of r -division that it is part of, it may be extracted from $\mathcal{Q}$ multiple times with different labels from different local Monge heaps belonging to different regions. However, its Dijkstra distance is fixed the first time it is extracted. After a vertex v is extracted for the first time, it is added to the Dijkstra search frontier using **ACTIVATE** which adds v to A^* and updates all the Monge heaps containing vertex v in X and their representatives in $\mathcal{Q}$.

Run time of FR-Dijkstra is bounded by the number of calls to **FINDMIN**, **EXTRACTMIN** and **ACTIVATE**. **EXTRACTMIN** and **ACTIVATE** are called at most once per vertex in

each Monge heap and FINDMIN is called whenever EXTRACTMIN or ACTIVATE is called. In region R_j , its DDG (D_j) has each boundary vertex appearing in $O(\log r)$ Monge heaps and this bounds the total number of operations to $O(\sqrt{r} \log r)$ per region. Each operation takes at most $O(\log r)$. Therefore FR-Dijkstra takes $O(\sqrt{r} \log^2 r)$ time per region R_j or $O((n/\sqrt{r}) \log^2 n)$ time in the entire graph.

We use FR-Dijkstra with slight changes to do BFS on compressed residual graph H in Chapter 4. Theoretically, BFS is just Dijkstra's algorithm with unit edge costs. We reserve the pseudo code for Chapter 4. We also modify FR-Dijkstra to do FastDFS on H in Chapter 4.

2.5.4 Construction of DDG

Dense distance graph D_j of a region R_j is constructed in a divide and conquer approach. The sub-graph R_j is recursively divided into smaller pieces using cyclic planar separators forming a decomposition tree. A boundary vertex in level i of decomposition is also a boundary vertex in level $i + 1$ sub-piece. In addition to that, decomposition of level i piece to form level $i + 1$ sub-pieces can introduce new boundary vertices in each of the level $i + 1$ sub-pieces. The dense distance graph for the parent at level i of decomposition is constructed from the dense distance graphs of its children at level $i + 1$. This is possible through FR-Dijkstra routine which runs in time proportional to number of boundary vertices in both the children which is $O(\sqrt{v})$ more the number of boundary vertices in the parent, v

being the number of vertices in the parent. Fakcharoenphol and Rao [cf section 5, [9]] also proposed a 3-level decomposition which ensures an exponential decrease in number of total vertices and boundary vertices for every 3 levels of decomposition and restricts the count of holes in every piece of decomposition tree to not exceed a constant value.

Computing the shortest path tree from each boundary vertex using FR-Dijkstra takes $O(\sqrt{r} \log^2 r)$ time. We invoke FR-Dijkstra for all boundary vertices. Therefore the total time taken for all Dijkstra computations is $O(\sqrt{r} \sqrt{r} \log^2 r) = O(r \log^2 r)$. Since there are $O(\log r)$ levels in the recursive decomposition, the overall time to compute dense distance graph per region takes time $O(r \log^3 r)$. The query time to check for connectivity from vertex $u \rightarrow v$ takes $O(\log r)$ time. Data structures with better construction time and query time exist for creation of dense distance graph to answer connectivity queries. Klein's multiple source shortest path data structure [21] has a construction time of $O(r \log r)$ per region and query time of $O(\log r)$. Thorup's data structure [29] has a $O(r \log r)$ construction time and can answer connectivity queries in constant time.

Chapter 3

New Matching Algorithm

Our algorithm adapts Lipton-Tarjan's divide and conquer technique as described in Section 2.3. We improve the merge time $g(n)$ from $O(n^{3/2})$ to $O(n^{6/5} \log^2 n)$ by exploiting planar graph properties. We first present the details of a simpler version of our merge algorithm which has a run time of $\tilde{O}(n^{4/3})$. We also provide proof of correctness and run-time analysis. We conclude this chapter by stating the similarity between our merge algorithm and Hopcroft-Karp algorithm.

Algorithm Organization We begin by describing two operations that are performed at the beginning of our merge algorithm namely

- Preprocessing (Section 3.2)
- Construction of Compressed Residual Graph H (Section 3.3)

We then perform a Hopcroft-Karp style algorithm on H to compute maximum matching in G . The details of the Hopcroft-Karp style algorithm is provided in Section 3.5.

3.1 Convention for Notation

We are given a bipartite graph G . We refer to its residual graph as G_M . The vertex and edge sets of G and G_M are identical (except for the directions) and a matching, alternating path or an alternating cycle in G is also a matching, alternating path or an alternating cycle in G_M . If P is a subset of edges in G , we will also use P to denote the same subset of edges in G_M , the directions of the edges being determined by whether or not an edge is in M . We know that r -division partitions the edges of G into regions $\bigcup_j R_j$. Since G and G_M have the same underlying set of edges, we use R_j to also represent regions of G_M . Dense distance graph D_j corresponding to each region R_j is constructed from boundary vertices of R_j . We use $\mathcal{K}_j$ to represent boundary vertices of both R_j and D_j .

H is a compressed residual graph that we construct using the r -division boundary vertices of G_M (details in Section 3.3) and the unmatched internal vertices in each region of G_M . We use the boundary vertices of G_M to define regions $\bigcup_j R_j^H$ in H and just like in D_j , we also use $\mathcal{K}_j$ to represent boundary vertices of region R_j^H in H . The compressed residual graph changes whenever G_M changes. For convenience, we will still use a single notation H to represent the changing compressed residual graph. We also state explicitly whether we are

referring to the compressed residual graph before or after the change to avoid confusion for readers.

3.2 Preprocessing

There are at most $O(\sqrt{n})$ augmenting paths remaining at the beginning of merge step (Lemma 2). We find r -division of $G(A \cup B, E)$. In each region (R_j) of G after r -division, we do DFS iteratively from unmatched vertices of type B to find augmenting paths lying wholly within R_j . An unmatched vertex can be an internal vertex or a boundary vertex.

Each DFS takes $O(r)$ time. We need to do at most $O(\sqrt{n})$ iterations of DFS in total from unmatched internal vertices as there cannot be more than $O(\sqrt{n})$ unmatched internal vertices at the beginning of merge step. Thus the total time taken to do DFS from unmatched internal vertices is $O(\sqrt{nr})$. Since the total number of boundary vertices in each region R_j of graph G after r -division is $O(\sqrt{r})$ and there is $O(n/r)$ regions, we can bound the total number of iterations of DFS from unmatched boundary vertices to be $O(n/\sqrt{r})$. Even though a boundary vertex can belong to multiple regions, it can have a matching in at most one region. Once a boundary vertex is matched in a region, we need not repeat DFS from this vertex in the remaining regions that contain it. The total time taken to do DFS from unmatched boundary vertices across all regions is $O(n\sqrt{r})$. For any $r < n$, $n\sqrt{r} > \sqrt{nr}$. Thus the preprocessing step has $O(n\sqrt{r})$ run time.

Preprocessing step ensures that augmenting paths within each region are eliminated and the remaining augmenting paths must span multiple regions. In other words, the remaining augmenting paths in G_M should include at least one matched boundary vertex.

Lemma 3. *After the preprocessing step, there are $O(\sqrt{n})$ augmenting paths remaining in G_M and there is no augmenting path which lies wholly inside a region R_j .*

3.3 Compressed Residual Graph H

Given a current matching M after the preprocessing step, the sparse graph H is a *multi-graph* constructed on the boundary vertices and free vertices of $A \cup B$. Let A_F and B_F denote the set of free vertices of A and B respectively after finding maximum matching in each region. The vertex set of H , denoted by V_H , will contain all the boundary vertices i.e., $\cup_{j=1}^l \mathcal{K}_j$. Therefore, every free vertex that is also a boundary vertex will automatically be in V_H . For every partition $R_j(V_j, E_j)$, if at least one free vertex from $A_F \cap V_j$ is not a boundary vertex, i.e., $(V_j \setminus \mathcal{K}_j) \cap A_F \neq \emptyset$, a special vertex a_j is added in V_H to represent all the free vertices of $(V_j \setminus \mathcal{K}_j) \cap A_F$. Similarly, vertex b_j is added in V_H for the set of free vertices of $(V_j \setminus \mathcal{K}_j) \cap B_F$. We call these additional vertices of V_H , a_j and b_j , *free internal vertices*. The vertex set V_H of H is thus given by $V_H = \cup_{j=1}^l (\mathcal{K}_j \cup \{a_j, b_j\})$. The nodes of H are classified depending on whether they are from A or B as follows: $A_H = \cup_j ((\mathcal{K}_j \cap A) \cup \{a_j\})$ and $B_H = \cup_j ((\mathcal{K}_j \cap B) \cup \{b_j\})$. Clearly, $V_H = A_H \cup B_H$. We refer to $A_H^F = (A_H \cap A_F) \cup \cup_j a_j$ and $B_H^F = (B_H \cap B_F) \cup \cup_j b_j$ as the free vertices of A_H and B_H .

After defining the vertex set V_H of H , edges between these vertices are constructed as follows. In order to define the edge set of H , we consider the residual graph G_M after preprocessing where we find maximum matching in each region of the r -division. Let M_j be the edges of the matching M that are contained in R_j , i.e., $M_j = M \cap E_j$. The edges in H are of three types.

- $u, v \in \mathcal{K}_j$ are both boundary vertices and there is a directed path from u to v in G_M that only passes through the edges of R_j . Note that H is a multi-graph in general because of edges of this type; multiple regions can contribute to edges between same pairs of boundary vertices.
- $u = b_j$ and $v \in \mathcal{K}_j$, and there is a directed path in G_M from some free vertex in $B_F \cap (V_j \setminus \mathcal{K}_j)$ to v that only passes through the edges of R_j .
- $u \in \mathcal{K}_j$ and $v = a_j$, and there is a directed path in G_M from u to a vertex v in the set $A_F \cap (V_j \setminus \mathcal{K}_j)$ that only passes through the edges of R_j .

We will denote by E_j^H , the set of edges in H between vertices $u, v \in (\mathcal{K}_j \cup \{a_j, b_j\})$. For every edge $(u, v) \in E_j^H$, the *projection* of the edge (u, v) on the residual graph G_M is the corresponding shortest directed path from u and v in G_M using only edges of R_j . This can be obtained by doing a BFS from u in R_j .

Lemma 4. H has $O(n/\sqrt{r})$ vertices and $O(n)$ edges.

Proof. The vertex set of H consists of free internal vertices and set of boundary vertices. At

most two free internal vertices are added per region. Since there are $O(n/r)$ partitions, total number of free internal vertices is $O(n/r)$. On the other hand, there are $O(\sqrt{r})$ boundary vertices in each region in H . Therefore the total number of boundary vertices in H can be bounded by $O(n/r) * O(\sqrt{r}) = O(n/\sqrt{r})$. This also bounds the total number of vertices in H .

In each region, every pair of boundary vertices may have an induced edge between them. Therefore there are $O(r)$ such edges per region. There are at most $O(\sqrt{r})$ edges per region where one end vertex is a free internal vertex. So, the bound on total number of edges in a region is $O(r)$. Since there are $O(n/r)$ partitions, the total number of edges in all the regions of H is $O(n)$. ■

For computing H , we construct a *dense distance graph* for each region as described by Fakcharoenphol and Rao [9]. We covered dense distance graphs in section 2.5. The dense distance graph stores all-pairs shortest path distances between boundary vertices in the region.

Let R_j^H be a sub-graph in H with vertex set $(\mathcal{K}_j \cup \{a_j, b_j\})$ and edge set E_j^H . We refer to $R_1^H, R_2^H \dots R_l^H$ as regions of H . Connectivity between each pair of boundary vertices in the region can be established in $O(\log r)$ time after construction of dense distance graph and there are $O(r)$ combinations of pairs of boundary vertices. To compute edges of the type $(u, v) \in b_j \times \mathcal{K}_j$, we add an additional vertex $\tilde{b}$ to the subset of the residual graph G_M defined by matching M_j in R_j and add an edge from $\tilde{b}$ to every vertex in $(B_F \cap V_j) \setminus \mathcal{K}_j$. Next, we

execute BFS from $\tilde{b}$ in the subset of residual graph G_M in the region R_j and include the edge (u, v) in R_j^H only if there is path to v from $\tilde{b}$ in the BFS search. BFS takes $O(r)$ time as the number of edges is $O(r)$ in R_j^M . Using a similar approach with the edges of G_M reversed and a newly added vertex $\tilde{a}$ in R_j , we compute edges of the type $(u, v) \in \mathcal{K}_j \times a_j$. This yields the following Lemma:

Lemma 5. *The edges of H in any partition R_j^H can be computed in $O(r \log r)$ time.*

Proof. While constructing H , we also store information on immediate neighbors of each vertex. In each region R_j^H , for every vertex u in the region, we maintain an adjacency list of all vertices that it has edges to, which we refer to as *neighbors* of u in R_j^H . With a constant number of holes (say h) in each region, instead of maintaining a single neighbors list for each vertex, we need to maintain h lists of neighbors for each vertex, one each for neighbor vertices lying on a particular face. Each boundary vertex u also has separate list for edges of type (u, a_j) . Since a boundary vertex belongs to multiple regions, it will have one or more *neighbors* lists for each region it belongs to depending on the number of holes in that region. Moreover, boundary vertices have a cyclic order in their respective face (hole). Therefore, for each vertex, the neighbors list corresponding to each hole has vertices stored in cyclic order. For the sake of simplicity, for the rest of chapter 3 and for chapter 4, we will assume that all boundary vertices lie on the infinite face and for each vertex u in a region, there is only one neighbors list in that region denoted by $N(u, R_j^H)$ comprising of just boundary vertices which are neighbors of u . u also maintains a separate list for edges of type (u, a_j) as mentioned before. All descriptions henceforth will make this assumption and can be easily carried over

to the handle constant number of holes as well. ■

Definition 3.3.1. We define *Augmenting path in H* as a simple directed path (no cycles) in H from a free vertex in B_H^F to a free vertex in A_H^F .

3.4 Projection and Lifting

Up until now, we have described the creation of the compressed graph H . Before diving into our algorithm, we introduce two operations involving G and H , namely *projection* and *lifting*.

3.4.1 Projecting a path.

To project a path P' in the compressed residual graph H to a path P in residual graph G_M , each edge (u, v) of P' is to be replaced by some directed path between the end vertices u and v in G_M . Edges (u, v) of type $u, v \in \mathcal{K}_j$ can be projected to G by querying the dense distance graph D_j which returns the shortest path between u and v . An edge (u, v) of type $u = b_j, v \in \mathcal{K}_j$ (or $u \in \mathcal{K}_j, v = a_j$) can be projected to G in just the same way they were constructed by doing BFS from $\tilde{b}$ (or $\tilde{a}$) and identifying a free vertex in $(V_j \setminus \mathcal{K}_j) \cap B_F$ (or $(V_j \setminus \mathcal{K}_j) \cap A_F$) that has a path to (or from) the boundary vertex.




Figure 3.1: A path in G_M is lifted to H . An edge in H is projected to shortest path in G_M .

3.4.2 Lifting a path.

Consider a directed path P in G_M . Among the vertices of P , let $p_{i_1}, p_{i_2}, \dots, p_{i_l}$ with $i_1 < i_2 < i_3 < \dots < i_l$, be all its boundary vertices. Let P_{i_t} be the sub-path of P lying between the vertices p_{i_t} and $p_{i_{t+1}}$. Note that P_{i_0} will be the sub-path in P appearing before the vertex p_{i_1} and P_{i_l} is the sub-path in P appearing after the vertex p_{i_l} . Also, note that if p_{i_t} and $p_{i_{t+1}}$ are adjacent to each other in P , then P_{i_t} will contain only one edge, i.e., the edge with p_{i_t} and $p_{i_{t+1}}$ as endpoints. We will map any sub-path P_{i_t} with u and u' as its first and last vertex to an edge (v, v') in H . This edge (v, v') is referred to as the *lift* of the path P_{i_t} and is constructed as follows. Note that if both u and u' are boundary vertices, we set $v \leftarrow u$ and $v' \leftarrow u'$. Suppose, u is a free internal vertex of B in partition R_j . In this case, we set u to b_j . A similar construction is applied in the case where u' is a free internal vertex of A . Let e'_{i_t} be the lift of the path P_{i_t} . It is easy to see that the path $\langle e'_{i_0}, e'_{i_1}, e'_{i_2}, \dots, e'_{i_l} \rangle$ is a path in H . We say that this path P' in H is obtained by lifting the path P to H . As a

consequence of the lifting operation, we get the following corollary.

Corollary 1. *If the matching M is not a maximum matching in G , then there is an augmenting path in H .*

Proof. Let M^* be optimal matching in G . $M^* \oplus M$ gives a set of vertex disjoint augmenting paths in G_M . Any augmenting path in G_M starting at $u \in B_F$ and ending at $u' \in A_F$ is lifted to a path in H beginning at $v \in B_H^F$ and ending at $V_H \in A_H^F$ by above construction of lifting which also happens to be an augmenting path in H by definition. ■

Lemma 6. *Let P_1 and P_2 be two vertex-disjoint directed paths in G_M and Q_1 and Q_2 be the paths obtained by lifting them to the graph H . Let Q'_1 (resp Q'_2) be all the vertices on the path Q_1 (resp Q_2) except for its start and end vertex, then*

$$Q'_1 \cap Q'_2 = \emptyset$$

Proof. This is again a consequence of lifting operation. Since paths P_1 and P_2 are vertex disjoint in G_M , it also implies that they share no common boundary vertices between them. When these paths are lifted to H , Q_1 and Q_2 will also have a disjoint set of boundary vertices. A path in H comprises of just the boundary vertices except for possibly the start and the end vertex which could be of type b_j and a_j respectively. By discarding the first and last vertex from Q_1 and Q_2 , the intermediate vertices are only boundary vertices. Thus we get $Q'_1 \cap Q'_2 = \emptyset$. ■




Figure 3.2: Vertex disjoint paths in G (shown in red) have disjoint boundary vertices in H

3.5 Merge Algorithm

After performing the preprocessing (Section 3.2) and construction of H (Section 3.3), we execute a Hopcroft-Karp style algorithm on H to compute maximum matching in G . We will show in Section 3.7 that this improves the merge time of our divide and conquer algorithm.

Our algorithm runs in phases till we have a maximum/perfect matching in G . In each phase, we do the following steps.

BFS We construct a layered graph in H by doing a BFS from the free vertices in B_H^F similar to the layered graph construction in Hopcroft-Karp algorithm described in Section 2.1. Let $\mathcal{V}$ be the set of vertices in the layered graph which includes B_H^F and all the vertices of H that are reachable from any vertex in B_H^F with distance less than or equal to the shortest augmenting path length $\mathcal{L}$ in H at the beginning of the iteration. The result of the BFS procedure is a labeling of all vertices in $\mathcal{V}$ with a layer number $L(.)$. For all $u \in B_H^F$, $L(u) = 0$. For all $v \in \mathcal{V} \setminus B_H^F$, $L(v)$ is the length of the shortest directed path in H from some vertex in B_H^F to v .

FINDAUGPATH After constructing the BFS layered graph, FINDAUGPATH procedure performs partial DFS from B_H^F in the layered graph to find a maximal set of shortest length augmenting paths in H . An arbitrary vertex v is chosen in B_H^F and a DFS is done from v in H . At any stage during the search, a partial directed path $\mathcal{P}'$ is maintained which begins at v and ends at some vertex u . FINDAUGPATH also keeps track of the vertices that have been visited so far during the DFS. An outgoing edge from u is chosen such that the next vertex u' is an unvisited vertex and has $L(u') = L(u) + 1$. u' is then added to the path $\mathcal{P}'$. u' is marked visited and the search continues from u' . If there is no such u' , u is removed from $\mathcal{P}'$ and search is repeated from the predecessor of u in $\mathcal{P}'$ choosing another edge leading to an unvisited vertex with the same layer number as u . If $u' \in A_H^F$, an augmenting path P' is found in H and AUGMENT procedure is invoked to augment along the projection P of this path in G_M . After AUGMENT procedure returns or if no augmenting path is found during

DFS from v , FINDAUGPATH initiates a new search from the next unvisited vertex in B_H^F .

AUGMENT The AUGMENT procedure takes as input, an augmenting path P' in H . We denote a partition R_j of G as *affected* if the path P' has at least one edge from the edges of H in E_j^H . Let $\hat{R}$ be the set of all affected partitions. Each directed edge (u, v) in P' belonging to E_j^H is projected in the corresponding region R_j . Let P be the projection of P' on G_M . By rules of projection, P also starts and ends in a unmatched vertex. We will show in Lemma 16 that P is a simple path and contains no self-intersections. Therefore, P is an augmenting path in G_M . After augmenting along P , the residual graph G_M changes and the edges in each partition in $\hat{R}$ are recomputed in H . Reconstruction can be done in each region using the same data structures that we used to construct H in Section 3.3.

In each phase of our Hopcroft-Karp style algorithm, FINDAUGPATH finds a maximal set of shortest length augmenting paths in H (Lemma 15) which are also boundary vertex disjoint (Lemma 14). Unlike the Hopcroft-Karp algorithm, we augment in G_M immediately after finding an augmenting path during partial DFS in H . Since H changes (only *affected* regions) after each augmentation, the new compressed residual graph H may introduce new augmenting paths. We show in Lemma 12 that all such augmenting paths are of length $\geq \mathcal{L}$ which is the length of the shortest augmenting path in the beginning of the phase. Also, since H changes after each augmentation, it may affect the layer numbers of some vertices in H . For this reason, it may seem necessary to perform BFS again to construct new layered graph after each augmentation. We, however show that it suffices to do BFS just once at the

beginning of each phase (Lemma 11, 12, 14) and that vertices whose layer numbers change will not be part of shortest length augmenting path in the current phase. We also show that the length of the shortest augmenting paths in H increases (Lemma 15) after each phase of our algorithm and the number of iterations required to compute maximum matching is $O(\sqrt{V_H})$ (Lemma 17).

Our algorithm maintains the following invariant.

- (I1) Projection P of an augmenting path P' in H onto G_M is a simple path i.e., the path P does not have any self-intersections.

3.6 Proof of Correctness

In this section, we state and prove some properties to justify the correctness of our Hopcroft-Karp style algorithm.

We assume the invariant (I1) for proving lemmas 11 to 15. We later prove the invariant (I1) in Lemma 16.

Definition 3.6.1. An edge (u, v) in H is called level respecting if $L(v) \leq L(u) + 1$ and the edge is said to be in the *level* $L(u)$.

$L(\cdot)$ refers to layer numbers assigned to vertices by the BFS procedure of our Hopcroft-Karp

style algorithm. Before finding the augmenting paths in H , all the edges in H between vertices in layered graph are level respecting.

Lemma 7. *Two level respecting edges (u, v) and (u', v') in H lying in the same region R_j^H and satisfying the following conditions*

1. $L(v) = L(u) + 1, L(v') = L(u') + 1$
2. $L(u') \geq L(u) + 1$

will always have vertex-disjoint projections.

Proof. Consider two level respecting edges (u, v) and (u', v') in region R_j^H satisfying the above 2 conditions. From the two conditions, we can infer $L(v') \geq L(u) + 2$. Let us assume that the projections of (u, v) and (u', v') share a common vertex w . This would mean that u has a path to v' through w in G_M and by rules of construction of H , there should be an edge (u, v') in H assigning $L(v') = L(u) + 1$. Thus, we arrive at a contradiction. ■

Reversing some edges in the region R_j of G_M can create and destroy edges in the region R_j^H of H while all other regions of H remain unaffected. In Lemmas 8 to 11, we state and prove some properties that are obeyed by new edges introduced in H due to changes in the residual graph G_M .

Definition 3.6.2. A directed path from vertex u to v in G_M (or H) is of shortest length if the path uses minimum number of edges among all the paths from u to v in G_M (or H).

Lemma 8. *If the projection of an edge (u, v) with $L(v) = L(u) + 1$ is reversed in G_M , the new edges created in H will be level respecting and will have a level greater than or equal to $L(u)$.*

Proof. After reversing the projection P of edge (u, v) , new paths are introduced between boundary vertices of R_j in G_M that use one or more reversed edges of P . This could lead to new edges being introduced in H and each of these edges have least one of the reversed edges of P in their projection.

Let (u', v') be one of the newly formed edges in H . Projection of (u', v') uses at least one of the reversed edges of P . Let w be the first common vertex which is both in projection of (u', v') and in P . Before reversing the projection P , there was a directed path from w to v in R_j along P . This implies that u' also had a path through w to v before reversing P . Thus, by construction of H , there must have been an edge (u', v) in H before reversing P as shown in the second diagram of Figure 3.3. Let $L(u) = i$ and $L(v) = i + 1$. Since the edge (u', v) is level respecting and $L(v) = i + 1$, we can infer that $L(u') \geq i$.

After reversing P , u' which had a path to v through w would now have a path to u through w using the reversed edges of P . u' will also have a path to all neighbors of u after reversal of P . Thus v' in the newly edge could either be u or a neighbor of u in R_j^H after reversal of P . If v' is a neighbor of u , (u, v') must have existed even before reversing P . (u, v') is also level respecting and therefore $L(v') \leq i + 1$. If v' is u , it would still satisfy the condition

$L(v') \leq i + 1$ as $L(u) = i$. Since $L(u') \geq i$ and $L(v') \leq i + 1$, we can conclude that the newly added edge (u', v') also satisfies the definition of level respecting. Moreover, the newly added




Figure 3.3: $L(u)$ and $L(v')$ can only increase or remain same after augmentation.

edge will have level greater than or equal to i since $L(w) \geq i$. ■

Lemma 9. *Reversing the projection of an edge $(u, v) \in R_j^H$ where $L(v) = L(u) + 1$ does not create or destroy a level respecting edge with level $< L(u)$ in R_j^H .*

Proof. We showed in Lemma 8 that reversing the projection of (u, v) only introduces level respecting edges in H . We also showed that these edges are at level $\geq L(u)$ in R_j^H . We now show that no level respecting edge with level $< L(u)$ is destroyed by reversing the projection of (u, v) .

Projection of any level respecting edge (u', v') at level $< i$ will only have vertices with $L(\cdot) \leq i$ and it should also be vertex-disjoint (hence also edge-disjoint) from the projection of (u, v) . Otherwise, u' would have a path to v in R_j through the common vertex of two

projections and the corresponding edge (u', v) in H would violate level respecting property. This contradicts the fact that all edges in H are level respecting. Thus reversing the projection of (u, v) does not remove any level respecting edge at level $< i$. ■

Using Lemmas 11 to 14, we will show that the boundary vertices which are visited by the FINGAUGPATH can be discarded as they will never be part of a newly found augmenting path in the same phase of the algorithm.

After finding an augmenting path P' in H , its projection on G_M , P is augmented, causing each of its edges to get reversed in G_M . When the path corresponding to projection of an edge in P' gets reversed, it can lead to new edges being created between the vertices in H in the region affected, which can affect the layer numbers of many vertices that were computed by the *BFS* procedure.

Lemma 10. *The new edges introduced in H after augmenting the projection of P' in G satisfy the level respecting property.*

Proof. We know that reversing the projection of an edge in R_j^H does not affect edges of H in other regions. We also saw in Lemma 9 that reversing the projection of an edge (u, v) in R_j^H where $L(v) = L(u) + 1$ does not affect the level respecting edges at lower levels. Since reversing the projection of an edge in P' does not affect the edges of H in other regions and in the lower levels of the same region, we can consider the effect of augmenting the path P (projection of P') as being same as incrementally reversing the projection of edges in P' , one

at a time from the end of the path A_H^F to the beginning B_H^F .

After augmenting the projection of each edge in P' , the newly created edges in H are also level respecting as shown in Lemma 8. Extending this property to all the edges in P' , we can say that all the newly introduced edges in H after augmenting the path P would be level respecting. ■

Lemma 11. *Layer number of vertices in H assigned by BFS step do not decrease after augmenting a path P in G .*

Proof. As shown in Lemma 10, all the newly added edges in H after augmenting the path P in G are level respecting. Moreover, some of the edges which existed before augmentation may be removed from H . Destroying an edge in H can only potentially increase the layer number of vertices. Since all the newly created edges after augmentation are level respecting with respect to the layer numbers $L(\cdot)$ computed by BFS at the beginning of the phase, the newly formed edges do not create a shorter path to any vertex from B_H^F . Therefore, if we do a BFS again from B_H^F to assign new layer numbers to vertices, the layer numbers would only increase or remain the same. ■

Lemma 12. *After augmenting along the projection of a path P' in H , the augmenting paths in the new graph H after augmentation are of length $\geq |P'|$.*

Proof. In Lemma 11, we showed that the layer numbers assigned by BFS to all vertices

including vertices in A_H^F can only increase or remain the same after augmenting along the projection of path P' . All vertices in A_H^F had layer number $|P'|$ before augmenting the projection of P' . After augmentation, using Lemma 11, we can infer that the length of shortest path to vertices in A_H^F from any vertex in B_H^F can only increase or remain same. Thus all the remaining augmenting paths have length $\geq |P'|$. ■

We showed in Lemma 11 that layer number of all vertices can only increase or remain the same after augmentation. Using Lemma 14 and Lemma 13, we show that any vertex which is visited by the FINDAUGPATH procedure in the current phase can be discarded and need not be visited by FINDAUGPATH again. Lemma 13 shows why this is true for any vertex which is visited but did not lead to a shortest length augmenting path. Lemma 14 shows that we can also discard vertices which participated in an augmenting path in the current phase as they will not be part of any other augmenting path of the shortest length discovered in the same phase by FINDAUGPATH.

Let $S(v)$ indicates the shortest path length from any vertex in B_H^F to v . At the beginning of each phase, $S(v) = L(v)$ which is assigned by BFS. If we construct a graph H' from H by reversing all the edges in H and then do BFS on H' starting from A_H^F vertices at layer 0, then we can make a similar argument that the shortest distance to any vertex v from A_H^F (or shortest distance from v to A_H^F in H), denoted by $S'(v)$ increases or remains the same after an augmentation.

The length of the shortest augmenting path through any vertex v can be represented as sum of the length of shortest path of v from any vertex in B_H^F and the length of shortest path from v to any vertex in A_H^F i.e. $S(v) + S'(v)$. Thus for any vertex v , if $S(v)$ increases after an augmentation, it will no longer be part of the shortest length augmenting path in the current iteration. Its layer number also increases in the next phase. We have also shown in Lemma 11 that $S(v)$ can never decrease. This justifies the fact that it suffices to compute BFS layers only once at the beginning of each phase and not after every augmentation. Only those vertices whose $S(\cdot) = L(\cdot)$ would be part of the shortest length augmenting paths in the current phase.

Lemma 13. *If a vertex is marked visited by FINDAUGPATH but did not lead to a shortest length augmenting path, then it can not be part of any shortest length augmenting path discovered later in the same phase.*

Proof. Consider a vertex z which was explored in the current phase by FINDAUGPATH but did not lead to a shortest length ($|P'|$) augmenting path in the current phase. Let $S(z) = i$. Since z was explored in the FINDAUGPATH and no augmenting path of length $|P'|$ was found, it implies $S'(z) > (|P'| - i)$. This implies that even if $S(z)$ remains the same after augmenting a path P' , we still have $S(z) + S'(z) > |P'|$.

Alternatively, we can prove this by contradiction. Let us assume that vertex z was marked as visited by FINDAUGPATH routine while doing a partial DFS from $b_1 \in B_H^F$, but was not part of a shortest length augmenting path. This implies $S'(z) > |P'| - i$. Later, FINDAUGPATH




Figure 3.4: If z is marked visited by partial DFS from b_1 , P_1 is found before P_2 .

finds an augmenting path from $b_2 \in B_H^F$ to $a \in A_H^F$ through z which implies $S'(z) = |P'| - i$. This leads to a contradiction as depicted in Figure 3.4. Since $S'(z)$ cannot reduce, the path from z to a should have existed even during partial DFS from b_1 and an augmenting path P_1 would have been found the first time z was visited before P_2 was discovered. This proves the lemma. ■

Lemma 14. *No boundary vertex will be part of two or more augmenting paths of the same length in H .*

Proof. To prove this lemma, we will show that for a vertex v which is part of augmenting path P' , after augmenting along the projection of P' , has at least one of $S(v)$ or $S'(v)$ increasing which means that the next shortest augmenting path through v will have a length $> |P'|$.

The case where $S(v)$ increases after augmenting P' is trivial as this implies that $S(v) + S'(v)$ is now greater than $|P'|$, the length of the shortest augmenting path in the current phase.

Let us consider the case where $S(v)$ doesn't change after an augmentation. In this case, we will show that $S'(v)$ should increase. For the sake of contradiction, let us assume that $S'(v)$ does not increase. Let (u, v) be the edge of the augmenting path P' which was just augmented. Let the projection of (u, v) be $\{u, p_1, p_2, \dots, p_l, v\}$. Let the new edge responsible for maintaining the same layer number of v be (u', v) . This edge could be formed after augmenting the projection of P' or may have existed before. If the edge (u', v) existed before, its projection after augmentation has to be edge-disjoint from the projection of (u, v) before augmentation implying that v has 2 incoming edges in G_M . If the edge (u', v) was formed after augmentation, its projection $\{u', p'_1, p'_2, \dots, p'_l, v\}$ may use some of the reversed edges of projection of (u, v) but the final edge (p'_l, v) in projection of (u', v) would still be different from final edge (p_l, v) in the projection of (u, v) . In this case too, we can see that v has at least 2 incoming edges in G_M .

We know that in a bipartite matching, any vertex in B has at most 1 incoming edge and every vertex in A has at most 1 outgoing edge in G_M . Since vertex v has at least 2 incoming edges in G_M , it means $v \in A$ and has only one outgoing edge in G_M . v can have many outgoing edges in H all of which share a common edge in their projections on G_M . Reversing the projection of any one of the outgoing edges from v in H during augmentation, invalidates all other outgoing edges from v in H (See Figure 3.5). So, v can only have a path to a free vertex in A_H^F through a vertex z which had layer number $L(z) < L(v)$ before augmenting the projection of P' . Since $S'(z) > S'(v)$, the second augmenting path through v has length




Figure 3.5: If $S(u)$ remains same after augmentation, v has to be of type A.

$> |P'|$.

■

Lemma 15. *Length of the shortest augmenting paths in H during the $(i + 1)^{th}$ iteration is at least 1 greater than the shortest augmenting path in i^{th} iteration.*

Proof. The shortest length of an augmenting path in H after running Hopcroft-Karp algorithm in each region is at least 2. Let $\mathcal{L}$ be the length of the shortest augmenting path at the beginning of a given phase. By Lemma 13 and 14, after augmenting a path of length $\mathcal{L}$, any remaining augmenting paths of the same length would use unvisited vertices except for possibly the first and last vertices which could be internal vertices. We have also shown in Lemma 12 that the length of any new augmenting path created in H after each augmentation because of the newly added edges is greater than or equal to $\mathcal{L}$. Lets say we do a partial

DFS from a free vertex $b_1 \in B_H^F$ and it did not lead to an augmenting path of length $\mathcal{L}$. Our algorithm continues to do partial DFS from the remaining free vertices in B_H^F . Lets assume that a new augmenting path P'' of length $\mathcal{L}$ is created from b_1 because of augmenting along some augmenting path discovered later in the phase. Since our algorithm does not repeat partial DFS from b_1 , P'' may be missed which contradicts our lemma. However, we can show that P'' cannot be created in the first place as it would mean $S'(b_1)$ which was greater than $\mathcal{L}$ initially has become equal to $\mathcal{L}$ which is not possible as we showed in Lemma 11 and 14. Therefore, all augmenting paths of length $\mathcal{L}$ are exhaustively found in the given iteration. The minimum length in the next iteration of merge algorithm is at least $\mathcal{L} + 1$. ■

3.6.1 Proof of Invariant

While running the Hopcroft-Karp style algorithm on H , we maintain the following invariant.

Lemma 16. *Let P' be an augmenting path reported by FINDAUGPATH and let P be its projection on G_M . Then P is a simple path.*

Proof. By construction, P' is a simple path. For the sake of contradiction, let us assume that there are at least two edges (u, v) and (u', v') in P' whose projections intersect. Without loss of generality, let u' come later in the path P' . So, $L(u') \geq L(u) + 1$. Moreover, FINDAUGPATH chooses edges such that $L(v) = L(u) + 1$ and $L(v') = L(u') + 1$. Let P_{uv} and $P_{u'v'}$ be the projections of the 2 edges. Since the projections intersect in G_M , the projections are in the same region R_j and share a common edge, say (w, x) . This is because w cannot have multiple




Figure 3.6: Projection of 2 edges of augmenting path in H cannot intersect in G

incoming and multiple outgoing edges in a bipartite graph. This gives us the condition that $L(v') \geq L(u) + 3$. P_{uv} is a directed path from u to v through w in the region R_j of G_M and $P_{u'v'}$ is a directed path from u' to v' through w in the same region. This means that there is also a directed path from u to v' and by construction of H , there would have been an edge from u to v' in H . By BFS labeling, $L(v') \leq L(u) + 1$. This contradicts with our earlier condition that $L(v') \geq L(u) + 3$. Therefore, our assumption that projections of 2 edges intersect is incorrect. Since no projections intersect, there cannot be a cycle in P and it is a simple path. ■

3.7 Algorithm Efficiency

Lemma 17. *After $\sqrt{|V_H|}$ iterations of the algorithm, there will be at most $O(\sqrt{|V_H|})$ unmatched nodes remaining.*

Proof. From lemma 15, length of augmenting path in H grows by at least 1 after every iteration. After $\sqrt{|V_H|}$ iterations, length of augmenting path in H is at least $\sqrt{|V_H|} + 2$ with at least $(\sqrt{|V_H|})$ boundary vertices. Since we eliminated augmenting paths within each region as part of preprocessing before running the Hopcroft-Karp style algorithm, the remaining augmenting should span multiple regions. This implies that all augmenting paths in H contain at least one boundary vertex.

We know that that symmetric difference of the optimal matching M^* and the matching M after $\sqrt{|V_H|}$ iterations will form a set of vertex-disjoint augmenting paths in G_M . By Lemma 6, these paths map to paths in H which are vertex disjoint in H except for the first and the last vertex. Thus the bound on vertex-disjoint augmenting paths in G can be found by bounding vertex-disjoint augmenting paths in H excluding the first and last vertex. There are $O(V_H)$ boundary vertices in total. From Lemma 15 and Lemma 6, the number of such vertex-disjoint augmenting paths in H after $(\sqrt{V_H})$ iterations is bound by $O(V_H)/(\sqrt{|V_H|}) = O(\sqrt{|V_H|})$ thus proving the lemma. ■

3.7.1 Efficiency of BFS, FINDAUGPATH and AUGMENT procedures

The layered graph can be constructed with a single BFS in $O(n)$ time. However, section 4.2 presents a way to accomplish this in $O(|V_H| \log^2 n)$ time, that is $O(\frac{n}{\sqrt{r}} \log^2 n)$.

Let P'_i be the i^{th} augmenting path in H computed by FINDAUGPATH procedure. For an edge in P'_i belonging to R_j^H , computing its projection in G_M using only the edges in R_j takes $O(r)$ time. Computing the new edges in each affected partition of H can be done by recomputing the dense distance graph for the partition and querying it. Dense distance graph construction takes $O(r \log^3 r)$ as described by Fakcharoenphol and Rao [9]. The number of affected partitions identified by the AUGMENT procedure is at most $\Delta = \sum_i |P'_i|$. Therefore, the total time taken by AUGMENT procedure is $O(r \Delta \log^3 r)$. Lemma 18 bounds Δ by $O(|V_H| \log n)$. Therefore, total time taken by AUGMENT procedure is $O(r |V_H| \log^3 r \log n)$.

Before an augmenting path is found, each edge in H is explored only once by FINDAUGPATH and there are $O(r)$ edges in each region R_j^H making it $O(n)$ across all regions in H . After each augmentation, the time taken to compute new edges in affected partitions can be taxed to the complexity of AUGMENT procedure. Therefore, the complexity of FINDAUGPATH is $O(n)$. In the next chapter, we show how this bound can be improved to $O(\frac{n}{\sqrt{r}} \log^2 n)$ which is proportional to the total number of vertices in H instead of number of edges in H .

Lemma 18. *Let $\mathbb{P}$ be the set of all augmenting paths in H generated by the FINDAUGPATH procedure. Then,*

$$\Delta = \sum_{P' \in \mathbb{P}} |P'| = O(|V_H| \log n)$$

Proof. Let P'_i be the i^{th} augmenting path generated by the FINDAUGPATH procedure. Consider the matching M_{i-1} in G before augmenting along projection of P'_i and let M^* be an optimal matching. $M_{i-1} \oplus M^*$ has a degree at most 2 and therefore forms a set of disjoint paths and cycles in G . These paths/cycles translate to disjoint paths/cycles in H as shown in Lemma 6 except for the start and the end vertices if they happen to be internal b_j or a_j . Let $\vec{\mathcal{P}}$ be the set of paths in $M_{i-1} \oplus M^*$ and let $\vec{\mathcal{P}}'$ be the set of paths in $\vec{\mathcal{P}}$ lifted to H . Our algorithm ensures that each augmenting path P'_i found in H is a minimum length path, but the minimum length of P'_i is unclear. Instead, we can use the average length of all paths in $\vec{\mathcal{P}}'$ as an upper bound on the length of P'_i . We know that there are $O(\sqrt{n})$ augmenting paths at the beginning of the merge step. Before i^{th} augmentation, the number of augmenting paths remaining is $k\sqrt{n} - i + 1$ where k is some constant.

The average length of $(i)^{th}$ augmenting path in H would be

$$O(|V_H|)/(k\sqrt{n} - i + 1)$$

where $O(V_H)$ is the total number of edges in $\vec{\mathcal{P}}'$ as there are $O(|V_H|)$ boundary vertices with degree equal to 2 in $\vec{\mathcal{P}}'$. To bound the total length of all augmenting paths in H , we sum the

average length of i^{th} augmenting path over all values of i from 1 to $k\sqrt{n}$ which gives

$$\sum_{i=1}^{k\sqrt{n}} O(|V_H|)/(k\sqrt{n} - i + 1) = O(|V_H|) \sum_{i=1}^{k\sqrt{n}} 1/(k\sqrt{n} - i + 1)$$

Substituting $(k\sqrt{n} - i + 1)$ by i' , we get

$$O(|V_H|) \sum_{i=1}^{k\sqrt{n}} 1/(k\sqrt{n} - i + 1) = O(|V_H|) \sum_{i'=1}^{k\sqrt{n}} 1/i'$$

$\sum_{i'=1}^{k\sqrt{n}} 1/i'$ is the $(k\sqrt{n})^{th}$ harmonic number which can be bounded by $\theta(\log(k\sqrt{n}))$. Therefore,

$$\Delta \leq O(|V_H|) \sum_{i'=1}^{k\sqrt{n}} 1/i' = O(|V_H| \log n) = O((n/\sqrt{r}) \log n)$$

.

■

By choosing $r = n^{2/3}$, we get the overall time taken by AUGMENT procedure to be $O(r|V_H| \log^3 r \log n) = O(n^{4/3} \log^4 n)$. BFS and FINDAUGPATH take $O(n)$ per iteration and there are $O(\sqrt{V_H})$ iterations in total, which results in total time of $O(n^{4/3})$ for these two operations together. Therefore, the overall complexity of the merge step of our algorithm is $O(n^{4/3} \log^4 n)$. We can reduce the power on $\log$ term from 4 to 2 by using Klein's MSSP data structure [21] or Thorup's connectivity oracle [29] for reconstruction of edges of H . In Chapter 4, we will show that the overall run time can be improved further by using faster BFS and FINDAUGPATH implementations along with a wise choice of r for r -division.

3.8 Hopcroft-Karp Equivalence of Our Algorithm

From our proofs, it can be observed that our algorithm is very similar to the traditional Hopcroft-Karp algorithm except that it runs on H instead of G . The similarity can be summarized as follows.

- We compute BFS layers only once at the beginning of each iteration [Lemma 11, 12, 14].
- We find vertex disjoint shortest length augmenting paths in H except for maybe the first and the last vertex.[Lemma 14, 13].
- The length of the shortest augmenting path in H grows every iteration [Lemma 15].
- Total number of iterations of our algorithm is $O(\sqrt{|V_H|})$ where V_H refers to set of vertices in H and $|V_H| = O(n/\sqrt{r})$ [Lemma 17]. Hopcroft-Karp algorithm takes $\sqrt{|V|}$ iterations where V refers to set of vertices in G and $|V| = n$.
- We bound the total length of all augmenting paths in H to be $O(|V_H| \log n)$ [Lemma 18]. Hopcroft-Karp algorithm bounds the total length of all augmenting paths in G to be $O(n \log n)$.

Chapter 4

Improved Merge Algorithm

In this chapter, we present faster BFS and FINDAUGPATH (DFS) implementations which run in $\tilde{O}(n/\sqrt{r})$ time instead of $O(n)$. Integrating these faster BFS and DFS along with the right choice of r for *r-division*, we show an improvement in the overall run time of our matching algorithm. First, we justify the choices of r for the three versions of our matching algorithm. The first version is $\tilde{O}(n^{4/3})$ discussed in Chapter 3. Second and third versions are presented in this chapter. In section 4.2, we show $\tilde{O}(n^{5/4})$ convergence by using just the faster BFS implementation and choosing $r = \sqrt{n}$. In section 4.3, we combine faster implementations of both BFS and DFS and fix $r = n^{2/5}$ to achieve $\tilde{O}(n^{6/5})$ matching algorithm.

4.1 Choice of r

There are two competing factors which affect the overall complexity of our matching algorithm. They are

- Recomputing the edges of affected regions in H after an augmentation: In Lemma 18, we bounded the total length of all augmenting paths to be

$$\Delta = \sum_{P' \in \mathbb{P}} |P'| = O(|V_H| \log n)$$

where V_H is $O(n/\sqrt{r})$. This is also the bound on number of times we recompute edges in a region. Time taken to recompute edges per region using DDG is $O(r \log^3 r)$. Therefore, the overall cost of this step over the entire run of the algorithm is $O(n\sqrt{r} \log^4 n)$. Note that computing maximum matching in all regions as a preprocessing step to eliminate augmenting paths within a region takes time $O(n\sqrt{r})$ in total and has the same bounds as recomputing the edges (ignoring the $\text{poly}(\log)$ term).

- Number of iterations and complexity of BFS/DFS: Number of iterations of algorithm is $O(\sqrt{V_H})$ as shown in Lemma 17. Complexity of Standard BFS/DFS is $O(n)$ which is the number of edges in H . In this chapter, we improve BFS and DFS to run in time $O((n/\sqrt{r}) \log^2 n)$ which is proportional to the number of vertices in H . Overall complexity of all the BFS/DFS operations would be $O(n^{3/2}/r^{1/4})$ with standard BFS/DFS and $\tilde{O}(n^{3/2}/r^{3/4})$ with improved BFS/DFS.

Ignoring the polylog terms and equating the complexity of above 2 operations, we get 3 cases.

Case 1: Using Standard BFS/DFS

$$n\sqrt{r} = (n^{3/2}/r^{1/4}) \rightarrow r = n^{2/3}$$

This gives an overall complexity of $\tilde{O}(n^{4/3})$.

Case 2: Using Improved BFS Since we are using 'divide and conquer' approach for computing maximum matching, there are at most $O(\sqrt{n})$ unmatched vertices in the merge step at the topmost level. Even if we find just one augmenting path per iteration, we need $O(\sqrt{n})$ iterations. Therefore, in this case, we use just the improved BFS. Now comparing the two factors discussed above, we have

$$n\sqrt{r} = (n^{3/2}/\sqrt{r}) \rightarrow r = \sqrt{n}$$

This gives an overall complexity of $\tilde{O}(n^{5/4})$.

Case 3: Using Improved BFS+DFS Here the number of iterations is $O(\sqrt{V_H})$ just like in Case 1. Equating the two factors gives us

$$n\sqrt{r} = (n^{3/2}/r^{3/4}) \rightarrow r = n^{2/5}$$

The overall complexity of our algorithm reduces to $\tilde{O}(n^{6/5})$.

4.2 Faster BFS

4.2.1 Algorithm Overview

BFS can be seen as Dijkstra's algorithm with unit/equal edge costs. Our Faster BFS algorithm is similar to the one presented in [18] except that we deal with only unit/equal edge costs. The algorithm contains three steps.

- In the first step, all free internal vertices b_j are assigned layer number 0.
- In the second step, we execute an implementation of Dijkstra's called FR-Dijkstra given by Fakcharoenphol and Rao [9] which uses bipartite groups and range-minimum query data structures. Before starting FR-Dijkstra's, we assign all free boundary vertices in B_H^F with label 0 in each bipartite Monge group (X, Y) where these vertices appear in Y . We also assign all the neighbors of free internal vertices b_j , a label 1 in the respective Monge groups containing them on Y side. FR-Dijkstra efficiently computes the next edge to add to the BFS Layered graph thus assigning layer numbers to vertices. See section 2.5 for description of FR-Dijkstra. For detailed analysis, see [9] or section 5.2 of [18]. This step takes $O((n/\sqrt{r}) \log^2 n)$ time in total.
- In the third step, we set the layer number of free internal vertex a_j as $L(a_j) =$

$\min_{\cup R_j^H, (u, a_j) \in E_j^H} L(u) + 1$. Since there are at most $O(n/\sqrt{r})$ vertices of type (u, a_j) , this step takes $O(n/\sqrt{r})$ time.

Implementation details with pseudo code is provided in section 4.2.2.

4.2.2 Algorithm Implementation

We now present our FR-Dijkstra adaptation to do BFS on H . By our construction, the dense distance graph per region captures only the connectivity between the boundary vertices of the region. As stated before, FR-Dijkstra based BFS (FastBFS) achieves speedup by executing in time proportional to the number of boundary vertices which is $O(n/\sqrt{r})$ while the number of edges between boundary vertices in DDG could be $O(n)$. In addition to this, FastBFS also handles the edges in H of type $(b_j, \mathcal{K}_j)$ and $(\mathcal{K}_j, a_j)$ exclusively in our algorithm which are at most $O(n/\sqrt{r})$ in number. The edge weights are neglected in DDGs and all the edges are considered to have equal weight.

Algorithm 2 BFS Using FR-Dijkstra

```

1: procedure FASTBFS( $H$ )
2:    $\forall v \in H, L(v) = \infty, LastLayer = -1, S(visited) = \emptyset$ 
3:   for  $v \in \bigcup_j \mathcal{K}_j \cap B_H^F$  do ▷ Free boundary vertices of type B
4:     for each  $(X, Y) \in H$  s.t.  $v \in Y$  do
5:       if  $(X, Y)$  heap is empty then
6:          $\mathcal{Q}.INSERT((X, Y), 0)$ 
7:          $(X, Y).INSERT(v, 0)$ 
8:   for  $v \in \bigcup_j b_j$  do ▷ Free internal vertices of type B
9:      $L(v) \leftarrow 0$ 
10:  for  $u \in \bigcup_j N(v, R_j^H)$  where  $v \in \bigcup_j b_j$  do
11:    for each  $(X, Y) \in H$  s.t.  $u \in Y$  do
12:      if  $(X, Y)$  heap is empty then
13:         $\mathcal{Q}.INSERT((X, Y), 1)$ 
14:         $(X, Y).INSERT(u, 1)$ 
15:  while  $!\mathcal{Q}.EMPTY()$  do
16:     $(X, Y) \leftarrow \mathcal{Q}.EXTRACTMIN()$ 
17:     $u \leftarrow (X, Y).EXTRACTMIN(Y \setminus M)$ 
18:    if  $u \notin S$  then ▷  $u$  is being visited for the first time
19:       $L(u) = d(u)$ 
20:      if  $L(u) == LastLayer$  then
21:        continue ▷ Dont activate next layer vertices
22:      for each  $(X', Y')$  s.t.  $u \in X'$  do ▷ relax edges in DDGs
23:         $(X', Y').ACTIVATE(u, d(u))$ 
24:         $v \leftarrow (X', Y').FINDMIN(Y' \setminus M')$ 
25:         $\mathcal{Q}.UPDATE((X', Y'), d(v))$ 
26:        if  $v$  is free vertex and  $(LastLayer == -1)$  then
27:           $LastLayer = d(v)$ 
28:      for each edge  $(u, v)$  where  $v \in \bigcup_j a_j$  do ▷ relax edges of type  $(\mathcal{K}_j, a_j)$ 
29:         $L(v) = L(u) + 1$ 
30:         $LastLayer = d(v)$ 
31:       $S = S \cup \{u\}$ 
32:    else
33:       $v \leftarrow (X, Y).FINDMIN(Y \setminus M)$ 
34:       $\mathcal{Q}.UPDATE((X, Y), d(v))$ 
35:  return

```

Pseudo code for FastBFS is shown in Algorithm 2. FastBFS runs on H . Initially, all vertices in H have $L(v) = \infty$ and S which maintains the set of visited vertices is $\emptyset$. **ACTIVATE**, **FINDMIN** and **EXTRACTMIN** have the same function as described in section 2.5.2. Note that we have eliminated all edges (b_j, a_j) by finding maximum matching in each region during the preprocessing step. We use a global heap (Queue would suffice for BFS) $\mathcal{Q}$ apart from local heaps for each bipartite Monge group (X, Y) .

Line 3 adds all free boundary vertices of type $\mathcal{K}_j \cap B_H^F$ to the local heaps of Monge groups that they are part of, with a distance label of 0. Each Monge group (X, Y) has at most one representative in the global heap $\mathcal{Q}$ which is the smallest distance label for a vertex in Y/M . We do the same for boundary vertices which are directly connected to any $v \in \bigcup_j b_j$ as shown in nested *for* loop starting in line 8. In the while loop, we extract the smallest distance label from $\mathcal{Q}$, and if the vertex corresponding to that label is being visited for the first time, we assign it's layer number and activate it in all the Monge groups it belongs to as shown in line 22. For every boundary vertex u activated, we also check if there are any edges (u, v) where $v \in A_H^F$. *LastLayer* is used to keep track of the layer where a vertex $\in A_H^F$ is discovered for the first time as shown in lines 26 and 28. *UPDATE()* operation is used to update the representative of a Monge group in $\mathcal{Q}$.

4.2.3 Analysis of FastBFS

FastBFS has the same complexity as FR-Dijkstra. Analysis of FR-Dijkstra in section 2.5.3 carries over here. Since there are only $O(n/\sqrt{r})$ edges of type $(b_j, \mathcal{K}_j)$ and $(\mathcal{K}_j, a_j)$, the total time taken to process them is $O(n/\sqrt{r})$. Each boundary vertex can be extracted from the local heaps at most $O(\log r)$ times in each region. Since there are $O(n/\sqrt{r})$ boundary vertices in total, we do $O((n/\sqrt{r}) \log r)$ extractions from all the local heaps put together. Each extraction is followed by updating new minimum label in the local heaps which takes $O(\log r)$ time. A vertex extracted from $\mathcal{Q}$ is activated only once per Monge group. Total run time of FastBFS is $O((n/\sqrt{r}) \log^2 n)$.

While assigning the layers during FastBFS, we can also track the parent of each vertex and hence find an augmenting path in H . This gives an overall complexity of $\tilde{O}(n^{5/4})$. (See Case 2 in section 4.1).

4.3 Faster DFS

In this section, we present an FR-Dijkstra style algorithm to perform FINDAUGPATH (DFS) faster. We call it the FastDFS.

4.3.1 Algorithm Overview

We saw in section 3.5 that FINDAUGPATH takes $O(n)$ time. FINDAUGPATH performs partial DFS in BFS layered graph constructed from H to find shortest length augmenting paths in H . Given a vertex u , FINDAUGPATH would explore all outgoing edges of u to find a valid vertex v such that v is an unvisited vertex during partial DFS and $L(v) = L(u) + 1$.

In order to do FINDAUGPATH efficiently, we make use of bipartite Monge groups defined for FR-Dijkstra and 2-D dynamic range search trees associated with every bipartite group. With these data structures, we are able to do DFS in time $O((n/\sqrt{r}) \log^2 r)$ instead of $O(n)$. Given a vertex u , the data structures help us to efficiently find a vertex v such that v is a unvisited neighbor of u and $L(v) = L(u) + 1$ without having to explore all outgoing edges of u .

To find a valid outgoing edge from u in partial DFS, we query the 2-D Range search trees associated with the bipartite group (X, Y) where the vertex u lies in X . The query is an interval I which is the overlap of 2 intervals.

- The interval defined by first and last neighbors of u in clockwise order in the region containing (X, Y) .
- The interval defined by the first and last vertices of Y in clockwise order in the Monge group (X, Y) .

The 2-D Range search tree returns a boundary vertex v which has a layer number $L(u) + 1$ and lies in I and also deletes v from Y in the corresponding Monge group. As a pre-processing step before DFS is performed, the intervals for each vertex u is computed in all the Monge groups (X, Y) where u lies in X . The intervals construction is detailed in Section 4.3.2. It is possible that a vertex v returned by the dynamic 2-D Range search tree doesn't have an edge from u . This can be checked in $O(\log r)$ time. If v is a neighbor, it is added to the stack only if it is unvisited vertex and the partial DFS proceeds from v . If v is not a neighbor of u or if it has already been marked visited in some other Monge group by partial DFS, the Range search trees are queried till an unvisited neighbor v' with $L(v') = L(u) + 1$ is found. Any vertex v returned by Range search tree can be removed from the Range search tree irrespective of whether it is a neighbor of u or not. This is justified in Lemma 19 where we show that if the vertex v returned by Range search tree is not a neighbor of u , it cannot be a neighbor of any vertex in X of the same Monge group. Because of vertex deletions, the 2-D Range trees are dynamic in nature. However, no re-balancing is required after deleting a vertex. If no valid outgoing edge is found from u , partial DFS backtracks by popping u from the stack and continues search from the parent of u . This condition for backtracking is same as described in *FINDAUGPATH* Procedure (section 3.5). The edges of type $(b_j, \mathcal{K}_j)$ and $(\mathcal{K}_j, a_j)$ are handled exclusively as there are only $O(n/\sqrt{r})$ in number. The construction of 2-D Range search trees is described in section 4.3.3.

4.3.2 Interval Construction

In FastBFS/FR-Dijkstra, for each vertex $x \in X$, the intervals of vertices in Y in the Monge group (X, Y) is updated online as new vertices are activated. For FastDFS, we construct the intervals as pre-processing step just once for each vertex in each Monge group and then use these intervals to do DFS efficiently.

For a vertex u in region R_j^H , its neighbors are defined on each hole/face in circular order, with one neighbor list per hole/face. For the sake of simplicity, we consider only one neighbor list $N(u, R_j^H)$ for each vertex per region. We use Fakcharoenphol and Rao's technique [9] to handle a constant number of holes. We know that each Monge group (X, Y) maintains a contiguous set of vertices in circular order in both X and Y . Given the first (N_1) and last vertex (N_L) of $N(u, R_j^H)$ of $u \in X$ in clockwise order, we can find the range of overlapping interval of vertices of $N(u, R_j^H)$ in Y in $O(\log |Y|)$ time. Let $|Y| = k$. Each vertex can have at most 2 overlapping intervals of its neighbors in each Monge group as shown in Figure 4.1. Note that the overlapping cases shown are not exhaustive. Computing the intervals for all the vertices in all the Monge groups takes $O((n/\sqrt{r}) \log^2 n)$ time.

We now redefine *Monge Crossing Property* in terms of connectivity instead of the shortest path. Consider a bipartite Monge graph (X, Y) in region R'_k with intervals defined for each vertex $x \in X$. Consider two vertices x_i and x_j with their intervals defined as I_i and I_j respectively. Then the following lemma holds true.




Figure 4.1: (a) Single overlap, (b) two overlapping intervals, (c) No overlap

Lemma 19. *If vertex $v \in I_i \cap I_j$ and $v \in N(x_j, R_k^H)$, then $v \in N(x_i, R_k^H)$ and vice versa.*




Figure 4.2: Monge Crossing Property for Connectivity

Proof. When 2 edges cross in the bipartite Monge graph, their projection share a common vertex as shown in Figure 4.2 (Common edge in case of a bipartite graph). x_j reaches v through u and x_i also has a path to u implying it also has a path to v . ■

In other words, given a Monge group (X, Y) , we can say that if $v \in Y \cap I_i$, but $v \notin N(x_i, R_k^H)$, then no vertex $\in X$ has an edge to v .

4.3.3 Range search tree

Besides the neighborhood interval construction for all vertices in all bipartite Monge groups, we also maintain a *2-D Range Search tree* (RST_i) for vertices in Y in each Monge group (X_i, Y_i) . The 2-D Range tree has vertices of Y stored in the cyclic order in primary data structure and has the vertices sorted according to their layer numbers in the secondary data structure.




Figure 4.3: 2-D Range Search Tree returns a vertex with specific layer number in the given interval

Each RST_i has a construction time of $O(|Y| \log^2 |Y|)$ with an overall construction time of $O((n/\sqrt{r}) \log^3 r)$ which is also $O((n/\sqrt{r}) \log^3 n)$. Total space usage per RST is $O(|Y| \log |Y|)$ and the total space used for all the RSTs is $O((n/\sqrt{r}) \log^2 r)$ or $O((n/\sqrt{r}) \log^2 n)$. Given a vertex u and its interval in the Monge group (X_i, Y_i) , the RST_i returns a vertex v such that $L(v) = L(u) + 1$ in $O(\log^2 |Y_i|)$ time. Deleting a vertex from RST has the same complexity as query time i.e. $O(\log^2 |Y_i|)$. With Fractional cascading, we can improve the construction time per RST_i to $O(|Y_i| \log |Y_i|)$ with query time of $O(\log |Y_i|)$. Overall construction time of all RSTs can be improved to $O((n/\sqrt{r}) \log^2 n)$.

4.3.4 Algorithm Implementation

FastDFS uses a stack in place of a queue which was used in BFS. For boundary to boundary edges, we use the Monge groups and their range search tree to find the next candidate in DFS search as shown in line 18. Given vertex u , the RST_i returns vertex v s.t. $L(v) = L(u) + 1$ and v lies in the range of overlap of intervals defined by $\{\text{first and the last element of } N(u)\}$ in the region and $\{\text{the first and last element of } Y_i\}$. It is possible that v may not have an edge from u . This can be checked in $O(\log n)$ time by doing a binary search for v in the Neighbor list of u which has vertices stored in cyclic order. Search is done in the region that the bipartite Monge group is a part of. Line 19 shows that v is inserted into the stack only after checking its connectivity from u in the current Monge group and if it has not already been visited elsewhere. If there is no connectivity from u to v , we can also infer that there can be no connectivity to v from any vertex in X_i corresponding to the current Monge

group. Therefore, the vertex v can be removed from the Range search tree. By removing a vertex returned by Range search tree, we ensure that the vertex is never returned again in that Monge group. $\mathcal{V}'$ is the set of all boundary vertices in BFS layered graph reachable from some free vertex of type B in H . Just like in BFS, the $(\mathcal{K}_j, a_j)$ edges (see line 15) are handled exclusively. A list of edges of type $(\mathcal{K}_j, a_j)$ are maintained for each boundary vertex and updated after every augmentation. This can be done during construction of edges of the region in H . The conditions for backtrack are the same as described in section 3.5 (*FINDAUGPATH Procedure*).

Algorithm 3 DFS in FR-Dijkstra Style

```

1: procedure FASTDFS( $H$ )
2:    $S(\text{visited}) = \emptyset$ 
3:   while  $S \cap B_H^F \neq B_H^F$  do
4:     if Stack.EMPTYP() then
5:       Stack.PUSH(a free vertex  $b$  from  $B_H^F \setminus S$ )
6:       if  $b \in \bigcup_j \mathcal{K}_j \cup B_F$  then
7:          $S = S \cup \{b\}$ 
8:       else
9:         while  $\exists$  an edge  $(b, v)$  of type  $(b_j, \mathcal{K}_j)$  do
10:          if  $v \notin S$  then
11:            Stack.PUSH( $v$ )
12:             $S = S \cup \{v\}$ 
13:            jump to line 14
14:       $u \leftarrow \text{Stack.TOP}()$ 
15:      if  $\exists$  edge  $(u, v)$  of type  $(\mathcal{K}_j, a_j)$  then
16:        Stack.PUSH( $v$ )
17:        Jump to line 28
18:      for each  $(X_i, Y_i)$  s.t  $u \in X_i$  do
19:        if  $RST_i.QUERY(u)$  returns a vertex  $v$  and  $v \in N(u) \setminus S$  then
20:          Stack.PUSH( $v$ )
21:           $S = S \cup \{v\}$ 
22:          Remove the vertex  $v$  from  $RST_i$ 
23:          Jump to line 28
24:        else
25:          if  $RST_i.QUERY(u)$  returns a vertex  $v$  and  $(v \in S \text{ or } v \notin N(u))$  then
26:            Remove the vertex  $v$  from  $RST_i$ 
27:            Jump to line 19
28:      if Stack.TOP()  $\in A_H^F$  then ▷ Augmenting path found
29:        Pop All elements of stack and perform augmentation.
30:      else
31:        if (Stack.TOP() ==  $u$ ) or (L(Stack.TOP()) == LastLayer) then
32:          if  $u$  is of type  $b_j$  then
33:             $S = S \cup \{u\}$ 
34:            Stack.POP() ▷ Backtrack
35:    return

```

4.3.5 Analysis of FastDFS

. Each query to RST_i takes $O(\log |Y_i|)$ time. Each vertex is in at most $O(\log |Y_i|)$ Monge groups per region and on average, in $O(\log r)$ Monge groups in entire graph H . For querying all the Monge groups (X_i, Y_i) which have a vertex u in X_i takes amortized time $O(\log^2 n)$. However, by removing vertex x from X when there is no valid $y \in Y$ as the next candidate for DFS search, we can ensure that $O(\log^2 n)$ query time can be reduced to $O(\log n)$. Exploring all the $(\mathcal{K}_j, a_j)$ edges takes $O(n/\sqrt{r})$ time. Overall, FastDFS runs in $O((n/\sqrt{r}) \log^2 n)$.

Combining FastBFS and FastDFS, we get a total run time of BFS+DFS to be $O(n^{6/5} \log^2 n)$. Total time taken for augmentation and re-computation of edges in H takes $O(n^{6/5} \log^4 n)$ time. The overall complexity of our maximum cardinality matching for planar bipartite graph algorithm is $O(n^{6/5} \log^4 n)$. The power on log term can be reduced from 4 to 2 using faster connectivity oracles like [21] or [29]. Thus the complexity of our algorithm becomes $O(n^{6/5} \log^2 n)$.

4.4 Alternate BFS

In this section, we show that BFS can be done in a similar fashion as FastDFS using the intervals (section 4.3.2) and Range search trees (section 4.3.3). Unlike FastDFS, we need only 1-D Range search tree (RST^*) for each bipartite Monge group to do FastBFS. We don't need a secondary tree which sorts vertices by layer numbers. Given vertex u , the RST_i^* returns

vertex v s.t. v lies in the range of overlap of intervals defined by first and the last element of $N(u)$ in the region and the first and last element of Y_i .

Pseudo code for Alternate BFS is shown in Algorithm 4. Lines 3 and 9 handle the initialization of layer numbers to free vertices $\in B_H^F$. Exhaustive BFS is done from a vertex u in all Monge groups (X, Y) where $u \in X$ as shown in line 28. Vertex v is added to the queue $\mathcal{Q}$ only if it belongs to $N(u, R_j^H)$ and the vertex v is removed from the Range search trees of all the Monge groups (X, Y) where $v \in Y$. If $v \notin N(u, R_j^H)$, remove v from just the range search tree of the current Monge group. Edges of type $(\mathcal{K}_j, a_j)$ are handled exclusively in line 23. FastBFS terminates when the queue $\mathcal{Q}$ becomes empty.

Overall run-time of this FastBFS is same as FastDFS which is $O(n/\sqrt{r} \log^2 n)$.

Algorithm 4 Alternate BFS

```

1: procedure FASTDFS( $H$ )
2:    $\forall v \in H, L(v) = \infty, LastLayer = -1, S(visited) = \emptyset$ 
3:   for  $v \in \bigcup_j \mathcal{K}_j \cap B_F$  do ▷ Free boundary vertices of type B
4:      $L(v) = 0$ 
5:      $\mathcal{Q}.PUSH(v)$ 
6:      $S = S \cup \{v\}$ 
7:     for each  $(X_i, Y_i) \in H$  s.t.  $v \in Y_i$  do
8:        $RST_i^*.REMOVE(v)$ 
9:   for  $v \in \bigcup_j b_j$  do ▷ Free internal vertices of type B
10:     $L(v) = 0$ 
11:    for  $u \in N(v, R_j^H)$  do
12:      if  $u \notin S$  then
13:         $L(u) = 1$ 
14:         $\mathcal{Q}.PUSH(u)$ 
15:         $S = S \cup \{u\}$ 
16:        for each  $(X_i, Y_i) \in H$  s.t.  $u \in Y_i$  do
17:           $RST_i^*.REMOVE(u)$ 
18:  while  $!\mathcal{Q}.EMPTY()$  do
19:     $u \leftarrow \mathcal{Q}.Top()$ 
20:    if  $L(u) == LastLayer$  then
21:       $\mathcal{Q}.POP()$ 
22:      continue
23:    while  $\exists$  an edge  $(u, v)$  of type  $(\mathcal{K}_j, a_j)$  do
24:      if  $v \notin S$  then
25:         $L(v) = L(u) + 1$ 
26:         $LastLayer = L(v)$ 
27:         $S = S \cup \{v\}$ 
28:      for each  $(X_i, Y_i)$  s.t.  $u \in X_i$  do
29:        if  $RST_i^*.QUERY(u)$  returns a vertex  $v$  and  $v \in N(u)$  then
30:           $L(v) = L(u) + 1$ 
31:          if  $v \in A_H^F$  then
32:             $LastLayer = L(v)$ 
33:           $\mathcal{Q}.PUSH(v)$ 
34:           $S = S \cup \{v\}$ 
35:          for each  $(X_j, Y_j) \in H$  s.t.  $v \in Y_j$  do
36:             $RST_j^*.REMOVE(v)$ 
37:          Jump to line 29
38:        else
39:          if  $RST_i^*.QUERY(u)$  returns a vertex  $v$  and  $(v \notin N(u))$  then
40:             $RST_i^*.REMOVE(v)$ 
41:            Jump to line 29
42:       $\mathcal{Q}.POP()$ 
43:  return

```

Chapter 5

Conclusion and Future Work

We presented a $\tilde{O}(n^{6/5})$ algorithm for finding maximum cardinality matching in planar bipartite graphs. We achieved this using a sparsification based approach where we reduce the actual graph G to a sparser graph H comprising of just the boundary vertices from r -division and special internal vertices without losing information needed for matching. The edges in the sparser graph H were constructed by maintaining dense distance graph (DDG) for each region of r -division. Motivated by FR-Dijkstra [9], we came up with a faster algorithm for BFS and DFS which runs in time proportional to number of vertices in H i.e. $O(n/\sqrt{r})$ instead of order of number of edges $O(n)$. We used a balanced value of r to ensure that the graph is sparse enough and at the same time, each region has a small number of vertices. As future work, we believe that the sparsification approach introduced in this work can be extended to following problems.

Near Linear time Maximum Cardinality Matching in Bipartite Planar Graphs

As stated before, our algorithm is not the fastest known solution. Borradaile et al. [4] showed that this problem can be solved in $O(n \log^3 n)$. Can the algorithm be improved to perform in near linear time if we could recompute induced internal edges in each region efficiently after augmentation? Currently, we compute all the edges in every region that the augmenting path goes through, but this is certainly an overkill.

Maximum Cardinality Matching in General Planar Graphs Most of the properties proved for our algorithm also extend to general (non bipartite) planar graphs. $O(n^{3/2})$ ($O(n^\omega)$ is fastest) is the best bound known so far for combinatorial algorithm for general matching in planar graphs, as a result of $O(m\sqrt{n})$ algorithm for arbitrary graphs by Micali and Vazirani [25],[30]. The complexity of general graph matching algorithms stems from the odd length alternating cycles which are absent in bipartite graphs. Nobert Blum [2],[3] talks about transforming general graph G to a bipartite graph G' and computing maximum matching by applying Hopcroft-Karp algorithm on G' . We need to verify if this reduction of general matching to bipartite matching along with our sparsification approach can help improve the complexity of general matching.

Maximum Weighted Matching in Bipartite Planar Graphs At the time of this writing, it has been proved that the sparsification approach can be adapted in weighted setting and improvement to $\tilde{O}(n^{4/3})$ has been achieved. Again, just like $\tilde{O}(n^{4/3})$, $\tilde{O}(n^{6/5})$ or even near-linear time may also be possible in weighted matching, bridging the gap between

the complexity of weighted and unweighted matching in planar bipartite graphs.

Approximate Bottleneck Matching Another important question is whether this sparsification approach can be extended to non-planar graphs which have sub-linear separator size. By using approximations and clustering, it is possible to reduce bottleneck matching problem to a sparse graph matching with vertices on grid centers. It remains to be seen if ϵ -approximation for bottleneck matching on non-planar graphs is plausible with our sparsification approach.

List of Notations

$\mathbf{G}$ - bipartite planar graph whose matching is to be computed

$\mathbf{G}_M$ - residual graph of G

$\mathbf{M}$ - current matching in G

$\mathbf{M}^*$ - maximum matching in G

$\mathbf{R}_j$ - a region in r -division of G/G_M

$\mathbf{V}_j$ - set of vertices in region R_j

$\mathbf{E}_j$ - set of edges in region R_j

$\mathcal{K}_j$ - set of boundary vertices in region R_j

$\mathbf{D}_j$ - dense distance graph constructed from R_j

$(\mathbf{X}, \mathbf{Y})$ - a bipartite group in Monge decomposition

$\mathbf{H}$ - compressed residual graph constructed from G_M

$\mathbf{B}_F$ - set of free vertices of type B in G_M

$\mathbf{A}_F$ - set of free vertices of type A in G_M

$\mathbf{V}$ - vertex set of G

$\mathbf{V}_H$ - vertex set of H

$\mathbf{R}_j^H$ - a region in H constructed from R_j

$\mathbf{E}_j^H$ - set of edges in R_j^H

$\mathbf{b}_j$ - free internal vertex of type B in R_j^H

$\mathbf{a}_j$ - free internal vertex of type A in R_j^H

$\mathbf{B}_H$ - set of vertices of type B in H

$\mathbf{A}_H$ - set of vertices of type A in H

$\mathbf{B}_H^F$ - set of free vertices of type B in H

$\mathbf{B}_H^F$ - set of free vertices of type A in H

$\mathbf{N}(\mathbf{u}, \mathbf{R}_j^H)$ - set of vertices which have an incoming edge from u in R_j^H (neighbors of u)

$(\mathbf{u}, \mathbf{v})$ - a directed edge from vertex u to vertex v in G_M or H as specified in the context

$\mathbf{P}$ - a directed path in G_M

$\mathbf{P}'$ - a directed path in H whose projection in G_M is P

$\mathbf{L}(\mathbf{u})$ - layer number assigned to vertex u by BFS in the current iteration

$\mathbf{S}(\mathbf{u})$ - length of the shortest path to a vertex u from any free vertex in B_H^F

$\mathbf{S}'(\mathbf{u})$ - length of the shortest path from a vertex u to any free vertex in A_H^F

Δ - total length of all augmenting paths found in H by FINDAUGPATH

$\mathbf{RST}_i$ - 2-D Range search tree constructed from bipartite group (X_i, Y_i) for efficient DFS

$\mathbf{RST}_i^*$ - 1-D Range search tree constructed from bipartite group (X_i, Y_i) for efficient BFS

without using FR-Dijkstra

Bibliography

- [1] C. Berge. Two theorems in graph theory. *Proceedings of the National Academy of Sciences*, 43(9):842–844, 1957.
- [2] N. Blum. A new approach to maximum matching in general graphs. *Automata, Languages and Programming*, pages 586–597, 1990.
- [3] N. Blum. Maximum matching in general graphs without explicit consideration of blossoms revisited. *arXiv preprint arXiv:1509.04927*, 2015.
- [4] G. Borradaile, P. N. Klein, S. Mozes, Y. Nussbaum, and C. Wulff-Nilsen. Multiple-source multiple-sink maximum flow in directed planar graphs in near-linear time. In *Foundations of Computer Science (FOCS), 2011 IEEE 52nd Annual Symposium on*, pages 170–179. IEEE, 2011.
- [5] W. H. Cunningham and A. Marsh. A primal algorithm for optimum matching. *Polyhedral Combinatorics*, pages 50–72, 1978.

- [6] M. D. Devine. Note—a model for minimizing the cost of drilling dual completion oil wells. *Management Science*, 20(4-part-i):532–535, 1973.
- [7] J. Edmonds and E. L. Johnson. Matching: A well-solved class of integer linear programs. In *in: Combinatorial structures and their applications (Gordon and Breach. Citeseer, 1970.*
- [8] J. Edmonds and R. M. Karp. Theoretical improvements in algorithmic efficiency for network flow problems. *Journal of the ACM (JACM)*, 19(2):248–264, 1972.
- [9] J. Fakcharoenphol and S. Rao. Planar graphs, negative weight edges, shortest paths, and near linear time. *Journal of Computer and System Sciences*, 72(5):868–889, 2006.
- [10] G. N. Frederickson. Fast algorithms for shortest paths in planar graphs, with applications. *SIAM Journal on Computing*, 16(6):1004–1022, 1987.
- [11] L. R. Ford and D. R. Fulkerson. Maximal flow through a network. *Canadian journal of Mathematics*, 8(3):399–404, 1956.
- [12] L. R. Ford Jr and D. R. Fulkerson. *Flows in networks*. Princeton university press, 2015.
- [13] M. Fujii, T. Kasami, and K. Ninomiya. Optimal sequencing of two equivalent processors. *SIAM Journal on Applied Mathematics*, 17(4):784–789, 1969.
- [14] A. Gerards. Matching. *Handbooks in operations research and management science*, 7:135–224, 1995.

- [15] J. E. Hopcroft and R. M. Karp. A $n^{5/2}$ algorithm for maximum matchings in bipartite graphs. In *Switching and Automata Theory, 1971., 12th Annual Symposium on*, pages 122–125. IEEE, 1971.
- [16] M. Iri, K. Murota, and S. Matsui. Heuristics for planar minimum-weight perfect matchings. *Networks*, 13(1):67–92, 1983.
- [17] M. Iri and A. Taguchi. The determination of the pen movement of an xy-plotter and its computational complexity. In *Proc. Spring Conference of the Operations Research Society of Japan*, volume 8, pages 204–205, 1980.
- [18] H. Kaplan, S. Mozes, Y. Nussbaum, and M. Sharir. Submatrix maximum queries in Monge matrices and Monge partial matrices, and their applications. In *Proceedings of the twenty-third annual ACM-SIAM symposium on Discrete Algorithms*, pages 338–355. SIAM, 2012.
- [19] P. Klein and S. Mozes. Optimization algorithms for planar graphs. <http://planarity.org/>, 2014.
- [20] P. Klein, S. Rao, M. Rauch, and S. Subramanian. Faster shortest-path algorithms for planar graphs. In *Proceedings of the twenty-sixth annual ACM symposium on Theory of computing*, pages 27–37. ACM, 1994.
- [21] P. N. Klein. Multiple-source shortest paths in planar graphs. In *SODA*, volume 5, pages 146–155, 2005.

- [22] P. N. Klein, S. Mozes, and C. Sommer. Structured recursive separator decompositions for planar graphs in linear time. In *Proceedings of the forty-fifth annual ACM symposium on Theory of computing*, pages 505–514. ACM, 2013.
- [23] R. J. Lipton and R. E. Tarjan. A separator theorem for planar graphs. *SIAM Journal on Applied Mathematics*, 36(2):177–189, 1979.
- [24] R. J. Lipton and R. E. Tarjan. Applications of a planar separator theorem. *SIAM journal on computing*, 9(3):615–627, 1980.
- [25] S. Micali and V. V. Vazirani. An $o(\sqrt{V}e)$ algorithm for finding maximum matching in general graphs. In *Foundations of Computer Science, 1980., 21st Annual Symposium on*, pages 17–27. IEEE, 1980.
- [26] G. L. Miller. Finding small simple cycle separators for 2-connected planar graphs. *Journal of Computer and System Sciences*, 32(3):265–279, 1986.
- [27] M. Mucha and P. Sankowski. Maximum matchings via gaussian elimination. In *Foundations of Computer Science, 2004. Proceedings. 45th Annual IEEE Symposium on*, pages 248–255. IEEE, 2004.
- [28] M. Mucha and P. Sankowski. Maximum matchings in planar graphs via gaussian elimination. *Algorithmica*, 45(1):3–20, 2006.
- [29] M. Thorup. Compact oracles for reachability and approximate distances in planar digraphs. *Journal of the ACM (JACM)*, 51(6):993–1024, 2004.

- [30] V. V. Vazirani. A simplification of the mv matching algorithm and its proof. *arXiv preprint arXiv:1210.4594*, 2012.