

References

1. Barefoot, A.C., Jr. 1963. Selected wood characteristics of young yellow poplar. Part II: Shrinkage of normal and abnormal wood. *Forest Prod. J.* 13(10): 443-448.
2. Beutler, A.J. 1965. An infrared backscatter moisture gage. *Tappi*, 48 (9): 490--493.
3. Busker, L.H. 1968. Measurement of water content above 30% by microwave absorption methods. *Tappi*, 51 (8): 348--453.
4. Chen, Y., Choong, E.T. & Wetzel, D.M. 1996. A numerical analysis technique to evaluate the moisture-dependent diffusion coefficient on moisture movement during drying. *Wood and Fiber Science*, 28 (3): 338--345.
5. Cloutier, A. & Fortin, Y. 1993. A model of moisture movement in wood based on water potential and the determination of the effective water conductivity. *Wood Science and Technology* 27(2): 95-114.
6. Connors, T.E. & McLain, T.E. 1988. Modeling moisture gradient effects on bending properties. *Wood and Fiber Science*, 20 (2): 226--242.
7. Danko, P. 1994. Microwave method for the measurement of wood moisture content. *Drev'arsky v'yskum*, 39 (4): 35--43.
8. Dennis, J.R. & Beall, F.C. 1977. Evaluation of a new portable radiofrequency moisture meter on lumber with drying gradients. *Forest Products Journal*, 27 (8): 24--29.
9. Feng, Y. & Suchsland, O. 1993. Improved technique for measuring moisture content gradients in wood. *Forest Products Journal*, 43 (3): 56--58.
10. Gorvad, M.R. & Arganbright, D.G. 1980. Comparison of methods for preparation of moisture content gradient sections. *Wood and Fiber*, 12 (1): 7--11.
11. Hart, C.A. 1964. Principles of moisture movement in wood. *Forest Products Journal*, 14 (5): 207--214.

12. Hattori, Y. & Kanagawa, Y. 1985. Non-destructive measurement of moisture distribution in wood with a medical x-ray CT scanner. *Journal of the Japan Wood Research Society*, 31 (12): 974--989.
13. Resch, H. & Barton, A.E. 1963. Moisture content determination for wood with highly volatile constituents. *Forest Products Journal*, 13 (11): 481--482.
14. James, W.L., Yen, Y. & King R.J. 1985. A microwave method for measuring moisture content, density, and grain angle of wood. US Dept. of Agriculture, Forest Service, Forest Products Laboratory FPL 0250.
15. King, R.J. & Basual, J.C. 1993. Measurement of basis weight and moisture content of composite boards using microwaves. *Forest Products Journal*, 43 (9): 15--22.
16. Kotok, E.S., Lowery, D.P. & Jensen, C.E. 1989. Surface temperature as an indicator of wood moisture content during drying. *Forest Products Journal*, 19 (9): 80--82.
17. Li, G. & Plumb, O.A. 1994. The effect of heterogeneity on wood drying. Part II: Experimental results. *Drying Technology* 12(8): 2003-2026.
18. Loos, W.E. 1961. Gamma-Ray absorption and wood moisture content and density. *Forest Products Journal*, 11 (3): 145--149.
19. Loos, W.E. 1965. Determination moisture content and density by Nuclear Radiation Techniques. *Forest Products Journal*, 15 (3): 102--106.
20. Magnusson, H., Eriksson, L. & Andersson, L.O. 1972. Measurement of moisture content in wood and pulp samples using the NMR-technique. *Swedish Paper Journal*, 75 (15): 619--622.
21. McMillen, J.M. 1955. Drying stresses in red oak. *Forest Products Journal*, 5 (1): 71--76.
22. Moxin, M.M. 1993. Improvement of an opto-thermal technique for wood. *Wood Science and Technology*, 28: 53--58.
23. Mon-lin Kuo et al. 1988. Applications of infrared photoacoustic spectroscopy for wood samples. *Wood and Fiber Science*, 20 (1): 132--145.

24. Olson, J.R., Arganbright, D.G. & Prussin, S.G. 1982. Use of an error analysis for evaluation of a dual-energy gamma radiation method for wood moisture content measurement. *Wood Science*, 15 (1): 1--13.
25. Parshin, A.J. & Zeeuw, Carl de. 1980. Textbook of wood technology--structure, identification, properties, and uses of the commercial woods of the United States and Canada. 4th edition. Chapter 6.
26. Rice, R.W. 1988. Mass transfer, creep and stress development during the drying of red oak. Ph.D dissertation, 153 pages. Virginia Polytechnique Institute and State University, Blacksburg, Virginia.
27. Shupe, T.F. , Choong, E.T. & Gibson, M.D. 1995. Differences in moisture content and shrinkage between outerwood, middlewood and core wood of two yellow-poplar trees. *Forest Prod. J.* 45(9): 85-90.
28. Troughton, G.E. & Clarke, M.R. 1987. Development of a new method to measure moisture content in unseasoned veneer and lumber. *Forest Products Journal*, 37 (1): 13--19.
29. Walters, E.O. 1972. Evaluation of microwave and nuclear moisture gage for establishing water content segregation in Southern Pine green veneer and lumber. *Forest Products Journal*, 22 (2): 52--58.
30. Wang, Hsiu Hwa, & Youngs, Robert L. 1996. Drying stress and check development in the wood of two oaks. *IAWA Journal*, 17 (1): 15--30.
31. William, B.S. 1992. Determining moisture content in eastern redcedar. *Forest Products Journal*, 42 (7): 67--69.
32. Wu, Q. & Milota, M.R. 1995. Shrinkage and set in drying of 4 by 4 Douglas-fir lumber. *Forest Prod. J.* 45(5): 59-63.