

References

- American Forest and Paper Association (1996). *Load and Resistance Factor Design Manual for Engineered Wood Construction*, American Forest & Paper Association, Washington, D.C.
- American Forest and Paper Association (1997a). *National Design Specification for Wood Construction*, American Forest & Paper Association, Washington, D.C.
- American Forest and Paper Association (1997b). *Commentary on the National Design Specification for Wood Construction*, American Forest & Paper Association, Washington, D.C.
- American Forest and Paper Association (1999). *General Dowel Equations for Calculating Lateral Connection Values – Technical Report 12*, American Forest and Paper Association, 1999, 18 pp.
- American Railway Engineering Association (1905). “Manual of Recommended Practice for Railway Engineering and Maintenance of Way,” Press of Blakely printing co., Chicago, Ill.
- American Society for Testing and Materials (1988). “D 2016-74 (Reapproved 1983): Standard Test Methods for Moisture Content of Wood,” in *1988 Annual Book of ASTM Standards*, Section 4, Vol. 04.09: Wood, ASTM, West Conshohocken, Pennsylvania.
- American Society for Testing and Materials (1998). “C 209-98: Standard Test Methods for Cellulosic Fiber Insulating Board,” *Annual Book of Standards*, vol. 04.06. ASTM, West Conshohocken, Pennsylvania.
- American Society for Testing and Materials (1998). “F 1575: Standard test method for determining bending yield moment of nails,” *Annual Book of Standards*, vol. 01.08. ASTM, West Conshohocken, Pennsylvania.
- American Society for Testing and Materials (1998). “F1667-97: Standard Specification for Driven Fasteners: Nails, Spikes, and Staples,” *Annual Book of ASTM Standards*, vol. 15.08 *Fasteners*. ASTM, West Conshohocken, Pennsylvania.
- American Society for Testing and Materials (1999). “D 1761-88 (Reapproved 1995): Standard Test Methods for Mechanical Fasteners in Wood,” in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.
- American Society for Testing and Materials (1999). “D 2395-93 (Reapproved 1997): Standard Test Methods for Specific Gravity of Wood and Wood-Based Materials,”

in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.

- American Society for Testing and Materials (1999). "D 5652-95: Standard Test Methods for Bolted Connections in Wood and Wood-Base Products," in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.
- American Society for Testing and Materials (1999). "D 5764-97a: Standard Test Method for Evaluating Dowel-Bearing Strength of Wood and Wood-Based Products," in *1999 Annual Book of ASTM Standards*, Section 4, Vol. 04.10: Wood, ASTM, West Conshohocken, Pennsylvania.
- ANSI / AHA A135.4-1995 (1995). *American National Standard for Basic Hardboard*. American Hardboard Association, Palatine, IL.
- ANSI / AHA A135.6-1998 (1998). *American Hardboard Association Standard for Hardboard Siding*. American Hardboard Association, Palatine, IL.
- Anderson, G.T. (2001). "Experimental Investigation of Group Action Factor for Bolted Wood Connections," *Masters Thesis*, Civil Engineering Department, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, December, 2001.
- Aune, P. and Patton-Mallory, M. (1986). "Lateral Load-Bearing Capacity of Nailed Joints Based on the Yield Theory: Experimental Verification," *Research Paper FPL 470, USDA, Forest Service, Forest Products Laboratory*, Madison, Wisconsin, 1986.
- Bonnicksen, L.W. and Suddarth, S.K. (1965). "Structural Reliability Analysis of Wood Load-Sharing System," Paper No. 82, Philadelphia, PA, American Society for Testing and Materials, Fifth Pacific Area National Meeting.
- Boresi, A.P., Schmidt, R.J., and Sidebottom, O.M. (1993). "Advanced Mechanics of Materials," 5th ed. John Wiley & Sons, New York, NY.
- Chou, Chun and Polensek, Anton. (1987). "Damping And Stiffness of Nailed Joints: Response to Drying" *Wood and Fiber Science*, 19(1), 1987, pp. 48-58.
- Dolan, J.D. (1989). "The Dynamic Response of Timber Shear Walls," *PhD Dissertation*, University of British Columbia, Vancouver, British Columbia.
- Doyle, D.V. and Scholten, J.A. (1963). "Performance of Bolted Joints in Douglassa-Fir," *U.S. Forest Service Research Paper FPL 2*, USDA, Forest Products Laboratory, Forest Service, May 1963.
- Fahlbusch, H. (1949). "A Contribution to the Problem of Bearing Strength of Bolts in Wood Under Static Loads," Report No. 49-09, *Institute for Mechanical*

Construction and Carpentry, Braunschweig, Germany. (Translation No. 218, Research Information Service, translated for USDA Forest Service, Forest Products Laboratory, New York, May 1955).

- Foliente, G. (1993). "Stochastic Dynamic Response of Wood Structural Systems," *PhD Dissertation*, Wood Science and Forest Products Department, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, December, 1993.
- Foliente, G. (1998). "Design of Timber Structures Subjected to Extreme Loads," *Prog. Struct. Eng. Mater.*, 1(3) 236-244.
- Foschi, R.O. (1974). "Load-Slip Characteristics of Nails," *Wood Science*, 7(1), 69-76.
- Foschi, R.O., Folz, B.R. and Yao, F.Z. (1989). "Reliability-based Design of Wood Structures," *Structural Research Series, Report No. 34*, Department of Civil Engineering, University of British Columbia, Vancouver, Canada, 1989.
- Foschi, R.O., Yao, F. and Rogerson, D. (2000). "Determining Embedment Response Parameters from Connector Tests," in *Proceedings of the World Conference in Timber Engineering, Whistler, British Columbia, Canada*.
- Girhammar, U.A. and Andersson, H. (1988). "Effect of Loading Rate on Nailed Timber Joint Capacity," *Journal of Structural Engineering*, ASCE, 114(11), 2439-2456.
- Goodell, H.R. and Phillips, R.S. (1944). "Bolt-Bearing Strength of Wood and Modified Wood: Effects of Different Methods of Drilling Bolt Holes in Wood and Plywood," *Report No. 1523, USDA Forest Service, Forest Products Laboratory*, Madison, WI.
- Grenoble, H.S. (1925). "Bearing Strength of Bolts in Wood," Tech. Note 147. Navy Department, Bureau of Aeronautics, Washington DC.
- Gutshall, S.T. and Dolan, J.D. (1994). "Monotonic and Cyclic Short-Term Performance of Nailed and Bolted Timber Connections," VPI&SU Department of Wood Science and Forest Products, Brooks Forest Products Research Center, Timber Engineering Center, Blacksburg, VA.
- Heine, C.P. (2001). "Cyclic Response of Multiple-Bolt Connections," *PhD Dissertation*, Wood Science and Forest Products Department, Virginia Polytechnic Institute and State University, Blacksburg, Virginia, August 2001.
- Heine, C.P. and Dolan, J.D. (2001). "A New Model to Predict the Load-Slip Relationship of Bolted Connections in Timber," *Wood and Fiber Science*, 33(4), 534-549.

- Humphrey, Phillip E. and Ostman, Larry J. (1989). "Bolted Timber Connections: Part II. Bolt Bending and Associated Wood Deformation," *Wood and Fiber Science*, 21(4), 1989, pp. 354-366.
- Johansen, K.W. (1949). "Theory of Timber Connections," *International Association for Bridge and Structural Engineering*, 9: 249-262.
- Kojis, Daniel D. and Postweiler, R.H. (1953). "Allowable Loads for Common Bolts at Various Angles to the Grain for Southern Yellow Pine," *Journal of the Forest Products Research Society*, 3(3):21-26.
- Koponen, S. (1992). "Modelling the Creep of Dowel Type Joints," *IUFRO S5.02, Timber Engineering: Proceedings of the 1992 Conference, Bordeaux and Nancy, France, August 1992*, 189-202.
- Kuenzi, E.W. (1955). "Theoretical Design of a Nailed or Bolted Joint Under Lateral Load," *Research Paper No. D1951*, USDA, Forest Service, Forest Products Laboratory, 1951.
- Liu, J.Y. and Soltis, L.A. (1984). "Lateral Resistance of Nailed Joints – A Test Method," *Forest Products Journal*, 34(1), 55-60.
- Mack, J.J. (1960). "The Strength of Nailed Timber Joints I.," *Division of Forest Products Technological Paper No. 9*, Division of Forest Products Commonwealth Scientific and Industrial Research Organization, Melbourne, Australia, 1960.
- McLain, T.E., Pellicane, P., Soltis, L., Wilkinson, T.L., and Zahn, J. (1990). "Comparison of EYM Predicted Yield Loads and Current ASD Loads for Nails, Bolts, and Screws," *National Forest Products Association*, Washington, DC.
- McLain, T.E. and Thangjitham, S. (1983). "Bolted Wood-Joint Yield Model," *Journal of Structural Engineering*, ASCE, 109(8), 1820-1835.
- Moller, T. (1950). "En Ny Method for Berakning av Spikforband: New Method of Estimating the Bearing Strength of Nailed Wood Connections," (in Swedish with English Translation). No. 117. *Chalmers Tekniska Hogskolas Handlingar*, Gothenburg, Sweden.
- Newlin, J.A. (1939). "Bearing Strength of Wood at Angle to the Grain," *Report No. R1203*, USDA Forest Service, Forest Products Laboratory, Madison, WI.
- Osgood, W.R. (1928). "Comparative Stress on Wood Surfaces Inclined to Grain," *Engr. News Record*, 100(6), 243-244.
- Ott, R.L. and Michael Longnecker (2001). "Statistical Methods and Data Analysis," 5th ed. R.R. Donnelley and Sons, Inc./Willard.

- Patton-Mallory, M. (1988). "End Distance Effects Comparing Tensile and Compression Loads on Bolted Wood Connections," *Proceedings of the 1988 International Conference on Timber Structures, Vol. 2, Seattle, Washington, September 1988*, 313-319.
- Rammer, Douglas R. (1999). "Parallel-to-Grain Dowel-Bearing Strength of Two Guatemalan Hardwoods," *Forest Products Journal*, 49(6): 77-87.
- Rammer, D.R. (2001). "Effect of Moisture Content on Nail Bearing Strength," *USDA Forest Service, Forest Products Laboratory, Research Paper FPL-RP-591*.
- Rammer, D.R. and Winistorfer, S.G. (2001). "Effect of Moisture Content on Dowel-Bearing Strength," *Wood and Fiber Science*, 33(1), 126-139.
- Rosowsky, D.V. and Reinhold, T.A. (1999). "Rate-of-Load and Duration-of-Load Effects for Wood Fasteners," *Journal of Structural Engineering*, 125(7), 719-724.
- Scholten, J.A. (1939). "Strength of Bolted Timber Joints," Report R1202, USDA Forest Service, Forest Products Laboratory, Madison, WI.
- Schreyer, Alexander et. al. (2001). "Strength Capacities and Behavior of New Composite Timber-Steel Connector," *Journal of Structural Engineering*, 127(8) 888-893.
- Smith, I. and Foliente, G. (2002). "Load and Resistance Factor Design of Timber Joints: International Practice and Future Direction," *Journal of Structural Engineering*, ASCE, 128(1), 48-59.
- Snodgrass, J.D. and Gleaves, W.W. (1960). "Effect of End-Distance on Strength of Single-Bolt Joints," Oregon State University, Oregon Forest Research Center, Corvallis, OR.
- Soltis, L.A., Karnasuidja, S. and Little, J.K. (1987). "Angle to Grain Strength of Dowel-Type Fasteners," *Wood and Fiber Science*, 19(1), 68-80.
- Tissell, J.R. (1967). "Horizontal Plywood Diaphragm Tests," *Laboratory Report No. 106, Tacoma, Washington, American Plywood Association*.
- Trayer, G.W. (1928). "Bearing Strength of Wood Under Steel Aircraft Bolts and Washers and Other Factors Influencing Fitting Design," *National Advisory Committee, Aeronautics, Technical Note No. 296*.
- Trayer, G.W. (1932). "The Bearing Strength of Wood Under Bolts," *Technical Bulletin No. 332, USDA, Forest Service, Washington, D.C., October 1932*, 1-40.

- Wilkinson, T.L. (1991a). "Bolted Connection Allowable Loads Based on the European Yield Model," *USDA Forest Service, Forest Products Laboratory*, Madison, WI.
- Wilkinson, T.L. (1991b). "Dowel Bearing Strength," *Research Paper FPL-RP-505*, USDA, Forest Service, Forest Products Laboratory, Madison, Wisconsin, October 1991.
- Wilkinson, T.L. (1993). "Bolt Connection Strength and Bolt Hole Size," *Research Paper FPL-RP-524*, *USDA Forest Service, Forest Products Laboratory*, Madison, WI.