

Table of Contents

Table of Contents	vi
List of Figures.....	ix
List of Tables	xvi
Chapter 1. Introduction.....	1
1.1. Background.....	1
1.2. Transverse Cracks in Dams	2
1.3. Filters and Crack-Stoppers.....	3
1.4. Objectives of the Research	4
Chapter 2. Literature Review	5
2.1. Introduction.....	5
2.2. Significant finding from previous studies.....	5
2.2.1. Sherard (1979)	5
2.2.2. Vaughan and Soares (1982).....	24
2.2.3. Sherard, Dunnigan, and Talbot (1984a).....	24
2.2.4. Sherard, Dunnigan, and Talbot (1984b)	25
2.2.5. Sherard and Dunnigan (1985).....	25
2.2.6. Kenney, Chahal, Chiu, Ofoegbu, Omange, and Ume (1985)	26
2.2.7. Das Neves (1989).....	26
2.2.8. Honjo and Veneziano (1989).....	27
2.2.9. Khor and Woo (1989)	27
2.2.10. Sherard and Dunnigan (1989).....	28
2.2.11. Indraratna, Vafai, and Haque (1996)	28
2.2.12. Locke, Indraratna and Adikari (2000)	28
2.3. Current Filter Criteria	29
2.3.1. Gradation-based Filter Criteria	29

2.3.2. Current USBR Filter Criteria (after USBR, 1994).....	32
Chapter 3. Filter Test Concept	34
3.1. Introduction.....	34
3.2. Water Supply and Data Acquisition Systems	37
3.3. Crack Orientations and Flow Directions	38
3.4. Clogging Mechanism.....	40
3.5. Summary.....	43
Chapter 4. Materials Tested.....	44
4.1. Introduction.....	44
4.2. Tests on Teton Dam Core Material (Base Material).....	44
4.3. Tests on Filter Material.....	51
Chapter 5. Tests Performed using 4-inch Diameter Filter Test Device.....	56
5.1. Introduction.....	56
5.2. Sample Preparation	58
5.3. Pilot Tests	60
5.3.1. Horizontal Crack Orientation and Horizontal Flow Direction	60
5.3.2. Vertical Crack Orientation and Horizontal Flow Direction.....	63
5.3.3. Vertical Crack Orientation and Vertical Flow Direction.....	66
5.4. Compaction Procedure and Water Supply.....	69
5.5. Major Test Results.....	71
5.5.1. Details for a Typical Test.....	71
5.5.2. Effect of the Percent Fines.....	73
5.5.3. Effect of Crack Width.....	76
5.5.4. Effect of Density.....	78
5.5.5. Effect of Water Content.....	80
5.6. Summary of Tests with 4-inch diameter Filter Test Device.....	84

Chapter 6. Tests Performed using the 12-inch Square Filter Test Device	86
6.1. Introduction.....	86
6.2. Pressure Membrane.....	90
6.3. Test with Vertical Crack and Vertical Flow (VV test condition)	93
6.4. Effect of Crack Width.....	96
6.5. Effect of Highly Plastic Fines Content	97
6.6. Tests on Very Coarse Filters.....	102
6.7. Summary	106
Chapter 7. Sand Castle Tests	108
7.1. Background.....	108
7.2. Description of device and test procedure.....	108
7.3. Test material	111
7.4. Test Results.....	112
7.5. Summary	119
Chapter 8. Summary, Conclusions and Recommendations for Further Research	120
8.1. Summary and Conclusions	120
8.2. Recommendations for Further Research.....	122
Reference	123
Appendix A. The 4-inch Filter Test Device	129
A.1. Device Assembly and Sample Preparations	129
A.2. Shop Drawings for the 4-inch diameter filter test device	145
Appendix B. The 12-inch Square Filter Test Device	155
B.1. Device Assembly and Sample Preparations.....	155
B.2. Shop Drawings for the 12-inch Square Filter Test Device	184
Vita	201

List of Figures

Figure 1.1 Ochoco Dam Piping Problem.....	2
Figure 2.1 Filter criteria based on the ratio of D_{15F} to D_{85B} (after Terzaghi et al., 1996).....	32
Figure 3.1 Filter test concept	35
Figure 3.2 Cross sections through 4-inch and 12-inch filter test devices.....	36
Figure 3.3 Schematic of Data Acquisition System.....	38
Figure 3.4 Crack orientation and Flow direction.....	39
Figure 3.5 (a) and (b) Early stages of clogging by erosion of base and filter.....	41
Figure 4.1 Grain size distribution of Teton Dam core material.....	45
Figure 4.2 Range of gradations meeting USBR specifications for granular filters	47
Figure 4.3 Plasticity chart showing Teton Dam core material (After ASTM D2487)	48
Figure 4.4 Standard Proctor compaction curve for Teton Dam core material.....	49
Figure 4.5 Effective stress paths for CU triaxial tests conducted on Teton Dam core material	50
Figure 4.6 Gradation curve for Ochoco Dam filter material	52
Figure 4.7 Gradation curves for Horsetooth Dam filter material.....	53
Figure 4.8 Standard Proctor compaction curves for Horsetooth Dam filter for 0% and 5% fines.....	55
Figure 5.1 Measuring thickness of each layer by depth gauge.....	58
Figure 5.2 4-inch diameter filter test device	59
Figure 5.3 Longitudinal cross section through 4-inch diameter filter test device with compacted sample.....	60
Figure 5.4 After Test 1 (HH condition)	62
Figure 5.5 After Test 2 (HH condition)	62
Figure 5.6 Tests 3 and 4 (VH condition)	63
Figure 5.7 Before Test 7	64
Figure 5.8 Tests 7 and 8 (VH condition)	65
Figure 5.9 Pressure measurement of Test 7 and 8	66
Figure 5.10 Early stage of Test 5 (VV condition)	67

Figure 5.11 Late stage of Test 5 (VV condition).....	68
Figure 5.12 Clogging layer after Test 5	68
Figure 5.13 Test 6 (VV condition).....	70
Figure 5.14 Flow vs. Time (Test 16)	71
Figure 5.15 Flow Rate vs. Time (Test 16).....	72
Figure 5.16 Pressure vs. Time (Test 16).....	72
Figure 5.17 Flow vs. Time comparing Test 16, 19, and 22	74
Figure 5.18 Flow Rate vs. Time comparing Test 16, 19, and 22.....	75
Figure 5.19 Pressure vs. Time comparing Test 16, 19, and 22.....	75
Figure 5.20 Flow vs. Time comparing Test 16, 17, and 18	77
Figure 5.21 Flow Rate vs. Time comparing Test 16, 17, and 18.....	77
Figure 5.22 Pressure vs. Time comparing Test 16, 17, and 18.....	78
Figure 5.23 Flow vs. Time comparing Test 13 and 16	79
Figure 5.24 Flow Rate vs. Time comparing Test 13 and 16.....	79
Figure 5.25 Pressure vs. Time comparing Test 13 and 16.....	80
Figure 5.26 Flow vs. Time comparing Test 16 and 25	81
Figure 5.27 Flow Rate vs. Time comparing Test 16 and 25.....	81
Figure 5.28 Pressure vs. Time comparing Test 16 and 25.....	82
Figure 5.29 Flow vs. Time comparing Test 24 and 26	83
Figure 5.30 Flow Rate vs. Time comparing Test 24 and 26.....	83
Figure 5.31 Pressure vs. Time comparing Test 24 and 26.....	84
Figure 6.1 Relationship of tests to field conditions	87
Figure 6.2 Comparison of cross section of the two filter test device.....	87
Figure 6.3 Permeameter orientation for vertical crack and horizontal flow	90
Figure 6.4 Exploded view of flexible membrane and backing panel	91
Figure 6.5 Flexible membrane used to fill void at top of specimen	92
Figure 6.6 Test 32 with 12-inch square filter test device (VV condition).....	94
Figure 6.7 Flow rate vs. Time of Test 32.....	95
Figure 6.8 Pressure vs. Time of Test 32	95
Figure 6.9 Flow rate vs. Time (Test 29, 30, and 31).....	96
Figure 6.10 Pressure vs. Time (Test 29, 30, and 31)	97

Figure 6.11 Test 33 (5% HPF).....	98
Figure 6.12 Test 34 (15% HPF).....	100
Figure 6.13 Flow rate vs. Time (Test 33, 34, and 35).....	101
Figure 6.14 Pressure vs. Time (Test 33, 34, and 35)	101
Figure 6.15 Gradation curves of Test 36, 37, and 38.....	103
Figure 6.16 Test 36 (coarse filter material)	104
Figure 6.17 Flow rate vs. Time (Test 36, 37, and 38).....	105
Figure 6.18 Pressure vs. Time (Test 36, 37, and 38)	105
Figure 7.1 Devices for Sand Castle Test.....	109
Figure 7.2 Test configuration for Sand Castle Test	110
Figure 7.3 Front view of test setup	110
Figure 7.4 Water Contents vs. Time to Collapse from SCT.....	116
Figure 7.5 Fines Content vs. Time to Collapse from SCT.....	116
Figure 7.6 The beginning of Test 28 (w=10%, fc=15%, non-plastic fine).....	118
Figure 7.7 Test 28 elapsed time of 14 seconds	118
Figure 7.8 Test 28 elapsed time of 45 seconds	119
Figure A.1 Step 1 (aluminum base)	130
Figure A.2 Step 2 (install assembly rods).....	130
Figure A.3 Step 3 (install aluminum side compaction panel).....	131
Figure A.4 Step 4 (place the compaction spacer and bottom plate)	131
Figure A.5 Step 5 (locate the bottom panel).....	132
Figure A.6 Step 6 (install assembly rods).....	132
Figure A.7 Step 7 (install the location pins)	133
Figure A.8 Step 8 (install the top plate).....	133
Figure A.9 Step 9 (ready to compact).....	134
Figure A.10 Step 10 (cross section to compact)	134
Figure A.11 Step 11 (compaction of test specimen).....	135
Figure A.12 Step 12 (compact base material).....	136
Figure A.13 Step 13 (compact filter material)	136
Figure A.14 Step 14 (compact pea gravel)	137
Figure A.15 Step 15 (install porous plate).....	137

Figure A.16 Step 16 (install spring).....	138
Figure A.17 Step 17 (remove the top plate).....	138
Figure A.18 Step 18 (assemble the bottom plate for testing)	139
Figure A.19 Step 19 (rotate 180 degree).....	139
Figure A.20 Step 20 (remove the bottom plate)	140
Figure A.21 Step 21 (remove the compaction spacer).....	141
Figure A.22 Step 22 (install pea gravel).....	141
Figure A.23 Step 23 (install the porous plate)	142
Figure A.24 Step 24 (install the spring).....	142
Figure A.25 Step 25 (install the top plate for testing).....	143
Figure A.26 Test 26 (rotate 90 degree).....	143
Figure A.27 Step 27 (remove the aluminum side panel)	144
Figure A.28 Step 28 (place the Lucite side panel).....	144
Figure A.29 Step 29 (secure the Lucite side panel).....	145
Figure A.30 Aluminum base.....	146
Figure A.31 Aluminum side panel for compaction	147
Figure A.32 Void-forming plate	148
Figure A.33 Lucite side panel.....	149
Figure A.34 Compaction spacer	150
Figure A.35 Bottom plate for compaction	151
Figure A.36 Top plate for compaction.....	152
Figure A.37 Top and bottom plate for testing.....	153
Figure A.38 Porous plate	154
Figure B.1 Step 1 (place wooden base support)	156
Figure B.2 Step 2 (install left, right, and bottom side panels on wooden base support)	156
Figure B.3 Step 3 (assemble left and right side panels with rods and nuts)	157
Figure B.4 Step 4 (place compaction plate supports)	157
Figure B.5 Step 5 (assemble side assembly bars with middle rods and nuts)	158
Figure B.6 Step 6 (place compaction plate).....	158
Figure B.7 Step 7 (place top compaction panel).....	159
Figure B.8 Step 8 (assemble top rods with nuts)	159

Figure B.9 Step 9 (place wooden compaction support).....	160
Figure B.10 Step 10 (rotate whole device 90 degree).....	160
Figure B.11 Step 11 (the device opening side to up).....	161
Figure B.12 Step 12 (remove wooden base support).....	161
Figure B.13 Step 13 (remove middle rods for compaction)	162
Figure B.14 Step 14 (cross section of compaction mold).....	162
Figure B.15 Step 15 (compacting base material).....	163
Figure B.16 Step 16 (compacting filter material).....	163
Figure B.17 Step 17 (compacting pea gravel layer)	164
Figure B.18 Step 18 (install porous plate)	164
Figure B.19 Step 19 (assemble middle rods and nuts).....	165
Figure B.20 Step 20 (assemble device after compaction).....	165
Figure B.21 Step 21 (place wooden base support and rotate 90 degree).....	166
Figure B.22 Step 22 (place the device in the original position).....	166
Figure B.23 Step 23 (remove wooden compaction support)	167
Figure B.24 Step 24 (place wooden compaction support on the opposite side and rotate 90 degree).....	167
Figure B.25 Step 25 (the device positioned for placement of second layer of pea gravel)	168
Figure B.26 Step 26 (remove wooden base support).....	168
Figure B.27 Step 27 (remove middle rods and nuts)	169
Figure B.28 Step 28 (remove compaction plate support)	169
Figure B.29 Step 29 (remove compaction plate)	170
Figure B.30 Step 30 (cross section view)	170
Figure B.31 Step 31 (compacting pea gravel layer)	171
Figure B.32 Step 32 (place porous plate).....	171
Figure B.33 Step 33 (assemble middle rods and nuts).....	172
Figure B.34 Step 34 (full view)	172
Figure B.35 Step 35 (place wooden base support and rotate 90 degree).....	173
Figure B.36 Step 36 (place the device in the original position).....	173
Figure B.37 Step 37 (remove wooden compaction support and rotate 90 degree).....	174
Figure B.38 Step 38 (the device with left side panel to up).....	174

Figure B.39 Step 39 (remove the nuts)	175
Figure B.40 Step 40 (remove side assembly bars).....	175
Figure B.41 Step 41 (remove left side panel)	176
Figure B.42 Step 42 (left side panel)	176
Figure B.43 Step 43 (detach left side panel insert).....	177
Figure B.44 Step 44 (the left side panel with the insert removed)	177
Figure B.45 Step 45 (parts for reconfiguring left side panel).....	178
Figure B.46 Step 46 (place O-ring in the groove)	178
Figure B.47 Step 47 (place membrane over the O-ring).....	179
Figure B.48 Step 48 (place the membrane retainer, and assemble with bolts).....	179
Figure B.49 Step 49 (assemble with re-configured left side panel and rotate 90 degree) ..	180
Figure B.50 Step 50 (place the device in the original position).....	180
Figure B.51 Step 51 (remove top rods).....	181
Figure B.52 Step 52 (remove top compaction panel)	181
Figure B.53 Step 53 (place top transparent plastic panel)	182
Figure B.54 Step 54 (assemble with top rods and nuts)	182
Figure B.55 Step 55 (place front and back panel and rotate 90 degree).....	183
Figure B.56 Step 56 (ready to test).....	183
Figure B.57 Bottom panel.....	185
Figure B.58 Front panel	186
Figure B.59 Back panel.....	187
Figure B.60 Compaction panel	188
Figure B.61 Compaction plate support.....	189
Figure B.62 Left side panel.....	190
Figure B.63 Left side panel insert.....	191
Figure B.64 Membrane retainer	192
Figure B.65 Right side panel	193
Figure B.66 Porous plate.....	194
Figure B.67 Top compaction panel parts.....	195
Figure B.68 Top compaction panel (part 1).....	196
Figure B.69 Top compaction panel (part 2).....	197

Figure B.70 Top compaction panel (part 3).....	198
Figure B.71 Top compaction panel (part 4).....	199
Figure B.72 Top transparent plastic panel	200

List of Tables

Table 2.1 Literature Review Summary	6
Table 2.2 Filter criteria developed (after Hsu, 1981), modified to include more recently developed criteria	30
Table 2.3 Criteria for filters and base soil categories (after USBR, 1994).....	33
Table 2.4 Gradation limits for prevention of segregation for coarse filters (USBR, 1994) .	33
Table 4.1 Particle size diameters corresponding to different size fractions for Teton Dam core material	46
Table 4.2 Results of Maximum and Minimum density tests	54
Table 5.1 Test summary of 4-inch filter test device	57
Table 6.1 Summary of tests performed using 12-inch square filter test device.....	89
Table 7.1 Sand Castle Test with 5% highly plastic fine	113
Table 7.2 Sand Castle Test with 10% highly plastic fine	114
Table 7.3 Sand Castle Test with 15% highly plastic fine	115
Table 7.4 Test results of HPF cases	117