

## LIST OF FIGURES

Figure	Page
2.1 Typical Phase I Test Setup .....	12
2.2 Typical Full-Penetration Groove Weld with Bead Reinforcement Remaining ....	22
3.1 Elevation of Little Buffalo Creek Bridge .....	28
3.2 Plan View of Little Buffalo Creek Bridge.....	28
3.3 Deck Extrusion Shapes.....	29
3.4 Two-Void Extrusion Detail .....	29
3.5 Mechanical Deck Splice Cross-section .....	31
3.6 Plan View of Entire Aluminum Deck .....	32
3.7 Transverse Section of Little Buffalo Creek Bridge Superstructure .....	33
3.8 Grouted Connection between Deck and Girders .....	34
3.9 Plan View of Test Trucks.....	36
3.10 Axle Weights and Spacing for HS20-44 Truck.....	38
3.11 WIM Gauge Locations .....	39
3.12 Deck Strain Gauge Plan .....	40
3.13 Transverse Truck Locations .....	44
4.1 Deck Gauges with Electronic Signal Noise .....	49
4.2 Deck Gauge Responses after Applying Correction Methods.....	50
4.3 Various Percent Composite Stress Diagrams.....	54
4.4 Percent Composite Curve.....	55
4.5 “Lever Method” Hinge Locations for Determining Distribution Factors .....	59
4.6 Influence Zone for Determining Dynamic Load Allowance.....	67
4.7 Schematic Fatigue Curves from SAS-ASD (1994).....	78
4.8 Schematic Fatigue Curves from AASHTO LRFD (1994).....	82
4.9 Transverse Deck Gauges Associated with the Mechanical Deck Splice Evaluation.....	84

5.1	Percent Composite Curve.....	86
5.2	Neutral Axis Locations from Load Case PS-1 versus Time .....	90
5.3	Neutral Axis Locations from Load Case PS-2 versus Time .....	91
5.4	Girder Flange Strains from Load Case PS-1 versus Position of First Rear Axle.....	93
5.5	Neutral Axis Locations from Load Case PS-1 versus Position of First Rear Axle.....	94
5.6	Top Flange Shapes Due to Torsion.....	95
6.1	Typical Continuous Load Fraction.....	100
6.2	Load Distribution amongst Girders for Load Cases 6 and 7.....	105
6.3	Load Distribution amongst Girders for Load Cases 8 and 9.....	106